



849 NW State Road 45  
Newberry, FL 32669 USA  
Ph: 888.472.2424 or 352.472.5500  
Fax: 352.472.2030  
Email: [info@timcoengr.com](mailto:info@timcoengr.com)  
Website: [www.timcoengr.com](http://www.timcoengr.com)

---

**FCC PART 15.249 & IC RSS-210 (i8) ANNEX A2.9**  
**UNLICENSED INTENTIONAL RADIATOR**  
**COMBINED TEST REPORT**

<b>Applicant</b>	<b>BUILDING 36 TECHNOLOGIES, LLC</b>
<b>Address</b>	<b>35 HIGHLAND CIRCLE SUITE 300 NEEDHAM MA 02494 USA</b>
<b>FCC ID</b>	<b>2AC3T-H200BRA</b>
<b>IC Certification Number</b>	<b>12323A-H200BRA</b>
<b>Model Number</b>	<b>B36-H200-B</b>
<b>Product Description</b>	<b>GATEWAY</b>
<b>FCC Standard Applied</b>	<b>47 CFR §15.249</b>
<b>Industry Canada Standard Applied</b>	<b>RSS-210 Issue 8 Annex A2.9</b>
<b>Date Sample Received</b>	<b>2/27/2015</b>
<b>Date Tested</b>	<b>4/1/2015 – 4/21/2015</b>
<b>Tested By</b>	<b>Cory Leverett</b>
<b>Approved By</b>	<b>Sid Sanders</b>

Report Number	Version Number	Description	Issue Date
411BUT15TestReport	Rev.1	Initial Issue	4/17/2015

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**

## Table of Contents

GENERAL REMARKS.....	7
GENERAL INFORMATION .....	8
TEST RESULTS SUMMARY.....	8
TEST PROCEDURES .....	9
RADIATION INTERFERENCE .....	10
20 dB BANDWIDTH AND BANDEDGE .....	11
99% BANDWIDTH AND BANDEDGE.....	12
ADJACENT RESTRICTED BAND .....	13
DUTY CYCLE .....	14
POWER LINE CONDUCTED INTERFERENCE.....	15
EMC EQUIPMENT LIST.....	18

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 6 of 18

## GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

### Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

### Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.  
849 NW State Road 45  
Newberry, FL 32669

#### Authorized Signatory Name:

**Cory Leverett**  
**Project Manager**  
Date: **4/17/2015**



#### Table of Contents

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 7 of 18

## GENERAL INFORMATION

### EUT Specification

The test results relate only to the items tested.			
<b>Applicable Standards</b>	FCC Part 15.249 & IC RSS-210 (i8), RSS-GEN (i4)		
<b>EUT Description</b>	GATEWAY		
<b>FCC ID</b>	2AC3T-H200BRA		
<b>IC Certification Number</b>	12323A-H200BRA		
<b>Model Number</b>	B36-H200-B		
<b>Operating Frequency</b>	TX: 908.4 MHz		RX: 908.4 MHz
<b>No. of Channels</b>	1	<b>Modulations</b>	QPSK
<b>EUT Power Source</b>	<input checked="" type="checkbox"/> 110–120Vac/50– 60Hz when Charging		
	<input type="checkbox"/> DC Power		
	<input type="checkbox"/> Battery Operated Exclusively		
<b>Test Item</b>	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
<b>Type of Equipment</b>	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
<b>Antenna Connector</b>	FCC Rules require that the antenna connector be unique. There is no antenna connector, it has an integrated PCB antenna		
<b>Test Facility</b>	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
<b>Conditions in the Test laboratory</b>	Temperature: 24–26°C Relative humidity: 50–65%		
<b>Test Exercise</b>	Continuous Transmission		
<b>Revision History of EUT</b>	None		

### TEST RESULTS SUMMARY

<b>FCC Rules Part No.</b>	<b>Industry Canada Rules</b>	<b>RESULTS – Pass/Fail/NA</b>
15.249 Fundamental Emission	RSS-210 (i8) ANNEX A2.9, RSS-GEN (i4)	Pass
15.249 & 15.209 Harmonics & Spurious	RSS-210 (i8) ANNEX A2.9, RSS-GEN (i4)	Pass
15.205 & 2.202 Occupied Bandwidth	RSS-GEN (i4), 6.6	Pass
15.249 & 15.205 Bandedge Compliance	RSS-GEN (i4), 6.6	NA(1)
15.207 Power Line Emissions	RSS-GEN (i4), 8.8	Pass

**Notes:** The EUT's band of operation does not have an adjacent restricted band. No Bandedge test is required only radiated emissions falling in a restricted band are reported.

[Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 8 of 18

## TEST PROCEDURES

**Radiation Interference:** ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worst case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental. Emissions were scanned from 30MHz to the tenth harmonic of the fundamental frequency at three places in the band. All emissions greater than 20 dB from the limit are not reported.

**Formula Of Conversion Factors:** The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL	= FS
33	20 dBuV	+ 10.36 dB	+ 0.5	= 30.86 dBuV/m @ 3m

**Power Line Conducted Interference:** The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

**Occupied Bandwidth:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

**ANSI C63.4-2003 10.1 Measurement Procedures:** The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

## [Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 9 of 18

## RADIATION INTERFERENCE

Rules Part No.: FCC 15.249, 15.209 & IC RSS-210 (i8) ANNEX A2.9, RSS-GEN (i4)

### Requirements:

Frequency	Limits
Part 15.209 & RSS-GEN (i4)	
9 to 490 kHz	2400/F (kHz) $\mu$ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) $\mu$ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB $\mu$ V/m @ 30 meters
30 – 88	40.0 dB $\mu$ V/m @ 3 meters
88 – 216	43.5 dB $\mu$ V/m @ 3 meters
216 – 960	46.0 dB $\mu$ V/m @ 3 meters
Above 960	54.0 dB $\mu$ V/m @ 3 meters
Part 15.249 & RSS-210 (i8) ANNEX A.2.9	
Fundamental 902 – 928 MHz	94.0 dB $\mu$ V/m @ 3 meters
Fundamental 2.4 – 2.4835 GHz	94.0 dB $\mu$ V/m @ 3 meters
Harmonics	54.0 dB $\mu$ V/m @ 3 meters

Test Data: Peak Detector Used unless otherwise noted in the table.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
908.4	21.15	9.6	V	0.14	12.41	22.16	17.84
908.4	24.61	12.3	V	0.15	12.45	24.86	15.14
908.4	30.09	11.7	V	0.17	12.51	24.40	15.60
908.4	34.13	13.3	V	0.20	12.83	26.29	13.71
908.4	41.05	20.4	V	0.26	12.93	33.62	6.38
908.4	48.55	20.6	V	0.32	11.45	32.32	7.68
908.4	60.09	16.1	V	0.38	7.28	23.72	16.28
908.4	63.84	21.3	V	0.40	6.38	28.11	11.89
908.4	120.67	14.0	H	0.64	10.83	25.49	18.01
908.4	364.25	14.8	H	1.27	14.43	30.50	15.50
908.4	364.25	16.0	V	1.27	14.43	31.69	14.31
908.4	750.13	8.5	V	1.91	21.40	31.77	14.23
908.4	750.13	10.6	H	1.91	21.40	33.94	12.06
908.4	850.25	7.4	V	2.11	22.61	32.14	13.86
908.4	850.25	10.0	H	2.11	22.61	34.72	11.28
908.4	908.40	65.1(QP)	H	2.39	23.30	90.78	3.22
908.4	928.10	5.4	H	2.42	23.48	31.34	14.66
908.4	928.10	6.9	V	2.42	23.48	32.80	13.20
908.4	949.92	7.4	V	2.45	23.70	33.50	12.50
908.4	949.92	10.1	H	2.45	23.70	36.24	9.76
908.4	1,816.80	10.6	V	2.96	30.13	43.66	10.34
908.4	1,816.80	11.4	H	2.96	30.13	44.46	9.54
908.4	2,725.20	14.2	V	3.41	32.51	50.14	3.86
908.4	2,725.20	14.7	H	3.41	32.51	50.61	3.39

### [Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 10 of 18

## 20 dB BANDWIDTH AND BANDEDGE


Rules Part No.: 15.249 (d)

**Requirements:** The field strength of any emissions appearing outside the bandedges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

### Test Data:

20 dB OCC BW = 105.76 KHz

Lower Bandedge = 57.78 dBc



Date: 21.APR.2015 10:26:34

### Table of Contents

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 11 of 18

## 99% BANDWIDTH AND BANDEDGE


Rules Part No.: RSS-GEN (i4), 6.6

**Requirements:** Emissions radiated outside of the specified frequency bands, except for the harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the highest general field strength limits listed in RSS-GEN, whichever is less stringent.

### Test Data:

99% OCC BW = 105.76 KHz

Upper Bandedge = 51.74 dBc



Date: 21.APR.2015 10:24:21

### Table of Contents

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 12 of 18



## **ADJACENT RESTRICTED BAND**

**Rules Part No.:** 15.249 (d), & RSS-GEN (i4), 6.6

**Requirements:** 50 dBc or in the case of restricted bands 54 dBuV/m.

**Test Data:** Not applicable the EUT does not have adjacent restricted band.

## **Results Meet Requirements**

[Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 13 of 18



## DUTY CYCLE

Not Applicable, The EUT was tested at 100% duty Cycle. No correction is needed

**Total # of pulses:** 80 in 100 ms

**Duration of pulse:** .480 ms maximum duration of pulse according to manufacturer.  
 $20 \times \log ((.480 \times 80) / 100) = 20 \times \log (.384) = -8.31 \text{dB}$

Dutycycle

[Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 14 of 18



## POWER LINE CONDUCTED INTERFERENCE

**Rules Part No.:** 15.207, & RSS-GEN (i4), 8.8

### Requirements:

Frequency (MHz)	Quasi Peak Limits (dBuv)	Average Limits (dBuV)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5.0 – 30	60	50

**Test Data:** The attached graphs represent the emissions read for power line conducted for this device while charging the battery. Both lines were observed.

[Table of Contents](#)


APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 15 of 18

### Line 1 Peak



Date: 1.APR.2015 09:46:27

### Table of Contents


APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 16 of 18

## Line 2 Peak



Date: 1.APR.2015 09:47:56

### [Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 17 of 18

## EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
Antenna: Biconnical Chamber	Eaton Chamber	94455-1	1057	06/14/13	06/14/15
Antenna: Log-Periodic Chamber	Eaton	96005	1243	05/31/13	05/31/15
Antenna: Passive Loop	EMC Test Systems	EMCO 6512	9706-1211	06/14/12	06/14/15
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/13	12/31/15
Ant: Double-Ridged Horn/ETS Horn 1 Ch	ETS-Lindgren Chamber	3117	00035923	06/13/14	06/13/16
EMI Test Receiver R & S ESIB 40 Screen Room	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
EMI Test Receiver R & S ESU 40 Chamber	Rohde & Schwarz	ESU 40	100320	03/11/14	03/11/16

### \* EMI RECEIVER SOFTWARE VERSION

The receiver firmware used was version 4.43 Service Pack 3

[Table of Contents](#)

APPLICANT: BUILDING 36 TECHNOLOGIES, LLC

IC: 12323A-H200BRA

FCC ID: 2AC3T-H200BRA

REPORT: B\BUILDING 36\411BUT15\411BUT15TestReport.docx Page 18 of 18