

RF EXPOSURE EVALUATION METHOD**FCC ID: 2AC5LLM-BTSP-CHO****SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT3.0:

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	3.061	2.023
CH39	2441	3.504	2.241
CH78	2480	3.066	2.026
2Mbps			
CH00	2402	2.357	1.721
CH39	2441	2.927	1.962
CH78	2480	2.573	1.808
3Mbps			
CH00	2402	2.541	1.795
CH39	2441	3.006	1.998
CH78	2480	2.641	1.837

Remark: The best case gain of the antenna is -2.0dBi.

-2.0 dBi logarithmic terms convert to numeric result is nearly 0.64

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

BT3.0:

Mode	[(max. power of channel, including tune-up tolerance, mW)]	(min. test separation distance,mm)]	[$\sqrt{f(\text{GHz})}$]	Result	Limit
1Mbps					
CH00	2.023	5	2.402	0.627	3
CH39	2.241	5	2.441	0.700	3
CH78	2.026	5	2.480	0.638	3
2Mbps					
CH00	1.721	5	2.402	0.533	3
CH39	1.962	5	2.441	0.613	3
CH78	1.808	5	2.480	0.570	3
3Mbps					
CH00	1.795	5	2.402	0.556	3
CH39	1.998	5	2.441	0.624	3
CH78	1.837	5	2.480	0.579	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.