FCC ID : **2AC73-A1**

Standalone SAR test exclusion considerations

December 8, 2015

```
- Device category = ✓ Portable device
                                        ☐ Mobile device
- Transmitting mode =

☑ Single Transmitting
                                                    ☐ Simultaneous Transmitting
- Max. transmitting frequency =
                                   2480
                                           MHz
- Min. test separation distance =
                                      0
                                           mm
- Max. Antenna Gain =
                            3.3
                                  dBi
- Max. power with turn-up tolerance =
                                       9.00
                                              dBm =
                                                                         Typical Power =
                                                                                             Max.
                                                                                                    9.00 dBm
                                                               mW
Note. BT & LE
```

KDB 447498 D01 clasue 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1g SAR and \leq 7.5 for 10g extremity SAR = [(8mW / 5mm)] X [$\sqrt{2.48GHz}$] = 2.5

Note. The calculation result was rounded to one decimal place for comparison.

→ SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.