

## **Radiation Hazard Assessment**

<b>Date</b>	25 <sup>th</sup> March 2025
<b>FCC ID</b>	2AC7B-G6500
<b>Brand Name</b>	Invenco
<b>Model Number</b>	G6-500, G6-500 IPT
<b>Product</b>	Outdoor and Indoor Payment Terminal
<b>Manufacturer</b>	Invenco Group Ltd
<b>Country of Origin</b>	New Zealand
<b>Serial Number</b>	U8LH001R

### **Product Description:**

The device tested is Payment Terminal with a number of features that would typically be used for the payment of fuel at a petrol station.

The device contains a NFC Card Reader that operates on 13.560 MHz

The product is powered at 24 Vdc using a power supply that is connected to the 120 Vac 60 Hz Public AC mains supply.

FCC part 15 testing as detailed in EMC Technologies NZ Ltd test report number 240910.2 dated 16<sup>th</sup> December 2024 shows the following:

13.560 MHz transmitter with a field strength of 59.1 dBuV/m (Quasi Peak detector) at a test distance of 10 metres

This gives a calculated transmitter power of 2.71 uW or 0.00271 mW.

Calculations were made using the formula:

$$\text{Power (watts)} = ((\text{field strength (V/m)} \times \text{distance (metres)})^2) / 30$$

As per FCC KDB 447498 D04 and Section 2.1091 radio frequency transmitters are required to be operated in a manner that ensures the public is not exposed to high levels of RF energy.

In normal use the transmitter in this device may come in close contact with the human body, the hand, when cards are placed in or near the device when a transaction is carried out.

As the radiated power is below 1 mW this transmitter will be below the SAR testing threshold and therefore no further action will be required.

**Result:** Complies