

Analysis Report

Report No.: 14090770HKG-001

The Equipment Under Test (EUT) is a transmitter of a RC Boat operating at 49.860 MHz as dictated by a crystal. The EUT is powered by a 3.0 V DC source (2 x 1.5V AA size batteries). The EUT has a left / right control lever and a forward / backward control lever.

After switching ON the EUT and the receiver of the RC Boat, activating the control buttons on the EUT can control the receiver moving forward, backward, left and right.

Antenna Type: External integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 75.0dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 78.0dB μ V/m at 3m in frequency 49.860MHz, thus;

The EIRP = [(FS*D) ^2*1000 / 30] = 0.0189mW

Thus;

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.0189mW.

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

$$= [474 * (1 + \log 100/f(MHz))] / 2$$

$$= 308.6\text{mW}$$

Since the above conducted output power is well below the SAR Exclusion Threshold level, so the EUT is considered to comply with SAR requirement without testing.