FCC Test Report

Report No.: AGC01680151102FE03

FCC ID : 2AC9LHB099-A

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Bluetooth Keyboard

BRAND NAME : N/A

MODEL NAME : HB099-A

CLIENT: Shenzhen Hastech industries Co., Ltd.

DATE OF ISSUE : Nov.27,2015

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Page 2 of 48

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Nov.27,2015	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2. TABLE OF CARRIER FREQUENCYS	5
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES	6
5. SYSTEM TEST CONFIGURATION	7
5.1. CONFIGURATION OF EUT SYSTEM	7
5.2. EQUIPMENT USED IN EUT SYSTEM	7
5.3. SUMMARY OF TEST RESULTS	7
6. TEST FACILITY	8
7. ALL TEST EQUIPMENT LIST	8
8. RADIATED EMISSION	10
8.1TEST LIMIT	10
8.2. MEASUREMENT PROCEDURE	11
8.3. TEST SETUP	13
8.4. TEST RESULT	15
9. BAND EDGE EMISSION	28
9.1. MEASUREMENT PROCEDURE	
9.2 TEST SETUP	28
9.3 RADIATED TEST RESULT	29
10. 20DB BANDWIDTH	33
10.1. MEASUREMENT PROCEDURE	33
10.2. TEST SET-UP	33
10.3. LIMITS AND MEASUREMENT RESULTS	33
11. FCC LINE CONDUCTED EMISSION TEST	36
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	36
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	36
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	37
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	37
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	38
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	40
APPENDIX B: PHOTOGRAPHS OF EUT	42

Page 4 of 48

1. VERIFICATION OF CONFORMITY

Applicant	Shenzhen Hastech industries Co., Ltd.		
Address	3rd, 4th floor G-A1 Bldg &1st, 2nd floor G-A2 Bldg, Democracy West Industry Park, Shajing Town, Bao'an District, Shenzhen, China.		
Manufacturer	Shenzhen Hastech industries Co., Ltd.		
Address 3rd, 4th floor G-A1 Bldg &1st, 2nd floor G-A2 Bldg, Democracy We Park, Shajing Town, Bao'an District, Shenzhen, China.			
Product Designation	Bluetooth Keyboard		
Brand Name	N/A		
Test Model	HB099-A		
Date of test	Nov.19,2015 to Nov.23,2015		
Deviation	None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested By	Time Unang-		
	Time Huang(Huang Nanhui)	Nov.27,2015	
Reviewed By	Forest, cei		
	Forrest Lei(Lei Yonggang)	Nov.27,2015	
Approved By	gelga shong		
•	Solger Zhang(Zhang Hongyi) Authorized Officer	Nov.27,2015	

Page 5 of 48

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz		
RF Output Power	-3.01dBm(Max)		
Bluetooth Version	V 3.0		
Modulation	GFSK		
Number of channels	79		
Hardware Version	HB099E Ver:02		
Software Version	N/A		
Antenna Designation	PCB Antenna (Met 15.203 Antenna requirement)		
Antenna Gain	0dBi		
Power Supply	DC 3.7V by battery		

Note: The EUT is equipped with the Bluetooth Chip BCM20730 which complies with Bluetooth V 3.0, but for this device the functionality is limited to GFSK (1MBit/s) by the firmware. End-user is not able to change the settings and enable any additional functionality by himself.

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
2400~2483.5MHZ	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

Page 6 of 48

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 % \circ

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	BT Link with Charging


- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.

Page 7 of 48

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Bluetooth Keyboard	N/A	HB099-A	EUT
2	Control box	N/A	N/A	A.E
3	PC	SONY	E1412AYCW	A.E
4	USB Cable	N/A	0.6m, unshielded	A.E
5	Temporary Antenna Connector	T10	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWITH	Compliant

Page 8 of 48

6. TEST FACILITY

Site Dongguan Precise Testing Service Co., Ltd.	
Location Building D,Baoding Technology Park,Guangming Road2,Dongcheng Distriction Dongguan, Guangdong, China,	
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016	
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016	
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016	
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016	
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016	
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A	
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016	
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016	

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

	Radiated Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Serial Number Last Calibration 101417 July 4, 2015 20D-1246 July 11, 2015 Y4511453 July 4, 2015 9718-269 July 7, 2015 96220 July 8, 2015 PTS-001 June 6, 2015 780208339 N/A						
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016					
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016					
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016					
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016					
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016					
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016					
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A					
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016					

Page 9 of 48

	Conducted Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration					
EMI Test Receiver	- Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016					
Artificial Mains Network	Narda	L2-16B	000WX31025 July 8, 2015							
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016					
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016					
Shielded Room	CHENGYU	843	PTS-002	June 6,2015	June 5,2016					

Page 10 of 48

8. RADIATED EMISSION

8.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics		
	(millivolts/meter)	(microvolts/meter)		
900-928MHz	50	500		
2400-2483.5MHz	50	500		
5725-5875MHz	50	500		
24.0-24.25GHz	250	2500		

Standard FCC 15.209

Frequency	Distance	Field	Strengths Limit			
(MHz)	(MHz) Meters		dB(μV)/m			
0.009 ~ 0.490	300	2400/F(kHz)				
0.490 ~ 1.705	30	24000/F(kHz)				
1.705 ~ 30	30	30				
30 ~ 88	3	100	40.0			
88 ~ 216	3	150	43.5			
216 ~ 960	3	200	46.0			
960 ~ 1000 3		500	54.0			
Above 1000	3	Other:74.0 dB(µV)/m	Other:74.0 dB(µV)/m (Peak) 54.0 dB(µV)/m (Average)			

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Page 11 of 48

8.2. MEASUREMENT PROCEDURE

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1.5MHz VBW and RBW for peak reading. Then 1.5MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC01680151102FE03 Page 12 of 48

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1.5MHz/1.5MHz for Peak, 1.5MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 13 of 48

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz



Page 14 of 48

RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 15 of 48

8.4. TEST RESULT


(Modulation:GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: Low Channel TX

Note:

Polarization:	Horizontal	Temperati	ıre: 22.5
Power:		Humidity:	53 6 %

Distance: 3m


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		170.6500	16.75	13.06	29.81	43.50	-13.69	peak			
2	*	311.3000	18.53	16.16	34.69	46.00	-11.31	peak			
3		385.6667	15.66	18.98	34.64	46.00	-11.36	peak			
4		515.0000	12.34	21.54	33.88	46.00	-12.12	peak			
5		576.4333	6.92	23.14	30.06	46.00	-15.94	peak			
6		901.3833	-0.69	28.65	27.96	46.00	-18.04	peak			

Temperature: 22.5

Humidity: 53.6 %

Page 16 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		120.5333	22.20	7.08	29.28	43.50	-14.22	peak			
2		215.9167	15.36	10.56	25.92	43.50	-17.58	peak			
3		322.6167	13.79	16.92	30.71	46.00	-15.29	peak			
4	*	385.6667	13.66	18.98	32.64	46.00	-13.36	peak			
5		534.4000	9.99	22.06	32.05	46.00	-13.95	peak			
6		796 3000	0.57	27 27	27 84	46 00	-18 16	peak			

Power:

Distance: 3m

Polarization: Vertical


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 17 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: Middle Channel TX

Note:

Polarization:	Horizontal	Temperature	e: 22.5
Power:		Humidity: 5	3.6 %

Distance: 3m


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		170.6500	18.75	13.06	31.81	43.50	-11.69	peak			
2	*	215.9167	21.77	12.60	34.37	43.50	-9.13	peak			
3		311.3000	20.53	16.16	36.69	46.00	-9.31	peak			
4		385.6667	16.66	18.98	35.64	46.00	-10.36	peak			
5		515.0000	13.84	21.54	35.38	46.00	-10.62	peak			
6		894.9167	1.96	28.48	30.44	46.00	-15.56	peak			

Temperature: 22.5

Humidity: 53.6 %

Page 18 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: Middle Channel TX

859.3500

1.53

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1	*	120.5333	24.20	7.08	31.28	43.50	-12.22	peak			
2		159.3333	12.69	15.33	28.02	43.50	-15.48	peak			
3		322.6167	14.79	16.92	31.71	46.00	-14.29	peak			
4		385.6667	11.66	18.98	30.64	46.00	-15.36	peak			
5		532.7833	9.17	22.02	31.19	46.00	-14.81	peak			

46.00 -16.92

Polarization:

Distance: 3m

Power:

Vertical

peak

RESULT: PASS

6

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

29.08


27.55

2. The "Factor" value can be calculated automatically by software of measurement system.

Humidity: 53.6 %

Page 19 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Polarization: Horizontal

Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: High Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		96.2833	16.63	10.07	26.70	43.50	-16.80	peak			
2		156.1000	15.77	15.30	31.07	43.50	-12.43	peak			
3		215.9167	19.27	12.60	31.87	43.50	-11.63	peak			
4		322.6167	18.21	16.92	35.13	46.00	-10.87	peak			
5		450.3333	14.18	20.59	34.77	46.00	-11.23	peak			
6	*	515.0000	14.34	21.54	35.88	46.00	-10.12	peak			

Power:

Distance: 3m

Page 20 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: High Channel TX

Note:

Polarization:	Vertical	Temperature: 2	22.5
Power:		Humidity: 53.6	%

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	115.6833	26.29	4.71	31.00	43.50	-12.50	peak		·	
2		159.3333	12.19	15.33	27.52	43.50	-15.98	peak			
3		322.6167	15.79	16.92	32.71	46.00	-13.29	peak			
4		385.6667	11.16	18.98	30.14	46.00	-15.86	peak			
5		607.1500	8.14	22.89	31.03	46.00	-14.97	peak			
6		709.0000	4.98	25.45	30.43	46.00	-15.57	peak		·	

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 21 of 48

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26

Distance: 3m

Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

M/N: HB099-A

Mode: Low Channel TX


EUT: Bluetooth Keyboard

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	101.20	-9.68	91.52	114.00	-22.48	peak			
2		3166.667	51.08	-8.20	42.88	74.00	-31.12	peak			
3		4825.000	45.36	-2.26	43.10	74.00	-30.90	peak			
4	*	2402.000	91.77	-9.68	82.09	94.00	-11.91	AVG	100	252	

Page 22 of 48

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance: 3m

M/N: HB099-A


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	101.26	-9.68	91.58	114.00	-22.42	peak			
2		3716.667	49.78	-6.56	43.22	74.00	-30.78	peak			
3		5291.667	45.21	-1.81	43.40	74.00	-30.60	peak			
4	*	2402.000	91.89	-9.68	82.21	94.00	-11.79	AVG	100	135	

Page 23 of 48

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance: 3m

M/N: HB099-A


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	101.84	-9.63	92.21	114.00	-21.79	peak			
2		3908.333	50.22	-5.37	44.85	74.00	-29.15	peak			
3		4700.000	46.99	-2.59	44.40	74.00	-29.60	peak			
4	*	2441.000	92.26	-9.63	82.63	94.00	-11.37	AVG	100	133	

Page 24 of 48

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance: 3m

M/N: HB099-A


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	101.64	-9.63	92.01	114.00	-21.99	peak			
2		2908.333	53.06	-8.58	44.48	74.00	-29.52	peak			
3		4433.333	47.30	-3.34	43.96	74.00	-30.04	peak			
4	*	2441.000	92.39	-9.63	82.76	94.00	-11.24	AVG	100	249	

Page 25 of 48

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

Distance: 3m

EUT: Bluetooth Keyboard

M/N: HB099-A


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	101.90	-9.59	92.31	114.00	-21.69	peak			
2		3250.000	52.25	-8.12	44.13	74.00	-29.87	peak			
3		4683.333	46.94	-2.63	44.31	74.00	-29.69	peak			
4	*	2480.000	92.06	-9.59	82.47	94.00	-11.53	AVG	100	244	

Page 26 of 48

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance: 3m

M/N: HB099-A

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	101.88	-9.59	92.29	114.00	-21.71	peak			
2		3483.333	52.59	-7.91	44.68	74.00	-29.32	peak			
3		5358.333	47.25	-1.81	45.44	74.00	-28.56	peak			
4	*	2480.000	91.47	-9.59	81.88	94.00	-12.12	AVG	100	138	

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 27 of 48

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	101.20	-9.68	91.52	114	-22.48	Horizontal
2402	101.26	-9.68	91.58	114	-22.42	Vertical
2441	101.84	-9.63	92.21	114	-21.79	Horizontal
2441	101.64	-9.63	92.01	114	-21.99	Vertical
2480	101.90	-9.59	92.31	114	-21.69	Horizontal
2480	101.88	-9.59	92.29	114	-21.71	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	91.77	-9.68	82.09	94	-11.91	Horizontal
2402	91.89	-9.68	82.21	94	-11.79	Vertical
2441	92.26	-9.63	82.63	94	-11.37	Horizontal
2441	92.39	-9.63	82.76	94	-11.24	Vertical
2480	92.06	-9.59	82.47	94	-11.53	Horizontal
2480	91.47	-9.59	81.88	94	-12.12	Vertical

Page 28 of 48

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE


1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1.5MHz / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




Page 29 of 48

9.3 RADIATED TEST RESULT

(Modulation:GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance:


M/N: HB099-A

Mode: Low Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2293.617	29.58	10.20	39.78	74.00	-34.22	peak			
2		2390.000	29.00	10.31	39.31	74.00	-34.69	peak			
3	*	2402.000	82.22	10.32	92.54	74.00	18.54	peak			

Page 30 of 48

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance:


M/N: HB099-A

Mode: Low Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2296.350	30.30	10.21	40.51	74.00	-33.49	peak			
2		2390.000	26.71	10.31	37.02	74.00	-36.98	peak			
3	*	2402.000	81.09	10.32	91.41	74.00	17.41	peak			

Page 31 of 48

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance:


M/N: HB099-A

Mode: High Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	82.05	10.41	92.46	74.00	18.46	peak			
2		2483.500	28.69	10.41	39.10	74.00	-34.90	peak			
3		2490.980	29.57	10.42	39.99	74.00	-34.01	peak			

Page 32 of 48

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance:

M/N: HB099-A

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	81.82	10.41	92.23	74.00	18.23	peak			
2		2483.500	26.76	10.41	37.17	74.00	-36.83	peak			
3		2490.723	30.05	10.42	40.47	74.00	-33.53	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 33 of 48


10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT Has been used temporary antenna connector for testing.

10.3. LIMITS AND MEASUREMENT RESULTS

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL								
Annliaghla Limita	Measurement Result							
Applicable Limits	Test Da	Criteria						
	Low Channel	1.133	PASS					
N/A	Middle Channel	1.132	PASS					
	High Channel	1.126	PASS					

Page 34 of 48

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Page 35 of 48

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 36 of 48

11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage					
Frequency	Q.P.(dBuV)	Average(dBuV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 37 of 48

11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by PC which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Humidity: 54.7 %

Page 38 of 48

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



Phase:

Power:

L1

Site: Conduction Limit: FCC Class B Conduction(QP)

EUT: Bluetooth Keyboard

M/N: HB099-A


Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	36.67		21.54	10.21	46.88		31.75	63.69	53.69	-16.81	-21.94	Р	
2	0.4540	31.93		16.92	10.37	42.30		27.29	56.80	46.80	-14.50	-19.51	Р	
3	2.1980	31.01		15.65	10.30	41.31		25.95	56.00	46.00	-14.69	-20.05	Р	
4	3.7820	27.15		11.78	10.46	37.61		22.24	56.00	46.00	-18.39	-23.76	Р	
5	7.2500	24.73		4.53	10.34	35.07		14.87	60.00	50.00	-24.93	-35.13	Р	
6	15.6860	30.21		16.42	10.11	40.32		26.53	60.00	50.00	-19.68	-23.47	Р	

Page 39 of 48

Line Conducted Emission Test Line 2-N



Site: Conduction Phase: N Temperature: 23.1 Limit: FCC Class B Conduction(QP) Power: Humidity: 54.7 %

EUT: Bluetooth Keyboard

M/N: HB099-A

Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1900	39.40		24.92	10.20	49.60		35.12	64.03	54.03	-14.43	-18.91	Р	
2	0.4620	35.21		16.42	10.37	45.58		26.79	56.66	46.66	-11.08	-19.87	Р	
3	0.8780	33.24		19.59	10.38	43.62		29.97	56.00	46.00	-12.38	-16.03	Р	
4	2.3780	28.03		14.35	10.38	38.41		24.73	56.00	46.00	-17.59	-21.27	Р	
5	3.6220	27.03		12.70	10.49	37.52		23.19	56.00	46.00	-18.48	-22.81	Р	
6	15.7580	28.05		14.78	10.11	38.16		24.89	60.00	50.00	-21.84	-25.11	Р	


Page 40 of 48


APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP






Page 42 of 48

APPENDIX B: PHOTOGRAPHS OF EUT


WHOLE VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT




Page 45 of 48

RIGHT VIEW OF EUT




VIEW OF EUT (Port)




Page 46 of 48


OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



----END OF REPORT----