FCC Test Report

Report No.: AGC01680151102FE01

FCC ID : 2AC9LHB099-A

PRODUCT DESIGNATION: Bluetooth Keyboard

BRAND NAME : N/A

MODEL NAME : HB099-A

CLIENT: Shenzhen Hastech industries Co., Ltd.

DATE OF ISSUE : Nov.27,2015

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC01680151102FE01 Page 2 of 24

Report Revise Record

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|-------------|---------------|-----------------|
| V1.0 | / | Nov.27,2015 | Valid | Original Report |

Report No.: AGC01680151102FE01 Page 3 of 24

TABLE OF CONTENTS

| 1. VERIFICATION OF CONFORMITY | 4 |
|--------------------------------------------------|----|
| 2. SYSTEM DESCRIPTION | 5 |
| 3. MEASUREMENT UNCERTAINTY | 5 |
| 4. PRODUCT INFORMATION | 6 |
| 5. SUPPORT EQUIPMENT | 7 |
| 6. TEST FACILITY | 8 |
| 7. FCCLINE CONDUCTED EMISSION TEST | |
| 7.1. LIMITS OF LINE CONDUCTED EMISSION TEST | |
| 7.2. BLOCK DIAGRAM OF TEST SETUP | g |
| 7.3. PROCEDURE OF LINE CONDUCTED EMISSION TEST | 10 |
| 7.4. TEST RESULT OF LINE CONDUCTED EMISSION TEST | 11 |
| 8. FCC RADIATED EMISSION TEST | |
| 8.1. LIMITS OF RADIATED EMISSION TEST | |
| 8.2. BLOCK DIAGRAM OF TEST SETUP | |
| 8.3. PROCEDURE OF RADIATED EMISSION TEST | |
| 8.4. TEST RESULT OF RADIATED EMISSION TEST | 15 |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP | 17 |
| APPENDIX B: PHOTOGRAPHS OF EUT | 18 |

Page 4 of 24

1. VERIFICATION OF CONFORMITY

| Applicant | Shenzhen Hastech industries Co., Ltd. |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Address | 3rd, 4th floor G-A1 Bldg &1st, 2nd floor G-A2 Bldg, Democracy West Industry Park, Shajing Town, Bao'an District, Shenzhen, China. |
| Manufacturer | Shenzhen Hastech industries Co., Ltd. |
| Address | 3rd, 4th floor G-A1 Bldg &1st, 2nd floor G-A2 Bldg, Democracy West Industry Park, Shajing Town, Bao'an District, Shenzhen, China. |
| Product Designation | Bluetooth Keyboard |
| Brand Name | N/A |
| Test Model HB099-A | |
| Measurement Procedure ANSI C63.4: 2009 | |
| Date of test Nov.19,2015 to Nov.23,2015 | |
| Deviation None | |
| Condition of Test Sample Normal | |
| Report Template | AGCRT-US-IT/AC(2013-03-01) |

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2009. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

| Tested By | hime Huang | • |
|-------------|------------------------------------------------|-------------|
| | Time Huang(Huang Nanhui) | Nov.27,2015 |
| Reviewed By | Foresto ce | |
| · | Forrest Lei(Lei Yonggang) | Nov.27,2015 |
| Approved By | gelja skuy | |
| | Solger Zhang(Zhang Hongyi) Authorized Officer | Nov.27,2015 |

Page 5 of 24

2. SYSTEM DESCRIPTION

| TEST MODE DESCRIPTION | | |
|-----------------------|-----------------------|--|
| NO. | TEST MODE DESCRIPTION | |
| 1 | USB | |

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

Page 6 of 24

4. PRODUCT INFORMATION

| Housing Type | Plastic and metal |
|--------------|--------------------|
| Power Supply | DC 3.7V by battery |

I/O Port Information (⊠Applicable ☐Not Applicable)

| I/O Port of EUT | | | | | |
|----------------------------------------------------|---|--|---|--|--|
| I/O Port Type Number Cable Description Tested With | | | | | |
| USB port | 1 | | 1 | | |

Page 7 of 24

5. SUPPORT EQUIPMENT

| Device Type | Manufacturer | Model Name | Serial No. | Data Cable | Power Cable |
|-------------|--------------|------------|------------|------------|----------------|
| PC | SONY | E1412AYCW | | | |

Page 8 of 24

6. TEST FACILITY

| Site | Dongguan Precise Testing Service Co., Ltd. | | |
|-------------|--------------------------------------------------------------------------------------------------------|--|--|
| Location | Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China, | | |
| Description | The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009. | | |

TEST EQUIPMENT

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

| Radiated Emission Test Site | | | | | | | |
|----------------------------------------|-----------------|--------------|------------------|---------------------|--------------------|--|--|
| Name of Equipment | Manufacturer | Model Number | Serial Number | Last Calibration | Due Calibration | | |
| EMI Test Receiver | Rohde & Schwarz | ESCI | 101417 | July 4, 2015 | July 3, 2016 | | |
| Trilog Broadband Antenna (25M-1GHz) | SCHWARZBECK | VULB9160 | 9160-3355 | July 4, 2015 | July 3, 2016 | | |
| Signal Amplifier | SCHWARZBECK | BBV 9475 | 9745-0013 | July 4, 2015 | July 3, 2016 | | |
| RF Cable | SCHWARZBECK | AK9515E | 96221 | July 4, 2015 | July 3, 2016 | | |
| 3m Anechoic Chamber | CHENGYU | 966 | PTS-001 | June 6, 2015 | June 5, 2016 | | |
| MULTI-DEVICE Positioning Controller | Max-Full | MF-7802 | MF780208339 | N/A | N/A | | |
| Active loop antenna (9K-30MHz) | Schwarzbeck | FMZB1519 | 1519-038 | June 6, 2015 | June 5, 2016 | | |
| Spectrum analyzer | Agilent | E4407B | MY46185649 | June 6, 2015 | June 5, 2016 | | |

| | Conducted Emission Test Site | | | | | |
|-----------------------------------|------------------------------|--------------|---------------|------------------|--------------------|--|
| Name of Equipment | Manufacturer | Model Number | Serial Number | Last Calibration | Due Calibration | |
| EMI Test Receiver | Rohde & Schwarz | ESCI | 101417 | July 4, 2015 | July 3, 2016 | |
| Artificial Mains Network | Narda | L2-16B | 000WX31025 | July 8, 2015 | July 7, 2016 | |
| Artificial Mains Network (AUX) | Narda | L2-16B | 000WX31026 | July 8, 2015 | July 7, 2016 | |
| RF Cable | SCHWARZBECK | AK9515E | 96222 | July 4, 2015 | July 3, 2016 | |
| Shielded Room | CHENGYU | 843 | PTS-002 | June 6,2015 | June 5,2016 | |

Page 9 of 24

7. FCCLINE CONDUCTED EMISSION TEST


7.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Eroguenev | Maximum RF Line Voltage | | |
|---------------|-------------------------|----------------|--|
| Frequency | Q.P.(dBuV) | Average(dBuV) | |
| 150kHz-500kHz | 66-56 | 56-46 | |
| 500kHz-5MHz | 56 | 46 | |
| 5MHz-30MHz | 60 | 50 | |

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

7.2. BLOCK DIAGRAM OF TEST SETUP



Page 10 of 24

7.3. PROCEDURE OF LINE CONDUCTED EMISSION TEST

(1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.


- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received DC5V power from PC with receive 120V/60Hz power from a LISN.
- (5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- (7) During the above scans, the emissions were maximized by cable manipulation.
- (8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- (9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition (mode 1) was reported on the Summary Data page.

Page 11 of 24

7.4. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST-L



Site: Conduction Phase: L1 Temperature: 23.1
Limit: FCC Class B Conduction(QP) Power: Humidity: 54.7 %

EUT: Bluetooth Keyboard


M/N: HB099-A Mode: USB Note:

| No. | Freq. (MHz) | Reading_Level (dBuV) | | | Correct Factor | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|----------------|-------------------------|----|-------|-------------------|-----------------------|----|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | dB | Peak | QP | AVG | QP | AVG | QP | AVG | | |
| 1 | 0.1980 | 37.12 | | 20.08 | 10.21 | 47.33 | | 30.29 | 63.69 | 53.69 | -16.36 | -23.40 | Р | |
| 2 | 0.4380 | 31.91 | | 15.80 | 10.36 | 42.27 | | 26.16 | 57.10 | 47.10 | -14.83 | -20.94 | Р | |
| 3 | 1.1420 | 29.65 | | 15.58 | 10.37 | 40.02 | | 25.95 | 56.00 | 46.00 | -15.98 | -20.05 | Р | |
| 4 | 2.7100 | 31.30 | | 16.14 | 10.48 | 41.78 | | 26.62 | 56.00 | 46.00 | -14.22 | -19.38 | Р | |
| 5 | 5.7260 | 24.00 | | 12.25 | 10.26 | 34.26 | | 22.51 | 60.00 | 50.00 | -25.74 | -27.49 | Р | |
| 6 | 15.3140 | 29.55 | | 14.39 | 10.12 | 39.67 | | 24.51 | 60.00 | 50.00 | -20.33 | -25.49 | Р | |

RESULT: PASS

Page 12 of 24

LINE CONDUCTED EMISSION TEST-N



Site: Conduction Phase: N Temperature: 23.1
Limit: FCC Class B Conduction(QP) Power: Humidity: 54.7 %

EUT: Bluetooth Keyboard

M/N: HB099-A Mode: USB Note:

| No. | Freq. (MHz) | Reading_Level (dBuV) | | | Correct Factor | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|----------------|-------------------------|----|-------|-------------------|-----------------------|----|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | dB | Peak | QP | AVG | QP | AVG | QP | AVG | | |
| 1 | 0.1940 | 37.52 | | 26.23 | 10.21 | 47.73 | | 36.44 | 63.86 | 53.86 | -16.13 | -17.42 | Р | |
| 2 | 0.4500 | 35.13 | | 19.39 | 10.37 | 45.50 | | 29.76 | 56.87 | 46.87 | -11.37 | -17.11 | Р | |
| 3 | 0.8820 | 32.72 | | 18.80 | 10.39 | 43.11 | | 29.19 | 56.00 | 46.00 | -12.89 | -16.81 | Р | |
| 4 | 1.5780 | 32.45 | | 17.71 | 10.36 | 42.81 | | 28.07 | 56.00 | 46.00 | -13.19 | -17.93 | Р | |
| 5 | 3.5660 | 26.58 | | 13.00 | 10.50 | 37.08 | | 23.50 | 56.00 | 46.00 | -18.92 | -22.50 | Р | |
| 6 | 15.6300 | 27.67 | | 14.71 | 10.11 | 37.78 | | 24.82 | 60.00 | 50.00 | -22.22 | -25.18 | Р | |

RESULT: PASS

Page 13 of 24

8. FCC RADIATED EMISSION TEST


8.1. LIMITS OF RADIATED EMISSION TEST

| Frequency (MHz) | Distance (m) | Maximum Field Strength Limit (dBuV/m/ Q.P.) |
|--------------------|-----------------|---------------------------------------------|
| 30~88 | 3 | 40.0 |
| 88~216 | 3 | 43.5 |
| 216~960 | 3 | 46.0 |
| Above 960 | 3 | 54.0 |

Note: The lower limit shall apply at the transition frequency.

8.2. BLOCK DIAGRAM OF TEST SETUP

System Diagram of Connections between EUT and Simulators



Page 14 of 24

8.3. PROCEDURE OF RADIATED EMISSION TEST

(1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.


- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received DC 5V power from PC with receive 120V/60Hz power from socket under the turntable through a LISN.
- (5) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- (6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- (7) The test mode(s) were scanned during the test:
- (8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.

The test data of the worst case condition (mode 1) was reported on the Summary Data page.

Page 15 of 24

8.4. TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test at 3m Distance-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 22.5 Limit: FCC Class B 3M Radiation Power: Humidity: 53.6 %

EUT: Bluetooth Keyboard Distance: 3m


M/N: HB099-A Mode: USB Note:

| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
| | - | MHz | dBu∀ | dB/m | dBu∀/m | dBu∀/m | dB | | cm | degree | |
| 1 | | 156.0999 | 19.77 | 15.30 | 35.07 | 43.50 | -8.43 | peak | | | |
| 2 | | 215.9166 | 23.27 | 12.60 | 35.87 | 43.50 | -7.63 | peak | | | |
| 3 | | 322.6166 | 19.71 | 16.92 | 36.63 | 46.00 | -9.37 | peak | | | |
| 4 | | 450.3333 | 15.18 | 20.59 | 35.77 | 46.00 | -10.23 | peak | | | |
| 5 | * | 515.0000 | 16.85 | 21.53 | 38.38 | 46.00 | -7.62 | peak | | | |
| 6 | | 576.4333 | 11.92 | 23.14 | 35.06 | 46.00 | -10.94 | peak | | | |

RESULT: PASS

Page 16 of 24

Radiated Emission Test at 3m Distance-Vertical



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: HB099-A Mode: USB Note: Polarization: Vertical Temperature: 22.5 Power: Humidity: 53.6 %

Distance: 3m

| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
| | - | MHz | dBu∀ | dB/m | dBu∀/m | dBu∀/m | dB | | cm | degree | |
| 1 | * | 120.5333 | 27.69 | 7.08 | 34.77 | 43.50 | -8.73 | peak | | | |
| 2 | | 159.3333 | 16.19 | 15.33 | 31.52 | 43.50 | -11.98 | peak | | | |
| 3 | | 322.6167 | 16.79 | 16.92 | 33.71 | 46.00 | -12.29 | peak | | | |
| 4 | | 385.6666 | 12.16 | 18.98 | 31.14 | 46.00 | -14.86 | peak | | | |
| 5 | | 607.1500 | 8.14 | 22.89 | 31.03 | 46.00 | -14.97 | peak | | | |
| 6 | | 709.0000 | 4.98 | 25.45 | 30.43 | 46.00 | -15.57 | peak | | | |

RESULT: PASS

Note: Above 1GHz have more than 20db margin, no recording in the report Measurement = Reading + Factor, Over = Measurement – Limit.


Page 17 of 24

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP




FCC RADIATED EMISSION TEST SETUP



Page 18 of 24

APPENDIX B: PHOTOGRAPHS OF EUT


WHOLE VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



Report No.: AGC01680151102FE01 Page 20 of 24

BACK VIEW OF EUT



LEFT VIEW OF EUT




Page 21 of 24

RIGHT VIEW OF EUT




VIEW OF EUT (Port)




Report No.: AGC01680151102FE01 Page 22 of 24

OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




Report No.: AGC01680151102FE01 Page 23 of 24


INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



----END OF REPORT----