FCC Test Report

Report No.: AGC01680161102FE07

FCC ID 2AC9LHB191

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Bluetooth Keyboard

BRAND NAME : N/A

MODEL NAME : HB191

CLIENT: Shenzhen Hastech Industries Co., Ltd.

DATE OF ISSUE : Nov.14, 2016

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC01680161102FE07 Page 2 of 22

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov.14, 2016	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. SYSTEM DESCRIPTION	5
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION	6
5. SUPPORT EQUIPMENT	7
6. TEST FACILITY	8
7. FCCLINE CONDUCTED EMISSION TEST	
7.1. LIMITS OF LINE CONDUCTED EMISSION TEST	g
7.2. BLOCK DIAGRAM OF TEST SETUP	g
7.3. PROCEDURE OF LINE CONDUCTED EMISSION TEST	10
7.4. TEST RESULT OF LINE CONDUCTED EMISSION TEST	10
8. FCC RADIATED EMISSION TEST	11
8.1. LIMITS OF RADIATED EMISSION TEST	
8.2. BLOCK DIAGRAM OF TEST SETUP	
8.3. PROCEDURE OF RADIATED EMISSION TEST	
8.4. TEST RESULT OF RADIATED EMISSION TEST	14
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	16
APPENDIX B: PHOTOGRAPHS OF EUT	17

Page 4 of 22

1. VERIFICATION OF CONFORMITY

Applicant	Shenzhen Hastech Industries Co., Ltd.			
Address	3rd, 4th floor G-A1 Bldg & 1st, 2nd floor G-A2 Bldg Democracy West Industry Park, Shajing Town, Baoan District, Shenzhen, China			
Manufacturer	Shenzhen Hastech Industries Co., Ltd.			
Address	3rd, 4th floor G-A1 Bldg & 1st, 2nd floor G-A2 Bldg Democracy West Industry Park, Shajing Town, Baoan District, Shenzhen, China			
Product Designation	Bluetooth Keyboard			
Brand Name	N/A			
Test Model	HB191			
Date of test	Nov.09, 2016 to Nov.10, 2016			
Deviation	None			
Condition of Test Sample	Normal			
Report Template	AGCRT-US-IT/AC			

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2014. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested By	Strive Wang	
	Strive Liang(Liang Faqiang)	Nov.10, 2016
Reviewed By	Lower ci	
	Forrest Lei(Lei Yonggang)	Nov.14, 2016
Approved By	Solya Zhong	
	Solger Zhang(Zhang Hongyi) Authorized Officer	Nov.14, 2016

Page 5 of 22

2. SYSTEM DESCRIPTION

EUT set up procedure:

- 1. Connect the EUT with the PC.
- 2. Make sure the EUT operates normally during the test.

Test Mode

TEST MODE DESCRIPTION					
NO.	TEST MODE DESCRIPTION	WORST			
1	USB(Wired Keyboard)	V			
Note: V	Note: V means EMI worst mode				

3. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Conducted measurement: +/- 2.75dB

Radiated measurement: +/- 3.2dB

Summary Of Test Results

FCC Rules	Description Of Test	Result
§15.107	Conduction Emission	Compliant
§15.109	Radiated Emission	Compliant

Page 6 of 22

4. PRODUCT INFORMATION

Housing Type	Metal			
Voltage	DC 3.0V by battery			
Note: The highest frequency of the internal sources of the FLIT is less than 108MHz, the measurement shall				

Note: The highest frequency of the internal sources of the EUT is less than 108MHz, the measurement shall only be made up to 1GHz Radiated Emission.

I/O Port Information (⊠Applicable ☐Not Applicable)

I/O Port of EUT					
I/O Port Type Q'TY Cable Tested with					
USB Port	1	0	1		

Page 7 of 22

5. SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Serial No.	Power Cable
PC	SONY	E1412AYCW	A.E	1.5m unshielded
IPOD	APPLE	A1367 CCQKQBPWF96V		N/A

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Report No.: AGC01680161102FE07 Page 8 of 22

6. TEST FACILITY

Site Dongguan Precise Testing Service Co., Ltd.			
Location Building D, Baoding Technology Park, Guangming Road2, Dongcheng District Dongguan, Guangdong, China,			
FCC Registration No.	371540		
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.		

ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017	
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017	
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017	
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017	
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017	
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A	
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2016	June 5, 2017	

Conducted Emission Test Site						
Name of Equipment Manufacturer		Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017	
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2016	July 7, 2017	
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2016	July 7, 2017	
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017	
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017	

Report No.: AGC01680161102FE07 Page 9 of 22

7. FCCLINE CONDUCTED EMISSION TEST


7.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francis	Maximum RF Line Voltage						
Frequency	Q.P.(dBuV)	Average(dBuV)					
150kHz-500kHz	66-56	56-46					
500kHz-5MHz	56	46					
5MHz-30MHz	60	50					

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

7.2. BLOCK DIAGRAM OF TEST SETUP



Page 10 of 22

7.3. PROCEDURE OF LINE CONDUCTED EMISSION TEST

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received charging voltage by PC or adapter which receive AC120V/60Hz power from a LISN.
- (5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- (7) During the above scans, the emissions were maximized by cable manipulation.
- (8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- (9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition (mode 1) was reported on the Summary Data page.

7.4. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The EUT was supplied by AAA battery.

Page 11 of 22

8. FCC RADIATED EMISSION TEST

8.1. LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)				
30~88	3	40.0				
88~216	3	43.5				
216~960	3	46.0				
960~1000	3	54.0				

Note: The lower limit shall apply at the transition frequency.

8.1.1 The following table is the setting of spectrum analyzer and receiver:

Spectrum Parameter	Setting				
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP				
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP				
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP				


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.2. BLOCK DIAGRAM OF TEST SETUP

System Diagram of Connections between EUT and Simulators

Report No.: AGC01680161102FE07 Page 12 of 22

RADIATED EMISSION TEST SETUP 30MHz-1000MHz



Page 13 of 22

8.3. PROCEDURE OF RADIATED EMISSION TEST

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.


Temperature: 24.6

Humidity: 54.3 %

Page 14 of 22

8.4. TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test at 3m Distance-Horizontal



Site: site #1 Limit: FCC Class B 3M Radiation

EUT:Bluetooth Keyboard

M/N:HB191

Mode:USB(Wired Keyboard)

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		215.9166	16.53	10.38	26.91	43.50	-16.59	peak			
2		264.4166	20.34	9.35	29.69	46.00	-16.31	peak			
3		408.3000	10.90	19.32	30.22	46.00	-15.78	peak			
4		479.4332	8.20	20.91	29.11	46.00	-16.89	peak			
5		712.2332	4.33	25.54	29.87	46.00	-16.13	peak			
6	*	928.8667	2.07	29.41	31.48	46.00	-14.52	peak			


Power:

Distance:

Polarization: Horizontal

Page 15 of 22

Radiated Emission Test at 3m Distance-Vertical



Site: site #1 Limit: FCC Class B 3M Radiation

EUT:Bluetooth Keyboard

M/N:HB191

Mode:USB(Wired Keyboard)

Note:

Polarization:	Vertical	Temperature: 24.6
Power:		Humidity: 54.3 %

Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		36.4667	20.03	4.27	24.30	40.00	-15.70	peak			
2		160.9499	8.77	15.27	24.04	43.50	-19.46	peak			
3		267.6499	11.65	14.43	26.08	46.00	-19.92	peak			
4		649.1833	6.72	23.83	30.55	46.00	-15.45	peak			
5		846.4166	4.23	27.31	31.54	46.00	-14.46	peak			
6	*	920.7833	4.08	29.19	33.27	46.00	-12.73	peak			


RESULT: PASS

Note: Measurement = Reading + Factor, Over = Measurement – Limit.

Report No.: AGC01680161102FE07 Page 16 of 22

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP




Report No.: AGC01680161102FE07 Page 17 of 22

APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



Report No.: AGC01680161102FE07 Page 18 of 22

FRONT VIEW OF EUT



BACK VIEW OF EUT



Report No.: AGC01680161102FE07 Page 19 of 22

LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (PORT)




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----