

FCC RF EXPOSURE REPORT

FCC ID: 2AC9W-CMC187

Project No. : 1605C201
Equipment : UHF Card Issuer
Model : CMC187
Applicant : FUTAIHUA INDUSTRIAL (SHENZHEN) CO.,LTD.
Address : B District, Foxconn Technology Park, Guanlan
Town, Baoan, Shenzhen, GuangDong, China

According: : FCC Guidelines for Human Exposure IEEE C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Internal	N/A	0

TEST RESULTS

EUT :	UHF Card Issuer	Model Name :	CMC187
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0	1.0000	15.89	38.8150	0.00772592	1	Complies
0	1.0000	15.60	36.3078	0.00722687	1	Complies
0	1.0000	15.30	33.8844	0.00674451	1	Complies

Note: the calculated distance is 20 cm.