

Measurement Results

1-0832/20-01-05_log1_conducted

[Test logging](#)

This addendum is electronically signed and valid without handwritten signature.
For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:

Michael Dorongovski
Lab Manager
Radio Communications

Table of Content

EUT Summary	3
1. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps	4
2. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps	11
3. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps	18
4. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 1 Msps	21
5. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps	25
6. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps	29
7. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 1 Msps	31
8. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps	35
9. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps	39
10. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps	41
11. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps	48
12. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps	55
13. FCC Part 15.247 TX Spurious Conducted ~ BT LE 1 Msps	58
14. FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps	62
15. FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps	66
16. Common2G4 Peak OP 3MHz/3MHz ~ BT LE 1 Msps	68

EUT Summary

EUT DEFINITION	
Manufacturer	SBO Hearing A/S
Type	MI_AU5_MNR_T
Kind	Hearing aid amplifier module
Serial Number Setup Number	C1 - 66372943 1.0
Version SW FW HW	xble_qual_app 54.7+ metax [1]+ metax[2] NI Final LAB
Comment 1 2	
Temperature [°C] Min Nom Max	1 20 40
Voltage [V] Min Nom Max @Current Max [A]	1.1 1.4 1.45 @1

EUT Common Settings BT Low Energy	
Intermodulation Value N	3
Image Freq. Low Mid High [MHz]	0 0 0
Power Class	2
1 Mbps supported	True TXpayload 255 RXpayload 255
2 Mbps supported	True TXpayload 255 RXpayload 255
Longrange S8 supported	False TXpayload 255 RXpayload 255
Longrange S2 supported	False TXpayload 255 RXpayload 255
Signaling Settings	USB_RS232 HCI 7 9600 None S1 None On
Signaling RF Settings	RF1com 0 0 On
User Interaction	No
Switch Matrix & Pathcompensation enabled	Yes

1. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps

Test References	
TC Start	12.04.2021 16:58:13
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE 1 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 1 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.06 10.79 15				
Start [MHz] Stop [MHz]	2401.000 2403.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				


DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	651	kHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps DTS BW_12042021_165842.png

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.06 10.79 20				
Start [MHz] Stop [MHz]	2401.000 2403.000				
RBW [MHz] VBW [MHz]	1.000000 3.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	2.9	dBm	PASS
Peak Power	---	1000	1.949845	mW	PASS
Frequency at Peak	---	---	2402.262	MHz	INFO




Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps_12042021_165859.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.17 10.8 15				
Start [MHz] Stop [MHz]	2439.000 2441.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	653	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.17 10.8 20				
Start [MHz] Stop [MHz]	2439.000 2441.000				
RBW [MHz] VBW [MHz]	1.000000 3.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	4.06	dBm	PASS
Peak Power	---	1000	2.54683	mW	PASS
Frequency at Peak	---	---	2439.734	MHz	INFO




Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps_12042021_165946.png

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.64 10.85 15				
Start [MHz] Stop [MHz]	2479.000 2481.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	654	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.64 10.85 20				
Start [MHz] Stop [MHz]	2479.000 2481.000				
RBW [MHz] VBW [MHz]	1.000000 3.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	2.54	dBm	PASS
Peak Power	---	1000	1.794734	mW	PASS
Frequency at Peak	---	---	2479.738	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 1 Msps_12042021_170032.png

TEST FINISHED

General Verdict

PASS

2. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps

Test References	
TC Start	12.04.2021 17:26:11
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2404
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2478
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2404 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			11.80 10.8 20		
Start [MHz] Stop [MHz]			2401.700 2406.300		
RBW [MHz] VBW [MHz]			0.100000 0.300000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1136	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			16.80 10.8 25		
Start [MHz] Stop [MHz]			2401.700 2406.300		
RBW [MHz] VBW [MHz]			2.000000 5.000000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	6.57	dBm	PASS
Peak Power	---	1000	4.539416	mW	PASS
Frequency at Peak	---	---	2404.579	MHz	INFO




Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msp_12042021_172658.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			12.65 10.8 20		
Start [MHz] Stop [MHz]			2437.700 2442.300		
RBW [MHz] VBW [MHz]			0.100000 0.300000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1191	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			17.65 10.8 25		
Start [MHz] Stop [MHz]			2437.700 2442.300		
RBW [MHz] VBW [MHz]			2.000000 5.000000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	7.44	dBm	PASS
Peak Power	---	1000	5.546257	mW	PASS
Frequency at Peak	---	---	2440.487	MHz	INFO




Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msp.12042021_172745.png

Test at TX 2478 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.30 10.85 15				
Start [MHz] Stop [MHz]	2475.700 2480.300				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1202	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.30 10.85 20				
Start [MHz] Stop [MHz]	2475.700 2480.300				
RBW [MHz] VBW [MHz]	2.000000 5.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	3.31	dBm	PASS
Peak Power	---	1000	2.142891	mW	PASS
Frequency at Peak	---	---	2477.38	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps_12042021_172832.png

TEST FINISHED	
General Verdict	PASS

3. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 10:33:41
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2476
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2476 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.85 10.84 20				
Start [MHz] Stop [MHz]	2473.700 2478.300				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1190	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.85 10.84 25				
Start [MHz] Stop [MHz]	2473.700 2478.300				
RBW [MHz] VBW [MHz]	2.000000 5.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	6.72	dBm	PASS
Peak Power	---	1000	4.698941	mW	PASS
Frequency at Peak	---	---	2476.46	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE 2 Msps_13042021_103430.png

TEST FINISHED	
General Verdict	PASS

4. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 1 Msp/s

Test References	
TC Start	12.04.2021 17:00:38
Ambit Temp [°C] Humidity [rel%]	23.6 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE 1 Msp/s
Add. Information	


Test Parameter	
Technology to test	BT LE 1 Msp/s
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.07 10.79 15	
Start [MHz] Stop [MHz]	2401.000 2403.000	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	652	kHz	PASS




Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 1 Msps_12042021_170107.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.18 10.8 15	
Start [MHz] Stop [MHz]	2439.000 2441.000	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	653	kHz	PASS




Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 1 Msps_12042021_170136.png

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.62 10.85 15	
Start [MHz] Stop [MHz]	2479.000 2481.000	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	653	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 1 Msps_12042021_170204.png

TEST FINISHED	
General Verdict	PASS

5. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps

Test References	
TC Start	12.04.2021 17:28:38
Ambit Temp [°C] Humidity [rel%]	23.4 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2404
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2478
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2404 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.80 10.8 20	
Start [MHz] Stop [MHz]	2401.700 2406.300	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1134	kHz	PASS




Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps_12042021_172907.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.62 10.8 20	
Start [MHz] Stop [MHz]	2437.700 2442.300	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1184	kHz	PASS




Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps_12042021_172936.png

Test at TX 2478 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.34 10.85 15	
Start [MHz] Stop [MHz]	2475.700 2480.300	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1199	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps_12042021_173005.png

TEST FINISHED	
General Verdict	PASS

6. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 10:34:35
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2476
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2476 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.90 10.84 20	
Start [MHz] Stop [MHz]	2473.700 2478.300	
RBW [MHz] VBW [MHz]	0.100000 0.300000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1196	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE 2 Msps_13042021_103505.png

TEST FINISHED	
General Verdict	PASS

7. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 1 Msps

Test References	
TC Start	12.04.2021 17:02:10
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE 1 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 1 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.07 10.79 15	
Start [MHz] Stop [MHz]	2401.250 2402.750	
RBW [MHz] VBW [MHz]	0.003000 0.010000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-13.54	dBm/3KHz	PASS




Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 1 Msps_12042021_170248.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.20 10.8 15	
Start [MHz] Stop [MHz]	2439.250 2440.750	
RBW [MHz] VBW [MHz]	0.003000 0.010000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-12.36	dBm/3KHz	PASS




Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 1 Msps_12042021_170326.png

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.63 10.85 15	
Start [MHz] Stop [MHz]	2479.250 2480.750	
RBW [MHz] VBW [MHz]	0.003000 0.010000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-14.02	dBm/3KHz	PASS



TEST FINISHED	
General Verdict	PASS

8. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps

Test References	
TC Start	12.04.2021 17:30:10
Ambit Temp [°C] Humidity [rel%]	23.4 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2404
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2478
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2404 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			11.81 10.8 20		
Start [MHz] Stop [MHz]			2402.275 2405.725		
RBW [MHz] VBW [MHz]			0.003000 0.010000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 20 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-11.58	dBm/3KHz	PASS




Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps_12042021_173050.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.61 10.8 20				
Start [MHz] Stop [MHz]	2438.275 2441.725				
RBW [MHz] VBW [MHz]	0.003000 0.010000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-10.68	dBm/3KHz	PASS




Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps_12042021_173128.png

Test at TX 2478 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.28 10.85 15	
Start [MHz] Stop [MHz]	2476.275 2479.725	
RBW [MHz] VBW [MHz]	0.003000 0.010000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-15.16	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps_12042021_173207.png

TEST FINISHED	
General Verdict	PASS

9. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 10:35:10
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2476
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2476 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.87 10.84 20	
Start [MHz] Stop [MHz]	2474.275 2477.725	
RBW [MHz] VBW [MHz]	0.003000 0.010000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-11.46	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE 2 Msps_13042021_103549.png

TEST FINISHED	
General Verdict	PASS

10. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps

Test References	
TC Start	12.04.2021 17:04:10
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE 1 Msps
Add. Information	



Test Parameter	
Technology to test	BT LE 1 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			8.05 10.79 15		
Start [MHz] Stop [MHz]			2401.000 2403.000		
RBW [MHz] VBW [MHz]			0.020000 0.100000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1043.696	kHz	INFO
T1 99%	2400.000000	---	2401.4871	MHz	PASS
T2 99%	---	2483.500000	2402.5307	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1191	kHz	INFO
T1 20DB	2400.000000	---	2401.4222	MHz	PASS


T2 20dB

2483.500000


2402.6130

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps 20dB_12042021_170453.png





Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps_12042021_170500.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.17 10.8 15		
Start [MHz] Stop [MHz]			2439.000 2441.000		
RBW [MHz] VBW [MHz]			0.020000 0.100000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1044.096	kHz	INFO
T1 99%	2400.000000	---	2439.4851	MHz	PASS
T2 99%	---	2483.500000	2440.5291	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1210	kHz	INFO
T1 20DB	2400.000000	---	2439.3984	MHz	PASS


T2 20dB

2483.500000


2440.6082

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps 20dB_12042021_170543.png





Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps_12042021_170549.png

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			7.62 10.85 15		
Start [MHz] Stop [MHz]			2479.000 2481.000		
RBW [MHz] VBW [MHz]			0.020000 0.100000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1045.495	kHz	INFO
T1 99%	2400.000000	---	2479.4823	MHz	PASS
T2 99%	---	2483.500000	2480.5277	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1191	kHz	INFO
T1 20DB	2400.000000	---	2479.4208	MHz	PASS


T2 20dB

2483.500000


2480.6114

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps 20dB_12042021_170633.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 1 Msps_12042021_170639.png

TEST FINISHED

General Verdict

PASS

11. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps

Test References	
TC Start	12.04.2021 17:32:13
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2404
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2478
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2404 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			11.79 10.8 20		
Start [MHz] Stop [MHz]			2401.700 2406.300		
RBW [MHz] VBW [MHz]			0.050000 0.200000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2111.649	kHz	INFO
T1 99%	2400.000000	---	2402.9656	MHz	PASS
T2 99%	---	2483.500000	2405.0772	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps 99PCT_12042021_173243.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps_12042021_173249.png

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2294	kHz	INFO
T1 20DB	2400.000000	---	2402.8661	MHz	PASS



T2 20dB

2483.500000

2405.1606

MHz

PASS




Test at TX 2440 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			12.62 10.8 20		
Start [MHz] Stop [MHz]			2437.700 2442.300		
RBW [MHz] VBW [MHz]			0.050000 0.200000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2118.548	kHz	INFO
T1 99%	2400.000000	---	2438.9550	MHz	PASS
T2 99%	---	2483.500000	2441.0735	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps 99PCT_12042021_173333.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps_12042021_173339.png

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2308	kHz	INFO
T1 20DB	2400.000000	---	2438.8505	MHz	PASS


T2 20dB

2483.500000


2441.1583

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps 20dB_12042021_173346.png





Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps_12042021_173353.png

Test at TX 2478 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			8.32 10.85 15		
Start [MHz] Stop [MHz]			2475.700 2480.300		
RBW [MHz] VBW [MHz]			0.050000 0.200000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2115.788	kHz	INFO
T1 99%	2400.000000	---	2476.9453	MHz	PASS
T2 99%	---	2483.500000	2479.0611	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2299	kHz	INFO
T1 20DB	2400.000000	---	2476.8472	MHz	PASS



T2 20dB

2483.500000

2479.1463

MHz

PASS



TEST FINISHED

General Verdict

PASS

12. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 10:35:55
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2476
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2476 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			11.87 10.84 20		
Start [MHz] Stop [MHz]			2473.700 2478.300		
RBW [MHz] VBW [MHz]			0.050000 0.200000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2107.509	kHz	INFO
T1 99%	2400.000000	---	2474.9628	MHz	PASS
T2 99%	---	2483.500000	2477.0703	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps 99PCT_13042021_103625.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps_13042021_103631.png

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2298	kHz	INFO
T1 20DB	2400.000000	---	2474.8610	MHz	PASS


T2 20dB

2483.500000


2477.1587

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps 20dB_13042021_103639.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE 2 Msps_13042021_103645.png

TEST FINISHED

General Verdict

PASS

13. FCC Part 15.247 TX Spurious Conducted ~ BT LE 1 Msps

Test References	
TC Start	12.04.2021 17:06:45
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE 1 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 1 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	3.04 0 20				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2402.33 MHz	---	---	2.75	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2399.833 MHz	0	---	23.42	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 1 Msps 2402_12042021_171218.png





Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 1 Msps 2402_12042021_171223.png

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	4.19 0 20				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2440.33 MHz	---	---	3.17	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15111 MHz	0	---	29.57	dB	INFO





Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	2.64 0 20				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2480.33 MHz	---	---	1.52	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15117.333 MHz	0	---	28.35	dB	INFO



TEST FINISHED	
General Verdict	PASS

14. FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 09:22:07
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2404
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2478
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2404 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			6.91 0 25		
Start [MHz] Stop [MHz]			24530.000 25030.000		
RBW [MHz] VBW [MHz]			0.100000 0.300000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 8 3001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2404.00 MHz	---	---	5.39	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2399.833 MHz	0	---	24.76	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2404_13042021_093108.png




Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2404_13042021_093113.png

Test at TX 2440 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.76 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 8 3001 SWE

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2440.50 MHz	---	---	6.35	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 6944.5 MHz	0	---	31.01	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2440_13042021_094014.png





Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2440_13042021_094019.png

Test at TX 2478 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	3.47 0 20				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	1000 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2478.50 MHz	---	---	1.92	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2484.167 MHz	0	---	28.83	dB	INFO



TEST FINISHED	
General Verdict	PASS

15. FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps

Test References	
TC Start	13.04.2021 10:36:50
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE 2 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 2 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2476
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2476 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			6.86 0 25		
Start [MHz] Stop [MHz]			24530.000 25030.000		
RBW [MHz] VBW [MHz]			0.100000 0.300000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 8 3001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2476.17 MHz	---	---	5.01	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 19331.833 MHz	0	---	30.01	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2476_13042021_104551.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE 2 Msps 2476_13042021_104556.png

TEST FINISHED	
General Verdict	PASS

16. Common2G4 Peak OP 3MHz/3MHz ~ BT LE 1 Msps

Test References	
TC Start	12.04.2021 16:56:42
Ambit Temp [°C] Humidity [rel%]	23.5 25
System Version	2.0.0.4
Test Specification	None
Test Method	
TC Version	0.0.1
My Description	Peak Output Power conducted 3MHz/3MHz - BT LE 1 Msps
Add. Information	


Test Parameter	
Technology to test	BT LE 1 Msps
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SigBT: Rohde&Schwarz,CMW,1201.0002k75/100683,3.7.171 SA: Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			13.03 10.79 20		
Start [MHz] Stop [MHz]			2399.500 2404.500		
RBW [MHz] VBW [MHz]			3.000000 3.000000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 10 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	2.96	dBm	Info
Peak Power	---	---	1.97697	mW	Info
Frequency at Peak	---	---	2402.33	MHz	Info




Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			14.17 10.8 20		
Start [MHz] Stop [MHz]			2437.500 2442.500		
RBW [MHz] VBW [MHz]			3.000000 3.000000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 10 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	4.12	dBm	Info
Peak Power	---	---	2.58226	mW	Info
Frequency at Peak	---	---	2439.675	MHz	Info




Plot_Common2G4 Peak OP 3MHz-3MHz ~ BT LE 1 Msps_12042021_165739.png

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	PASS

READ SA SETTINGS:		
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.68 10.85 20	
Start [MHz] Stop [MHz]	2477.500 2482.500	
RBW [MHz] VBW [MHz]	3.000000 3.000000	
Detector TraceMode	POS MAXH	
Sweep: Time [ms] Count Points per Section Type	1000 10 1001 SWE	

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	2.63	dBm	Info
Peak Power	---	---	1.832314	mW	Info
Frequency at Peak	---	---	2479.665	MHz	Info



TEST FINISHED	
General Verdict	PASS

- END OF DOCUMENT -