

Testing Tomorrow's Technology

Application for

**US Code Title 47, Part 2, Subpart J, Section 2.947, Certification
Per
Part 15, Subpart C, for Intentional Radiators, Section 15.249, Intentional Radiator
Operating within the Band 2400 MHz to 2483.5 MHz**

For the


Wink Inc.

**Model: Hub
(Bluetooth Radio Evaluation)**

**UST Project: 14-0071
Test Date(s): April 14 to May 7, 2014
Issue Date: May 13, 2013**

Total Number of Pages in this Report: 25

**3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com**



Testing Tomorrow's Technology

I certify that I am authorized to sign for the test facility and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

US TECH (Agent Responsible For Test):

By: 

Name: Alan Ghasiani

Title: Consulting Engineer - President

Date: May 13, 2014

This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of U.S. Technologies. The results contained in this report are subject to the adequacy and representative character of the sample provided.

**3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com**

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

MEASUREMENT/TECHNICAL REPORT

COMPANY NAME: Wink Inc.
MODEL(S): Hub
FCC ID: 2ACAJ-WINK22
DATE: May 13, 2014

This report concerns (check one): Original grant Class II change

Equipment type: Intentional Radiator Operating within the bands 2400-2483.5 MHz

Deferred grant requested per 47 CFR 0.457(d) (1) (ii)? yes No

If yes, defer until: _____
date

N.A. agrees to notify the Commission by N.A.
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Report prepared by:

US Tech
3505 Francis Circle
Alpharetta, GA 30004

Phone Number: (770) 740-0717
Fax Number: (770) 740-1508

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

SUMMARY OF TEST REQUIREMENTS

| <u>FCC Requirement</u> | <u>Title</u> | <u>Disposition</u> |
|-------------------------------|---|---------------------------|
| 15.205 | Restricted Bands | Pass |
| 15.207 | Intentional Radiator Power Line Conducted Emissions | Pass |
| 15.209 | Intentional Radiator Radiated Emissions | Pass |
| 15.249(a) | Fundamental Field Strength | Pass |

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

Table of Contents

| | |
|---|----------|
| 1 General Information | 7 |
| 1.1 Purpose of this Report | 7 |
| 1.2 Product Description..... | 7 |
| 1.3 Related Submittal(s)/Grant(s) | 7 |
| 2 Tests and Measurements | 8 |
| 2.1 Configuration of Tested System..... | 8 |
| 2.2 EUT Characterization..... | 10 |
| 2.3 Test Facility..... | 10 |
| 2.4 Test Equipment..... | 11 |
| 2.5 Modifications to EUT | 12 |
| 2.6 Measurement Standards (CFR 15.31) | 12 |
| 2.7 Frequency Range of Radiated Measurements (CFR 15.33) | 12 |
| 2.7.1 Frequency Range for Intentional Radiators..... | 12 |
| 2.7.2 Frequency Range for Unintentional Radiators | 12 |
| 2.7.3 Measurement Detector Function and Bandwidth (CFR 15.35)..... | 12 |
| 2.8 Antenna Requirement (CFR 15.203) | 14 |
| 2.9 Intentional Radiator, Power Line Conducted Emissions (CFR 15.207) | 14 |
| 2.10 Intentional Radiator, Radiated Emissions (CFR 15.249 (a), (e)) | 14 |
| 2.11 Restricted Bands of Operation (CFR 15.205) | 14 |
| 2.12 Band Edge Measurements (CFR15.249(d))..... | 17 |
| 2.12.1 High Band Edge | 17 |

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

List of Tables

| | |
|--|----|
| Table 1. EUT and Peripherals..... | 10 |
| Table 2. Test Instruments | 11 |
| Table 3. Allowed Antenna(s) | 14 |
| Table 4. Peak Measurements (CFR15.249 (a)) | 15 |
| Table 5. Average Measurements (CFR 15.35(b), 15.249(a))..... | 16 |
| Table 6. Bandwidth Measurements, 6 dB | 22 |

List of Figures

| | |
|---|----|
| Figure 1. Test Configuration | 9 |
| Figure 2. Duty Cycle | 13 |
| Figure 3. Radiated Band Edge – Low Channel Delta – Peak | 17 |
| Figure 4. Radiated Band Edge – High Channel Delta – Average | 18 |
| Figure 5. Radiated Band Edge – High Channel Delta – Peak..... | 19 |
| Figure 6. Radiated Band Edge – High Channel Delta - Average | 20 |
| Figure 7. Low Channel 20 dB Bandwidth..... | 23 |
| Figure 8. Mid Channel 20dB Bandwidth..... | 24 |
| Figure 9. High Channel 20dB Bandwidth | 25 |

List of Appendices

Appendix Title

| | |
|---|--------------------------------|
| A | Agency Agreement |
| B | Application Forms |
| C | Letter of Confidentiality |
| D | Equipment Label |
| E | Block Diagram(s) |
| F | Schematic(s) |
| G | Test Configuration Photographs |
| H | External Photographs |
| I | Internal Photographs |
| J | Theory of Operation |
| K | User's Manual |

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

1 General Information

1.1 Purpose of this Report

This report is prepared as a means of presenting test data to be used by a Telecom Certification Body in determination of whether this product is permitted for unlicensed dissemination to the general public according to the FCC Rules and Regulations for RF Devices Intentional Radiators.

1.2 Product Description

The Equipment under Test (EUT) is the WINK Inc. home automation radio module, model HUB. The HUB has five transmitters, including: three 2.4 GHZ transmitters (Wifi, Bluetooth, and Zigbee), one 908 MHz transmitter (Zwave), and one 431 MHz transmitter (Lutron). The circuit board uses four trace antennas. The Bluetooth and Wifi radios share one antenna and the other transmitters each have their own antennas.

This report will cover in detail test results for the Bluetooth transmitter; test results for the other transmitters will be covered in different reports.

Below is an excerpt from a customer email describing the function parameters of the transmitters.

Our specific test:

Hopping on 79 channels starting at 2402MHz with 1MHz channel spacing. Symbol rate = 1M symbol / second with 8-DPSK modulation (EDR) with a PRBS9 test pattern, total data rate= 3Mb/s, which is worst case.

EUT used proprietary software to adjust frequencies and power level.

1.3 Related Submittal(s)/Grant(s)

1.3.1 The EUT is subject to the following FCC authorizations:

- a) Certification under section 15.249 as a transmitter.
- b) Verification/Declaration of Conformity under 15.101 as a digital device and receiver.

1.3.2 Certification of the Transmitter

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

The EUT employs spread spectrum modulation, but is not being certified under CFR 15.247 because the field strength of the fundamental and its harmonics are within the limits specified in 47 CFR 15.249. Therefore the EUT is instead being presented under the requirements of CFR 15.249. The EUT will operate within the frequency band of 2400 MHz to 2483.5 MHz.

1.3.3 Verification of the Digital apparatus

The verification report is submitted separately, in combination with the certification report for the Zigbee radio.

2 Tests and Measurements

2.1 Configuration of Tested System

The sample was set up and tested per ANSI C63.4, Methods of Measurement from Low-Voltage Electrical and Electronic Equipment in the Frequency Range of 9 kHz to 40 GHz (2003). Conducted and radiated emissions data were taken with the EMC test receiver (or spectrum analyzer's) resolution bandwidth adjusted to 9 kHz and 120 kHz, respectively. All measurements are peak unless stated otherwise. The video filter associated with the spectrum analyzer was off throughout the evaluation process. A Block diagram of the tested system is shown in Figure 1. A listing of the EUT and its test peripherals is found in Table 1 below. Test configuration photographs for spurious and fundamental emissions measurements are in the attached appendices.

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 1. Test Configuration

US Tech Test Report:

Report Number:

Customer:

Issue Date:

FCC ID:

Model:

FCC Part 15.249

14-0071

WINK INC.

May 13, 2014

2ACAJ-WINK22

Hub

Table 1. EUT and Peripherals

| PERIPHERAL MANUFACTURER | MODEL NUMBER | SERIAL NUMBER | FCC ID: | CABLES P/D |
|--------------------------------|--------------|--------------------|-----------------------|------------------------|
| Gateway WINK Inc. (EUT) | HUB | Engineering Sample | Pending: 2ACAJ-WINK22 | 1.5 m U Power cable |
| Antenna See antenna details | -- | -- | -- | -- |

S= Shielded, U=Unshielded, P= Power line, D= Data line

2.2 EUT Characterization

The sample used for testing was received by US Tech on April 14, 2014 in good operating condition.

2.3 Test Facility

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA. This site has been fully described and registered with the FCC under site designation number 186022. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number 2982A-1.

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

2.4 Test Equipment

Table 2 describes test equipment used to evaluate this product.

Table 2. Test Instruments

| TEST INSTRUMENT | MODEL NUMBER | MANUFACTURER | SERIAL NUMBER | DATE OF LAST CALIBRATION |
|---------------------------------|------------------|-------------------|--------------------|--------------------------|
| SPECTRUM ANALYZER | E4407B | AGILENT | US41442935 | 11/8/2013 |
| SPECTRUM ANALYZER | 8566B | HEWLETT-PACKARD | 2410A00109 | 2/03/2014 |
| RF PREAMP 100 kHz to 1.3 GHz | 8447D | HEWLETT-PACKARD | 2944A06291 | 2/06/2014 |
| LOOP ANTENNA | SAS-200/562 | A. H. Systems | 142 | 9/12/2013 2 yr cycle |
| BICONICAL ANTENNA | 3110B | EMCO | 9306-1708 | 7/02/2012 2 yr cycle |
| LOG PERIODIC ANTENNA | 3146 | EMCO | 3110-3236 | 6/05/12 2 yr cycle |
| HORN ANTENNA | SAS-571 | A. H. Systems | 605 | 7/23/2013 2 yr cycle |
| PREAMP 1.0 GHz to 26.0 GHz | 8449B | HEWLETT-PACKARD | 3008A00480 | 2/06/14 |
| HORN ANTENNA | 3116 | EMCO | 9505-2255 | 8/9/2012 2 yr cycle |
| LISN | 8028-50-TS24-BNC | Solar Electronics | 910495 & 910496 | 3/19/2014 |
| CALCULATION PROGRAM | N/A | N/A | Ver. 6.0 | N/A |

Note: The calibration interval of the above test instruments is 12 months unless stated otherwise, and all calibrations are traceable to NIST/USA.

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

2.5 Modifications to EUT

No modifications were made by US Tech to bring the EUT into compliance with FCC Part 15, Subpart B, Class B Limits for the receiver and digital portion of the EUT or the Subpart C, Transmitter requirements.

2.6 Measurement Standards (CFR 15.31)

Intentional and unintentional radiators are to use the methods of ANSI C63.4: 2003. Measurements were made on an Open Area Test Site (OATS) wherever possible. For battery powered equipment, new (or fully charged) batteries are used. Section 15.31(m) indicates that if the EUT System operates over the 2400 MHz to 2483.5 MHz ISM band, measurements must be made near the bottom of the band (around 2400 MHz for example) and in the middle of the band (2440 MHz for example) as well as near the top of the band (2483.5 MHz for example).

2.7 Frequency Range of Radiated Measurements (CFR 15.33)

The frequency range is detailed below for intentional and unintentional radiators.

2.7.1 Frequency Range for Intentional Radiators

The spectrum was investigated from the lowest RF signal generated without going below 9 kHz to the 10th harmonic of the highest fundamental transmitter frequency.

2.7.2 Frequency Range for Unintentional Radiators

The spectrum was investigated from the lowest RF signal generated without going below the lowest frequency for which an emissions limit is specified (30 MHz) to the 5th harmonic of the highest fundamental frequency of the digital device (12.5 GHz maximum).

2.7.3 Measurement Detector Function and Bandwidth (CFR 15.35)

On any frequency below 1000 MHz, the limits shown are based upon measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths. On frequencies above 1000 MHz, the radiation limits are based upon the use of measuring instrumentation employing an average detector function.

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

When average detector measurements are specified for use, including emission measurements below 1000 MHz, there is also a corresponding limit for Peak detector measurements having a limit of 20 dB above the corresponding average limit unless a different peak emission limit is specified. Measurements above 1000 MHz utilize a minimum resolution bandwidth of 1 MHz.

When radiated emissions limits are expressed in terms of the average value of the emission and pulsed operation is employed, the measurement field strength is determined by averaging over one complete pulse train (Duty Cycle) including blanking intervals for pulse trains up to 0.1 second in duration. The exact method of calculating the average field strength for this radio is expressed below.

1. Adaptive frequency hopping is turned on, then all 1600 timeslots are used, this requires 1 second

2. Each time slot is therefore 625uS

3. Each BT packet is 366uS

4. A unit is setup as a master or slave but not both

5. Master transmits on odd numbered timeslots, slave on even number time slots

Based on those specifications:

FCC 100mS window = 160 timeslots, if unit is master, then 80 timeslots are used so signal length = $80 \times 366\mu\text{s} = 29\text{mS}$

FCC window =100mS so duty cycle = $29/100 = 29\%$ worst case, duty correction factor = $20 \log$

.29 =

-10.75dB,

DUTY CYCLE= -10.75 dB

Figure 2. Duty Cycle

Note: The transmitter was programmed to transmit at > 98% Duty cycle (the frequency sweeping/hopping was stopped and pulsed operation was disabled) for all testing; therefore throughout the test report the duty cycle factor calculated above was applied where applicable (to AVG detection measurements).

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

2.8 Antenna Requirement (CFR 15.203)

The EUT has an internal radiator; there are no external antenna ports.

Table 3. Allowed Antenna(s)

| MANUFACTURER | TYPE OF ANTENNA | MODEL | REPORT REFERENCE | GAIN dB _i | TYPE OF CONNECTOR |
|--------------|-----------------|-----------|------------------|----------------------|-------------------|
| Antenna 1 | WINK INC. | 'F' Trace | NA | 2.3 | Trace antenna |

2.9 Intentional Radiator, Power Line Conducted Emissions (CFR 15.207)

The EUT requires 12.0 VDC to operate; this power is supplied by switching power supply that is plugged in to AC Mains. The EUT is not intended to be operated without this power supply.

2.10 Intentional Radiator, Radiated Emissions (CFR 15.249 (a), (e))

The EUT was placed into a continuous transmit mode of operation. A preliminary scan was performed on the EUT to find signal frequencies that were caused by the transmitter part of the product and to obtain the worse case result the EUT tested in all X, Y and Z axis. Radiated measurements below 30 MHz were tested with a RBW = 9 kHz; emissions below 1 GHz were tested with a RBW = 120 kHz and radiated measurements above 1 GHz were measured using a RBW = 1 MHz and VBW = 3 MHz.

Test data is found in the tables below.

2.11 Restricted Bands of Operation (CFR 15.205)

Only radiated harmonics and other spurious signals can be permitted to fall into the restricted bands of 15.205. All signals found in paragraph 2.7 above shall be examined for this requirement. Limits are based upon the limits of paragraph 15.209. Above 1 GHz, the limits are for Average value. See Table 4 and Table 5 below for peak and Average measurements. According to CFR 15.35, the peak limits can exceed the average limits by 20 dB.

US Tech Test Report:
 Report Number:
 Customer:
 Issue Date:
 FCC ID:
 Model:

FCC Part 15.249
 14-0071
 WINK INC.
 May 13, 2014
 2ACAJ-WINK22
 Hub

Table 4. Peak Measurements (CFR15.249 (a))

| Tested By: JW | Test: FCC Part 15, Para 15.249(a) | | | Client: Wink Inc. | | | |
|---------------------|-----------------------------------|--------------------|-------------------------------|--------------------|----------------------------|----------------|-------------------|
| | Project: 14-0071 | | | Model: HUB | | | |
| Frequency (MHz) | Test Data (dBuV) | AF+CL-PA (dB/m) | Corrected Results (dBuV/m) | Limits (dBuV/m) | Distance / Polarization | Margin (dB) | Detection Mode |
| Low Channel - Peak | | | | | | | |
| 2402.00 | 65.24 | 31.78 | 97.02 | 114.0 | 3m/Vert. | 17.0 | PK |
| 4945.07 | 48.28 | 3.58 | 51.86 | 74.0 | 3m/Vert. | 22.1 | PK |
| Mid Channel - Peak | | | | | | | |
| 2438.13 | 62.90 | 31.88 | 94.78 | 114.0 | 3m/Vert. | 19.2 | PK |
| 4884.78 | 47.14 | 4.19 | 51.33 | 74.0 | 3m/Vert. | 22.7 | PK |
| High Channel - Peak | | | | | | | |
| 2480.20 | 63.14 | 31.73 | 94.87 | 114.0 | 3m/Vert. | 19.1 | PK |
| 4883.18 | 45.23 | 4.19 | 49.42 | 74.0 | 3m/Vert. | 24.6 | PK |

1. (*) Falls within the restricted bands of CFR 15.205. Limits based on CFR15.209 & 20 dB relaxation for peak measurements of CFR 15.35.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic (25GHz using EMCO 3116 Horn Antenna)
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 2402.00MHz:

| | |
|--|--------------|
| Magnitude of Measured Frequency | 65.24 dBuV |
| +Antenna Factor + Cable Loss+ Amplifier Gain | 31.78 dBVm |
| Corrected Result | 97.02 dBuV/m |

Test Date: April 28, 2014 and May 8, 2014

Tested By

Signature: John C Wynn Name: John Wynn

US Tech Test Report:
 Report Number:
 Customer:
 Issue Date:
 FCC ID:
 Model:

FCC Part 15.249
 14-0071
 WINK INC.
 May 13, 2014
 2ACAJ-WINK22
 Hub

Table 5. Average Measurements (CFR 15.35(b), 15.249(a))

| Tested By: JW | Test: FCC Part 15, Para 15.249(a) | | | Client: Wink Inc. | | | |
|------------------------|-----------------------------------|--------------------|-------------------------------|--------------------|----------------------------|----------------|-------------------|
| | Project: 14-0071 | | | Model: HUB | | | |
| Frequency (MHz) | Test Data (dBuV) | AF+CL-PA (dB/m) | Corrected Results (dBuV/m) | Limits (dBuV/m) | Distance / Polarization | Margin (dB) | Detection mode |
| Low Channel - Average | | | | | | | |
| 2402.00 | 64.85 | 21.03 | 85.88 | 94.0 | 3m/Vert. | 8.1 | AVG |
| 4945.07 | 44.68 | -7.17 | 37.51 | 54.0 | 3m/Vert. | 16.5 | AVG |
| Mid Channel - Average | | | | | | | |
| 2438.13 | 61.90 | 21.13 | 83.03 | 94.0 | 3m/Vert. | 11.0 | AVG |
| 4884.78 | 44.89 | -6.56 | 38.33 | 54.0 | 3m/Vert. | 15.7 | AVG |
| High Channel - Average | | | | | | | |
| 2480.20 | 62.71 | 20.98 | 83.69 | 94.0 | 3m/Vert. | 10.3 | AVG |
| 4883.18 | 45.23 | -6.56 | 38.67 | 54.0 | 3m/Vert. | 15.3 | AVG |

1. (*) Falls within the restricted bands of CFR 15.205. Limits based on CFR15.209 & 20 dB relaxation for peak measurements of CFR 15.35.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic (25GHz using EMCO 3116 Horn Antenna)
3. (~)Measurements taken at 1 meter were extrapolated to 3 meter using a factor of (-9.5 dB).
4. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
5. A -10.75 duty cycle reduction was applied to the average measurements. See section 2.7.3.

Sample Calculation at 2402.00MHz:

| | |
|--|--------------|
| Magnitude of Measured Frequency | 64.85 dBuV |
| +Antenna Factor + Cable Loss+ Amplifier Gain +Duty Cycle | 21.03 dB/m |
| Corrected Result | 85.88 dBuV/m |

Test Date: April 28, 2014 and May 8, 2014

Tested By
 Signature: John C Wynn Name: John Wynn

2.12 Band Edge Measurements (CFR15.249(d))

Band Edge measurements were made at a Low Channel and High Channel peak at highest EUT related emission outside the upper and lower occupied bandwidth. A measurement was made of the fundamental and the emission was measured using a quasi peak setting. A Resolution Bandwidth of $> 1\%$ of the emission bandwidth was used. This procedure was repeated for the high channel. The limits were derived as described in the following sections.

2.12.1 High Band Edge

Above 2483.5 MHz the limit per section 15.249(d) is 50 dB below the fundamental or the value expressed by CFR 15.209 (54 dBuV/m) whichever is the lesser attenuation.




Figure 3. Radiated Band Edge – Low Channel Delta – Peak

Note: Low channel sideband is greater than 20 dB

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 4. Radiated Band Edge – High Channel Delta – Average

Note: Low channel sideband is greater than 20 dB

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 5. Radiated Band Edge – High Channel Delta – Peak

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 6. Radiated Band Edge – High Channel Delta - Average

Test Date: May 8, 2014

Tested By

Signature:



Name: John Wynn

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

Calculation of worst case PEAK upper band edge measurement:

| | | |
|--|---------------|---------------|
| High Channel Corrected Measured Value from Table 5 | 98.87 | dBuV |
| <u>High Channel Band Edge Delta from Figure 7</u> | <u>-57.52</u> | <u>dB</u> |
| Calculated Result | 41.35 | dBuV/m |
| Average Limit + 20dB Relaxation for PEAK | 74.00 | dBuV/m |
| <u>Calculated Result</u> | <u>-41.35</u> | <u>dBuV/m</u> |
| Band Edge Margin | 32.65 | dBuV/m |

Calculation of worst case AVERAGE upper band edge measurement:

| | | |
|--|---------------|---------------|
| High Channel Corrected Measured Value from Table 6 | 83.69 | dBuV |
| <u>High Channel Band Edge Delta from Figure 7</u> | <u>-45.65</u> | <u>dB</u> |
| Calculated Result | 38.04 | dBuV/m |
| Peak Limit | 54.00 | dBuV/m |
| <u>Calculated Result</u> | <u>38.04</u> | <u>dBuV/m</u> |
| Band Edge Margin | 15.96 | dBuV/m |

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub

2.13 6 dB Bandwidth Measurement per CFR 15.249

The EUT antenna port was connected to a spectrum analyzer having a 50Ω input impedance. Measurements were performed similar to the method of FCC, KDB Publication No. DA for a bandwidth of 6 dB. The RBW was set to approximately 1/100 of the manufacturers claimed RBW and with the $VBW \geq RBW$.

Table 6. Bandwidth Measurements, 6 dB

| Frequency (MHz) | 6dB Bandwidth Limit (MHz) | 6dB Bandwidth Measured (MHz) |
|-----------------|---------------------------|------------------------------|
| 2402 | <0.5 | 0.159 |
| 2440 | <0.5 | 0.158 |
| 2480 | <0.5 | 0.159 |

Test Date: April 30, 2014

Tested By

Signature:

Name: John Wynn

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 7. Low Channel 20 dB Bandwidth

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 8. Mid Channel 20dB Bandwidth

US Tech Test Report:
Report Number:
Customer:
Issue Date:
FCC ID:
Model:

FCC Part 15.249
14-0071
WINK INC.
May 13, 2014
2ACAJ-WINK22
Hub




Figure 9. High Channel 20dB Bandwidth