Total 35 Pages

# RF TEST REPORT

Test item

Smart Beacon

Model No.

Smart Beacon

Order No.

DEMC1405-01625

Date of receipt

2014-05-02

Test duration

2014-05-15~ 2014-05-29

Date of issue

2014-06-02

Use of report

FCC Original Grant

Applicant : SK Planet, Inc.

475 Brannan Street, Suite 420, San Francisco, CA 94107

Test laboratory :

Digital EMC Co., Ltd.

42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 449-935

Test specification

: FCC Part 15 Subpart C 247

Test environment

: See appended test report

Test result

□ Pass

☐ Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:

Reviewed by:

Engineer HyunSu Son Deputy General Manager

HongHee Lee

 DEMC1405-01625
 FCCID:
 2ACB7SKB100

 Report No.:
 DRTFCC1406-0701

# **Test Report Version**

Test Report No.	Date	Description
DRTFCC1406-0701	Jun. 02, 2014	Initial issue

FCCID: **2ACB7SKB100**Report No.: **DRTFCC1406-0701** 

# **Table of Contents**

1. GENERAL INFORMATION	. 4
2. EUT DESCRIPTION	. 4
3. SUMMARY OF TESTS	. 5
4. TEST METHODOLOGY	. 6
4.1 EUT CONFIGURATION	6
4.2 EUT EXERCISE	6
4.3 GENERAL TEST PROCEDURES	6
4.4 DESCRIPTION OF TEST MODES	6
5. INSTRUMENT CALIBRATION	. <b>7</b>
6. FACILITIES AND ACCREDITATIONS	. 7
6.1 FACILITIES	7
6.2 EQUIPMENT	7
7. ANTENNA REQUIREMENTS	. 7
8. TEST RESULT	. 8
8.1 6dB Bandwidth Measurement	8
8.2 Maximum Peak Conducted Output Power	
8.3 Maximum Power Spectral Density	14
8.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions	
8.5 Radiated Measurement	
8.5.1 Radiated Spurious Emissions	
8.6 POWERLINE CONDUCTED EMISSIONS	
8.70ccupied Bandwidth	
9. LIST OF TEST EQUIPMENT	
APPENDIX I	34
APPENDIX II	34

 DEMC1405-01625
 FCCID:
 2ACB7SKB100

 DEMC1405-01625
 Report No.:
 DRTFCC1406-0701

## 1. GENERAL INFORMATION

**Applicant**: SK Planet, Inc.

Address : 475 Brannan Street, Suite 420, San Francisco, CA 94107

FCC ID : 2ACB7SKB100

**EUT** : Smart Beacon

Model : Smart Beacon

Additional Model(s) : N/A

**Data ofTest** : 2014-05-15 ~ 2014-05-29

Contact person : David Hu

## 2. EUT DESCRIPTION

Product	Smart Beacon		
Model Name Smart Beacon			
Power Supply	DC 5 V		
Frequency Range	2402 ~ 2480MHz(40 channels)		
Max. RF Output Power	3.31 dBm		
Modulation Type	GFSK		
Antenna Specification	Antenna Type: Internal Antenna Gain: 2.26 dBi(PK)		

 DEMC1405-01625
 FCCID:
 2ACB7SKB100

 DEMC1405-01625
 Report No.:
 DRTFCC1406-0701

## 3. SUMMARY OF TESTS

FCC Part Section(s)	RSS Section(s)	Parameter	Limit	Test Condition	Status Note 1		
I. Transmitter	I. Transmitter Mode (TX)						
15.247(a)	RSS-210 [A8.2]	6 dB Bandwidth	> 500 kHz		С		
15.247(b)	RSS-210 [A8.4]	Transmitter Output Power	< 1Watt		С		
15.247(d)	RSS-210 [A8.5]	A8.5] Edge BW S-210 Transmitter Power Spectral		Conducted	C		
15.247(e)	RSS-210 [A8.2]				С		
-	RSS Gen [4.6.1]	Occupied Bandwidth (99%)	RSS-Gen(4.6.1)		NA		
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Restricted Bands and Radiated <fcc 15.209="" limits<="" td=""><td>CNote2</td></fcc>		CNote2		
15.207	RSS-Gen [7.2.4]	AC Conducted Emissions	< FCC 15.207 limits	AC Line Conducted	С		
15.203	-	Antenna Requirements	FCC 15.203	-	С		

Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable

Note 2: This test item was performed in each axis and the worst case data was reported.

#### 4. TEST METHODOLOGY

Generally the tests were performed according to the KDB558074 v03r1. And ANSI C63.10-2009 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

## **4.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **4.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### 4.3 GENERAL TEST PROCEDURES

#### **Conducted Emissions**

According to the requirements in Section 6.2 of ANSI C63.10, the EUT is placed on the turntable, which is 0.8 m above ground plane and the conducted emissions from the EUT are measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and Average detector.

#### **Radiated Emissions**

The EUT is placed on a turntable, which is 0.8 m above ground plane. The turntable shall rotate360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10

#### 4.4 DESCRIPTION OF TEST MODES

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting. The Bluetooth low energy mode and below low, middle and high channels were tested and reported.

Test Mode	Channel	Frequency [MHz]
	0	2402
BT LE	19	2440
	39	2480

## 5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

## 6. FACILITIES AND ACCREDITATIONS

#### **6.1 FACILITIES**

The open area test site(OATS) or semi anechoic chamber and conducted measurement facility used to collect the radiated and conducted test data are located at the 38, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 449-935. The site is constructed in conformance with the requirements.

- Semi anechoic chamber registration Number:678747

## **6.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

#### 7. ANTENNA REQUIREMENTS

## According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

The internal antenna is attached on the main PCB using the special spring tension. Therefore this E.U.T Complies with the requirement of §15.203

## 8. TEST RESULT

#### 8.1 6dB Bandwidth Measurement

## Test Requirements and limit, §15.247(d) & RSS-210[A8.2]

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

#### **■TEST CONFIGURATION**

Refer to the APPENDIX I.

#### **■ TEST PROCEDURE**

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of KDB558074 v03r1.

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.

#### (RBW:100kHz/VBW:300kHz)

- 3. Detector = **Peak**.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


## **■ TEST RESULTS: Comply**

Test Mode	Frequency [MHz]	Test Results [kHz]	
	2402	732.5	
LE	2440	743.9	
	2480	714.0	

## **■ RESULTPLOTS**

#### 6 dB Bandwidth

Test Frequency: 2402 MHz




#### 6 dB Bandwidth

Test Frequency: 2440 MHz



## 6 dB Bandwidth

## Test Frequency: 2480 MHz



## 8.2 Maximum Peak Conducted Output Power

## Test Requirements and limit, §15.247(b) & RSS-210[A8.4]

A transmitter antenna terminal of EUT is connected to the input of a spectrum analyzer.

Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

#### TEST CONFIGURATION

Refer to the APPENDIX I.

#### TEST CONFIGURATION:

Maximum Peak Conducted Output Power is measured using Measurement Procedure Option1 of KDB558074 v03r1.

- 1. Set the RBW ≥ DTS bandwidth. Actual RBW = 2 MHz
- 2. Set VBW ≥ 3 x RBW. Actual VBW = 6 MHz
- 3. Set span  $\ge$  3 x RBW.
- 4. Sweep time = auto couple
- 5. Detector = peak
- 6. Trace mode = max hold
- 7. Allow trace to fully stabilize
- 8. Use peak marker function to determine the peak amplitude level.

## ■TEST RESULTS: Comply


Test Mode	Test Results[dBm]			
	2402 MHz	2440 MHz	2480 MHz	
LE	3.16	3.29	3.31	

## **■ RESULT PLOTS**

Peak Output Power Test Frequency: 2402 MHz



Peak Output Power Test Frequency: 2440 MHz



**Peak Output Power** 

Test Frequency: 2480 MHz



## 8.3 Maximum Power Spectral Density.

## Test requirements and limit, §15.247(e) & RSS-210[A8.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard –specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segmentwithin the fundamental EBW during any time interval of continuous transmission.

#### **■TEST CONFIGURATION**

Refer to the APPENDIX I.

#### **■ TEST PROCEDURE:**

#### Method PKPSD of KDB558074 v03r1 is used.


- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to **1.5 times** the DTS bandwidth.
- 3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 4. Set the VBW ≥3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### **■TEST RESULTS: Comply**


Test Mode	Frequency [MHz]	PKPSD [dBm]		
	2402	-11.42		
LE	2440	-11.80		
	2480	-11.88		

## **■ RESULT PLOTS**

Maximum PKPSD Test Frequency: 2402 MHz




## Maximum PKPSD Test Frequency: 2440 MHz



Maximum PKPSD

Test Frequency: 2480 MHz



## 8.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions

## Test requirements and limit, §15.247(d) & RSS-210[A8.5]

**§15.247(d)** specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in band average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

#### **■TEST CONFIGURATION**

Refer to the APPENDIX I.

#### **■ TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer.

#### - Measurement Procedure 1 - Reference Level

- 1. Set instrument center frequency to DTS channel center frequency.
- 2. Set the span to  $\geq$  1.5 times the DTS bandwidth.
- 3. Set the RBW = 100 kHz.
- 4.Set the VBW ≥ 3 x RBW.
- 5.Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum PSD level

#### - Measurement Procedure 2 - Unwanted Emissions

- 1. Set the center frequency and span to encompass frequency range to be measured.
- 2. Set the RBW = 100 kHz.( Actual 1 MHz , See below note)
- 3. Set the VBW ≥3 x RBW.(Actual 3 MHz, See below note)
- 4. Detector = **peak**.
- 5. Ensure that the number of measurement points ≥ span/RBW
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
- 9. Use the peak marker function to determine the maximum amplitude level.

**Note:** The conducted spurious emission was tested with below settings.

Frequency range: 9 kHz ~ 30 MHz

RBW = 100kHz, VBW = 300kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT: 1001

Frequency range: 30 MHz ~ 10 GHz, 10 GHz~25 GHz

RBW= 1MHz, VBW= 3MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT: 40001

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SAPN = 100 MHz and BINS = 2001 to get accurate emission level within 100 kHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

**■TEST RESULTS: Comply** 


**■ RESULT PLOTS** 

LE & 2402 MHz


#### Reference




## Low Band-edge




FCCID: **2ACB7SKB100** 





**Conducted Spurious Emissions** 




## LE & 2440 MHz

#### Reference





**Conducted Spurious Emissions** 



FCCID: **2ACB7SKB100** 








### LE & 2480 MHz


#### Reference











## **Conducted Spurious Emissions**



#### 8.5 Radiated Measurement.

#### 8.5.1 Radiated Spurious Emissions.

## Test Requirements and limit, §15.247(d) & RSS-210[A8.5]

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and (b), then the 15.209(a) limit in the table below has to be followed

#### • FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3


<sup>\*\*</sup> Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

• FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:

	<u> </u>	ennosions are penni	, <u>, , , , , , , , , , , , , , , , , , </u>		
MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.52025	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	12.57675 ~	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	12.57725	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	13.36 ~ 13.41	162.0125 ~ 167.17	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.42 ~ 16.423	167.72 ~ 173.2	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	16.69475 ~	240 ~ 285	2655 ~ 2900		
8.291 ~ 8.294	16.69525	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	16.80425 ~	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	16.80475	608 ~ 614	3345.8 ~ 3358		
	25.5 ~ 25.67	960 ~ 1240	3600 ~ 4400		
	37.5 ~ 38.25				
	73 ~ 74.6				
	74.8 ~ 75.2				

<sup>•</sup> FCC Part 15.205(b): The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

### **Test Configuration**



#### **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

#### Note: Measurement Instrument Setting for Radiated Emission Measurements.

1. Frequency Range Below 1 GHz
RBW = 100 or 120 kHz, VBW = 3 x RBW, Detector = Peak or Quasi Peak

#### 2. Frequency Range > 1 GHz

#### Peak Measurement> 1 GHz

RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

## Average Measurement> 1GHz

RBW = 1MHz, VBW ≥ 1/T, Detector = Peak, Sweep Time = Auto, Trace Mode = Max Hold for at least 50 \* (1/Duty cycle) traces

Mode	Duty Cycle(%) T <sub>on</sub> (us)		1/T <sub>on</sub> (kHz)	Determined VBW Setting	
BT(LE)	63.94	0.399	2.506	3kHz	

## 9 kHz ~ 25GHz Data

## Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2389.69	V	Υ	PK	47.05	-4.20	42.85	74.00	31.15
2389.84	V	Υ	AV	35.94	-4.20	31.74	54.00	22.26
4804.44	Н	Х	PK	52.23	4.84	57.07	74.00	16.93
4803.73	Н	Х	AV	45.21	4.84	50.05	54.00	3.95
7206.64	Н	Х	PK	47.72	11.37	59.09	74.00	14.91
7205.35	Н	Х	AV	37.63	11.37	49.00	54.00	5.00

## Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4880.51	Η	Х	PK	51.98	5.11	57.09	74.00	16.91
4879.66	Τ	Χ	AV	44.45	5.11	49.56	54.00	4.44
7320.13	Τ	Χ	PK	48.53	11.46	59.99	74.00	14.01
7319.41	Н	Х	AV	38.81	11.46	50.27	54.00	3.73

## Highest Channel

Thighest Charmer										
Frequency (MHz)	ANT Position (Axis)		Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)		
2483.64	V	Х	PK	47.99	-4.06	43.93	74.00	30.07		
2483.62	V	Χ	AV	36.10	-4.06	32.04	54.00	21.96		
4959.58	Ι	Χ	PK	52.00	5.40	57.40	74.00	16.60		
4959.97	Ι	Χ	AV	45.42	5.40	50.82	54.00	3.18		
7440.81	Η	Χ	PK	50.47	11.56	62.03	74.00	11.97		
7440.54	Н	Χ	AV	41.42	11.56	52.98	54.00	1.02		

#### **Note**

- 1. No other spurious and harmonic emissions were reported greater than listed emissions above table.
- 2. Above listed point data is the worst case data.
- 3. Sample Calculation.

 $\begin{aligned} & \text{Margin} = \text{Limit} - \text{Result} & / & \text{Result} = \text{Reading} + \text{T.F} / & \text{T.F} = \text{AF} + \text{CL} - \text{AG} \\ & \text{Where, T.F} = \text{Total Factor,} & \text{AF} = \text{Antenna Factor,} & \text{CL} = \text{Cable Loss,} & \text{AG} = \text{Amplifier Gain} \end{aligned}$ 

## 8.6 POWERLINE CONDUCTED EMISSIONS

## Test Requirements and limit, §15.207&RSS-Gen[7.2.2]

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range	Conducted Limit (dBuV)					
(MHz)	Quasi-Peak	Average				
0.15 ~ 0.5	66 to 56 *	56 to 46 *				
0.5 ~ 5	56	46				
5 ~ 30	60	50				

<sup>\*</sup> Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

## **Test Configuration**

See test photographs for the actual connections between EUT and support equipment.

#### **TEST PROCEDURE**

- 1. The EUT is placed on a wooden table 80 cm above the reference groundplane.
- 2. The EUT is connected via LISN to a test power supply.
- 3. The measurement results are obtained as described below:
- 4. Detectors Quasi Peak and Average Detector.

FCCID: **2ACB7SKB100** DEMC1405-01625 DRTFCC1406-0701 Report No.:

## **■RESULT PLOTS**

## **AC Line Conducted Emissions (Graph)**

Test Mode: LE & 2440MHz



# Results of Conducted Emission

Digital EMC

Date: 2014-05-29


Model No. Type Serial No. **Test Condition** 


Smart Beacon Identical prototype Referrence No. Power Supply Temp/Humi. Operator

120 V 60 Hz 24 'C 43 % R.H. H.S.SON

Memo

LIMIT: FCC P15.207 QP FCC P15.207 AV





 DEMC1405-01625
 FCCID:
 2ACB7SKB100

 DEMC1405-01625
 Report No.:
 DRTFCC1406-0701

## **AC Line Conducted Emissions (List)**

Test Mode: LE& 2440MHz

# Results of Conducted Emission

Digital EMC Date : 2014-05-29

Model No. Type

Smart Beacon

Referrence No. Power Supply Temp/Humi.

Operator

: 120 V 60 Hz : 24 'C 43 % R.H. : H.S.SON

Serial No. : Identical prototype Test Condition : LE

Memo

LIMIT : FCC P15.207 QP FCC P15.207 AV

	NO	FREQ	READ	ING	C.FACTOR	REST	ULT	LIM	IIT	MAR	GIN	PHASE
			OP	AV		QP	AV	OP	AV	OP	AV	
		[MHz]	[dBuV]		[dB]			-	[dBuV]	-		
_		[	[	,	53	[ ]	E	1,000	[		<u>.</u>	31
	1	0.15326	48.1	33.0	0.1	48.2	33.1	65.8	55.8	17.6	22.7	N
	2	0.19458	43.9	31.0	0.1	44.0	31.1	63.8	53.8	19.8	22.7	N
	3	0.37850	38.2	28.0	0.1	38.3	28.1	58.3	48.3	20.0	20.2	N
	4	0.52418	47.8	40.9	0.1	47.9	41.0	56.0	46.0	8.1	5.0	N
	5	0.67307	34.8	27.4	0.1	34.9	27.5	56.0	46.0	21.1	18.5	N
	6	0.90950	31.7	23.3	0.1	31.8	23.4	56.0	46.0	24.2	22.6	N
	7	3.31528	33.4	27.8	0.3	33.7	28.1	56.0	46.0	22.3	17.9	N
	8	5.85488	24.7	17.6	0.3	25.0	17.9	60.0	50.0	35.0	32.1	N
	9	8.41036	28.1	22.3	0.2	28.3	22.5	60.0	50.0	31.7	27.5	N
	10	16.84232	12.9	7.1	0.3	13.2	7.4	60.0	50.0	46.8	42.6	N
	11	0.15430	52.8	34.6	0.1	52.9	34.7	65.8	55.8	12.9	21.1	L1
	12	0.19545	48.2		0.1	48.3	34.9	63.8	53.8	15.5	18.9	L1
	13	0.36750	36.4	26.6	0.2	36.6	26.8	58.6	48.6	22.0	21.8	L1
	14	0.52554	46.7	39.3	0.2	46.9	39.5	56.0	46.0	9.1	6.5	L1
	15	0.62929	33.6	25.3	0.2	33.8	25.5	56.0	46.0	22.2	20.5	L1
	16	1.66772	31.4	23.5	0.2	31.6	23.7	56.0	46.0	24.4	22.3	L1
	17	3.62136	29.8	23.1	0.3	30.1	23.4	56.0	46.0	25.9	22.6	L1
	18	6.42012		23.7	0.3	28.6	24.0	60.0	50.0	31.4	26.0	L1
	19	8.41180	29.9	23.7			24.0	60.0	50.0	29.8	26.0	L1
	20	15.62360		9.1	0.4	15.4	9.5	60.0	50.0	44.6		L1

## 8.70ccupied Bandwidth

## Test Requirements, RSS-Gen [4.6.1]

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

#### **■ TEST CONFIGURATION**

#### **■TEST PROCEDURE**

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual.

#### **■ TEST RESULTS:N/A**

 DEMC1405-01625
 FCCID:
 2ACB7SKB100

 Report No.:
 DRTFCC1406-0701


# 9. LIST OF TEST EQUIPMENT

Туре	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	E4440A	13/10/24	14/10/24	US45303051
MXA Signal Analyzer	Agilent Technologies	N9020A	13/09/24	14/09/24	MY50200834
Digital Multimeter	H.P	34401A	14/02/27	15/02/27	3146A13475
Dynamic Measurement DC Source	Agilent Technologies	66332A	14/02/07	15/02/07	GB37470190
Thermohygrometer	BODYCOM	BJ5478	14/05/13	15/05/13	120612-2
Vector Signal Generator	Rohde Schwarz	SMJ100A	14/01/07	15/01/07	100148
Signal Generator	Rohde Schwarz	SMF100A	13/07/22	14/07/22	102341
High-pass filter	Wainwright	WHKX3.0	13/09/12	14/09/12	9
LOOP Antenna	Schwarzbeck	FMZB1513	14/04/29	16/04/29	1513-128
BILOG ANTENNA	SCHAFFNER	CBL6112B	12/11/06	14/11/06	2737
Horn Antenna	ETS	3115	13/02/28	15/02/28	00021097
HORN ANT	A.H.Systems	SAS-574	13/03/20	15/03/20	154
Amplifier (22dB)	H.P	8447E	14/01/07	15/01/07	2945A02865
Amplifier (30dB)	Agilent	8449B	14/02/27	15/02/27	3008A00370
EMI TEST RECEIVER	R&S	ESU	14/01/07	15/01/07	100014
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESR	14/02/07	15/02/07	101767
CVCF	NF	4420	13/09/12	14/09/12	3049354420023
LISN	R&S	ESH2-Z5	13/09/12	14/09/12	828739/006
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A/ MA2411B	13/10/29	14/10/29	1338004 / 1306053

## **APPENDIX I**

## **Conducted Test set up Diagram &Path loss Information**

#### **•**Conducted Measurement



#### Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)	
0.03	1.24	15	2.28	
1	1.32	20	2.46	
2402 & 2440 & 2480	1.48	25	2.73	
5	1.50	-	-	
10	1.69	-	-	

Note. 1: The path loss from EUT to Spectrum analyzer was measured and used for test. Path loss = Cable A

## **Duty cycle plots**

#### TEST PROCEDURE

## Duty Cycle measured using section 6.0 b) of KDB558074 v03r1:

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.


Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \le 16.7$  microseconds.)

Test Mode: BT LE & 2440 MHz

#### Test Plots:

## **Duty Cycle**



Duty Cycle =  $T_{on} / (T_{on} + T_{off}) = 399 \text{ us } /624 \text{ us} = 63.94 \%$