

## FCC Part 1 Subpart I FCC Part 2 Subpart J **INDUSTRY CANADA RSS 102 ISSUE 5**

#### RF EXPOSURE REPORT

**FOR** 

**BLE SMART MEASURE PRO** 

**MODEL NUMBER: STHT77366** 

**FCC ID: 2ACBG3000** IC ID: 11952A-3000

**REPORT NUMBER: 15R21104-E5** 

**ISSUE DATE: SEPTEMBER 23, 2015** 

Prepared for ikeGPS 1000 2<sup>nd</sup> Ave, Suite 1730 Seattle, WA 98104 U.S.A.

Prepared by

**UL VERIFICATION SERVICES INC. 47173 BENICIA STREET** FREMONT, CA 94538, U.S.A.

TEL: (510) 771-1000 FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

## **Revision History**

Rev.	Issue Date	Revisions	Revised By
	9/23/15	Initial Issue	P. Zhang

# **TABLE OF CONTENTS**

1. A	TTESTATION OF TEST RESULTS	4
2. T	EST METHODOLOGY	5
3. R	EFERENCES	5
4. F	ACILITIES AND ACCREDITATION	5
5. N	AXIMUM PERMISSIBLE RF EXPOSURE	е
5.1.	FCC RULES	6
5.2.	IC RULES	7
5.3.	EQUATIONS	8
5.4.	LIMITS AND IC EXEMPTION	.10
6. S	TANDALONE SAR TEST EXCLUSION CONSIDERATIONS	.11
6.1.	FCC	.11
6.2	INDUSTRY CANADA	12

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** ikeGPS

**EUT DESCRIPTION:** BLE SMART MEASURE PRO

MODEL: STHT77366

**SERIAL NUMBER:** 2175294 (Conducted); 2175293 (Radiated)

**DATE TESTED:** JULY 30 –AUGUST 10, 2015

#### APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC PART 1 SUBPART I & PART 2 SUBPART J Pass
INDUSTRY CANADA RSS 102 ISSUE 5 Pass

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For

UL Verification Services Inc. By:

Calculated By:

PENG ZHANG

CONSUMER TECHNOLOGY DIVISION

**PROJECT LEAD** 

**UL VERIFICATION SERVICES INC** 

**CHARLES VERGONIO** 

CONSUMER TECHNOLOGY DIVISION

LAB ENGINEER

**UL VERIFICATION SERVICES INC** 

#### 2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01 and IC Safety Code 6.

## 3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. Document 15R21104-E1 for operation in the 2.4 GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from the applicable test reports.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

## 5. MAXIMUM PERMISSIBLE RF EXPOSURE

#### 5.1. **FCC RULES**

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Lim	nits for Occupational	I/Controlled Exposu	res			
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842# 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34	614 824/f	1.63 2.19/f	*(100) *(180/f²)	30 30		

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

<sup>\* =</sup> Plane-wave equivalent power density
NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## 5.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment) Frequency Range | Electric Field Magnetic Field **Power Dentisty** Reference Period (MHz) (V/m rms) (A/m rms) (W/m<sup>2</sup>)(minutes) 0.003-10 21 83 90 Instantaneous\* 6\*\* 0.73/f0.1 - 101.1-10 87/f 0.56\*\* 0.0728 6 10-20 27.46 -2 58.07/ f<sup>0.25</sup>  $0.1540/f^{0.25}$ 8.944/ f0.5 20-48 6 6 22.06 0.05852 1.291 48-300 3.142 f 0.34170.008335 f 0.34170.02619 f 0.6834300-6000 6 6000-15000 61.4 0.163 10 6 616000/ f 1.2 15000-150000 61.4 0.163 10  $0.158 f^{0.5}$ 616000/f1.2 150000-300000 4.21 x 10-4 f 0.5 6.67 x 10<sup>-5</sup> f

Note: f is frequency in MHz.

DATE: SEP 23, 2015

FCC ID:2ACBG3000

<sup>\*</sup> Based on nerve stimulation (NS).

<sup>\*\*</sup> Based on specific absorption rate (SAR).

REPORT NO: 15R21104-E5 MODEL NUMBER: STHT77366

### 5.3. EQUATIONS

#### **POWER DENSITY**

Power density is given by:

 $S = EIRP / (4 * Pi * D^2)$ 

Where

S = Power density in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power in mW D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

#### **DISTANCE**

Distance is given by:

D = SQRT (EIRP / (4 \* Pi \* S))

Where

D = Separation distance in cm EIRP = Equivalent Isotropic Radiated Power in mW S = Power density in mW/cm<sup>2</sup>

#### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

Source-based time-averaged EIRP = (DC / 100) \* EIRP

Where

DC = Duty Cycle in %, as applicable EIRP = Equivalent Isotropic Radiated Power in W DATE: SEP 23, 2015

FCC ID:2ACBG3000

 REPORT NO: 15R21104-E5
 DATE: SEP 23, 2015

 MODEL NUMBER: STHT77366
 FCC ID:2ACBG3000

## MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

Total EIRP = (EIRP1) + (EIRP2) + ... + (EIRPn)

where

EIRPx = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

#### MIMO AND COLOCATED TRANSMITTERS

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as (Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

#### 5.4. LIMITS AND IC EXEMPTION

#### **VARIABLE LIMITS**

For mobile radio equipment operating in the cellular phone band, the lowest power density limit is calculated using the lowest frequency:

824 MHz / 1500 = 0.55 mW/cm<sup>2</sup> (FCC) 824 MHz / 150 = 5.5 W/m<sup>2</sup> (IC).

#### **FIXED LIMITS**

For operation in the PCS band, the 2.4 GHz band and the 5 GHz bands:

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup> From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m<sup>2</sup>

#### **INDUSTRY CANADA EXEMPTION**

RSS-102 Clause 2.5.2 RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 4.49/f<sup>0.5</sup> W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10<sup>-2</sup> f<sup>0.6834</sup> W (adjusted for tune-up tolerance), where f is in MHz;(2.67W for 2.4GHz and 4.47W for 5GHz)
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

# 6. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

#### 6.1. FCC

SAR test exclusion in accordance with KDB 447498.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ]  $\leq$  3.0, for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

SAR Exclusion Calculations Table for Portable Devices (separation distance < 20cm)

Antenna	Tx	Frequency	Avg Output power		Separation	Calculated
Antenna	I X	(MHz)	dBm	mW	distances (mm)	Threshold
BT LE	BT LE	2412	-10.91	0	5	0.0

#### Conclusion:

The computed value is < 3; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

#### 6.2. INDUSTRY CANADA

Industry Canada notice 2013 DRS0911 states that the SAR exclusion limits contained in Draft RSS-102 issue 5 will be accepted prior to its release. The SAR exclusion table from Draft RSS-102 issue 5 is reproduced below:

Table 1: SAR evaluation - exemption limits for routine evaluation based on frequency and separation distance.

	Exemption Limits (mW)						
Frequency MHz	At separation distance of ≤5mm	At separation distance of 10mm	At separation distance of 15mm	At separation distance of 20mm	At separation distance of 25mm		
≤300	71 mW	101 mW	132 mW	162 mW	193 mW		
450	52 mW	70 mW	88 mW	106 mW	123 mW		
835	17 mW	30 mW	42 mW	55 mW	67 mW		
1900	7 mW	10 mW	18 mW	34 mW	60 mW		
2450	4 mW	7 mW	15 mW	30 mW	52 mW		
3500	2 mW	6 mW	16 mW	32 mW	55 mW		
5800	1 mW	6 mW	15 mW	27 mW	41 mW		

	Exemption Limits (mW)						
Frequency MHz	At separation distance of 30mm	At separation distance of 35mm	At separation distance of 40mm	At separation distance of 45mm	At separation distance of ≥50mm		
≤300	223 mW	254 mW	284 mW	315 mW	345 mW		
450	141 mW	159 mW	177 mW	195 mW	213 mW		
835	80 mW	92 mW	105 mW	117 mW	130 mW		
1900	99 mW	153 mW	225 mW	316 mW	431 mW		
2450	83 mW	123 mW	173 mW	235 mW	309 mW		
3500	86 mW	124 mW	170 mW	225 mW	290 mW		
5800	56 mW	71 mW	85 mW	97 mW	106 mW		

The minimum antenna to user distance that will be encountered in normal use is 0mm. This results in an exemption limit of 4mW at 2450 MHz.

As the maximum output power is 0.08mW (0.02mW EIRP) the DUT qualifies for SAR test exclusion.

#### **END OF REPORT**