

# M.B. Compliance Solutions

## **RF Exposure**

For the

**Ionit Networks LLC** 

**Ultrasonic Fluid Level Transmitter** 

May 20, 2014

**Prepared for:** 

Ionit Networks LLC

5600 Post Road, Suite 114, Unit 225

East Greenwich, RI 02818

## **Prepared By:**

H.B. Compliance Solutions

5005 S. Ash Avenue, Suite # A-10

Tempe, Arizona 85282

**Reviewed By:** 

Hoosamuddin Bandukwala

Cert # ATL-0062-E



#### Standalone SAR Test Exclusion Consideration

According to KDB447498D01 General RF Exposure Guidance v05

4.3.1. Standalone SAR test exclusion considerations Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·

#### $[Vf(GHz)] \le 3.0$ for 1-g SAR and $\le 7.5$ for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Maximum peak output power at antenna input terminal = 8.41 (dBm) Maximum peak output power at antenna input terminal = 6.9 (mW) Antenna gain (typical) = -2(dBi) Prediction frequency = 916.2 (MHz) or 0.9 (GHZ)



## To solve for the EIRP;

```
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f} (GHz)]
General RF Exposure = (6.9 / 5 mm) x \sqrt{0}.9GHz = 1.309 ①
SAR requirement:
```

S= 3 0 ② ;

① < ②.

Therefore SAR report is not required.

# **END OF TEST REPORT**