

MRT Technology (Taiwan) Co., Ltd

Phone: +886-3-3288388 Fax: +886-3-3288918 Web: www.mrt-cert.com Report No.: 1801TW1901-U3 Report Version: 1.0 Issue Date: 2018-01-31

MEASUREMENT REPORT C2PC

FCC PART 15.247 Bluetooth

FCC ID: 2ACC5-GT500

APPLICANT: AMobile Intelligent Corp.

Application Type: Certification

Product: 5" Rugged Android™ Handheld Device with LTE solution

Model No.: GT-500 N

Trad Mark: AMobile

FCC Classification: (DSS) FCC Part 15 Spread Spectrum Transmitter

FCC Rule Part(s): Part 15.247

Test Procedure(s): ANSI C63.10-2013, DA 00-705

Test Date: January 24 ~ 30, 2018

Tested By : Fran Chen

(Fran Chen)

Reviewed By : Paddy Chen

(Paddy Chen)

Approved By : Any her

(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and DA 00-705. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

FCC ID: 2ACC5-GT500 Page Number: 1 of 52



Revision History

Report No.	Version	Description	Issue Date	Note
1801TW1901-U3	1.0	Original Report	2018-01-31	

Note:

- (1) This report is C2PC. The reason for variation is to remove the barcode scanner, other hardware is unchanged.
- (2) The verification of this report is according to the worse case for Radiated spruious emission from the original report (Report No.: 1610TW0501-U3, Grant date: 2016/12/02).

FCC ID: 2ACC5-GT500 Page Number: 2 of 52



CONTENTS

De	scriptic	on	Page
1.	INTR	ODUCTION	7
	1.1.	Scope	7
	1.2.	MRT Test Location	7
2.	PRO	DUCT INFORMATION	8
	2.1.	Equipment Description	8
	2.2.	Product Specification Subjective to this Standard	
	2.3.	Test Mode	8
	2.4.	Operation Frequency / Channel List	9
	2.5.	Test Configuration	10
	2.6.	Test Software	10
	2.7.	EMI Suppression Device(s)/Modifications	10
	2.8.	Labeling Requirements	10
3.	DESC	CRIPTION of TEST	11
	3.1.	Evaluation Procedure	11
	3.2.	AC Line Conducted Emissions	11
	3.3.	Radiated Emissions	12
4.	ANTE	ENNA REQUIREMENTS	13
5.	TEST	EQUIPMENT CALIBRATION DATE	14
6.	MEA	SUREMENT UNCERTAINTY	15
7.	TEST	* RESULT	16
	7.1.	Summary	16
	7.2.	20dB Bandwidth Measurement	17
	7.2.1.	Test Limit	17
	7.2.2.	Test Procedure used	17
	7.2.3.	Test Setting	17
	7.2.4.	Test Setup	17
	7.2.5.	Test Result	18
	7.3.	Output Power Measurement	19
	7.3.1.	Test Limit	19
	7.3.2.	Test Procedure Used	19
	7.3.3.	Test Setting	20
	7.3.4.	Test Setup	20
	7.3.5.	Test Result	21



7.4.	Carrier Frequency Separation Measurement	22
7.4.1.	Test Limit	22
7.4.2.	Test Procedure Used	22
7.4.3.	Test Setting	22
7.4.4.	Test Setup	22
7.4.5.	Test Result	23
7.5.	Number of Hopping Channels Measurement	24
7.5.1.	Test Limit	24
7.5.2.	Test Procedure Used	24
7.5.3.	Test Settitng	24
7.5.4.	Test Setup	24
7.5.5.	Test Result	25
7.6.	Time of Occupancy Measurement	26
7.6.1.	Test Limit	26
7.6.2.	Test Procedure Used	26
7.6.3.	Test Settitng	26
7.6.4.	Test Setup	26
7.6.5.	Test Result	27
7.7.	Out-of-Band Spurious Emissions Emissions Measurement	28
7.7.1.	Test Limit	28
7.7.2.	Test Procedure Used	28
7.7.3.	Test Setting	29
7.7.4.	Test Setup	29
7.7.5.	Test Result	30
7.8.	Radiated Spurious Emission Measurement	31
7.8.1.	Test Limit	31
7.8.2.	Test Procedure Used	31
7.8.3.	Test Setting	31
7.8.4.	Test Setup	33
7.8.5.	Test Result	35
7.9.	Radiated Restricted Band Edge Measurement	43
7.9.1.	Test Limit	43
7.9.2.	Test Procedure Used	43
7.9.3.	Test Setting	43
7.9.4.	Test Setup	45
7.9.5.	Test Result	46
7.10.	AC Conducted Emissions Measurement	50
7.10.1.	Test Limit	50



8.	CONCL	USION	.52
	7.10.3.	Test Result	.51
	7.10.2.	Test Setup	.50



§2.1033 General Information

Applicant	AMobile Intelligent Corp.				
Applicant Address	8F1, No.700, Zhongzheng Rd., Zhonghe Dist.,New Taipei City 235, Taiwan				
Manufacturer	MAKER TECHNOLOGY				
Manufacturer Address	12th Floor,NO.82 building,NO.1198 North QinzhouRoad,Xuhui District,Shanghai,China				
Test Site	MRT Technology (Taiwan) Co., Ltd				
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)				
MRT FCC Registration No.	291082				
FCC Rule Part(s)	Part 15.247				
Test Device Serial No.	N/A ☐ Production ☐ Pre-Production ☐ Engineering				

Test Facility / Accreditations

- 1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.
- 2. MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.
- 3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.

FCC ID: 2ACC5-GT500 Page Number: 6 of 52




1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



FCC ID: 2ACC5-GT500 Page Number: 7 of 52



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	5" Rugged Android™ Handheld Device with LTE solution
FCC ID	2ACC5-GT500
Model No.	GT-500 N
Brand Name	△M obile
Supports Radios Spec.	WWAN: GSM/GPRS/EGPRS/WCDMA/HSPA/CDMA/EVDO/LTE WLAN: 2.4G: 802.11b/g/n-20/n-40; 5G: 802.11a/n-20/n-40 WPAN: Bluetooth/NFC
Bluetooth Specification	Dual Mode; V2.1+EDR/ V4.1 LE

2.2. Product Specification Subjective to this Standard

Operating Frequency	2402~2480MHz
Type of modulation	FHSS (GFSK, π/4 DQPSK,8DPSK)
Data Rate	1Mbps(GFSK), 2Mbps(π/4 DQPSK), 3Mbps (8DPSK)

2.3. Test Mode

Test Mode Mod

Note: The test mode of worst case is BT 3Mbps (8DPSK).

FCC ID: 2ACC5-GT500 Page Number: 8 of 52



2.4. Operation Frequency / Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A

FCC ID: 2ACC5-GT500 Page Number: 9 of 52



2.5. Test Configuration

The **5**" Rugged Android™ Handheld Device with LTE solution, FCC ID: 2ACC5-GT500 was tested per the guidance of ANSI C63.10-2013 and DA 00-705. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. Test Software

The test utility software used during testing was "MTK Engineer Mode".

2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.8. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: 2ACC5-GT500 Page Number: 10 of 52



3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) were used in the measurement of the **5" Rugged Android™ Handheld Device with LTE solution, FCC ID: 2ACC5-GT500.**

Deviation from measurement procedure......None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50uH$ Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.10.

FCC ID: 2ACC5-GT500 Page Number: 11 of 52



3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beamwidth of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated emissions test results are shown in Section 7.8 & 7.9.

FCC ID: 2ACC5-GT500 Page Number: 12 of 52



4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the 5" Rugged Android™ Handheld Device with LTE solution, is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The 5" Rugged Android™ Handheld Device with LTE solution, FCC ID: 2ACC5-GT500 unit complies with the requirement of §15.203.

Antenna List

No.	. Manufacturer Part No.		Antenna Type	Peak Gain
1	N/A	AP316-DB_V1	РСВ	0.73dBi for 2.4GHz

FCC ID: 2ACC5-GT500 Page Number: 13 of 52



5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2018.03.15
Cable	Rosnol	N1C50-RG400- B1C50-500CM	MRTTWE00013	1 year	2018.05.19
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2018.03.16

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2018.05.14
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2018.03.16
Acitve Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2018.04.13
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2018.04.17
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2018.04.24
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2018.04.24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2018.04.19
Cable	HUBERSUHNER	SF106	MRTTWA00010	1 year	2018.05.19
Cable	Rosnol	K1K50-UP0264-	MRTTWA00012	1 year	2018.05.19
Cable	1.031101	K1K50-4M	1011 (1 1 00 7 00 0 1 2	i year	2010.00.10

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2018.07.24
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2018.03.19

Test Software

Software	Version	Function	
e3	9.160520a	EMI Test Software	
EMI	V3	EMI Test Software	

FCC ID: 2ACC5-GT500 Page Number: 14 of 52



6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement - SR2

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

150kHz~30MHz: 2.42dB

Conducted Measurement-SR1

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.3dB

Radiated Emission Measurement - AC1

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 4.22dB

FCC ID: 2ACC5-GT500 Page Number: 15 of 52



7. TEST RESULT

7.1. Summary

Product Name: 5" Rugged Android™ Handheld Device with LTE solution

FCC Classification: (DSS) FCC Part 15 Spread Spectrum Transmitter

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)	20dB Bandwidth	N/A	Α		Original Report No.:1610TW0501-U3
15.247(b)(1)	Output Power	<1 Watt if > 75 non- overlapping channels used		PASS	Section 7.3
15.247(a)(1)	Carrier Frequency Separation	25KHz or 2/3 of 20 dB BW for systems with Output Power < 125mW	Conducted	N/A	Original Report No.:1610TW0501-U3
15.247(a)(1)(iii)	Number of Hopping Channels	> 15 Channels		N/A	Original Report No.:1610TW0501-U3
15.247(a)(1)(iii)	Time of Occupancy	< 0.4 sec in 31.6 sec period		N/A	Original Report No.:1610TW0501-U3
15.247(d)	Out-of-Band Emissions	Conducted ≥ 20dBc		N/A	Original Report No.:1610TW0501-U3
15.205 15.209	Spurious Emission	< FCC 15.209 limits	Radiated	PASS	Section 7.8
15.205 15.209	Band Edge Measurement	<pre>≤ 74dBuV/m(Peak) ≤ 54dBuV/m(Average)</pre>	Kadiated	PASS	Section 7.9
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	N/A	Original Report No.:1610TW0501-U3

Note:

- All modes of operation and data rates were investigated. For radiated emission test, every axis
 (X, Y, Z) was also verified. The test results shown in the following sections represent the worst
 case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

FCC ID: 2ACC5-GT500 Page Number: 16 of 52



7.2. 20dB Bandwidth Measurement

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

ANSI C63.10-2013 - Section 6.9.2

7.2.3. Test Setting

- 1. Set RBW ≥ 1% of the 20dB bandwidth
- 2. VBW ≥ 3 x RBW
- 3. Span = approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

7.2.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 17 of 52



7.2.5. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 18 of 52



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power permissible output power is 1 Watt for all other frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels.

7.3.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.5


FCC ID: 2ACC5-GT500 Page Number: 19 of 52



7.3.3. Test Setting

- 1. Set RBW ≥ the 20 dB bandwidth of the emission being measured.
- 2. VBW ≥ 3 x RBW
- 3. Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace to stabilize, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss)
- 8. Note: A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

7.3.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 20 of 52



7.3.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Peak Power (dBm)	EIRP (dBm)	Peak Power Limit (dBm)	EIRP Limit (dBm)
DH5	00	2402	3.88	4.61	< 30	< 36
DH5	39	2441	3.75	4.48	< 30	< 36
DH5	78	2480	3.54	4.27	< 30	< 36
3DH5	00	2402	3.18	3.91	< 30	< 36
3DH5	39	2441	3.27	4	< 30	< 36
3DH5	78	2480	2.46	3.19	< 30	< 36

Note:

- 1. The peak power of all test modes is less than 125mW.
- 2. Peak Power Output Value =Reading value on power meter + cable loss

FCC ID: 2ACC5-GT500 Page Number: 21 of 52



7.4. Carrier Frequency Separation Measurement

7.4.1. Test Limit

The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


7.4.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.2

7.4.3. Test Setting

- 1. Span = wide enough to capture the peaks of two adjacent channels.
- 2. RBW \geq 1 % of the span
- 3. VBW ≥ RBW
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

7.4.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 22 of 52



7.4.5. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 23 of 52



7.5. Number of Hopping Channels Measurement

7.5.1. Test Limit

This frequency hopping system must employ a minimum of 15 hopping channels.


7.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.3

7.5.3. Test Settitng

- 1. Span = the frequency band of operation.
- 2. RBW ≥ 1 % of the span
- 3. VBW ≥ RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

7.5.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 24 of 52



7.5.5. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 25 of 52



7.6. Time of Occupancy Measurement

7.6.1. Test Limit

The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

7.6.2. Test Procedure Used


ANSI C63.10-2013 - Section 7.8.4

7.6.3. Test Settitng

- 1. Span = zero span, centered on a hopping channel.
- 2. RBW = 1MHz
- 3. VBW ≥ RBW
- 4. Sweep time = as necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (data rate, modulation format, etc.), repeat this test for each variation. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.

7.6.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 26 of 52



7.6.5. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 27 of 52



7.7. Out-of-Band Spurious Emissions Emissions Measurement

7.7.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.8


FCC ID: 2ACC5-GT500 Page Number: 28 of 52



7.7.3. Test Setting

- Span = wide enough to capture the peak level of the in-band emission and all spurious
 emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the
 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100 KHz
- 3. VBW ≥ RBW
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize
 Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

7.7.4. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 29 of 52



7.7.5. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 30 of 52



7.8. Radiated Spurious Emission Measurement

7.8.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC	C Part 15 Subpart C Paragraph	า 15.209
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.8.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

7.8.3. Test Setting

Peak Field Strength Measurements

- Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3 * RBW
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold

FCC ID: 2ACC5-GT500 Page Number: 31 of 52



7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements


- Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ 1/T
- 4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 5. Detector = Peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Allow max hold to run for at least 50 times (1/duty cycle) traces

FCC ID: 2ACC5-GT500 Page Number: 32 of 52




7.8.4. Test Setup

9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




FCC ID: 2ACC5-GT500 Page Number: 33 of 52



1GHz ~ 18GHz Test Setup:



18GHz ~40GHz Test Setup:




FCC ID: 2ACC5-GT500 Page Number: 34 of 52



7.8.5. Test Result

EUT	GT-500 N	Test Date	2018/01/24	
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	25°C / 60%	
Polarity	Horizontal	Site / Engineer	AC1 / Fran	
Test Mode	MODE1-CH39	Test Voltage	By Battery	



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		55.281	1.43	20.63	22.06	-17.94	40	100	400	QP
2		105.721	0.76	19.06	19.82	-23.68	43.5	160	320	QP
3		200.629	1.51	19.12	20.63	-22.87	43.5	115	20	QP
4		344.371	1.38	23.29	24.67	-21.33	46	175	125	QP
5		433.975	3.39	24.79	28.18	-17.82	46	100	-40	QP
6	*	728.612	3.48	29.93	33.41	-12.59	46	200	200	QP


Note:

- 1. " * " means the worst value in this measurement data \circ
- 2. Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB) \circ
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) •
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report \circ
- 5. Other channel/mode was also verified. The test results shown represent the worst case emissions °
- 6. No emission found between lowest internal used/generated frequency to 30MHz •

FCC ID: 2ACC5-GT500 Page Number: 35 of 52



EUT	GT-500 N	Test Date	2018/01/24
	VULB 9162 (30MHz~8GHz)	1000 = 0.00	25°C / 60%
Factor	VOLD 9 102 (301VII 12 001 12)	Temp. / Humidity	25°C / 60%
Polarity	Vertical	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH39	Test Voltage	By Battery



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		55.281	4.52	20.63	25.15	-14.85	40	100	400	QP
2		97.263	1.21	18.79	20	-23.5	43.5	120	50	QP
3		195.355	1.65	18.99	20.64	-22.86	43.5	150	360	QP
4		302.6	2.09	21.51	23.6	-22.4	46	175	175	QP
5		486.688	2.18	25.92	28.1	-17.9	46	190	250	QP
6	*	902.424	7.69	31.97	39.66	-6.34	46	145	125	QP


Note:

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB) \circ
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report •
- 5. Other channel/mode was also verified. The test results shown represent the worst case emissions \circ
- 6. No emission found between lowest internal used/generated frequency to 30MHz •

FCC ID: 2ACC5-GT500 Page Number: 36 of 52



EUT	GT-500 N	Test Date	2018/01/24
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%
Polarity	Horizontal	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH00	Test Voltage	By Battery




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4804	33.43	2.7	36.13	-37.87	74	150	400	Peak
2		7206	31.17	11.26	42.43	-31.57	74	150	400	Peak
3	*	9608	28.21	14.47	42.68	-31.32	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB) \circ
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) \circ
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report \circ

FCC ID: 2ACC5-GT500 Page Number: 37 of 52



EUT	GT-500 N	Test Date	2018/01/24
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%
Polarity	Vertical	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH00	Test Voltage	By Battery




No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
INO	NO	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		4804	33.35	2.7	36.05	-37.95	74	150	400	Peak
2		7206	30.47	11.26	41.73	-32.27	74	150	400	Peak
3	*	9608	28.81	14.47	43.28	-30.72	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB) ∘
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) •
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report •

FCC ID: 2ACC5-GT500 Page Number: 38 of 52



	EUT	GT-500 N	Test Date	2018/01/24
I	Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%
F	Polarity	Horizontal	Site / Engineer	AC1 / Fran
Те	st Mode	MODE1-CH39	Test Voltage	By Battery




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4882	37.07	2.83	39.9	-34.1	74	150	400	Peak
2		7323	30.26	11.79	42.05	-31.95	74	150	400	Peak
3	*	9764	30.47	14.82	45.29	-28.71	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB) ∘
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) \circ
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report •

FCC ID: 2ACC5-GT500 Page Number: 39 of 52



EUT	GT-500 N	Test Date	2018/01/24
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%
Polarity	Vertical	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH39	Test Voltage	By Battery




No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		4882	38.93	2.83	41.76	-32.24	74	150	400	Peak
2		7323	30.5	11.79	42.29	-31.71	74	150	400	Peak
3	*	9764	29.87	14.82	44.69	-29.31	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB) ∘
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) •
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report \circ

FCC ID: 2ACC5-GT500 Page Number: 40 of 52



EUT	GT-500 N	Test Date	2018/01/24
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%
Polarity	Horizontal	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH78	Test Voltage	By Battery




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4960	32.05	2.98	35.03	-38.97	74	150	400	Peak
2		7440	29.56	12.34	41.9	-32.1	74	150	400	Peak
3	*	9920	29.91	15.18	45.09	-28.91	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB) ∘
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) \circ
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report \circ

FCC ID: 2ACC5-GT500 Page Number: 41 of 52



EUT	GT-500 N	Test Date	2018/01/24		
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	25°C / 60%		
Polarity	Vertical	Site / Engineer	AC1 / Fran		
Test Mode	MODE1-CH78	Test Voltage	By Battery		



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
No		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		4960	31.79	2.98	34.77	-39.23	74	150	400	Peak
2		7440	28.28	12.34	40.62	-33.38	74	150	400	Peak
3	*	9920	31	15.18	46.18	-27.82	74	150	400	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB) ∘
- 3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) \circ
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report \circ

FCC ID: 2ACC5-GT500 Page Number: 42 of 52



7.9. Radiated Restricted Band Edge Measurement

7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209						
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]				
0.009 - 0.490	2400/F (kHz)	300				
0.490 - 1.705	24000/F (kHz)	30				
1.705 – 30	30	30				
30 – 88	100	3				
88 – 216	150	3				
216 – 960	200	3				
Above 960	500	3				

7.9.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

7.9.3. Test Setting

Peak Field Strength Measurements

- Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3 * RBW
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold

FCC ID: 2ACC5-GT500 Page Number: 43 of 52



7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements


- Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 10. RBW = 1MHz
- 11. VBW ≥ 1/T
- 12. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 13. Detector = Peak
- 14. Sweep time = auto
- 15. Trace mode = max hold
- 16. Allow max hold to run for at least 50 times (1/duty cycle) traces

FCC ID: 2ACC5-GT500 Page Number: 44 of 52




7.9.4. Test Setup

1GHz ~ 18GHz Test Setup:



18GHz ~40GHz Test Setup:




FCC ID: 2ACC5-GT500 Page Number: 45 of 52

Report No.: 1801TW1901-U3



7.9.5. Test Result

EUT	GT-500 N	Test Date	2018/01/15
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH00	Test Voltage	By Battery



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
No		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1	*	2331.1	48.44	-2.89	45.55	-28.45	74	150	360	Peak
2		2390	46.9	-2.59	44.31	-29.69	74	150	360	Peak
3		2402.2	98.19	-2.53	95.66	21.66	74	150	360	Peak


Note:

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) Preamplifier(dB) \circ
- 3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) •

FCC ID: 2ACC5-GT500 Page Number: 46 of 52



EUT	GT-500 N	Test Date	2018/01/15
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH00	Test Voltage	By Battery




No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
No		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1	*	2330.9	49.23	-2.89	46.34	-27.66	74	165	105	Peak
2		2390	46.88	-2.59	44.29	-29.71	74	165	105	Peak
3		2402.2	88.44	-2.53	85.91	11.91	74	165	105	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) Preamplifier(dB) °
- 3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) •

FCC ID: 2ACC5-GT500 Page Number: 47 of 52



EUT	GT-500 N	Test Date	2018/01/15
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH78	Test Voltage	By Battery




No		Frequency	Reading	C.F	Measurement	Margin	Limit	Height	Angle	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV)	(cm)	(deg)	(QP/PK/AV)
1		2479.875	96.39	-2.12	94.27	20.27	74	165	5	Peak
2		2483.5	48.03	-2.11	45.92	-28.08	74	165	5	Peak
3	*	2483.75	49	-2.11	46.89	-27.11	74	165	5	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) Preamplifier(dB) °
- 3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) •

FCC ID: 2ACC5-GT500 Page Number: 48 of 52



EUT	GT-500 N	Test Date	2018/01/15
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Fran
Test Mode	MODE1-CH78	Test Voltage	By Battery



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		2479.85	87.24	-2.12	85.12	11.12	74	145	185	Peak
2		2483.5	46.65	-2.11	44.54	-29.46	74	145	185	Peak
3	*	2494.775	48.81	-2.05	46.76	-27.24	74	145	185	Peak

- 1. " * " means the worst value in this measurement data $\,^{\circ}$
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) Preamplifier(dB) °
- 3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) \circ

FCC ID: 2ACC5-GT500 Page Number: 49 of 52



7.10. AC Conducted Emissions Measurement


7.10.1. Test Limit

FCC Part 15 S	Subpart C Paragraph 15.207 / RS	S-Gen Limits
Frequency (MHz)	QP (dBµV)	Average (dBμV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.10.2. Test Setup



FCC ID: 2ACC5-GT500 Page Number: 50 of 52



7.10.3. Test Result

Refer to the original report No.: 1610TW0501-U3.

FCC ID: 2ACC5-GT500 Page Number: 51 of 52



8. CONCLUSION

The data collected relate only the item(s) tested and show that the 5" Rugged Android™
Handheld Device with LTE solution, FCC ID: 2ACC5-GT500 is in compliance with Part 15C of
he FCC Rules.
The End