DYNAMIC FREQUENCY SELECTION DFS Test Report

APPLICANT: TCL Communication Ltd.

EQUIPMENT: Tablet PC

BRAND NAME : ALCATEL ONETOUCH

MODEL NAME : 9006W

MARKETING NAME : ONETOUCH PIXI 2 (7)

FCC ID : 2ACCJB014

STANDARD : FCC Part 15 Subpart E

CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Apr. 01, 2015 and completely tested on May 08, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 1 of 20 Report Issued Date : May 15, 2015

Testing Laboratory

Report No.: FZ540109

Report Version : Rev. 01

TABLE OF CONTENTS

RE	VISION	HISTORY	3
GE	NERAL	DESCRIPTION	
	1.1 1.2 1.3 1.4 1.5 1.6 1.7	Applicant	4 4 4 5
2	REQU	IREMENTS AND PARAMETERS FOR DFS TEST	7
	2.1 2.2 2.3 2.4	Applicability of DFS Requirements Interference Threshold values, Master or Client incorporating In-Service Monitoring DFS Response requirement values Short Pulse Radar Test Waveforms	10
3	CALIB	RATION SETUP AND DFS TEST RESULTS	12
	3.1 3.2	Calibration of Radar Waveform	
4	LIST	OF MEASURING EQUIPMENT	20
ΑI	PPEND	IX A. SETUP PHOTOGRAPHS	

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 2 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FZ540109	Rev. 01	Initial issue of report	May 15, 2015

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 3 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

GENERAL DESCRIPTION

1.1 Applicant

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.2 Manufacturer

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.3 Feature of Equipment Under Test

Product Feature			
Equipment	Tablet PC		
Brand Name	ALCATEL ONETOUCH		
Model Name	9006W		
Marketing Name	ONETOUCH PIXI 2 (7)		
FCC ID	2ACCJB014		
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA HSPA+(Downlink Only)/LTE WLAN 2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.1 LE		
IMEI Code	014399000021048		
HW Version	V03		
SW Version	B2E		
EUT Stage	Production Unit		

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard			
DFS Function	Client without radar detection function		
Tx/Rx Channel Frequency Range	5260 MHz ~ 5320 MHz		
EUT support WLAN function	<5260 MHz ~ 5320 MHz> 802.11a 802.11n HT20 802.11n HT40		
Type of Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)		

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 4 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

1.5 Specification of Accessory

	Specification of Accessory				
AC Adentes	Brand Name	ALCATEL onetouch	Model Name	UC13US	
AC Adapter	Power Rating	I/P: 100-240Vac, \$	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG0C1	CBA0059AG0C1		
Dettern	Brand Name	ALCATEL onetouch	Model Name	TLp032B2	
Battery	Power Rating	3.7Vdc, 3240mAh			
	P/N	C3240009C2YHYKFG			
USB Cable	Brand Name	NA	Model Name	NA	
USB Cable	Signal Line Type	0.8m shielded without core			

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 5 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL(SHENZHEN) INC.	
	1F&2F, Building A, Morning Business Center, No.4003 ShiGu Rd., Xili	
	Town, Nanshan District, Shenzhen, Guangdong, P. R. China	
Test Site Location	TEL: +86-755-8637-9589	
	FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
rest site No.	DFS01-SZ	

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules
- FCC KDB 905462 D03 UNII Clients Without Radar Detection New Rules

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.8 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	HW / FW Version	Power Cord
1.	WLAN AP	Cisco	Air-AP1262N-A-K9	LDK102073	HW: v02 FW: 12.4(25d)JA1	Shielded, 1.8 m
					1 *** 12.1(200)67**	AC I/P:
2.	Notebook	Lenovo	EdgeE540	N/A	N/A	Unshielded, 1.2 m
						Shielded, 1.8 m

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014

Page Number : 6 of 20 Report Issued Date: May 15, 2015 Report Version

: Rev. 01

2 Requirements and Parameters for DFS Test

2.1 Applicability of DFS Requirements

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

	Operational Mode			
Requirement	Master	Client Without Radar Detection	Client With Radar Detection	
Non-Occupancy Period	Yes	Not required	Yes	
DFS Detection Threshold	Yes	Not required	Yes	
Channel Availability Check Time	Yes	Not required	Not required	
U-NII Detection Bandwidth	Yes	Not required	Yes	

Table 2: Applicability of DFS requirements during normal operation

	Operational Mode			
Requirement		Client	Client	
requirement	Master	Without Radar	With Radar	
		Detection	Detection	
DFS Detection Threshold	Yes	Not required	Yes	
Channel Closing Transmission Time	Yes	Yes	Yes	
Channel Move Time	Yes	Yes	Yes	
U-NII Detection Bandwidth	Yes	Not required	Yes	
Client Beacon Test	N/A	Yes	Yes	

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 7 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

	Operational Mode			
Additional requirements for devices with multiple bandwidth modes	Master or Client With Radar Detection	Client Without Radar Detection		
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required		
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link		
All other tests	Any single BW mode	Not required		

Note

Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 8 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

2.2 Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes 1, 2, and 3)	
EIRP ≥ 200 milliwatt	-64 dBm	
EIRP < 200 milliwatt and	62 dDm	
power spectral density < 10 dBm/MHz		
EIRP < 200 milliwatt that do not meet the power	C4 dDm	
spectral density requirement	-64 dBm	

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

The radar *Detection Threshold*, lowest antenna gain is the parameter of Interference *radar DFS* detection threshold, The Interference *Detection Threshold* is the (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 9 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

2.3 DFS Response requirement values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over
	remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth
	See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014

Page Number : 10 of 20 Report Issued Date: May 15, 2015

Report No. : FZ540109

Report Version : Rev. 01

2.4 Short Pulse Radar Test Waveforms

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (µsec)	PRI (µsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	Roundup $ \begin{bmatrix} \left(\frac{1}{360}\right). \\ \left(\frac{19 \cdot 10^6}{PRI_{\mu sec}}\right) \end{bmatrix} $	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 $\,\mu$ sec, with a minimum increment of 1 $\,\mu$ sec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 11 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01


3 Calibration Setup and DFS Test Results

3.1 Calibration of Radar Waveform

3.1.1 Radar Waveform Calibration Procedure

The Interference Radar Detection Threshold Level is (-62dBm) + (0) [dBi]+ 1 dB= -61dBm that had been taken into account the output power range and antenna gain. The following equipment setup was used to calibrate the radiated Radar Waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the Master or Client Device. The spectrum analyzer was switched to the zero span (Time Domain) at the frequency of the Radar Waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz to measure the type 0 radar waveform. The spectrum analyzer had offset -5.45dB to compensate receiving horn antenna gain 10.0dBi and RF cable loss 4.55dB. The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm. Capture the spectrum analyzer plots on short pulse radar waveform.

3.1.2 Radiated Calibration Setup




3.1.3 Calibration Deviation

There is no deviation with the original standard.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 12 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

3.1.4 Radar Waveform Calibration Result



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 13 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

3.2 In-Service Monitoring: Channel Move Time, Channel Closing **Transmission Time and Non-Occupancy Period**

3.2.1 Limit of In-Service Monitoring

The EUT has In-Service Monitoring function to continuously monitor the radar signals, If radar is detected, it must leave the channel (Shutdown). The Channel Move Time to cease all transmissions on the current Channel upon detection of a Radar Waveform above the DFS Detection Threshold within 10 sec. The total duration of Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Non-Occupancy Period time is 30 minute during which a Channel will not be utilized after a Radar Waveform is detected on that Channel. The non-associated Client Beacon Test is during the 30 minutes observation time. The EUT should not make any transmissions in the DFS band after EUT power up.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014

Page Number : 14 of 20 Report Issued Date: May 15, 2015

Report No. : FZ540109

Report Version : Rev. 01

3.2.2 Test Procedures

- 1. The radar pulse generator is setup to provide a pulse at frequency that the Master and Client are operating. A type 0 radar pulse with a 1us pulse width and a 1428 us PRI is used for the testing.
- 2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62dBm at the antenna of the Master device.
- 3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4. A U-NII device operating as a Client Device will associate with the Master at Channel. The MPEG file "TestFile.mpg" specified by the FCC is streamed from the "file computer" through the Master to the Client Device and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5. When a radar Burst with a level equal to the DFS Detection Threshold + 1dB is generated on the Operating Channel of the U-NII device. At time T0 the Radar Waveform generator sends a Burst of pulse of the radar waveform at Detection Threshold + 1dB.
- 6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). One 12 seconds plot is reported for the Short Pulse Radar Types 1. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7. Measurement of the aggregate duration of the Channel Closing Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: Dwell (0.4ms)= S (12000ms) / B (30000); where Dwell is the dwell time per spectrum analyzer sampling bin, S is the sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: C (ms)= N X Dwell (0.4 ms); where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8. Measure the EUT for more than 30 minutes following the channel move time to verify that no transmissions or beacons occur on this Channel.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014


Page Number : 15 of 20 Report Issued Date: May 15, 2015

Report No. : FZ540109

Report Version : Rev. 01

3.2.3 Test Setup

Radiated Test Setup Photo



3.2.4 Test Deviation

There is no deviation with the original standard.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 16 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

3.2.5 Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

Test Mode :	Client without radar detection	Temperature :	27 ℃
Test Engineer :	Jim Long	Relative Humidity :	46%


BW / Channel	Test Item	Test Result	Limit	Pass/Fail
	Channel Move Time	0.536 s	< 10s	Pass
40MU- / 5240 MU-	Channel Clasina Transmission Time	200ms +	< 260ms	Pass
40MHz / 5310 MHz	Channel Closing Transmission Time	5.2 ms	< 2001115	
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass

Note: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 17 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01


3.2.6 Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots




SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 18 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

3.2.7 Data Traffic and Noise Floor Plots





TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 19 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSV 7	101473	10Hz~7GHz	Jan. 28, 2015	May 08, 2015	Jan. 27, 2016	DFS (DFS01-SZ)
Signal	Dec	CM 1400A	101000	100// 17. 60/ 17	lan 20 2015	May 08, 2015	Jan. 27, 2016	DFS
Generator	R&S	SMJ100A	101909	100KHz~6GHz	Jan. 28, 2015			(DFS01-SZ)
Horn Antenna	BEIJING XIBAO	XB-WDB-1- 18	040504	1GHz ~ 18GHz	Oct. 10, 2014	May 08, 2015	Oct. 09, 2015	DFS
								(DFS01-SZ)
Horn Antenna	BEIJING XB XIBAO	XB-WDB-1- 18 040506	040506	1GHz ~ 18GHz	Oct. 10, 2014	May 08, 2015	Oct 00 2015	DFS
			040506				Oct. 09, 2015	(DFS01-SZ)

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB014 Page Number : 20 of 20
Report Issued Date : May 15, 2015
Report Version : Rev. 01