

HAC T-Coil TEST REPORT

No. I15Z42998-SEM03

For

TCL Communication Ltd.

GSM Quad-band / UMTS Tril-band / LTE 5-band mobile phone

Model name: 50560

With

Hardware Version: 04

Software Version: vH55

Results Summary: T Category = T4

Issued Date: 2016-01-18



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191 Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email: cttl_terminals@catr.cn, website: www.chinattl.com



REPORT HISTORY

Report Number	Revision	Issue Date	Description
I15Z42998-SEM03	Rev.0	2016-01-18	Initial creation of test report



TABLE OF CONTENT

1 TEST LABORATORY	4
1.1 TESTING LOCATION	4 4
1.4 Signature	
2 CLIENT INFORMATION	
2.1 Applicant Information	
3 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1 About EUT	
3.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3 Internal Identification of AE used during the test	6 6
4 CONDUCTED OUTPUT POWER MEASUREMENT	7
4.1 Summary	
4.2 CONDUCTED POWER	
5. REFERENCE DOCUMENTS	7
6 OPERATIONAL CONDITIONS DURING TEST	8
6.1 HAC MEASUREMENT SET-UP	
6.2 AM1D PROBE	9
6.3 AMCC	
6.5 TEST ARCH PHANTOM & PHONE POSITIONER	10
6.6 ROBOTIC SYSTEM SPECIFICATIONS	
7 T-COIL TEST PROCEDUERES	
8 T-COIL PERFORMANCE REQUIREMENTS	14
8.1 T-Coil coupling field intensity	14
8.2 Frequency response	14
9 HAC T-COIL TEST DATA SUMMARY	15
9.1 Noise ambient	15
9.2 T-Coil Coupling Field Intensity	
9.2.2 Perpendicul ar Field Intensity	15
9.3 Frequency Response at Perpendicular Measurement Point	16
9.4 SIGNAL QUALITY	16
10 MEASUREMENT UNCERTAINTY	
11 MAIN TEST INSTRUMENTS	
ANNEX A TEST LAYOUT	
ANNEX B TEST PLOTS	
ANNEX C FREQUENCY REPONSE CURVES	40
ANNEX D PROBE CALIBRATION CERTIFICATE	43



1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)	
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District,	
	Beijing, P. R. China100191	

1.2 Testing Environment

Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards

1.3 Project Data

Project Leader:	Qi Dianyuan	
Test Engineer:	Lin Hao	
Testing Start Date:	December 29, 2015	
Testing End Date:	December 29, 2015	

1.4 Signature

Lin Hao

(Prepared this test report)

Qi Dianyuan

(Reviewed this test report)

Xiao Li

Deputy Director of the laboratory

(Approved this test report)



2 Client Information

2.1 Applicant Information

Company Name:	TCL Communication Ltd.			
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,			
Address /Post.	Pudong Area Shanghai, P.R. China. 201203			
City:	Shanghai			
Postal Code:	201203			
Country:	China			
Contact Person:	Gong Zhizhou			
Email:	zhizhou.gong@tcl.com			
Telephone:	0086-21-51798260			
Fax: 0086-21-61460602				

2.2 Manufacturer Information

Company Name:	TCL Communication Ltd.			
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,			
Address /Post.	Pudong Area Shanghai, P.R. China. 201203			
City:	Shanghai			
Postal Code:	201203			
Country:	China			
Contact Person: Gong Zhizhou				
Email: zhizhou.gong@tcl.com				
Telephone: 0086-21-51798260				
Fax:	0086-21-61460602			



3 Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1 About EUT

Description:	GSM Quad-band / UMTS Tril-band / LTE 5-band mobile phone			
Model name: 5056O				
	GSM 850/900/1800/1900, WCDMA 850/1700/1900			
Operating mode(s):	BT, Wi-Fi, LTE Band 2/4/5/12/30			

3.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	014584000003563	04	vH55
EUT2	014584000003589	04	vH55

^{*}EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test T-coil with the EUT2 and conducted power with the EUT1.

3.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAC2500037C2	/	SCUD

^{*}AE ID: is used to identify the test sample in the lab internally.

3.4 Air Interfaces / Bands Indicating Operating Modes

Air-interface	Band(MHz)	Туре	C63.19/tested	Simultaneous	отт	Power
All-illiterrace			Cos. 19/lested	Transmissions	011	Reduction
GSM	850	VO	Yes		NA	NA
GSIVI	1900	V		DT W/I ANI		
GPRS/EDGE	850	DT	NA	BT, WLAN		No
GPK3/EDGE	1900	וט	INA			
	850				NA	
WCDMA	1700	VO	Yes	BT, WLAN		NA
(UMTS)	1900					INA
	HSPA	DT	NA			
LTE	Band 2/4/5/12/30	DT	NA	BT, WLAN	NA	NA
ВТ	2450	DT	NA	GSM, WCDMA, LTE	NA	NA
WLAN	2450	DT	NA	GSM, WCDMA, LTE	NA	NA

VO: Voice CMRS/PSTN Service Only

V/D: Voice CMRS/PSTN and Data Service

DT: Digital Transport

^{*} HAC Rating was not based on concurrent voice and data modes, Non current mode was found to represent worst case rating for both M and T rating



4 CONDUCTED OUTPUT POWER MEASUREMENT

4.1 Summary

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured output power should be greater and within 5% than EMI measurement.

4.2 Conducted Power

GSM		Conducted Power (dBm)						
850MHz	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)					
OSUMINZ	32.18	32.51	32.44					
CCM	Conducted Power (dBm)							
GSM 1900MHz	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)					
I 900IVITZ	28.58	28.58	28.68					
WCDMA		Conducted Power (dBm)						
850MHz	Channel 4233(846.6MHz)	Channel 4182(836.4MHz)	Channel 4132(826.4MHz)					
OSUMINZ	22.62	22.72	22.75					
WCDMA	Conducted Power (dBm)							
1900MHz	Channel 9538(1907.6MHz)	Channel 9400(1880MHz)	Channel 9262(1852.4MHz)					
1900WITZ	22.00	22.01	21.94					
WCDMA		Conducted Power (dBm)						
1700MHz	Channel 1513 (1752.6MHz)	Channel1412(1732.4MHz)	Channel 1312 (1712.4MHz)					
17 OUNTIL	23.52	23.44	23.51					

5. Reference Documents

The following document listed in this section is referred for testing.

Reference	Title	Version
ANSI C63.19-2011	American National Standard for Methods of Measurement	
	of Compatibility between Wireless Communication Devices E	
	and Hearing Aids	



6 OPERATIONAL CONDITIONS DURING TEST

6.1 HAC MEASUREMENT SET-UP

These measurements are performed using the DASY5 NEO automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Intel Core2 1.86 GHz computer with Windows XP system and HAC Measurement Software DASY5 NEO, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 6.1 HAC Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.








Figure 6.2 T-Coil setup with HAC Test Arch and AMCC

6.2 AM1D probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V "phantom" voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately



vertical when the signal connector is at the underside of the probe (cable hanging downwards). Specification:

Frequency range	0.1~20kHz (RF sensitivity < -100dB, fully RF shielded)			
Sensitivity	< -50dB A/m @ 1kHz			
Pre-amplifier	40dB, symmetric			
Dimensions	Tip diameter/length: 6/290mm, sensor according to ANSI-C63.19			

6.3 AMCC

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 500hm, and a shunt resistor of 100hm permits monitoring the current with a scale of 1:10

Port description:

Signal	Connector	Resistance
Coil In	BNC	Typically 50Ohm
Coil Monitor	BNO	100hm±1% (100mV corresponding to 1 A/m)
Specification:		

Dimensions 370 x 370 x 196 mm, according to ANSI-C63.19

6.4 AMMI



Figure 6.3 AMMI front panel

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Specification:

Sampling rate	48 kHz / 24 bit
Dynamic range	85 dB
Test signal generation	User selectable and predefined (vis PC)
Calibration	Auto-calibration / full system calibration using AMCC with monitor output
Dimensions	482 x 65 x 270 mm

6.5 Test Arch Phantom & Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x ©Copyright. All rights reserved by CTTL.



370 mm).

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near field $<\pm0.5$ dB.




Figure 6.4 HAC Phantom & Device Holder

6.6 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX160L

Repeatability: ±0.02 mm

No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Intel Core2 Clock Speed: 1.86 GHz

Operating System: Windows XP

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic

Software: DASY5 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock



6.7 T-Coil measurement points and reference plane

Figure 6.5 illustrates the standard probe orientations. Position 1 is the perpendicular orientation of the probe coil; orientation 2 is the transverse orientations. The space between the measurement positions is not fixed. It is recommended that a scan of the WD be done for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

- 1) The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the WD handset, which, in normal handset use, rest against the ear.
- 2) The measurement plane is parallel to, and 10 mm in front of, the reference plane.
- 3) The reference axis is normal to the reference plane and passes through the center of the receiver speaker section (or the center of the hole array); or may be centered on a secondary inductive source. The actual location of the measurement point shall be noted in the test report as the measurement reference point.
- 4) The measurement points may be located where the axial and radial field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the WD and shall be located in the same half of the phone as the WD receiver. In a WD handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.
- 5) The relative spacing of each measurement orientation is not fixed. The axial and two radial orientations should be chosen to select the optimal position.
- 6) The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis. The actual location of the measurement point shall be noted in test reports and designated as the measurement reference point.




Figure 6.5 Axis and planes for WD audio frequency magnetic field measurements



7 T-Coil TEST PROCEDUERES

The following illustrate a typical test scan over a wireless communications device:

- 1) Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.
- 2) Set the reference drive level of signal voice defined in C63.19 per 7.4.2.1.
- 3) The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit.
- 4) The DUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.
- 5) The DUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The DUT audio output was positioned tangent (as physically possible) to the measurement plane.
- 6) The DUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.
- 7) Determined the optimal measurement locations for the DUT by following the three steps, coarse resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 7.4.4.2. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.
- 8) All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of there samples.
- 9) At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for perpendicular and transverse orientation, and the frequency response was measured for perpendicular.
- 10) Corrected for the frequency response after the DUT measurement since the DASY5 system had known the spectrum of the input signal by using a reference job.
- 11) In SEMCAD postprocessing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.



8 T-Coil PERFORMANCE REQUIREMENTS


In order to be rated for T-Coil use, a WD shall meet the requirements for signal level and signal quality contained in this part.

8.1 T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ -18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.


8.2 Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. Figure 7.1 and Figure 7.2 provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE-Frequency response is between 300 Hz and 3000 Hz.

Figure 8.1—Magnetic field frequency response for WDs with a field ≤-15 dB (A/m) at 1 kHz



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 8.2—Magnetic field frequency response for WDs with a field that exceeds –15 dB(A/m) at 1 kHz



8.3 Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 1

Table 1: T-Coil signal quality categories

Category	Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

9 HAC T-Coil TEST DATA SUMMARY

9.1 Noise ambient

Probe Position	ABM2 (dB A/m)		
transverse	-59.17		
perpendicular	-60.53		

9.2 T-Coil Coupling Field Intensity

9.2.1 Transverse Field Intensity

Cell Phone Mode	Minimum limit (dB A/m)	Result (dB A/m)	Verdict
GSM 850	-18	0.26	Pass
GSM 1900	-18	13.54	Pass
WCDMA850	-18	13.05	Pass
WCDMA1700	-18	12.58	Pass
WCDMA1900	-18	12.26	Pass

9.2.2 Perpendicular Field Intensity

Cell Phone Mode	Phone Mode Minimum limit (dB A/m) Result (dB A/m)		Verdict
GSM 850	-18	-2.13	Pass
GSM 1900	-18	14.12	Pass
WCDMA850	-18	14.00	Pass
WCDMA1700	WCDMA1700 -18		Pass
WCDMA1900	-18	13.91	Pass



9.3 Frequency Response at Perpendicular Measurement Point

Cell Phone Mode	Frequency Response Curve	Verdict
GSM 850	Figure C.1	Pass
GSM 1900	Figure C.2	Pass
WCDMA850	Figure C.3	Pass
WCDMA1700	Figure C.4	Pass
WCDMA1900	Figure C.5	Pass

9.4 Signal Quality

Probe Position	Band	Ch.	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	T category
	GSM850	190	-4.2, -20.8	0.26	39.80	T4
	GSM1900	661	2.9, -17.5	13.54	61.54	T4
transverse	WCDMA850	4407	4.2, -19.2	13.05	63.36	T4
	WCDMA1700	1637	4.6, -19.6	12.58	63.80	T4
	WCDMA1900	9800	5.4, -20	12.26	64.23	T4
	GSM850	190	-8.3, -4.2	-2.13	41.09	T4
	GSM1900	661	3.3, -10.8	14.12	58.06	T4
perpendicular	WCDMA850	4407	4.2, -8.8	14.00	65.85	T4
	WCDMA1700	1637	4.6, -8.8	13.87	65.33	T4
	WCDMA1900	9800	4.2, -8.8	13.91	65.48	T4

Note: The LCD backlight is turn off, Bluetooth function is turn off and volume is adjusted to maximum level during T-Coil testing. Signal strength measurement scan plots are presented in Annex B.

9.5 Total Measurement Conclusion

Probe Position	Frequency Band(MHz)	ABM1	Frequency Response	T Category
	GSM 850	Pass		T4
	GSM 1900	Pass		T4
transverse	WCDMA850	Pass	/	T4
	WCDMA1700	Pass		T4
	WCDMA1900	Pass		T4
	GSM 850	Pass	Pass	T4
	GSM 1900	Pass	Pass	T4
perpendicular	WCDMA850	Pass	Pass	T4
	WCDMA1700	Pass	Pass	T4
	WCDMA1900	Pass	Pass	T4



10 MEASUREMENT UNCERTAINTY

No.	Error source	Туре	Uncertainty Value a _i (%)	Prob. Dist.	Div.	ABM1	ABM2 ci	Std. Unc. ABM1 "" "(%)	Std. Unc. ABM2 u'_i (%)
1	System Repeatability	A	0.016	N	1	1	1	0.016	0.016
Prob	Probe Sensitivity								
2	Reference Level	В	3. 0	R	$\sqrt{3}$	1	1	3. 0	3. 0
3	AMCC Geometry	В	0. 4	R	$\sqrt{3}$	1	1	0. 2	0.2
4	AMCC Current	В	0. 6	R	$\sqrt{3}$	1	1	0.4	0.4
5	Probe Positioning during Calibration	В	0. 1	R	$\sqrt{3}$	1	1	0. 1	0.1
6	Noise Contribution	В	0.7	R	$\sqrt{3}$	0. 014	1	0.0	0.4
7	Frequency Slope	В	5. 9	R	$\sqrt{3}$	0. 1	1	0.3	3. 5
Probe	System								
8	Repeatability / Drift	В	1. 0	R	$\sqrt{3}$	1	1	0.6	0.6
9	Linearity / Dynamic Range	В	0.6	N	1	1	1	0.4	0.4
10	Acoustic Noise	В	1.0	R	$\sqrt{3}$	0.1	1	0. 1	0.6
11	Probe Angle	В	2. 3	R	$\sqrt{3}$	1	1	1.4	1.4
12	Spectral Processing	В	0. 9	R	$\sqrt{3}$	1	1	0. 5	0.5
13	Integration Time	В	0.6	N	1	1	5	0.6	3.0
14	Field Distribution	В	0.2	R	$\sqrt{3}$	1	1	0.1	0.1
Test	Signal	-							
15	Ref.Signal Spectral Response	В	0. 6	R	$\sqrt{3}$	0	1	0.0	0.4
Posit	Positioning								
16	Probe Positioning	В	1.9	R	$\sqrt{3}$	1	1	1.1	1.1
17	Phantom Thickness	В	0. 9	R	$\sqrt{3}$	1	1	0.5	0.5



18	DUT Positioning	В	1.9	R	$\sqrt{3}$	1	1	1. 1	1.1
Exte	External Contributions								
19	RF Interference	В	0. 0	R	$\sqrt{3}$	1	0.3	0.0	0.0
20	Test Signal Variation	В	2. 0	R	$\sqrt{3}$	1	1	1.2	1.2
	pined Std. Uncertainty 1 Field)	$u_{c} = \sqrt{\sum_{i=1}^{20} c_{i}^{2} u_{i}^{2}}$					4. 1	6. 1	
Expa	nded Std. Uncertainty	ı	$u_e = 2u_c$	N		k = 2		8. 2	12. 2

11 MAIN TEST INSTRUMENTS

Table 2: List of Main Instruments

No.	Name	Туре	Serial Number	Calibration Date	Valid Period
01	Audio Magnetic 1D Field Probe	AM1DV3	3128	January 6, 2015	NCR
02	Audio Magnetic Calibration Coil	AMCC	1064	NCR	NCR
03	Audio Measuring Instrument	AMMI	1044	NCR	NCR
04	HAC Test Arch	N/A	1014	NCR	NCR
05	DAE	DAE4	771	January 27, 2015	One year
06	Software	DASY5 V5.0 Build 119.9	N/A	NCR	NCR
07	Software	SEMCAD V13.2 Build 87	N/A	NCR	NCR
08	Universal Radio Communication Tester	CMU 200	105948	September 17, 2015	One year

END OF REPORT BODY



ANNEX A TEST LAYOUT



Picture A1: HAC T-Coil System Layout



ANNEX B TEST PLOTS

T-Coil GSM 850 Transverse

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3128;

Transverse 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 8.23 dBA/mBWC Factor = 0.16 dB

Location: 3.8, -17.9, 3.7 mm

Transverse 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.80 dB ABM1 comp = 0.26 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -20.8, 3.7 mm






Fig B.1 T-Coil GSM 850



T-Coil GSM 850 Perpendicular

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3128;

Perpendicular 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 10.28 dBA/m BWC Factor = 0.16 dB Location: 3.8, -25, 3.7 mm

Perpendicular 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 41.09 dBABM1 comp = -2.13 dBA/m

BWC Factor = 0.16 dB

Location: -8.3, -4.2, 3.7 mm






Fig B.2 T-Coil GSM 850



T-Coil GSM 1900 Transverse

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3128;

Transverse 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.29 dBA/mBWC Factor = 0.16 dB

Location: 5.8, -16.7, 3.7 mm

Transverse 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 61.54 dB

ABM1 comp = 13.54 dBA/m

BWC Factor = 0.16 dB

Location: 2.9, -17.5, 3.7 mm






Fig B.3 T-Coil GSM 1900



T-Coil GSM 1900 Perpendicular

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3128;

Perpendicular 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.50 dBA/mBWC Factor = 0.16 dB

Location: 5.4, -10.8, 3.7 mm

Perpendicular 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 58.06 dB

ABM1 comp = 14.12 dBA/m

BWC Factor = 0.16 dB

Location: 3.3, -10.8, 3.7 mm






Fig B.4 T-Coil GSM 1900



T-Coil WCDMA 850 Transverse

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: WCDMA 850; Frequency: 836.4 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Transverse 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.47 dBA/mBWC Factor = 0.16 dB

Location: 5.8, -16.7, 3.7 mm

Transverse 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 63.36 dB

ABM1 comp = 13.05 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, -19.2, 3.7 mm






Fig B.5 T-Coil WCDMA 850



T-Coil WCDMA 850 Perpendicular

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: WCDMA 850; Frequency: 836.4 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Perpendicular 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.69 dBA/mBWC Factor = 0.16 dB

Location: 5.4, -10.8, 3.7 mm

Perpendicular 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 65.85 dB

ABM1 comp = 14.00 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, -8.8, 3.7 mm






Fig B.6 T-Coil WCDMA 850



T-Coil WCDMA 1700 Transverse

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: WCDMA 1700; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Transverse 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.40 dBA/mBWC Factor = 0.16 dB

Location: 5.8, -16.7, 3.7 mm

Transverse 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 63.80 dB

ABM1 comp = 12.58 dBA/m

BWC Factor = 0.16 dB

Location: 4.6, -19.6, 3.7 mm






Fig B.7 T-Coil WCDMA 1700



T-Coil WCDMA 1700 Perpendicular

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:21.8°C

Communication System: WCDMA 1700; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Perpendicular 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.56 dBA/m BWC Factor = 0.16 dB Location: 5, -10.8, 3.7 mm

Perpendicular 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 65.33 dB ABM1 comp = 13.87 dBA/m BWC Factor = 0.16 dB

Location: 4.6, -8.8, 3.7 mm






Fig B.8 T-Coil WCDMA 1700



T-Coil WCDMA 1900 Transverse

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Transverse 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.35 dBA/mBWC Factor = 0.16 dB

Location: 5.8, -16.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z)

(121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 64.23 dB

ABM1 comp = 12.26 dBA/m

BWC Factor = 0.16 dB

Location: 5.4, -20, 3.7 mm






Fig B.9 T-Coil WCDMA 1900



T-Coil WCDMA 1900 Perpendicular

Date: 2015-12-29

Electronics: DAE4 Sn771

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature:23.0°C

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3128;

Perpendicular 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.55 dBA/m BWC Factor = 0.16 dB Location: 5, -10.8, 3.7 mm

Perpendicular 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated

grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 37.15

Measure Window Start: 300ms Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 65.48 dBABM1 comp = 13.91 dBA/m

BWC Factor = 0.16 dB Location: 4.2, -8.8, 3.7 mm






Fig B.10 T-Coil WCDMA 1900



ANNEX C FREQUENCY REPONSE CURVES




Figure C.1 Frequency Response of GSM 850




Figure C.2 Frequency Response of GSM 1900






Figure C.3 Frequency Response of WCDMA 850




Figure C.4 Frequency Response of WCDMA 1700






Figure C.5 Frequency Response of WCDMA 1900



ANNEX D PROBE CALIBRATION CERTIFICATE

Calibration Laboratory of Schmid & Partner Engineering AG

Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

CALIDRATION	ERTIFICA		o: AM1DV3-3128_Jan15
Object	AM1DV3 - SN		
Calibration procedure(s)	QA CAL-24.v4 Calibration pro audio range	4 ocedure for AM1D magnetic field pro	obes and TMFS in the
Calibration date:	January 6, 20	15	
The measurements and the uncert	ainties with confidence	national standards, which realize the physical unce probability are given on the following pages an ratory facility: environment temperature (22 ± 3)°(n)	d are part of the certificate.
	1.6		
Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	ID # SN: 0810278	Cal Date (Certificate No.) 03-Oct-14 (No:15573)	Scheduled Calibration Oct-15
Keithley Multimeter Type 2001 Reference Probe AM1DV2			Scheduled Calibration Oct-15 Jan-15
Primary Standards Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4	SN: 0810278	03-Oct-14 (No:15573)	Oct-15
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4	SN: 0810278 SN: 1008	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14)	Oct-15 Jan-15 Sep-15
Keithley Multimeter Type 2001 Reference Probe AM1DV2	SN: 0810278 SN: 1008 SN: 781	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14) Check Date (in house)	Oct-15 Jan-15 Sep-15
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4 Secondary Standards	SN: 0810278 SN: 1008 SN: 781	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14)	Oct-15 Jan-15 Sep-15
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4 Secondary Standards AMCC	SN: 0810278 SN: 1008 SN: 781	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14) Check Date (in house) 01-Oct-13 (in house check Oct-13)	Oct-15 Jan-15 Sep-15 Scheduled Check Oct-16
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4 Secondary Standards AMCC AMMI Audio Measuring Instrument	SN: 0810278 SN: 1008 SN: 781	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14) Check Date (in house) 01-Oct-13 (in house check Oct-13)	Oct-15 Jan-15 Sep-15 Scheduled Check Oct-16
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4 Secondary Standards AMCC AMMI Audio Measuring Instrument	SN: 0810278 SN: 1008 SN: 781 ID # 1050 1062	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14) Check Date (in house) 01-Oct-13 (in house check Oct-13) 26-Sep-12 (in house check Sep-12)	Oct-15 Jan-15 Sep-15 Scheduled Check Oct-16 Sep-15 Signature
Keithley Multimeter Type 2001 Reference Probe AM1DV2 DAE4 Secondary Standards AMCC	SN: 0810278 SN: 1008 SN: 781 ID # 1050 1062	03-Oct-14 (No:15573) 14-Jan-14 (No. AM1D-1008_Jan14) 12-Sep-14 (No. DAE4-781_Sep14) Check Date (in house) 01-Oct-13 (in house check Oct-13) 26-Sep-12 (in house check Sep-12)	Oct-15 Jan-15 Sep-15 Scheduled Check Oct-16 Sep-15

Certificate No: AM1DV3-3128_Jan15

Page 1 of 3



[References

- ANSI-C63.19-2007
 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] ANSI-C63.19-2011 American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below. The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- Coordinate System: The AM1D probe is mounted in the DASY system for operation with a HAC
 Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to
 "southwest" orientation.
- Functional Test: The functional test preceding calibration includes test of Noise level
 - RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- Connector Rotation: The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and –120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- Sensor Angle: The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- Sensitivity: With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

Certificate No: AM1DV3-3128_Jan15



AM1D probe identification and configuration data

Item	AM1DV3 Audio Magnetic 1D Field Probe	
Type No	SP AM1 001 BA	
Serial No	3128	

Overall length	296 mm	
Tip diameter	6.0 mm (at the tip)	
Sensor offset	3.0 mm (centre of sensor from tip)	
Internal Amplifier	20 dB	

Manufacturer / Origin	Schmid & Partner Engineering AG, Zürich, Switzerland
Manufacturing date	April 26, 2012
Last calibration date	n/a

Calibration data

Connector rotation angle	(in DASY system)	155.7 °	+/- 3.6 $^{\circ}$ (k=2)
Sensor angle	(in DASY system)	1.46 °	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	0.00780 V / (A/m)	+/- 2.2 % (k=2)

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: AM1DV3-3128_Jan15



The photos of HAC test are presented in the additional document:

Appendix to test report no. I15Z42998-SEM02/03

The photos of HAC test