DYNAMIC FREQUENCY SELECTION DFS Test Report

APPLICANT : TCL Communication Ltd.

EQUIPMENT : Tablet PC
BRAND NAME : alcatel
MODEL NAME : 9015B

MARKETING NAME : Alcatel POP™ 7 LTE

FCC ID : 2ACCJB066

STANDARD : FCC Part 15 Subpart E

CLASSIFICATION: (NII) Unlicensed National Information Infrastructure

The product was received on Jul. 05, 2016 and completely tested on Jul. 20, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Ken Chen / Manager

Ven Cher

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 1 of 20 Report Issued Date : Aug. 16, 2016 Report Version : Rev. 01

Testing Laboratory

TABLE OF CONTENTS

1	GENERAL DESCRIPTION5			
	1.1 1.2 1.3 1.4 1.5 1.6 1.7	Applicant	5 5 6	
2	REQU	IREMENTS AND PARAMETERS FOR DFS TEST	7	
	2.1 2.2 2.3 2.4	Applicability of DFS Requirements Interference Threshold values, Master or Client incorporating In-Service Monitoring DFS Response requirement values Short Pulse Radar Test Waveforms	10	
3	CALIE	RATION SETUP AND DFS TEST RESULTS	12	
	3.1 3.2	Calibration of Radar Waveform		
4	LIST	OF MEASURING EQUIPMENT	20	
ΑP	PENDI	X A. SETUP PHOTOGRAPHS		

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 2 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FZ670507	Rev. 01	Initial issue of report	Aug. 16, 2016

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 3 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

SUMMARY OF DYNAMIC FREQUENCY SELECTION TEST

UNII	Bandwidth and Channel	Description	Measured	Limit	Result
		Channel Move Time	0.645 sec	10 sec	Pass
U-NII-2A 5250-5350MHz	40MHz (CH62) 5310MHz	Channel Closing Transmission time	<200ms + 4 ms (aggregate)	200 ms + aggregate of 60 ms over remaining 10 s period	Pass
		Non-Occupancy Period and Client Beacon Test	No transmission or Beacons occurred	30 minutes	Pass

Note: Since the product is client without radar detection function, only Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period Test are required to be performed.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 4 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

1 General Description

1.1 Applicant

TCL Communication Ltd.

5F, C-Tower, No. 232, Liang Jing Road, ZhangJiang High-Tech Park, Pudong Area, Shanghai, 201203, P. R. China

1.2 Manufacturer

TCL Communication Ltd.

5F, C-Tower, No. 232, Liang Jing Road, ZhangJiang High-Tech Park, Pudong Area, Shanghai, 201203, P. R. China

1.3 Feature of Equipment Under Test

Product Feature			
Equipment	Tablet PC		
Brand Name	alcatel		
Model Name	9015B		
Marketing Name	Alcatel POP™ 7 LTE		
FCC ID	2ACCJB066		
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.1 LE		
HW Version	Pixi4-7 4G TMO_MAIN_V03		
SW Version	5RA2		
EUT Stage	Production Unit		

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard			
DFS Function	Client without radar detection function		
Tx/Rx Channel Frequency Range	5260 MHz ~ 5320 MHz		
	<5260 MHz ~ 5320 MHz>		
EUT support WLAN function	802.11a		
EUT Support WLAN function	802.11n HT20		
	802.11n HT40		
Type of Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)		

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 5 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL(SHENZHEN) INC.
	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Took Cita Location	Nanshan District, Shenzhen, Guangdong, P. R. China
Test Site Location	TEL: +86-755-8637-9589
	FAX: +86-755-8637-9595
Test Site No.	Sporton Site No.
rest Site No.	DFS01-SZ

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v01r02
- FCC KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r01

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.7 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	HW / FW Version	Power Cord
						AC I/P:
1	14/1 451 45	0.	Air-CAP3702E-A-K9	1 DIC400007		Unshielded, 1.8 m
1.	WLAN AP	Cisco		AII-CAP3/UZE-A-K9	-CAP3702E-A-K9 LDK102087	N/A
						Shielded, 2 m
						AC I/P:
	Notebook	Lamavia	novo EdgeE540	N/A	N/A	Unshielded, 1.2 m
2.		Notebook Lenovo EdgeE540 N/A				DC O/P:
						Shielded, 1.8 m

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 6 of 20 Report Issued Date : Aug. 16, 2016

Report No. : FZ670507

Report Version : Rev. 01

2 Requirements and Parameters for DFS Test

2.1 Applicability of DFS Requirements

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

	Operational Mode			
Requirement	Master	Client Without Radar Detection	Client With Radar Detection	
Non-Occupancy Period	Yes	Not required	Yes	
DFS Detection Threshold	Yes	Not required	Yes	
Channel Availability Check Time	Yes	Not required	Not required	
U-NII Detection Bandwidth	Yes	Not required	Yes	

Table 2: Applicability of DFS requirements during normal operation

	Operational Mode			
Requirement		Client	Client	
Keyunement	Master	Without Radar	With Radar	
		Detection	Detection	
DFS Detection Threshold	Yes	Not required	Yes	
Channel Closing Transmission Time	Yes	Yes	Yes	
Channel Move Time	Yes	Yes	Yes	
U-NII Detection Bandwidth	Yes	Not required	Yes	
Client Beacon Test	N/A	Yes	Yes	

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 7 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

	Operational Mode		
Additional requirements for devices with multiple bandwidth modes	Master or Client With Radar Detection	Client Without Radar Detection	
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required	
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link	
All other tests	Any single BW mode	Not required	

Note

Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 8 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

2.2 Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes 1, 2, and 3)	
EIRP ≥ 200 milliwatt	-64 dBm	
EIRP < 200 milliwatt and	62 dDm	
power spectral density < 10 dBm/MHz	-62 dBm	
EIRP < 200 milliwatt that do not meet the power	C4 dDro	
spectral density requirement -64 dBm		

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

The radar *Detection Threshold*, lowest antenna gain is the parameter of Interference *radar DFS* detection threshold, The Interference *Detection Threshold* is the (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 9 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

2.3 DFS Response requirement values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over
	remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth
	See Note 3.

Note 1: The instant that the *Channel Move Time* and the *Channel Closing Transmission Time* begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar *Burst* generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the *U-NII Detection Bandwidth* detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 10 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

2.4 Short Pulse Radar Test Waveforms

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (µsec)	PRI (µsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	Roundup $ \begin{bmatrix} \left(\frac{1}{360}\right) \\ \left(\frac{19 \cdot 10^6}{PRI_{\mu sec}}\right) \end{bmatrix} $	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggrega	ite (Radar Ty	pes 1-4)	80%	120	

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 $\,\mu$ sec, with a minimum increment of 1 $\,\mu$ sec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 11 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01


3 Calibration Setup and DFS Test Results

3.1 Calibration of Radar Waveform

3.1.1 Radar Waveform Calibration Procedure

The Interference **Radar Detection Threshold Level** is (-62dBm) + (0) [dBi]+ 1 dB= -61dBm that had been taken into account the output power range and antenna gain. The following equipment setup was used to calibrate the radiated Radar Waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the Master or Client Device. The spectrum analyzer was switched to the zero span (Time Domain) at the frequency of the Radar Waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz to measure the type 0 radar waveform. The spectrum analyzer had offset -6.8dB to compensate receiving horn antenna gain 10.5dBi and RF cable loss 3.7dB. The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm. Capture the spectrum analyzer plots on short pulse radar waveform.

3.1.2 Radiated Calibration Setup




3.1.3 Calibration Deviation

There is no deviation with the original standard.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 12 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

3.1.4 Radar Waveform Calibration Result



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 13 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

3.2 In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

3.2.1 Limit of In-Service Monitoring

The EUT has In-Service Monitoring function to continuously monitor the radar signals, If radar is detected, it must leave the channel (Shutdown). The Channel Move Time to cease all transmissions on the current Channel upon detection of a Radar Waveform above the DFS Detection Threshold within 10 sec. The total duration of *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Non-Occupancy Period time is 30 minute during which a Channel will not be utilized after a Radar Waveform is detected on that Channel. The non-associated Client Beacon Test is during the 30 minutes observation time. The EUT should not make any transmissions in the DFS band after EUT power up.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 14 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

3.2.2 Test Procedures

- 1. The radar pulse generator is setup to provide a pulse at frequency that the Master and Client are operating. A type 0 radar pulse with a 1us pulse width and a 1428 us PRI is used for the testing.
- 2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62dBm at the antenna of the Master device.
- 3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4. A U-NII device operating as a Client Device will associate with the Master at Channel. The MPEG file "TestFile.mpg" specified by the FCC is streamed from the "file computer" through the Master to the Client Device and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5. When a radar Burst with a level equal to the DFS Detection Threshold + 1dB is generated on the Operating Channel of the U-NII device. At time T0 the Radar Waveform generator sends a Burst of pulse of the radar waveform at Detection Threshold + 1dB.
- 6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). One 12 seconds plot is reported for the Short Pulse Radar Types 1. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7. Measurement of the aggregate duration of the Channel Closing Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: Dwell (0.4ms)= S (12000ms) / B (30000); where Dwell is the dwell time per spectrum analyzer sampling bin, S is the sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: C (ms)= N X Dwell (0.4 ms); where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8. Measure the EUT for more than 30 minutes following the channel move time to verify that no transmissions or beacons occur on this Channel.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066


Page Number : 15 of 20 Report Issued Date: Aug. 16, 2016

Report No.: FZ670507

Report Version : Rev. 01

3.2.3 Test Setup

Radiated Test Setup Photo



3.2.4 Test Deviation

There is no deviation with the original standard.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 16 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

3.2.5 Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

Test Mode :	Client without radar detection	Temperature :	24 ℃
Test Engineer :	Miller Wang	Relative Humidity :	53%


BW / Channel	Test Item	Test Result	Limit	Pass/Fail
	Channel Move Time	0.645s	< 10s	Pass
40MH- / 5240 MH-	Channel Clasina Transmission Time	200ms +	< 260ms	Pass
40MHz / 5310 MHz	Channel Closing Transmission Time	4ms	< 2001115	
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass

Note: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 17 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01


3.2.6 Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots




SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 18 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

3.2.7 Data Traffic and Noise Floor Plots





TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 19 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSV 7	101473	10Hz~7GHz	Jan. 12, 2016	Jul. 20, 2016	Jan. 11, 2017	Conducted (DFS01-SZ)
Signal Generator	R&S	SMJ100A	101909	100KHz~6GHz	Jan. 12, 2016	Jul. 20, 2016	Jan. 11, 2017	Conducted (DFS01-SZ)
Horn Antenna	BEIJING XIBAO	XB-WDB-1-1 8	040504	1GHz ~ 18GHz	Oct. 17, 2015	Jul. 20, 2016	Oct. 16, 2016	Conducted (DFS01-SZ)
Horn Antenna	BEIJING XIBAO	XB-WDB-1-1 8	040506	1GHz ~ 18GHz	Oct. 17, 2015	Jul. 20, 2016	Oct. 16, 2016	Conducted (DFS01-SZ)

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ACCJB066 Page Number : 20 of 20
Report Issued Date : Aug. 16, 2016
Report Version : Rev. 01