



FCC PART 15B TEST REPORT

No. 25T04Z100410-012

for

TCL Communication Ltd.

Projector

P30D8F

with

Hardware Version: TP3_M_F

Software Version: V11

Issued Date: 2025-07-15

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
25T04Z100410-012	Rev.0	1 st edition	2025-07-15

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING	7
5. SUMMARY OF TEST RESULTS	8
6. TEST EQUIPMENTS UTILIZED	9
7. MEASUREMENT UNCERTAINTY	10
ANNEX A: MEASUREMENT RESULTS	11

1. Test Laboratory

1.1. Testing Location

CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

1.2. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2025-06-10

Testing End Date: 2025-07-01

1.4. Signature



An Hui

(Prepared this test report)



Zhang Ying

(Reviewed this test report)



Zang Qi

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
Contact: Ting Wang
Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: +86 755 36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
Contact: Ting Wang
Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: +86 755 36612000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Projector
Model Name	P30D8F
FCC ID:	2ACCJB234

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
UT10a	P30D8F3J1EH000A	TP3_M_F	V11

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	Manufacturer	Remark
AE1	Battery	TLp043G7	Veken	--
AE2	Adapter	PD100E-B1C0AVUC	Mass Power Electronics Inc.	--
AE2-1	Adapter	PD100E-B1C0AVEC	Mass Power Electronics Inc.	No testing required
AE3	Cable	UL2725-18	Huizhou Besiter Power Technology Co., Ltd	--
AE4	Headset	/	/	Provided by laboratory
AE5	HD	/	/	Provided by laboratory
AE6	PC	/	/	Provided by laboratory

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	UT10a + AE1 + AE2 +AE3+ AE4+ AE5	Charger+WIFI+BT+USB+VIO
Set.2	UT10a + AE1 + AE2 +AE3+ AE4+ AE5+ AE6	Charger+WIFI+BT+USB+PC+VIDIO
Set.4	UT10a +AE1 + AE2 +AE3+ AE4+ AE5+ AE6 + AE7	WIFI+BT+OTG(Type-c)

Note:

Equipment Under Test (EUT) is a model of Projector.

It supports

It has MP3, Camera, USB memory, Bluetooth 5.1, Wi-Fi (802.11a/b/g/n/ac, 802.11n supports 20MHz and 40MHz bandwidth, 802.11ac supports 20MHz, 40MHz and 80MHz bandwidth) and GNSS function.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2024
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(huayuan North Road)

6. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESW44	103023	R&S	2025-06-06	1 year
2	Test Receiver	ESCI 3	100344	R&S	2026-04-01	1 year
3	LISN	ENV216	101200	R&S	2026-06-05	1 year
4	EMI Antenna	VULB 9163	01222	SCHWARZBECK	2025-09-11	1 year
5	EMI Antenna	3115	6914	ETS-Lindgren	2026-05-07	1 year

Test software information		
Test Item	Software	Version
Radiated Emission	EMC32	V11.50.00
Conducted Emission	EMC32	V8.53.00

Semi-anechoic chamber utilized did not exceed following limits along the testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz

Shielded room utilized did not exceed following limits along the testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz – 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

7. Measurement Uncertainty

Where relevant, the following measurement uncertainty(worse case) levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Location 1: CTTL(huayuan North Road)

Test item	Frequency ranges	Measurement uncertainty
Radiated Emission	30MHz-1GHz	4.72dB($k=2$)
	1GHz-18GHz	4.84dB($k=2$)
Conducted Emission	150kHz-30MHz	AC Power Line: 3.08dB($k=2$)

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode, and is connected to a charger in the case of charging mode.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

The model of the PC is M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit ($\mu\text{V/m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/3MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement results for Set.1:

Charing Mode/Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17915.00	47.48	-26.80	45.40	28.88	54.00	6.52	H
17955.80	47.40	-26.80	45.40	28.80	54.00	6.60	V
17915.30	47.06	-26.80	45.40	28.46	54.00	6.94	H
17974.20	46.95	-26.80	45.40	28.35	54.00	7.05	H
17913.30	46.90	-26.80	45.40	28.30	54.00	7.10	H
17988.40	46.83	-26.80	45.40	28.23	54.00	7.17	V

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.50	58.38	-26.80	45.40	39.78	74.00	15.62	H
17919.10	57.89	-26.80	45.40	39.29	74.00	16.11	H
17914.00	57.87	-26.80	45.40	39.27	74.00	16.13	H
17921.50	57.86	-26.80	45.40	39.26	74.00	16.14	V
17981.30	57.72	-26.80	45.40	39.12	74.00	16.28	V
17925.50	57.55	-26.80	45.40	38.95	74.00	16.45	H

Measurement results for Set.2:
Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17959.90	47.07	-26.80	45.40	28.47	54.00	6.93	V
17982.30	47.01	-26.80	45.40	28.41	54.00	6.99	H
17941.50	46.99	-26.80	45.40	28.39	54.00	7.01	H
17906.50	46.98	-26.80	45.40	28.38	54.00	7.02	H
17981.00	46.87	-26.80	45.40	28.27	54.00	7.13	V
17945.90	46.81	-26.80	45.40	28.21	54.00	7.19	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17913.60	57.89	-26.80	45.40	39.29	74.00	16.11	H
17923.50	57.79	-26.80	45.40	39.19	74.00	16.21	V
17926.90	57.68	-26.80	45.40	39.08	74.00	16.32	V
17988.40	57.62	-26.80	45.40	39.02	74.00	16.38	V
17967.70	57.59	-26.80	45.40	38.99	74.00	16.41	V
17971.40	57.55	-26.80	45.40	38.95	74.00	16.45	H

Measurement results for Set.4:
OTG Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17921.10	47.23	-26.80	45.40	28.63	54.00	6.77	H
17993.50	47.07	-26.80	45.40	28.47	54.00	6.93	V
17982.30	47.06	-26.80	45.40	28.46	54.00	6.94	V
17959.50	47.04	-26.80	45.40	28.44	54.00	6.96	H
17962.30	47.00	-26.80	45.40	28.40	54.00	7.00	H
17967.00	46.95	-26.80	45.40	28.35	54.00	7.05	H

OTG Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17917.00	58.30	-26.80	45.40	39.70	74.00	15.70	H
17931.70	58.03	-26.80	45.40	39.43	74.00	15.97	H
17932.00	57.96	-26.80	45.40	39.36	74.00	16.04	H
17956.80	57.95	-26.80	45.40	39.35	74.00	16.05	H
17926.60	57.80	-26.80	45.40	39.20	74.00	16.20	V
17995.20	57.79	-26.80	45.40	39.19	74.00	16.21	V

Measurement results for Set.1:

Full Spectrum




Fig A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
36.762149	17.84	29.54	11.70	120.000	125.0	V	310.0
47.028057	13.53	29.54	16.01	120.000	107.0	V	202.0
122.824746	13.74	33.06	19.32	120.000	175.0	V	47.0
745.797307	33.94	35.56	1.62	120.000	125.0	H	23.0
813.586340	32.57	35.56	2.99	120.000	316.0	H	278.0
949.201900	29.04	35.56	6.52	120.000	125.0	H	90.0

Full Spectrum





Fig A.2 Radiated Emission from 1GHz to 18GHz

Measurement results for Set.2:

Full Spectrum




Fig A.3 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
31.535114	28.95	29.54	0.59	120.000	100.0	V	219.0
32.415870	27.40	29.54	2.14	120.000	192.0	V	-29.0
144.041307	26.95	29.54	2.59	120.000	275.0	V	135.0
226.083664	14.41	33.06	18.65	120.000	125.0	V	23.0
813.531422	31.78	35.56	3.78	120.000	125.0	H	-22.0
857.951674	30.69	35.56	4.87	120.000	283.0	H	15.0

Full Spectrum





Fig A.4 Radiated Emission from 1GHz to 18GHz

Measurement results for Set.4:

Full Spectrum




Fig A.5 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
33.298000	13.59	29.54	15.95	120.000	107.0	V	225.0
46.684000	10.92	29.54	18.62	120.000	304.0	H	292.0
91.740500	15.55	33.06	17.51	120.000	117.0	V	225.0
110.946500	20.57	33.06	12.49	120.000	117.0	V	45.0
142.665500	23.31	33.06	9.75	120.000	100.0	V	83.0
248.541000	16.50	35.56	19.06	120.000	292.0	H	53.0

Full Spectrum




Fig A.6 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U = 3.08 \text{ dB}$, $k=2$.

Charging Mode, Set.1:




Fig A.7 Conducted Emission from 150kHz to 30MHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.254000	48.3	2000.0	9.000	On	L1	19.9	13.4	61.6	
0.258000	47.7	2000.0	9.000	On	L1	19.9	13.8	61.5	
0.510000	40.7	2000.0	9.000	On	N	19.9	15.3	56.0	
1.014000	41.0	2000.0	9.000	On	N	19.7	15.0	56.0	
2.010000	33.1	2000.0	9.000	On	L1	19.8	22.9	56.0	
2.394000	34.8	2000.0	9.000	On	L1	19.8	21.2	56.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.230000	45.2	2000.0	9.000	On	L1	19.9	7.2	52.4	
0.390000	42.1	2000.0	9.000	On	L1	19.9	6.0	48.1	
0.510000	37.2	2000.0	9.000	On	L1	20.0	8.8	46.0	
0.742000	35.2	2000.0	9.000	On	L1	20.0	10.8	46.0	
1.258000	32.2	2000.0	9.000	On	L1	19.9	13.8	46.0	
2.534000	26.6	2000.0	9.000	On	L1	19.8	19.4	46.0	

Charging Mode, Set.2:




Fig A.8 Conducted Emission from 150kHz to 30MHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.254000	47.5	2000.0	9.000	On	L1	19.9	14.2	61.6	
0.258000	46.7	2000.0	9.000	On	L1	19.9	14.8	61.5	
0.514000	41.1	2000.0	9.000	On	L1	20.0	14.9	56.0	
1.014000	41.3	2000.0	9.000	On	N	19.7	14.7	56.0	
1.950000	35.2	2000.0	9.000	On	L1	19.8	20.8	56.0	
2.454000	36.5	2000.0	9.000	On	L1	19.8	19.5	56.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.226000	44.5	2000.0	9.000	On	L1	19.9	8.1	52.6	
0.394000	41.7	2000.0	9.000	On	L1	20.0	6.3	48.0	
0.506000	37.5	2000.0	9.000	On	N	19.9	8.5	46.0	
0.742000	35.3	2000.0	9.000	On	L1	20.0	10.7	46.0	
1.382000	33.1	2000.0	9.000	On	L1	19.9	12.9	46.0	
2.538000	27.9	2000.0	9.000	On	L1	19.8	18.1	46.0	

END OF REPORT