

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 BandV_ERP

Band:V								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	22.27	-1.37	18.75	<=38.45	Pass
			836.6	22.26	-1.37	18.74	<=38.45	Pass
			846.6	22.31	-1.37	18.79	<=38.45	Pass
	HSDPA	Subtest 1	826.4	22.05	-1.37	18.53	<=38.45	Pass
		Subtest 2	826.4	21.99	-1.37	18.47	<=38.45	Pass
		Subtest 3	826.4	22.01	-1.37	18.49	<=38.45	Pass
		Subtest 4	826.4	21.99	-1.37	18.47	<=38.45	Pass
		Subtest 1	836.6	22.15	-1.37	18.63	<=38.45	Pass
		Subtest 2	836.6	22.16	-1.37	18.64	<=38.45	Pass
		Subtest 3	836.6	22.18	-1.37	18.66	<=38.45	Pass
		Subtest 4	836.6	22.15	-1.37	18.63	<=38.45	Pass
		Subtest 1	846.6	22.00	-1.37	18.48	<=38.45	Pass
		Subtest 2	846.6	22.01	-1.37	18.49	<=38.45	Pass
		Subtest 3	846.6	22.02	-1.37	18.50	<=38.45	Pass
		Subtest 4	846.6	21.98	-1.37	18.46	<=38.45	Pass
	HSUPA	Subtest 1	826.4	21.04	-1.37	17.52	<=38.45	Pass
		Subtest 2	826.4	20.97	-1.37	17.45	<=38.45	Pass
		Subtest 3	826.4	19.39	-1.37	15.87	<=38.45	Pass
		Subtest 4	826.4	19.23	-1.37	15.71	<=38.45	Pass
		Subtest 5	826.4	20.98	-1.37	17.46	<=38.45	Pass
		Subtest 1	836.6	21.25	-1.37	17.73	<=38.45	Pass
		Subtest 2	836.6	19.17	-1.37	15.65	<=38.45	Pass
		Subtest 3	836.6	21.27	-1.37	17.75	<=38.45	Pass
		Subtest 4	836.6	21.12	-1.37	17.60	<=38.45	Pass
		Subtest 5	836.6	21.12	-1.37	17.60	<=38.45	Pass
		Subtest 1	846.6	19.66	-1.37	16.14	<=38.45	Pass
		Subtest 2	846.6	19.66	-1.37	16.14	<=38.45	Pass
		Subtest 3	846.6	19.62	-1.37	16.10	<=38.45	Pass
		Subtest 4	846.6	20.80	-1.37	17.28	<=38.45	Pass
		Subtest 5	846.6	19.43	-1.37	15.91	<=38.45	Pass

Note1: ERP=Conducted Power+Antenna Gain-2.15