

The Photos of SAR test

No. I16Z41073-SEM01

For

TCL Communication Ltd.

UMTS/GSM mobile phone

Model name: 5012G/SMART PLUS

With

Hardware Version: PIO

Software Version: v7GA4

FCC ID: 2ACCJH057



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.


Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191 Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504


Email: cttl_terminals@catr.cn, website: www.chinattl.com




Picture 1: Constituents of the sample




Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position



Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm or 0mm between the EUT and the phantom bottom:




Picture 6: Front – 10mm



Picture 7: Rear - 15mm




Picture 8: Left – 10mm




Picture 9: Right – 10mm



Picture 10: Bottom - 10mm



Picture 11: Top – 10mm



Picture 12: Bottom with headset



Picture 13: Bottom – 0mm