

Fig.102. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.103. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1






Fig.104. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.105. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5






Fig.106. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.107. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3






Fig.108. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5



A.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

- 1. Set RBW = 30kHz.
- 2. Set VBW = 100 kHz.
- 3. Set span to 3MHz
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.
- 7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

| Standard | Limit |
|------------------------------|-------|
| FCC 47 CFR Part 15.247(a)(1) | NA * |

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for "carrier frequency separation" test case, in Annex A.8.

Measurement Results:

For GFSK

| Channel | 20dB Bandwidth (kHz) | | Conclusion |
|---------|----------------------|--------|------------|
| 0 | Fig.109 | 950.00 | NA |
| 39 | Fig.110 | 949.00 | NA |
| 78 | Fig.111 | 946.00 | NA |

Forπ/4 DQPSK

| Channel | 20dB Bandwidth (kHz) | | Conclusion |
|---------|----------------------|---------|------------|
| 0 | Fig.112 | 1291.00 | NA |
| 39 | Fig.113 | 1285.00 | NA |
| 78 | Fig.114 | 1279.00 | NA |

For 8DPSK

| Channel | 20dB Bandwidth (kHz) | | Conclusion |
|---------|----------------------|---------|------------|
| 0 | Fig.115 | 1264.00 | NA |
| 39 | Fig.116 | 1292.00 | NA |
| 78 | Fig.117 | 1269.00 | NA |

Conclusion: NA

Test graphs as below:






Fig.109. 20dB Bandwidth: GFSK, Channel 0




Fig.110. 20dB Bandwidth: GFSK, Channel 39






Fig.111. 20dB Bandwidth: GFSK, Channel 78




Fig.112. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0






Fig.113. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39




Fig.114. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78






Fig.115. 20dB Bandwidth: 8DPSK, Channel 0




Fig.116. 20dB Bandwidth: 8DPSK, Channel 39






Fig.117. 20dB Bandwidth: 8DPSK, Channel 78



A.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

| Standard | Limit(kHz) |
|------------------------------|---------------------------------------|
| FCC 47 CFR Part 15.247(a)(1) | over 25 kHz or (2/3) * 20dB bandwidth |

Measurement Result:

For GFSK

| Channel | Carrier frequency separation (kHz) | | Conclusion |
|---------|------------------------------------|---------|------------|
| 39 | Fig.118 | 1311.00 | Р |

For π/4 DQPSK

| Channel | Carrier frequency separation (kHz) | | Conclusion |
|---------|------------------------------------|---------|------------|
| 39 | Fig.119 | 1144.00 | Р |

For 8DPSK

| Channel | Carrier frequency separation (kHz) | | Conclusion |
|---------|------------------------------------|--------|------------|
| 39 | Fig.120 | 998.00 | Р |

Conclusion: PASS
Test graphs as below:






Fig.118. Carrier frequency separation measurement: GFSK, Channel 39




Fig.119. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39






Fig.120. Carrier frequency separation measurement: 8DPSK, Channel 39



A.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

| Standard | Limit |
|------------------------------------|--------------------------------------|
| FCC 47 CFR Part 15.247(a) (1)(iii) | At least 15 non-overlapping channels |

Measurement Result:

For GFSK

| Channel | Number of hopping channels | | Conclusion |
|---------|----------------------------|----|------------|
| 0~39 | Fig.121 | 70 | D |
| 40~78 | Fig.122 | 79 | Р |

Forπ/4 DQPSK

| Channel | Number of hopping channels | | Conclusion |
|---------|----------------------------|----|------------|
| 0~39 | Fig.123 | 70 | D |
| 40~78 | Fig.124 | 19 | Р |

For 8DPSK

| Channel | Number of hopping channels | | Conclusion |
|---------|----------------------------|----|------------|
| 0~39 | Fig.125 | 70 | В |
| 40~78 | Fig.126 | 79 | F |

Conclusion: PASS
Test graphs as below:






Fig.121. Number of hopping frequencies: GFSK, Channel 0 - 39




Fig.122. Number of hopping frequencies: GFSK, Channel 40 - 78






Fig.123. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39




Fig.124. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78






Fig.125. Number of hopping frequencies: 8DPSK, Channel 0 - 39




Fig.126. Number of hopping frequencies: 8DPSK, Channel 40 - 78



A.10. AC Powerline Conducted Emission

Test Condition

| Voltage (V) | Frequency (Hz) |
|-------------|----------------|
| 120 | 60 |

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

| Frequency range (MHz) | Quasi-peak Limit (dBμV) | Conclusion |
|--------------------------|-------------------------|------------|
| 0.15 to 0.5 | 66 to 56 | |
| 0.5 to 5 | 56 | Р |
| 5 to 30 | 60 | |

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)

| Frequency range (MHz) | Average Limit (dBμV) | Conclusion |
|--------------------------|----------------------|------------|
| 0.15 to 0.5 | 56 to 46 | |
| 0.5 to 5 | 46 | Р |
| 5 to 30 | 50 | |


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

Conclusion: PASS
Test graphs as below:



Traffic: Set.10




Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 1.212000 | 44.8 | GND | N | 10.4 | 11.2 | 56.0 |
| 1.225500 | 44.0 | GND | N | 10.4 | 12.0 | 56.0 |
| 1.342500 | 46.5 | GND | L1 | 10.3 | 9.5 | 56.0 |
| 1.437000 | 44.6 | GND | L1 | 10.3 | 11.4 | 56.0 |
| 1.806000 | 46.6 | GND | L1 | 10.4 | 9.4 | 56.0 |
| 4.281000 | 44.8 | GND | N | 10.5 | 11.2 | 56.0 |

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.537000 | 32.5 | GND | N | 10.4 | 13.5 | 46.0 |
| 1.203000 | 34.1 | GND | N | 10.4 | 11.9 | 46.0 |
| 1.806000 | 35.2 | GND | L1 | 10.4 | 10.8 | 46.0 |
| 2.157000 | 32.5 | GND | L1 | 10.4 | 13.5 | 46.0 |
| 2.548500 | 33.3 | GND | N | 10.5 | 12.7 | 46.0 |
| 4.344000 | 34.5 | GND | L1 | 10.5 | 11.5 | 46.0 |



Traffic: Set.11




Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.159000 | 44.5 | GND | L1 | 10.3 | 21.0 | 65.5 |
| 0.568500 | 44.4 | GND | N | 10.4 | 11.6 | 56.0 |
| 1.167000 | 40.2 | GND | N | 10.4 | 15.8 | 56.0 |
| 2.058000 | 39.4 | GND | N | 10.5 | 16.6 | 56.0 |
| 2.490000 | 38.5 | GND | L1 | 10.4 | 17.5 | 56.0 |
| 3.466500 | 38.0 | GND | N | 10.5 | 18.0 | 56.0 |

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.559500 | 35.1 | GND | N | 10.4 | 10.9 | 46.0 |
| 0.762000 | 30.9 | GND | N | 10.4 | 15.1 | 46.0 |
| 1.167000 | 29.9 | GND | N | 10.4 | 16.1 | 46.0 |
| 1.563000 | 27.7 | GND | L1 | 10.3 | 18.3 | 46.0 |
| 2.071500 | 29.1 | GND | N | 10.5 | 16.9 | 46.0 |
| 2.490000 | 28.2 | GND | L1 | 10.4 | 17.8 | 46.0 |



Traffic: Set.12




Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.577500 | 42.3 | GND | N | 10.4 | 13.7 | 56.0 |
| 9.649500 | 40.7 | GND | L1 | 10.7 | 19.3 | 60.0 |
| 10.140000 | 39.5 | GND | N | 10.7 | 20.5 | 60.0 |
| 10.243500 | 41.1 | GND | L1 | 10.7 | 18.9 | 60.0 |
| 10.288500 | 41.3 | GND | N | 10.7 | 18.7 | 60.0 |
| 11.017500 | 40.4 | GND | L1 | 10.7 | 19.6 | 60.0 |

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.262500 | 36.1 | GND | L1 | 10.3 | 15.2 | 51.4 |
| 0.366000 | 34.9 | GND | L1 | 10.3 | 13.7 | 48.6 |
| 0.577500 | 35.8 | GND | N | 10.4 | 10.2 | 46.0 |
| 3.813000 | 29.4 | GND | N | 10.5 | 16.6 | 46.0 |
| 4.402500 | 29.8 | GND | N | 10.5 | 16.2 | 46.0 |
| 4.956000 | 29.7 | GND | N | 10.6 | 16.3 | 46.0 |



Traffic: Set.13 (New cover)




Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 1.383000 | 50.1 | GND | L1 | 10.3 | 5.9 | 56.0 |
| 1.441500 | 50.1 | GND | N | 10.4 | 5.9 | 56.0 |
| 1.500000 | 49.4 | GND | L1 | 10.3 | 6.6 | 56.0 |
| 1.806000 | 49.3 | GND | N | 10.4 | 6.7 | 56.0 |
| 1.864500 | 49.8 | GND | N | 10.4 | 6.2 | 56.0 |
| 1.923000 | 48.8 | GND | L1 | 10.4 | 7.2 | 56.0 |

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 1.329000 | 38.2 | GND | L1 | 10.3 | 7.8 | 46.0 |
| 1.387500 | 39.0 | GND | N | 10.4 | 7.0 | 46.0 |
| 1.441500 | 38.6 | GND | N | 10.4 | 7.4 | 46.0 |
| 1.504500 | 35.8 | GND | N | 10.4 | 10.2 | 46.0 |
| 1.810500 | 37.4 | GND | L1 | 10.4 | 8.6 | 46.0 |
| 1.869000 | 37.7 | GND | L1 | 10.4 | 8.3 | 46.0 |



Idle: Set.10



Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 1.378500 | 50.1 | GND | L1 | 10.3 | 5.9 | 56.0 |
| 1.437000 | 50.3 | GND | L1 | 10.3 | 5.7 | 56.0 |
| 1.486500 | 48.3 | GND | N | 10.4 | 7.7 | 56.0 |
| 1.801500 | 48.5 | GND | N | 10.4 | 7.5 | 56.0 |
| 1.860000 | 49.1 | GND | L1 | 10.4 | 6.9 | 56.0 |
| 1.909500 | 48.1 | GND | L1 | 10.4 | 7.9 | 56.0 |

Final Result 2

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.901500 | 36.9 | GND | N | 10.4 | 9.1 | 46.0 |
| 0.960000 | 36.9 | GND | N | 10.4 | 9.1 | 46.0 |
| 1.324500 | 37.6 | GND | N | 10.4 | 8.4 | 46.0 |
| 1.383000 | 39.2 | GND | N | 10.4 | 6.8 | 46.0 |
| 1.437000 | 38.7 | GND | L1 | 10.3 | 7.3 | 46.0 |
| 1.860000 | 37.3 | GND | L1 | 10.4 | 8.7 | 46.0 |

END OF REPORT