

Report No.: SZEM180100071902

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 26

FCC REPORT

Application No: SZEM1801000719RG

Applicant: TCL Communication Ltd.

Manufacturer: TCL Communication Ltd.

Product Name: LTE / UMTS / GSM mobile phone

Model No.(EUT): 5044Y
Trade Mark: alcatel

FCC ID: 2ACCJH088

Standards: 47 CFR Part 2(2018)

47 CFR Part 22 subpart H(2018) 47 CFR Part 24 subpart E(2018) 47 CFR Part 27 subpart C(2018)

Test Method: FCC KDB 971168 D01 Power Meas License Digital Systems v03

TIA-603-E 2016

Date of Receipt: 2018-01-03

Date of Test: 2018-01-04 to 2018-01-31

Date of Issue: 2018-02-02

Test Result: PASS *

Authorized Signature:

Derell young

Derek Yang

Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Report No.: SZEM180100071902

Page: 2 of 26

2 Version

	Revision Record				
Version	Chapter	Date	Modifier	Remark	
01		2018-02-02		Original	

Authorized for issue by:		
Tested By	Mike Mu	
		2018-02-02
	(Mike Hu) /Project Engineer	Date
Checked By	John Hong	
	Jim 10 g	2018-02-02
	(Jim Huang) /Reviewer	Date



Report No.: SZEM180100071902

Page: 3 of 26

3 Test Summary

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913, §24.232 §27.50	ERP≤7W {GSM850,WCDMAband 5} EIRP ≤ 2 W. (GSM1900,WCDMA band2,LTE BAND7)	Section 1 of Appendix B	PASS
Peak-Average Ratio	§24.232 §27.50	≤13dB	Section 2 of Appendix B	PASS
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	PASS
Bandwidth	§2.1049(h), §22.917, §24.238 §27.53	OBW:No limit EBW: No limit	Section 4 of Appendix B	PASS
Band Edge Compliance	§2.1051, §22.917, §24.238 §27.53	1, LTE band 7 2%*EBW Channel 2%*EBW 10dBm Edge 10dBm 100dBm 100	Section 5 of Appendix B	PASS
Spurious emissions at antenna terminals	§2.1051, §22.917, §24.238 §27.53	1,≤ -25dBm(LTE band 7) 2,≤ -13dBm(other band)	Section 6 of Appendix B	PASS
Field strength of spurious radiation	§2.1051, §22.917, §24.238 §27.53	1,≤ -25dBm(LTE band 7) 2,≤ -13dBm(other band)	Section 7 of Appendix B	PASS
Frequency stability	§2.1055, §22.355, §24.235 §27.54	≤ ±2.5ppm.	Section 8 of Appendix B	PASS



Report No.: SZEM180100071902

Page: 4 of 26

4 Content

			Page
1	CO	VER PAGE	1
2	VEF	RSION	2
3	TES	ST SUMMARY	3
4	COI	NTENT	4
5	GEI	NERAL INFORMATION	6
	5.1	CLIENT INFORMATION	6
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	Test Mode	
	5.4	TEST ENVIRONMENT	7
	5.5	TEST FREQUENCY	8
	5.6	TEST LOCATION	10
	5.7	TEST FACILITY	10
	5.8	DEVIATION FROM STANDARDS	10
	5.9	ABNORMALITIES FROM STANDARD CONDITIONS	10
	5.10	OTHER INFORMATION REQUESTED BY THE CUSTOMER	11
	5.11	TECHNICAL SPECIFICATION	11
6	DES	SCRIPTION OF TESTS	12
	6.1	CONDUCTED OUTPUT POWER	12
	6.2	EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	12
	6.3	OCCUPIED BANDWIDTH	13
	6.4	BAND EDGE AT ANTENNA TERMINALS	13
	6.5	Spurious And Harmonic Emissions at Antenna Terminal	14
	6.6	PEAK-AVERAGE RATIO	15
	6.7	FIELD STRENGTH OF SPURIOUS RADIATION	15
	6.8	FREQUENCY STABILITY / TEMPERATURE VARIATION	16
	6.9	TEST SETUPS	18
	6.9.	1 Test Setup 1	18
	6.9.	2 Test Setup 2	19
	6.9.	3 Test Setup 3	20
	6.9.	4 Test Setup 4	21
	6.10	TEST CONDITIONS	22



Report No.: SZEM180100071902

Page: 5 of 26

7	MAIN TEST INSTRUMENTS	24
8	MEASUREMENT UNCERTAINTY	26
9	PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	26



Report No.: SZEM180100071902

Page: 6 of 26

5 General Information

5.1 Client Information

Applicant:	TCL Communication Ltd.		
Address of Applicant:	7/F, Block F4, TCL Communication Technology Building, TCL International E City, Zhong Shan Yuan Road, Nanshan District, Shenzhen, Guangdong, P.R. China 518052		
Manufacturer:	TCL Communication Ltd.		
Address of Manufacturer: 7/F, Block F4, TCL Communication Technology International E City, Zhong Shan Yuan Road, Na Shenzhen, Guangdong, P.R. China 518052			
Factory:	TCL Mobile Communication Co.,LTD.Huizhou		
Address: No.86, Hechang 7th West Road, ZhongKai Hi-tech Dev District, Huizhou, Guangdong			

5.2 General Description of EUT

Product Name:	LTE / UMTS / GSM mobile phone	
Model No.:	5044Y	
Trade Mark:	alcatel	
Sample Type:	Portable production	
Antenna Type:	PIFA Antenna	
	GSM850: -1.53dBi; GSM1900:0.67dBi	
Antenna Gain:	WCDMA B2:0.65dB; WCDMA B5: -1.53 dB	
	LTE B7: 0.54dBi	

5.3 Test Mode

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS/EGPRS, GMSK modulation
GSM/TM2	GSM system, EGPRS, 8PSK modulation
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
UMTS/TM2	UMTS system, WCDMA, 16QAM modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation

NOTE: The test mode(s) are selected according to relevant radio technology specifications.



Report No.: SZEM180100071902

Page: 7 of 26

5.4 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	52%	
Atmospheric Pressure:	1	015Pa
Temperature	TN	25 °C
	VL	3.5 V
Voltage :	VN	3.8 V
	VH	4.2 V

NOTE: VL= lower extreme test voltage

VN= nominal voltage

VH= upper extreme test voltage

TN= normal temperature



Report No.: SZEM180100071902

Page: 8 of 26

5.5 Test Frequency

To at Marila	TX / RX	RF Channel		
Test Mode		Low (L)	Middle (M)	High (H)
	TV	Channel 128	Channel 190	Channel 251
0014050	TX	824.2MHz	836.6 MHz	848.8 MHz
GSM850	DV	Channel 128	Channel 190	Channel 251
	RX	869.2 MHz	881.6 MHz	893.8 MHz
Took Mode	TV / DV		RF Channel	
Test Mode	TX / RX	Low (L)	Middle (M)	High (H)
	TX	Channel 512	Channel 661	Channel 810
GSM1900	1^	1850.2MHz	1880.0 MHz	1909.8 MHz
G3W1900	RX	Channel 512	Channel 661	Channel 810
	KA.	1930.2 MHz	1960.0 MHz	1989.8 MHz
Test Mode	TX / RX		RF Channel	
rest Mode	IA/RA	Low (L)	Middle (M)	High (H)
	TX	Channel 4132	Channel 4182	Channel 4233
WCDMA850	1^	826.4MHz	836.4 MHz	846.6 MHz
W CDIVIA030	RX	Channel 4357	Channel 4407	Channel 4458
	KA.	871.4 MHz	881.4 MHz	891.6 MHz
Test Mode	TV / DV	RF Channel		
rest Mode	TX / RX	Low (L)	Middle (M)	High (H)
	TX RX	Channel 9262	Channel 9400	Channel 9538
WCDMA1900		1852.4 MHz	1880.0 MHz	1907.6 MHz
W CDIVIA 1900		Channel 9662	Channel 9800	Channel 9938
		1932.4 MHz	1960.0 MHz	1987.6 MHz
Test Mode	TX / RX		RF Channel	
rest Mode		Low (L)	Middle (M)	High (H)
	TX	Channel 20775	Channel 21100	Channel 21425
LTE BAND 7	17	2502.5 MHz	2535 MHz	2567.5 MHz
5MHz	RX	Channel 2775	Channel 3100	Channel 5825
	IXX	2622.5 MHz	2655 MHz	2687.5 MHz
Test Mode	TX / RX		RF Channel	
rest Mode	TX / KX	Low (L)	Middle (M)	High (H)
	TX	Channel 20800	Channel 21100	Channel 21400
LTE BAND 7 10MHz	17	2505 MHz	2535 MHz	2565 MHz
	RX	Channel 2800	Channel 3100	Channel 3400
	IXX	2625 MHz	2655 MHz	2685 MHz
Test Mode	TX / RX		RF Channel	
I GSL MOUE	IX/IX	Low (L)	Middle (M)	High (H)
LTE BAND 7	TY	Channel 20825	Channel 21100	Channel 21375
15MHz	TX	2507.5 MHz	2535 MHz	2562.5 MHz

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the itis initiation of lability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180100071902

Page: 9 of 26

	DV	Channel 2825	Channel 3100	Channel 3375
	RX	2627.5 MHz	2655 MHz	2682.5 MHz
Test Mode	TX / RX	RF Channel		
r est Mode		Low (L)	Middle (M)	High (H)
LTE BAND 7 20MHz	TX	Channel 20850	Channel 21100	Channel 21350
		2510 MHz	2535 MHz	2560 MHz
	RX	Channel 2850	Channel 3100	Channel 3350
		2630 MHz	2655 MHz	2680 MHz



Report No.: SZEM180100071902

Page: 10 of 26

5.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

5.8 Deviation from Standards

None.

5.9 Abnormalities from Standard Conditions

None.



Report No.: SZEM180100071902

Page: 11 of 26

5.10Other Information Requested by the Customer

None.

5.11 Technical Specification

Characteristics	Description		
	⊠ GSM		
Radio System Type	□ UMTS □		
	GSM850	Transmission (TX): 824 to 849 MHz	
	GSIVIOSU	Receiving (RX): 869 to 894 MHz	
	GSM1900	Transmission (TX): 1850 to 1910 MHz	
	G3W1900	Receiving (RX): 1930 to 1990 MHz	
Supported Frequency Range	UMTS band 2	Transmission (TX): 1850 to 1910 MHz	
Supported Frequency Range	UWIS band 2	Receiving (RX): 1930 to 1990 MHz	
	UMTS band 5	Transmission (TX): 824 to 849 MHz	
		Receiving (RX): 869 to 894 MHz	
	LTE band 7	Transmission (TX): 2500 to 2570 MHz	
		Receiving (RX): 2620 to 2690 MHz	
	GSM850:33.3 dBm		
	GSM1900: 30.3dBm		
Target TX Output Power	UMTS band 2: 24dBm		
	UMTS band 5: 24dBm		
	LTE band 7: 23dBm		
	GSM system:	⊠0.2 MHz	
Supported Channel Bandwidth	UMTS system:	⊠5 MHz	
	LTE band7	⊠5 MHz; ⊠10 MHz; ⊠15 MHz, ⊠20 MHz	

Characteristics	Description		
	GSM850	246KGXW; 240KG7W	
Designation of Emissions (Note: the necessary bandwidth of which is the worst value from the measured occupied bandwidths for each type of channel bandwidth configuration.)	GSM1900	246KGXW; 242KG7W	
	UMTS band 2	4M23F9W; 4M23W7D	
	UMTS band 5	4M22F9W; 4M20W7D	
	LTE band7	4M50G7D;4M48W7D	
		8M93G7D;8M93W7D	
		13M5G7D;13M5W7D	
		17M9G7D;17M9W7D	



Report No.: SZEM180100071902

Page: 12 of 26

6 Description of Tests

6.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Note: Reference test setup 1

6.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 0.8m high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8). Calculate power in dBm by the following formula:

ERP (dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

Where:

Pg is the generator output power into the substitution antenna.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180100071902

Page: 13 of 26

Above 1GHz test procedure as below:

1). Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber

2). Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

3). Test the EUT in the lowest channel, the middle channel the Highest channel

4). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.

5). Repeat above procedures until all frequencies measured was complete.

Note: Reference test setup 2

6.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Note: Reference test setup 1

6.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03



Report No.: SZEM180100071902

Page: 14 of 26

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

Note: Reference test setup 1

6.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Note: Reference test setup 1



Report No.: SZEM180100071902

Page: 15 of 26

6.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Note: Reference test setup 1

6.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 Power Meas License Digital Systems v03

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)



Report No.: SZEM180100071902

Page: 16 of 26

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] – cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log10(Power [Watts]).

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete

Note: Reference test setup 3

6.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 Power Meas License Digital Systems v03

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of his document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180100071902

Page: 17 of 26

transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Note: Reference test setup 4




Report No.: SZEM180100071902

Page: 18 of 26

6.9 Test Setups

6.9.1 Test Setup 1




Ground Reference Plane



Report No.: SZEM180100071902

Page: 19 of 26

6.9.2 Test Setup 2



Hon Selection


Hon Selection

Test Receiver

Test Receiver

Figure 1. 30MHz to 1GHz

Figure 2. above 1GHz






Figure 1. 30MHz to 1GHz

Figure 2. above 1GHz



Report No.: SZEM180100071902

Page: 20 of 26

6.9.3 Test Setup 3




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 2. 30MHz to 1GHz




Figure 3. above 1GHz





Figure 3. above 1GHz



Report No.: SZEM180100071902

Page: 21 of 26

6.9.4 Test Setup 4



Ground Reference Plane



Report No.: SZEM180100071902

Page: 22 of 26

6.10 Test Conditions

Test Case		Test Conditions			
		Test Environment	Ambient Climate & Rated Voltage		
	Average Power,	Test Setup	Test Setup 1		
	Total	RF Channels (TX)	L, M, H		
Transmit		,	(L= low channel, M= middle channel, H= high channel)		
Output Power		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
Data	Average	Test Environment	Ambient Climate & Rated Voltage		
	Power, Spectral	Test Setup	Test Setup 1		
	Density (if required)	RF Channels (TX)	L, M, H		
			(L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Peak-to-Ave	erage Ratio	Test Setup	Test Setup 1		
(if required)		RF Channels	L, M, H		
		(TX)	(L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Modulation Characteris	tice	Test Setup	Test Setup 1		
Onaracions	1103	RF Channels (TX)	M (M= middle channe)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
	Occupied Bandwidth	Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
		RF Channels	L, M, H		
		(TX)	(L= low channel, M= middle channel, H= high channel)		
Bandwidth		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
	Emission	Test Environment	Ambient Climate & Rated Voltage		
	Bandwidth	Test Setup	Test Setup 1		
	(if required)	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		
Band	Edges	Test Environment	Ambient Climate & Rated Voltage		
Compliance		Test Setup	Test Setup 1		
		RF Channels (TX)	L, H		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180100071902

Page: 23 of 26

		(L= low channel, H= high channel)		
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM12;LTE/TM1;LTE/TM2		
	Test Environment	Ambient Climate & Rated Voltage		
Spurious Emission at Antenna Terminals	Test Setup	Test Setup 1		
Antenna Tenninais	RF Channels	L,M, H		
	(TX)	(L= low channel, M= middle channel, H= high channel)		
	Test Mode	GSM/TM1;UMTS/TM1;LTE/TM1		
	Test Environment	Ambient Climate & Rated Voltage		
Field Strongth of	Test Setup	Test Setup 2		
Field Strength of Spurious Radiation	Test Mode RF Channels	GSM/TM1;GSM/TM2;UMTS/TM1;UMTS/TM2;LTE/TM1;LTE/TM2; NOTE: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.		
		L, M, H		
	(TX)	(L= low channel, M= middle channel, H= high channel)		
	Test Env.	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;		
	Test Env.	(2) VL, VN and VH of Rated Voltage at Ambient Climate.		
Frequency Stability	Test Setup	Test Setup 4		
	RF Channels	L, M, H		
	(TX)	(L= low channel, M= middle channel, H= high channel)		
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;LTE/TM1;LTE/TM2		



Report No.: SZEM180100071902

Page: 24 of 26

7 Main Test Instruments

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-05-10	2018-05-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2017-10-09	2018-10-09
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-02	201711-15	2020-11-15
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
5	Horn Antenna (18- 26GHz)	ETS-LINDGREN	3160	SEM003-12	2017-11-24	2020-11-24
6	Pre-amplifier (0.1- 1300MHz)	Agilent Technologies	8447D	SEM005-01	2017-04-14	2018-04-14
7	Pre-Amplifier (0.1- 26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-10	2017-10-17	2018-10-17
8	Band filter	Amindeon	82346	SEM023-01	N/A	N/A
9	Universal radio communication tester	Rohde &Schwarz	CMU200	SEM010-01	2017-10-09	2018-10-09
10	Universal radio communication tester	Rohde &Schwarz	CMW500	SEM010-03	2017-10-23	2018-10-23
11	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-10-09	2018-10-09
12	BiConiLog Antenna (30MHz-3GHz)	Schwarzbeck	VULB9163	SEM003-05	2015-10-17	2018-10-17
13	Horn Antenna (800MHz-18GHz)	Rohde &Schwarz	HF907	SEM003-06	2015-06-14	2018-06-14



Report No.: SZEM180100071902

Page: 25 of 26

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy mm-dd)	Cal. Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-10
2	EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-14
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2017-07-06	2018-07-06
5	.Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14

	RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Humi/ Temp Indicator	MingGao	TH101B	W006-09	2017-03-09	2018-03-09
2	Signal Analyzer	Rohde Schwarz	FSV	W005-02	2017-03-06	2018-03-06
3	Barometer	ChangChun	DYM3	SEL0088	2017-05-24	2018-05-24
4	Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66319D	W009-02	2017-07-23	2018-07-23
5	Digital Multimeter	Fluke	15B+	W055-01	2017-03-09	2018-03-09
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	W005-02	2017-03-06	2018-03-06
7	Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2017-03-06	2018-03-06



Report No.: SZEM180100071902

Page: 26 of 26

8 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data	
Transmit Output Power Data	Power [dBm]	U = 0.37 dB	
Bandwidth	Magnitude [%]	U = 0.2%	
Band Edge Compliance	Disturbance Power [dBm]	U = 2.0 dB	
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = 2.0 dB	
		For 3 m Chamber:	
		U = 4.5 dB (30 MHz to 1GHz)	
Field Strength of Spurious	ERP [dBm]	U = 3.3 dB (above 1 GHz)	
Radiation	EKF [dBiii]	For 10 m Chamber:	
		U = 4.5 dB (30 MHz to 1GHz)	
		U = 3.2 dB (above 1 GHz)	
Frequency Stability	Frequency Accuracy [ppm]	U = 0.24 ppm	

9 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM801000719RG.

The End