

TEST REPORT No.I17Z40067-SRD07

for

TCL Communication Ltd.

GSM Quad-band/HSPA-UMTS Six-band/LTE 13-band mobile

phoneMODEL NAME:BBB100-2

FCC ID: 2ACCJN018

with

Hardware Version: 05

Software Version: AAJ048

Issued Date: 2017-03-10



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No.52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@catr.cn, website: www.chinattl.com



CONTENTS

1. B1	EST LABORATORY	3
1.1.	8BTESTING LOCATION	
1.2. 1.3.	9BTESTING ENVIRONMENT	
1.4.	11BSignature	
	CLIENT INFORMATION	
2.1.	12BAPPLICANT INFORMATION	
2.2.	13BManufacturer Information	
3. BE	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1.	14BABOUT EUT	5
3.2.	15BINTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3.	16BINTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4.	17BGENERAL DESCRIPTION	7
3.5.	18BEUT Set-ups	7
4. BF	REFERENCE DOCUMENTS	7
4.1.	19BDocuments Supplied by the Applicant	7
4.2.	20BREGULATIONS AND STANDARDS	7
5. BL	ABORATORY ENVIRONMENT	9
6. BS	SUMMARY OF TEST RESULTS	10
6.1.	21BSUMMARY OF TEST RESULTS	10
6.2.	22BTERMS USED IN THE SUMMARY OF TEST RESULTS	11
6.3.	23BSTATEMENTS	11
7. B1	EST EQUIPMENTS UTILIZED	12
ANNE	X A: MEASUREMENT RESULTS	13
24B	A.1. ELECTRIC FIELD STRENGTH OF FUNDAMENTAL AND OUTSIDE THE ALLOCATED BANDS	13
25B/	A.2. ELECTRIC FIELD RADIATED EMISSIONS (< 30MHz)	15
26B	A.3. ELECTRIC FIELD RADIATED EMISSIONS (≥30MHz)	18
	A.4. FREQUENCY TOLERANCE	
	A.5. 20DB BANDWIDTH	
29BA	A.6. CONDUCTED EMISSION	26
FINAL	RESULT	27
ANNE	K C: TEST LAYOUT 错误! 未定义+	3签。



1. Test Laboratory

1.1. Testing Location

Company Name: CTTLBeijing, TelecommunicationMetrologyCenter of MIIT

Address: No 52, Huayuanbei Road, Haidian District, Beijing, P.R.China

Postal Code: 100191

Telephone: +86-10-62304633-2678

Fax: +86-10-62304633-2504

1.2. Testing Environment

Ambient Temperature: 15 ~ 25°C

Relative Humidity: 30 ~ 60%

Air pressure 860 ~ 1060 mbar

1.3. Project Data

Receipt of Sample: 2017-03-07

Testing Start Date: 2017-03-07

Testing End Date: 2017-03-10

1.4. Signature

Zheng Mengxuan

榮勞遍

(Prepared this test report)

Zhu Liang

(Reviewedthis test report)

LvSongdong

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.

Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

Country: China

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-21-31363544

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.

Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

Country: China

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-21-31363544



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description:	GSM Quad-band/HSPA-UMTS Six-band/LTE 13-band	
	mobile phone	
FCC ID	2ACCJN018	
With NFC Function:	Yes	
Frequency:	13.56 MHz	
Antenna:	Internal	
Operation Voltage:	3.6VDC to 4.35VDC (nominal: 3.8VDC)	
Operation Temperature:	-20°C to +55°C	

Note1: Photographs of EUT are shown in ANNEX B of this test report. For component list, please refer to documents of the manufacturer.

3.2. Internal Identification of EUT Used during the Test

Mobile phone identification

 EUT ID*
 IMEI
 HW Version
 SW Version

 UT10a
 004402243183229
 05
 AAJ048

3.3. Internal Identification of AE Used during the Test

0.0. <u></u>	ilai laoiltilloatioli oi 7	te occa daring the	1000
AE ID*	Description	SN	Reversion
AE1	battery	1	/
AE2	battery	1	1
AE3	Travel charger	1	16TCT-CH-1886
AE4	Travel charger	1	16TCT-CH-1872
AE5	Travel charger	1	16TCT-CH-0005
450	LIOD Oakla	,	,
AE6	USB Cable	1	1
AE7	USB Cable	1	1
AE60	NFC Card	1	1
,	• • • • •	·	·
AE10	Travel charger	1	1
AE11	Travel charger	1	1
AE1			

Name CAC3440001C3 Model BAT-63108-003

Manufacturer ATL

^{*}EUT ID: is used to identify the test sample in the lab internally.



Capacitance 3440mAh Nominal voltage 3.85V

AE2

Name CAC3440003C1

Model TLp034E1

Manufacturer BYD

Capacitance 3440mAh

Nominal voltage 3.85V

AE3

Name CBA0060AGHC1

Model QC10US

Manufacturer BYD

Length of cable /

AE4

Name CBA0060ACHC1

Model QC10AU
Manufacturer BYD
Length of cable /

AE5

Name CBA0060AJHC1

Model QC10IN
Manufacturer BYD
Length of cable /

AE6

Model CDA0000105CF

Manufacturer /
Length of cable 99cm

AE7

Model CDA0000108C2

Manufacturer /
Length of cable 99cm

AE60

Model / Manufacturer /

AE10

Name CBA0060AAHC1

Model QC10EU
Manufacturer BYD
Length of cable /

AE11

Name CBA0060ABHC1



Model QC10UK
Manufacturer BYD
Length of cable /

3.4. General Description

This is a product supporting GSM Quad-band/CDMA/EVDO Tri-band/ HSPA-UMTS Six-band/LTE 15 band mobile phonewith 2.4G/5G technologies.

Manuals and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

Manufacturer's declaration: NFC work does not depend on other access methods, such as WLAN, GPRS, etc.

3.5. EUT Set-ups

EUT Set-up No.	Combination of EUT and AE	Remarks
Set. NFC01_1	EUT10 + AE1 + AE6 + AE3 + AE60	1
Set. NFC01_2	EUT10 + AE1 + AE6 + AE4 + AE60	
Set. NFC01_3	EUT10 + AE1 + AE6 + AE5 + AE60	
Set. NFC02	EUT1	
Set. NFC03	EUT10 + AE60	

The TransmitState of NFC: the NFC function is on. The EUT will transmit the NFC data and command continuously during the test.

The TransmitStateof without modulation: The EUT will transmit the CW signal at the operating frequency.

4. Reference Documents

4.1. <u>Documents Supplied by the Applicant</u>

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Regulations and Standards

The following documents listed in this section are referred for testing.

Reference	Title	Version
CFR 47 Part 2	Part 2—Frequency Allocations and Radio Treaty Matters;	2015
	General Rules and Regulations.	
CFR 47 Part15	Part 15 — Radio Frequency Devices.	2015
	Subpart C—Intentional Radiators.	
	§ 15.35Measurement detector functions and bandwidths.	
	§ 15.207 Conducted limits.	

^{*}AE ID: is used to identify the test sample in the lab internally.





§ 15.209 Radiated emission limits, general requirements. §15.215Additional provisions to the general radiated emission limitations.

§15.225 Operation within the band 13.110–14.010 MHz.

ANSI C63.10 American National Standard of Procedures for Compliance 2013

Testing of Unlicensed Wireless Devices



5. LABORATORY ENVIRONMENT

Semi-anechoic chamberSAC-1(23 meters \times 17meters \times 10meters) did not exceed following limits along the EMC testing:

T (Min 45 °O May 05 °O
Temperature	Min. = 15 °C,Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	>2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	<±4 dB, 3m/10m distance,
	from 30 to 1000 MHz
Site voltage standing-wave ratio(S _{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-Anechoic Chamber FAC-3(8.6m×6.1m×3.85m) did not exceed following limits along thetesting:

Min. = 15 °C, Max. = 25°C
Min. = 30 %, Max. = 60 %
> 110 dB
>2MΩ
< 1Ω
Between 0 and 6 dB, from 1to 18GHz
Between 0 and 6 dB, from 80 to 4000 MHz

Conducted Chamber did not exceed following limits along the testing:

Temperature	Min. = 15 °C, Max. = 25°C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2MΩ
Ground system resistance	< 0.5 Ω

Control Room did not exceed following limits along the testing:

Temperature	Min. = 15 °C,Max. = 25°C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2MΩ
Ground system resistance	< 0.5 Ω



6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

No	Test Cases	Clause in Regulation	Section in This Report	Verdict
1	Electric Field Strength of Fundamental Emissions	CFR 47 § 15.225(a)		P(Set. NFC03)
2	Electric Field Strength of Outside the Allocated Bands	CFR 47 § 15.225(b) CFR 47 § 15.225(c)	A.1	P(Set. NFC03)
3	Electric Field Radiated Emissions	CFR 47 § 15.209 CFR 47 § 15.225(d)	A.2	P(Set. NFC01_1, NFC 01_2, NFC01_3)
			A.3	P(Set. NFC01)
4	Frequency Tolerance	CFR 47 § 15.225(e)	A.4	P(Set. NFC02)
5	20dB Bandwidth	CFR 47 § 15.215(c)	A.5	P(Set. NFC02, 03)
6	Conducted Emissions	CFR 47 § 15.207	A.6	P(Set. NFC01_1, NFC 01_2, NFC01_3)
The measurement is carried out according to ANSI C63.4.See ANNEX A for details.				

Test Conditions:

For this report, all the test cases listed above were tested under normalTemperature, Voltage, Humidity, and Air Pressure. The specific conditions are as following:

	Tmin	-20 ℃
Temperature	T nom	25°C
	T max	55°C
	V min	3.6V
Voltage	V nom	3.8V
	V max	4.2 V
Humidity	H nom	44%
Air Pressure	A nom	1010 mbar



6.2. Terms Used in the Summary of Test Results

Terms Used in Condition Column:

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage
V min	Low Voltage
V max	High voltage
H nom	Norm Humidity
A nom	Norm Air Pressure

Terms Used in Verdict Column:

Р	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

Abbreviations:

AC	Alternating Current
AFH	Adaptive Frequency Hopping
BW	Band Width
E.I.R.P.	equivalent isotropical radiated power
ISM	Industrial, Scientific and Medical
RF	Radio Frequency
Tx	Transmitter

6.3. Statements

The test cases listed in Section 6.1 of this report for the EUT specified in Section 3 were performed by CTTL according to the reference documents in Section 4.

The EUT meets all applicable requirements of the regulations and standards in Section 4.2.

This report only deals with the NFC function among the features described in section 3.



7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL. DUE DATE
1.	Thermal Chamber	PL-2G	343074	ESPEC	2017-05-12
2.	Spectrum Analyzer	RSA3408A	B 010277	Tektronix	2017-05-27
3.	H-field Antenna	HFH2-Z2	829324/0007	R&S	2017-12-16
4.	EMI Antenna	VULB 9163	9163-235	Schwarz beck	2018-03-02
5.	Test Receiver	ESCI	100344	R&S	2018-03-01
6.	Universal Radio Communication Tester	CMW500	143008	R&S	2017-12-01
7.	Universal Radio Communication Tester	CMW500	116588	R&S	2017-12-01
8.	Spectrum Analyzer	E4440A	MY48250642	Agilent	2018-03-03
9.	LISN	ESH2-Z5	829991/012	R&S	2017-04-11



ANNEX A: MEASUREMENT RESULTS

A.1.Electric Field Strength of Fundamentaland Outside the Allocated bands

A.1.1. Reference

See Clause 13.5, Clause 13.4, Clause 8, and Annex E of ANSI C63.4-2009 specifically. See Clause 4, Clause 5, and Clause 6 of ANSI C63.4-2009 generally.

A.1.2. MeasurementMethods


The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3mfrom the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with thepeak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
12.56-14.56	10/30kHz

The E-field measured at 3m is calculated as:

E-field $(dB\mu V/m) = Rx (dB\mu V) + CableLoss (dB) + AF@3m (dB/m)$





A.1.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC (See 3.5).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of $15 \sim 25$ °C.

A.1.4. Limits

Eroguanov Panga (MUT)	E-field Strength Limit @ 30 m	E-field Strength Limit @ 3 m			
FrequencyRange (MHz)	(μ V/m)	(dBµV/m)			
13.560 ± 0.007	+15,848	124			
13.410 to 13.553	+334	90			
13.567 to 13.710	+334	90			
13.110 to 13.410	1106	04			
13.710 to 14.010	+106	81			

Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

Extrapolation(dB) = $40\log_{10}$ (Measurement Distance/Specification Distance)

A.1.5. Measurement Results

Measurement results of normal conditions see Figure C-1 for different set-ups of EUT. The result displayed take into account applicable antenna factors and cable losses.

Conclusions: Set. NFC03,PASS.




Figure A-1: Set. NFC03



A.1.6. Measurement Uncertainty

Measurement uncertainty: U = 3.94 dB, k=2.

A.2. Electric Field Radiated Emissions (< 30MHz)

A.2.1. Reference

See Clause 6.4of ANSI C63.10-2013 specifically. See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

A.2.2. MeasurementMethods


The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3mfrom the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
0.009-0.15	100/300 Hz
0.15-30	10/30 kHz

The E-field measured at 3m is calculated as:

E-field (dB μ V/m) = Rx (dB μ V)+ CableLoss (dB)+ AF@3m (dB/m)





A.2.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC (See 3.5).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of $15 \sim 25$ °C.

A.2.4. Limits

FrequencyRange (MHz)	E-field Strength Limit @ 30m	E-field Strength Limit @ 3m		
FrequencyRange (WITZ)	(mV/m)	(dBµV/m)		
0.009-0.490	2400/F(kHz)	129-94		
0.490-1.705	24000/F(kHz)	74-63		
1.705-30	30	70		

Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

Extrapolation(dB) = $40\log_{10}$ (Measurement Distance/Specification Distance)

A.2.5. Measurement Results

Measurement results of normal conditions see Figure C-2 for different set-ups of EUT. The result displayed take into account applicable antenna factors and cable losses.

Conclusions: Set. NFC01_01, Set. NFC01_02, Set. NFC01_03,PASS.




Figure A-2: Set. NFC01_1







Figure A-3: Set. NFC01_2



Full Spectrum

Figure A-4: Set. NFC01_3

A.2.6. Measurement Uncertainty

Measurement uncertainty: U = 3.94 dB, k=2.



A.3.Electric Field Radiated Emissions (≥30MHz)

A.3.1. Reference


See Clause 6.5of ANSI C63.10-2013 specifically. See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

A.3.2. MeasurementMethods

The electric field radiated emissions from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 10mfrom the receiving antenna. The receiving antennasconnected to a measurement receiver comply with Clause 15 of ANSI C63.2-1996 and Clause 6.5 of ANSI C63.10-2013. In order to search for maximum field strength emitted from the EUT, the receiving antenna can be moved between the height of 1.0 mto 4.0 m.Detected E-field was maximized at each frequencyby rotating the EUT through 360° and adjusting the receiving antenna positions for both vertical and horizontal antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
30-1000	120kHz





A.3.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC (See 3.5).

EUT1 had been connected to a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of $15 \sim 25$ °C.

A.3.4. Limits

FrequencyRange	E-field Strength Limit	E-field Strength Limit	E-field Strength Limit		
(MHz)	@ 3m	@ 3m	@ 10m		
(1411 12)	(mV/m)	(dB μ V/m)	(dBµV/m)		
30-88	100	40	30		
88-216	150	43.5	33.5		
216-960	200	46	36		
960-1000	500	54	44		

A.3.5. Measurement Results

Measurement results of normal conditions see Figure C-3for different set-ups of EUT. The result displayed take into account applicable antenna factors and cable losses.

Conclusions: Set. NFC01_01, Set. NFC01_02, Set. NFC01_03, PASS.



A.3.6. Measurement Uncertainty

Measurement uncertainty: *U* = 3.9 dB, k=2




Figure A-5: Set. NFC01_1

Final_Result

Frequency	QuasiPeak	Limit	Margin	Meas.	Bandwidth	Height	Pol	Azimuth
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	Time	(kHz)	(cm)		(deg)
32.790000	23.95	30.00	6.05	1000.0	120.000	119.0	V	68.0
44.605000	19.64	30.00	10.36	1000.0	120.000	185.0	V	169.0
48.462000	20.52	30.00	9.48	1000.0	120.000	210.0	V	201.0
142.326000	21.07	33.50	12.45	1000.0	120.000	125.0	V	61.0
149.116000	20.86	33.50	12.66	1000.0	120.000	119.0	V	60.0
957.602000	24.83	36.00	11.19	1000.0	120.000	216.0	V	107.0






Figure A-6: Set. NFC01_2

Frequency in Hz

Final_Result

Frequency	QuasiPeak	Limit	Margin	Meas.	Bandwidth	Height	Pol	Azimuth
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	Time	(kHz)	(cm)		(deg)
30.000000	22.68	30.00	7.32	1000.0	120.000	225.0	V	106.0
31.880000	21.98	30.00	8.02	1000.0	120.000	193.0	V	60.0
43.030000	24.49	30.00	5.51	1000.0	120.000	175.0	V	173.0
43.465000	22.93	30.00	7.07	1000.0	120.000	290.0	V	184.0
149.153000	19.95	33.50	13.57	1000.0	120.000	283.0	V	150.0
910.848000	24.14	36.00	11.88	1000.0	120.000	112.0	V	175.0






Figure A-7: Set. NFC01_3

Final_Result

Frequency	QuasiPeak	Limit	Margin	Meas.	Bandwidth	Height	Pol	Azimuth
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	Time	(kHz)	(cm)		(deg)
30.000000	21.74	30.00	8.26	1000.0	120.000	125.0	V	150.0
42.374000	24.22	30.00	5.78	1000.0	120.000	297.0	V	61.0
42.980000	24.39	30.00	5.61	1000.0	120.000	225.0	V	183.0
142.363000	13.58	33.50	19.94	1000.0	120.000	295.0	V	210.0
149.153000	22.13	33.50	11.39	1000.0	120.000	175.0	V	60.0
940.128000	24.68	36.00	11.34	1000.0	120.000	225.0	V	120.0

A.4.Frequency Tolerance


A.4.1. Reference

See Clause 13.6 of ANSI C63.4-2009 specifically.

See Clause 4, Clause 5, and Clause 6 of ANSI C63.4-2009 generally.

A.4.2. MeasurementMethods





The transmitter output signal was picked up by coil antenna connected to the frequency counter. The center frequency was measured with 30Hz RBW and 1kHz span.

During the test, the EUT was placed in a thermal chamber until thermal balance and lasting appropriate time.

A.4.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of without modulation (See 3.5). EUT1 had been not connected to a travel adapter.

Operation Temperature: T min, T nom, and T max with V nom.

Operation Voltage: V min and V max with T nom.

A.4.4. Test Layouts

See A.4.2.

A.4.5. Limits

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

A.4.6. Measurement Results

Measurement results see Table A-1for different test conditions.

Conclusions: Set. NFC02, PASS.



Table A-1: Frequency Stability VS Temperature and Voltage

Temperature	Voltage	Frequency Error (MHz)						
	voltage	Startup	2 Min Later	5 Min Later	10 Min Later			
T min	V nom	13.5599938	13.5601488	13.5600350	13.5600970			
T max	V nom	13.5600099	13.5600175	13.5599957	13.5600561			
T nom	V nom	13.5599831	13.5599882	13.5599963	13.5599894			
T nom	V min	13.5601113	13.5601790	13.5601080	13.5601235			
T nom	V max	13.5599176	13.5601457	13.5601231	13.5601272			

Temperature	Voltage	Frequency Error (%)						
	Voltage	Startup	2 Min Later	5 Min Later	10 Min Later			
T min	V nom	0.000	0.001	0.000	0.001			
T max	V nom	0.000	0.000	0.000	0.000			
T nom	V nom	0.000	0.000	0.000	0.000			
T nom	V min	0.001	0.001	0.001	0.001			
T nom	V max	-0.001	0.001	0.001	0.001			

A.4.7. Measurement Uncertainty

Measurement uncertainty: *U* =77Hz, k=2

A.5. 20dB Bandwidth

A.5.1. Reference


See Clause 13.7 of ANSI C63.4-2009 specifically.

See Clause 4, Clause 5, and Clause 6 of ANSI C63.4-2009 generally.

A.5.2. MeasurementMethods

The transmitter output signal was picked up by coil antenna to the spectrum analyzer.

The transmitter output signal was picked up by coil antenna connected to the spectrum analyzer. The bandwidth of the center frequency was measured with 140Hz RBW, 420Hz VBW and 14kHz span.





A.5.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC and without modulation (See 3.5).

EUT had been not connected to a travel adapter..

During the measurements, the ambient temperature is in the range of 15 ~ 25 °C.

A.5.4. Test Layouts

See A.5.2.

A.5.5. Limits

The 20dB bandwidth shall be less than 80% of the permittedfrequency band. For 13.56 MHz NFC, the permittedfrequency band is 14kHz, so the limit is 11.2 kHz.

A.5.6. Measurement Results

Measurement results see Figure A-4.

Conclusions: Set. NFC02 and NFC03, PASS.




Figure A-8: Test result of EUT1 at test set. NFC02

A.5.7. Measurement Uncertainty

Measurement uncertainty: U = 77Hz, k=2



A.6. Conducted emission

A.6.1. Reference

See Clause 6.2of ANSI C63.10-2013 specifically. See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.


A.6.2. MeasurementMethods

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak/ AverageDetector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
0.15-30	9kHz



A.6.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC (See 3.5).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature is in the range of 15 ~ 25 $^{\circ}$ C.

A.6.4. Limits

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Average Limit (dBμV)
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50




A.6.5. Measurement Results

Measurement results see Figure C-5. Conclusions: Set. NFC01_1, PASS.

Note: The measurement result at 13.56MHz is the fundamental emission of NFC signal.

CBA0060AGHC1(the worst case)



Final Result 1

Frequency	QuasiPeak	Meas.	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	Time	(kHz)			(dB)	(dB)	(dBµV)
0.199500	40.9	2000.0	9.000	On	L1	19.8	22.7	63.6
0.271500	34.4	2000.0	9.000	On	L1	19.8	26.7	61.1
0.645000	42.7	2000.0	9.000	On	L1	19.8	13.3	56.0
2.589000	32.4	2000.0	9.000	On	N	19.1	23.6	56.0
15.072000	50.9	2000.0	9.000	On	L1	19.8	9.1	60.0
17.911500	39.2	2000.0	9.000	On	N	19.9	20.8	60.0

Final Result 2

Frequency	Average	Meas.	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	Time	(kHz)			(dB)	(dB)	(dBµV)
0.645000	33.3	2000.0	9.000	On	L1	19.8	12.7	46.0
0.739500	28.1	2000.0	9.000	On	L1	19.8	17.9	46.0
1.738500	28.3	2000.0	9.000	On	N	19.7	17.7	46.0
2.589000	24.5	2000.0	9.000	On	N	19.1	21.5	46.0
15.189000	44.9	2000.0	9.000	On	L1	19.8	5.1	50.0
17.911500	32.7	2000.0	9.000	On	N	19.9	17.3	50.0

Figure A-9: Test result of EUT1 at test set. NFC01



A.6.6. Measurement Uncertainty

Measurement uncertainty: *U* = 3.38 dB, k=2

END OF REPORT