



FCC RF Test Report

APPLICANT : TCL Communication Ltd.
EQUIPMENT : USB Connect 5G (NA)
BRAND NAME : Vodafone
MODEL NAME : IK512US
FCC ID : 2ACCJSCD002
STANDARD : 47 CFR Part 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Jul. 18, 2024 ~ Jul. 30, 2024

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Maximum EIRP and Emission Designator	7
1.7 Testing Location	9
1.8 Test Software	9
1.9 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode	10
2.2 Connection Diagram of Test System	13
2.3 Support Unit used in test configuration and system	13
2.4 Measurement Results Explanation Example	13
2.5 Frequency List of Low/Middle/High Channels	14
3 CONDUCTED TEST ITEMS	19
3.1 Measuring Instruments	19
3.2 Test Setup	19
3.3 Test Result of Conducted Test	19
3.4 Conducted Output Power and EIRP	20
3.5 Peak-to-Average Ratio	22
3.6 Occupied Bandwidth	23
3.7 Conducted Band Edge	24
3.8 Conducted Spurious Emission	25
3.9 Frequency Stability	26
4 RADIATED TEST ITEMS	27
4.1 Measuring Instruments	27
4.2 Test Setup	27
4.3 Test Result of Radiated Test	28
4.4 Radiated Spurious Emission	29
5 LIST OF MEASURING EQUIPMENT	30
6 MEASUREMENT UNCERTAINTY	31
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG450613A	Rev. 01	Initial issue of report	Aug. 16, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2) (Band 25)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4) (Band 66)	EIRP < 1Watt		-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	Report Only	-
3.7	§2.1051 §24.238(a) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 25) (Band 4) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §24.238(a) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 25) (Band 4) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §24.235 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §24.238(a) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 25) (Band 4) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 29.95 dB at 9400.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

TCL Communication Ltd.

5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong

1.2 Manufacturer

Vodafone Procurement Company S.à.r.l.

15 rue Edward Steichen, L-2540 Luxembourg, Grand-Duché de Luxembourg

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	USB Connect 5G (NA)
Brand Name	Vodafone
Model Name	IK512US
FCC ID	2ACCJSCD002
IMEI Code	Conducted: 352912230200255 Radiation: 352912230200271
HW Version	V3.0
SW Version	IK512US_ZZ_01.00_04
EUT Stage	Production Unit

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 25 : 1930 MHz ~ 1995 MHz LTE Band 66 : 2110 MHz~ 2200 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 25 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 66 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	<ANT 1>: LTE Band 2 : 22.56 dBm; LTE Band CA_2C : 22.45 dBm LTE Band 4 : 22.78 dBm LTE Band 25 : 22.74 dBm LTE Band 66 : 22.85 dBm LTE Band CA_66B : 22.81 dBm

	LTE Band CA_66C : 22.84 dBm <ANT 2>: LTE Band 2 : 22.66 dBm LTE Band 4 : 22.46 dBm LTE Band 66 : 22.45 dBm
Antenna Gain	<ANT 1>: LTE Band 2 : 2.25 dBi LTE Band 4 : 4.00 dBi LTE Band 25 : 2.55 dBi LTE Band 66 : 4.00 dBi <ANT 2>: LTE Band 2 : 2.01 dBi LTE Band 4 : 2.96 dBi LTE Band 66 : 2.96 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Note:

1. ANT 2 for LTE Band 2/4/66 only support ENDC or inter band CA, not support intra band CA.
2. The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP of ANT 1 for LTE Band 2/4/25/66/2C/66B/66C are shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP and Emission Designator

LTE Band 2		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1850.7 ~ 1909.3	0.2999	1M10G7D	0.2382	1M09W7D
3	1851.5 ~ 1908.5	0.2999	2M74G7D	0.2547	2M74W7D
5	1852.5 ~ 1907.5	0.2999	4M51G7D	0.2541	4M51W7D
10	1855.0 ~ 1905.0	0.3020	9M05G7D	0.2523	9M05W7D
15	1857.5 ~ 1902.5	0.2992	13M5G7D	0.2535	13M5W7D
20	1860.0 ~ 1900.0	0.3027	17M9G7D	0.2559	17M9W7D
LTE Band 25		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1850.7 ~ 1914.3	0.3350	1M10G7D	0.2661	1M09W7D
3	1851.5 ~ 1913.5	0.3289	2M74G7D	0.2600	2M74W7D
5	1852.5 ~ 1912.5	0.3357	4M51G7D	0.2661	4M51W7D
10	1855.0 ~ 1910.0	0.3350	9M05G7D	0.2636	9M05W7D
15	1857.5 ~ 1907.5	0.3357	13M5G7D	0.2612	13M5W7D
20	1860.0 ~ 1905.0	0.3381	17M9G7D	0.2679	17M9W7D
LTE Band 4		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1754.3	0.4677	1M10G7D	0.3707	1M11W7D
3	1711.5 ~ 1753.5	0.4721	2M72G7D	0.3758	2M72W7D
5	1712.5 ~ 1752.5	0.4699	4M54G7D	0.3724	4M48W7D
10	1715.0 ~ 1750.0	0.4721	9M03G7D	0.3767	9M11W7D
15	1717.5 ~ 1747.5	0.4732	13M5G7D	0.3776	13M4W7D
20	1720.0 ~ 1745.0	0.4764	17M9G7D	0.3784	17M9W7D
LTE Band 66		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1779.3	0.4742	1M10G7D	0.4276	1M11W7D
3	1711.5 ~ 1778.5	0.4764	2M72G7D	0.4188	2M72W7D
5	1712.5 ~ 1777.5	0.4753	4M54G7D	0.4207	4M48W7D
10	1715.0 ~ 1775.0	0.4753	9M03G7D	0.4227	9M11W7D
15	1717.5 ~ 1772.5	0.4764	13M5G7D	0.4178	13M4W7D
20	1720.0 ~ 1770.0	0.4842	17M9G7D	0.4295	17M9W7D



LTE Band CA_2C	QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5MHz+20MHz	0.2911	23M3G7D	0.2495	22M8W7D
10MHz+15MHz	0.2897	23M2G7D	0.2500	23M5W7D
10MHz+20MHz	0.2917	27M9G7D	0.2518	28M2W7D
15MHz+10MHz	0.2904	23M4G7D	0.2466	23M6W7D
15MHz+15MHz	0.2871	28M5G7D	0.2518	28M5W7D
15MHz+20MHz	0.2838	32M5G7D	0.2523	32M5W7D
20MHz+5MHz	0.2871	23M1G7D	0.2535	23M2W7D
20MHz+10MHz	0.2917	28M0G7D	0.2495	28M0W7D
20MHz+15MHz	0.2871	32M9G7D	0.2506	32M7W7D
20MHz+20MHz	0.2951	37M5G7D	0.2541	37M7W7D
LTE Band CA_66B	QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5MHz+5MHz	0.4667	9M25G7D	0.3899	9M31W7D
5MHz+10MHz	0.4581	13M9G7D	0.4074	13M9W7D
5MHz+15MHz	0.4667	18M1G7D	0.4074	18M1W7D
10MHz+5MHz	0.4603	13M9G7D	0.4018	14M0W7D
15MHz+5MHz	0.4645	18M2G7D	0.4111	18M2W7D
10MHz+10MHz	0.4797	18M7G7D	0.4256	18M7W7D
LTE Band CA_66C	QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5MHz+20MHz	0.4656	23M3G7D	0.4055	23M2W7D
10MHz+15MHz	0.4634	23M5G7D	0.3972	23M3W7D
10MHz+20MHz	0.4560	27M9G7D	0.4046	28M0W7D
15MHz+10MHz	0.4539	23M4G7D	0.4074	23M5W7D
15MHz+15MHz	0.4571	28M8G7D	0.3972	28M5W7D
15MHz+20MHz	0.4592	32M7G7D	0.3945	32M6W7D
20MHz+5MHz	0.4592	23M5G7D	0.3954	23M2W7D
20MHz+10MHz	0.4592	28M1G7D	0.4009	28M1W7D
20MHz+15MHz	0.4677	32M9G7D	0.4083	32M8W7D
20MHz+20MHz	0.4831	37M7G7D	0.4227	37M6W7D

Note:

1. LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4.
2. LTE Band 25 overlaps the entire frequency range of LTE Band 2. Therefore, the test results provided in this report covers Band 25 as well as Band 2.

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	25	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	25						v	v	v	v				v		v	
	66						v	v	v	v				v		v	
26dB and 99% Bandwidth	25	v	v	v	v	v	v	v	v	v				v		v	
	66	v	v	v	v	v	v	v	v	v				v		v	
Conducted Band Edge	25	v	v	v	v	v	v	v	v	v		v		v	v		v
	66	v	v	v	v	v	v	v	v	v		v		v	v		v
Conducted Spurious Emission	25	v	v	v	v	v	v	v	v	v		v			v	v	v
	66	v	v	v	v	v	v	v	v	v		v			v	v	v
Frequency Stability	25				v			v						v		v	
	66				v			v						v		v	
E.R.P / E.I.R.P	25	v	v	v	v	v	v	v	v	v	v	v			v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	25	Worst Case														v	
	66	Worst Case														v	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4. 5. LTE Band 25 overlaps the entire frequency range of LTE Band 2. Therefore, the test results provided in this report covers Band 25 as well as Band 2.																




Test Items	Band	Bandwidth (MHz)										Modulation				RB #			Test Channel		
		20+20	20+15	20+10	20+5	15+20	15+15	15+10	10+20	10+15	5+20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	2C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v			v	v	v
26dB and 99% Bandwidth	2C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v				v		v	
Conducted Band Edge	2C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v		v		v	v		v
Conducted Spurious Emission	2C_CA	v	v	v	v	v	v	v	v	v	v	v				v			v	v	v
E.I.R.P.	2C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	2C_CA	Worst Case																		v	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 3. All test items are based on engineering evaluation. 4. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power																				

Test Items	Band	Bandwidth (MHz)								Modulation				RB #			Test Channel		
		10+10	15+5	5+15	10+5	5+10	5+5	5+3	3+5	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	66B_CA	v	v	v	v	v	v	-	-	v	v	v	v	v			v	v	v
26dB and 99% Bandwidth	66B_CA	v	v	v	v	v	v	-	-	v	v					v		v	
Conducted Band Edge	66B_CA	v	v	v	v	v	v	-	-	v	v	v		v		v	v		v
Conducted Spurious Emission	66B_CA	v	v	v	v	v	v	-	-	v				v			v	v	v
E.I.R.P.	66B_CA	v	v	v	v	v	v	-	-	v	v	v	v	v			v	v	v
Radiated Spurious Emission	66B_CA	Worst Case																v	
Note	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. All test items are based on engineering evaluation. 5. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power																		



Test Items	Band	Bandwidth (MHz)										Modulation				RB #			Test Channel		
		20+20	20+15	20+10	20+5	15+20	15+15	15+10	10+20	10+15	5+20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	66C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v			v	v	v
26dB and 99% Bandwidth	66C_CA	v	v	v	v	v	v	v	v	v	v	v	v					v		v	
Conducted Band Edge	66C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v		v		v	v		v
Conducted Spurious Emission	66C_CA	v	v	v	v	v	v	v	v	v	v	v				v			v	v	v
E.I.R.P.	66C_CA	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	66C_CA	Worst Case																		v	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 3. All test items are based on engineering evaluation. 4. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power																				

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	Fcc DoC	N/A	Shielded, 1.5m
3.	Notebook	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.5 + 10 = 14.5 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	26140	26340	26590
	Frequency	1860	1880	1905
15	Channel	26115	26340	26615
	Frequency	1857.5	1880	1907.5
10	Channel	26090	26340	26640
	Frequency	1855	1880	1910
5	Channel	26065	26340	26665
	Frequency	1852.5	1880	1912.5
3	Channel	26055	26340	26675
	Frequency	1851.5	1880	1913.5
1.4	Channel	26047	26340	26683
	Frequency	1850.7	1880	1914.3

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3



LTE Band 2C_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
5 + 20	PCC	Channel	18633	18808	18983
		Frequency	1853.3	1870.8	1888.3
	SCC	Channel	18750	18925	19100
		Frequency	1865	1882.5	1900
20 + 5	PCC	Channel	18700	18875	19050
		Frequency	1860	1877.5	1895
	SCC	Channel	18817	18992	19167
		Frequency	1871.7	1889.2	1906.7
10 + 20	PCC	Channel	18655	18806	18956
		Frequency	1855.5	1870.6	1885.6
	SCC	Channel	18799	18950	19100
		Frequency	1869.9	1885	1900
20 + 10	PCC	Channel	18700	18851	19001
		Frequency	1860	1875.1	1890.1
	SCC	Channel	18844	18995	19145
		Frequency	1874.4	1889.5	1904.5
10 + 15	PCC	Channel	18653	18829	19005
		Frequency	1855.3	1872.9	1890.5
	SCC	Channel	18773	18949	19125
		Frequency	1867.3	1884.9	1902.5
15 + 10	PCC	Channel	18675	18851	19027
		Frequency	1857.5	1875.1	1892.7
	SCC	Channel	18795	18971	19147
		Frequency	1869.5	1887.1	1904.7
15 + 15	PCC	Channel	18675	18825	18975
		Frequency	1857.5	1872.5	1887.5
	SCC	Channel	18825	18975	19125
		Frequency	1872.5	1887.5	1902.5
15 + 20	PCC	Channel	18678	18803	18929
		Frequency	1857.8	1870.3	1882.9
	SCC	Channel	18849	18974	19100
		Frequency	1874.9	1887.4	1900
20 + 15	PCC	Channel	18700	18826	18951
		Frequency	1860	1872.6	1885.1
	SCC	Channel	18871	18997	19122
		Frequency	1877.1	1889.7	1902.2
20 + 20	PCC	Channel	18700	18801	18902
		Frequency	1860	1870.1	1880.2
	SCC	Channel	18898	18999	19100
		Frequency	1879.8	1889.9	1900



LTE Band 66B_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
5 + 5	PCC	Channel	131997	132398	132599
		Frequency	1712.5	1752.6	1772.7
	SCC	Channel	132045	132446	132647
		Frequency	1717.3	1757.4	1777.5
5 + 10	PCC	Channel	132000	132375	132550
		Frequency	1712.8	1750.3	1767.8
	SCC	Channel	132072	132447	132622
		Frequency	1720	1757.5	1775
10 + 5	PCC	Channel	132022	132397	132572
		Frequency	1715	1752.5	1770
	SCC	Channel	132094	132469	132644
		Frequency	1722.2	1759.7	1777.2
5 + 15	PCC	Channel	132002	132353	132504
		Frequency	1713	1748.1	1763.2
	SCC	Channel	132095	132446	132597
		Frequency	1722.3	1757.4	1772.5
15 + 5	PCC	Channel	132047	132398	132549
		Frequency	1717.5	1752.6	1767.7
	SCC	Channel	132140	132491	132642
		Frequency	1726.8	1761.9	1777
10 + 10	PCC	Channel	132022	132373	132523
		Frequency	1715	1750.1	1765.1
	SCC	Channel	132121	132472	132622
		Frequency	1724.9	1760	1775



LTE Band 66C_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
10 + 15	PCC	Channel	132025	132351	132477
		Frequency	1715.3	1747.9	1760.5
	SCC	Channel	132145	132471	132597
		Frequency	1727.3	1759.9	1772.5
15 + 10	PCC	Channel	132047	132373	132499
		Frequency	1717.5	1750.1	1762.7
	SCC	Channel	132167	132493	132619
		Frequency	1729.5	1762.1	1774.7
10 + 20	PCC	Channel	132027	132328	132428
		Frequency	1715.5	1745.6	1755.6
	SCC	Channel	132171	132472	132572
		Frequency	1729.9	1760	1770
20 + 10	PCC	Channel	132072	132373	132473
		Frequency	1720	1750.1	1760.1
	SCC	Channel	132216	132517	132617
		Frequency	1734.4	1764.5	1774.5
15 + 15	PCC	Channel	132047	132347	132447
		Frequency	1717.5	1747.5	1757.5
	SCC	Channel	132197	132497	132597
		Frequency	1732.5	1762.5	1772.5
15 + 20	PCC	Channel	132050	132325	132401
		Frequency	1717.8	1745.3	1752.9
	SCC	Channel	132221	132496	132572
		Frequency	1734.9	1762.4	1770
20 + 15	PCC	Channel	132072	132348	132423
		Frequency	1720	1747.6	1755.1
	SCC	Channel	132243	132519	132594
		Frequency	1737.1	1764.7	1772.2
20 + 5	PCC	Channel	132072	132397	132522
		Frequency	1720	1752.5	1765
	SCC	Channel	132189	132514	132639
		Frequency	1731.7	1764.2	1776.7
5 + 20	PCC	Channel	132005	132330	132455
		Frequency	1713.3	1745.8	1758.3
	SCC	Channel	132122	132447	132572
		Frequency	1725	1757.5	1770
20 + 20	PCC	Channel	132072	132323	132374
		Frequency	1720	1745.1	1750.2
	SCC	Channel	132270	132521	132572
		Frequency	1739.8	1764.9	1770


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and EIRP

3.4.1 Description of the Conducted Output Power Measurement and EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 25.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4 and Band 66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB


3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.


3.4.3 Test Procedures for LTE ULCA

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter PCC & SCC output ports were connected to the system simulator.
3. Set EUT at maximum power, set the PCC/SCC CA band, channel, bandwidth and RB config.


PCC config_ (Channel Bandwidth / Channel / Band)




SCC config_ (Channel Bandwidth / Channel / Band)



PCC config_ (Number of RB / Starting RB)




SCC config_ (Number of RB / Starting RB)




4. Select lowest, middle, and highest channels for each ULCA band and different modulation.
5. Check the ULCA spectrum and record the total power from the system simulator.

Check the ULCA spectrum (eg. 20M+20M)



Read the Total UL CA output power (PCC+SCC)



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power $P(\text{Watts})$

$$= P(\text{W}) - [43 + 10\log(P)] (\text{dB})$$

$$= [30 + 10\log(P)] (\text{dBm}) - [43 + 10\log(P)] (\text{dB}) = -13\text{dBm}.$$

9. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Jul. 26, 2024~ Jul. 30, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2023	Jul. 26, 2024~ Jul. 30, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Jul. 26, 2024~ Jul. 30, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2024	Jul. 18, 2024	Jul. 02, 2025	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	Jul. 18, 2024	Jul. 27, 2024	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Oct. 24, 2023	Jul. 18, 2024	Oct. 23, 2025	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Jul. 18, 2024	Jul. 04, 2025	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 09, 2024	Jul. 18, 2024	Apr. 08, 2025	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18, 2023	Jul. 18, 2024	Oct. 17, 2024	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 18, 2023	Jul. 18, 2024	Oct. 17, 2024	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Jul. 18, 2024	Jul. 03, 2025	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 18, 2023	Jul. 18, 2024	Oct. 17, 2024	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Jul. 18, 2024	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Jul. 18, 2024	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.72 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	LiangHuaCong	Temperature :	24~26°C
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and EIRP

LTE Band 2_ANT 1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				18700	18900	19100			
Frequency (MHz)				1860	1880	1900	L	M	H
20	QPSK	1	0	22.53	22.56	22.50	0.3006	0.3027	0.2985
20	QPSK	1	49	22.43	22.51	22.44	0.2938	0.2992	0.2944
20	QPSK	1	99	22.44	22.46	22.38	0.2944	0.2958	0.2904
20	QPSK	50	0	21.56	21.58	21.55	0.2404	0.2415	0.2399
20	QPSK	50	24	21.48	21.55	21.52	0.2360	0.2399	0.2382
20	QPSK	50	50	21.48	21.56	21.48	0.2360	0.2404	0.2360
20	QPSK	100	0	21.50	21.53	21.48	0.2371	0.2388	0.2360
20	16QAM	1	0	21.82	21.83	21.76	0.2553	0.2559	0.2518
20	64QAM	1	0	20.63	20.67	20.63	0.1941	0.1959	0.1941
20	256QAM	1	0	17.61	17.64	17.61	0.0968	0.0975	0.0968
Channel				18675	18900	19125	EIRP(W)		
Frequency (MHz)				1857.5	1880	1902.5	L	M	H
15	QPSK	1	0	22.46	22.51	22.43	0.2958	0.2992	0.2938
15	16QAM	1	0	21.79	21.78	21.70	0.2535	0.2529	0.2483
Channel				18650	18900	19150	EIRP(W)		
Frequency (MHz)				1855	1880	1905	L	M	H
10	QPSK	1	0	22.48	22.55	22.47	0.2972	0.3020	0.2965
10	16QAM	1	0	21.74	21.77	21.69	0.2506	0.2523	0.2477
Channel				18625	18900	19175	EIRP(W)		
Frequency (MHz)				1852.5	1880	1907.5	L	M	H
5	QPSK	1	0	22.52	22.48	22.43	0.2999	0.2972	0.2938
5	16QAM	1	0	21.75	21.80	21.71	0.2512	0.2541	0.2489
Channel				18615	18900	19185	EIRP(W)		
Frequency (MHz)				1851.5	1880	1908.5	L	M	H
3	QPSK	1	0	22.48	22.52	22.43	0.2972	0.2999	0.2938
3	16QAM	1	0	21.79	21.81	21.73	0.2535	0.2547	0.2500
Channel				18607	18900	19193	EIRP(W)		
Frequency (MHz)				1850.7	1880	1909.3	L	M	H
1.4	QPSK	1	0	22.46	22.52	22.44	0.2958	0.2999	0.2944
1.4	16QAM	1	0	21.44	21.52	21.46	0.2339	0.2382	0.2350



LTE Band 4_ANT 1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				20050	20175	20300			
Frequency (MHz)				1720	1732.5	1745	L	M	H
20	QPSK	1	0	22.75	22.78	22.73	0.4732	0.4764	0.4710
20	QPSK	1	49	22.58	22.62	22.57	0.4550	0.4592	0.4539
20	QPSK	1	99	22.63	22.67	22.59	0.4603	0.4645	0.4560
20	QPSK	50	0	21.78	21.80	21.75	0.3784	0.3802	0.3758
20	QPSK	50	24	21.73	21.74	21.70	0.3741	0.3750	0.3715
20	QPSK	50	50	21.76	21.78	21.68	0.3767	0.3784	0.3698
20	QPSK	100	0	21.73	21.75	21.71	0.3741	0.3758	0.3724
20	16QAM	1	0	21.74	21.78	21.76	0.3750	0.3784	0.3767
20	64QAM	1	0	20.73	20.78	20.70	0.2972	0.3006	0.2951
20	256QAM	1	0	17.67	17.75	17.74	0.1469	0.1496	0.1493
Channel				20025	20175	20325	EIRP(W)		
Frequency (MHz)				1717.5	1732.5	1747.5	L	M	H
15	QPSK	1	0	22.71	22.75	22.68	0.4688	0.4732	0.4656
15	16QAM	1	0	21.70	21.77	21.73	0.3715	0.3776	0.3741
Channel				20000	20175	20350	EIRP(W)		
Frequency (MHz)				1715	1732.5	1750	L	M	H
10	QPSK	1	0	22.74	22.74	22.65	0.4721	0.4721	0.4624
10	16QAM	1	0	21.69	21.76	21.68	0.3707	0.3767	0.3698
Channel				19975	20175	20375	EIRP(W)		
Frequency (MHz)				1712.5	1732.5	1752.5	L	M	H
5	QPSK	1	0	22.71	22.72	22.71	0.4688	0.4699	0.4688
5	16QAM	1	0	21.71	21.70	21.68	0.3724	0.3715	0.3698
Channel				19965	20175	20385	EIRP(W)		
Frequency (MHz)				1711.5	1732.5	1753.5	L	M	H
3	QPSK	1	0	22.70	22.74	22.65	0.4677	0.4721	0.4624
3	16QAM	1	0	21.70	21.75	21.69	0.3715	0.3758	0.3707
Channel				19950	20175	20393	EIRP(W)		
Frequency (MHz)				1710	1732.5	1754.3	L	M	H
1.4	QPSK	1	0	22.67	22.70	22.69	0.4645	0.4677	0.4667
1.4	16QAM	1	0	21.65	21.69	21.68	0.3673	0.3707	0.3698



LTE Band 25_ANT 1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				26140	26340	26590			
Frequency (MHz)				1860	1880	1905	L	M	H
20	QPSK	1	0	22.69	22.74	22.63	0.3342	0.3381	0.3296
20	QPSK	1	49	22.39	22.53	22.50	0.3119	0.3221	0.3199
20	QPSK	1	99	22.59	22.63	22.62	0.3266	0.3296	0.3289
20	QPSK	50	0	21.83	21.86	21.83	0.2742	0.2761	0.2742
20	QPSK	50	24	21.68	21.83	21.76	0.2649	0.2742	0.2698
20	QPSK	50	50	21.69	21.73	21.70	0.2655	0.2679	0.2661
20	QPSK	100	0	21.58	21.72	21.67	0.2588	0.2673	0.2642
20	16QAM	1	0	21.66	21.73	21.66	0.2636	0.2679	0.2636
20	64QAM	1	0	20.59	20.63	20.58	0.2061	0.2080	0.2056
20	256QAM	1	0	17.14	17.22	17.19	0.0931	0.0948	0.0942
Channel				26115	26340	26615	EIRP(W)		
Frequency (MHz)				1857.5	1880	1907.5	L	M	H
15	QPSK	1	0	22.61	22.71	22.54	0.3281	0.3357	0.3228
15	16QAM	1	0	21.51	21.62	21.52	0.2547	0.2612	0.2553
Channel				26090	26340	26640	EIRP(W)		
Frequency (MHz)				1855	1880	1910	L	M	H
10	QPSK	1	0	22.55	22.70	22.48	0.3236	0.3350	0.3184
10	16QAM	1	0	21.57	21.66	21.63	0.2582	0.2636	0.2618
Channel				26065	26340	26665	EIRP(W)		
Frequency (MHz)				1852.5	1880	1912.5	L	M	H
5	QPSK	1	0	22.62	22.71	22.48	0.3289	0.3357	0.3184
5	16QAM	1	0	21.58	21.70	21.55	0.2588	0.2661	0.2570
Channel				26055	26340	26675	EIRP(W)		
Frequency (MHz)				1851.5	1880	1913.5	L	M	H
3	QPSK	1	0	22.54	22.62	22.53	0.3228	0.3289	0.3221
3	16QAM	1	0	21.56	21.59	21.60	0.2576	0.2594	0.2600
Channel				26047	26340	26683	EIRP(W)		
Frequency (MHz)				1850.7	1880	1914.3	L	M	H
1.4	QPSK	1	0	22.66	22.70	22.59	0.3319	0.3350	0.3266
1.4	16QAM	1	0	21.62	21.70	21.53	0.2612	0.2661	0.2559



LTE Band 66_ANT 1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				132072	132322	132572			
Frequency (MHz)				1720	1745	1770	L	M	H
20	QPSK	1	0	22.78	22.85	22.81	0.4764	0.4842	0.4797
20	QPSK	1	49	22.64	22.71	22.69	0.4613	0.4688	0.4667
20	QPSK	1	99	22.62	22.77	22.72	0.4592	0.4753	0.4699
20	QPSK	50	0	21.76	21.83	21.80	0.3767	0.3828	0.3802
20	QPSK	50	24	21.70	21.81	21.80	0.3715	0.3811	0.3802
20	QPSK	50	50	21.71	21.79	21.65	0.3724	0.3793	0.3673
20	QPSK	100	0	21.63	21.78	21.65	0.3656	0.3784	0.3673
20	16QAM	1	0	22.23	22.33	22.23	0.4198	0.4295	0.4198
20	64QAM	1	0	20.66	20.71	20.60	0.2924	0.2958	0.2884
20	256QAM	1	0	17.51	17.64	17.53	0.1416	0.1459	0.1422
Channel				132047	132322	132597	EIRP(W)		
Frequency (MHz)				1717.5	1745	1772.5	L	M	H
15	QPSK	1	0	22.74	22.78	22.77	0.4721	0.4764	0.4753
15	16QAM	1	0	22.08	22.21	22.20	0.4055	0.4178	0.4169
Channel				132022	132322	132622	EIRP(W)		
Frequency (MHz)				1715	1745	1775	L	M	H
10	QPSK	1	0	22.77	22.73	22.73	0.4753	0.4710	0.4710
10	16QAM	1	0	22.11	22.26	22.17	0.4083	0.4227	0.4140
Channel				131997	132322	132647	EIRP(W)		
Frequency (MHz)				1712.5	1745	1777.5	L	M	H
5	QPSK	1	0	22.65	22.77	22.71	0.4624	0.4753	0.4688
5	16QAM	1	0	22.10	22.24	22.21	0.4074	0.4207	0.4178
Channel				131987	132322	132657	EIRP(W)		
Frequency (MHz)				1711.5	1745	1778.5	L	M	H
3	QPSK	1	0	22.72	22.78	22.71	0.4699	0.4764	0.4688
3	16QAM	1	0	22.10	22.22	22.21	0.4074	0.4188	0.4178
Channel				131979	132322	132665	EIRP(W)		
Frequency (MHz)				1710.7	1745	1779.3	L	M	H
1.4	QPSK	1	0	22.75	22.76	22.75	0.4732	0.4742	0.4732
1.4	16QAM	1	0	22.13	22.31	22.22	0.4102	0.4276	0.4188



CA_2C_ANT 1

Combination 20MHz+20MHz (100RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.42	0.2931
M	QPSK	1	Max	1	0	22.45	0.2951
H	QPSK	1	Max	1	0	22.41	0.2924
L	16QAM	1	Max	1	0	21.80	0.2541
M	16QAM	1	Max	1	0	21.75	0.2512
H	16QAM	1	Max	1	0	21.73	0.2500
L	64QAM	1	Max	1	0	20.54	0.1901
M	64QAM	1	Max	1	0	20.65	0.1950
H	64QAM	1	Max	1	0	20.50	0.1884
L	256QAM	1	Max	1	0	17.55	0.0955
M	256QAM	1	Max	1	0	17.52	0.0948
H	256QAM	1	Max	1	0	17.65	0.0977
Combination 20MHz+15MHz (100RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.33	0.2871
L	16QAM	1	Max	1	0	21.74	0.2506
Combination 15MHz+20MHz (75RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.28	0.2838
L	16QAM	1	Max	1	0	21.77	0.2523
Combination 15MHz+15MHz (75RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.33	0.2871
L	16QAM	1	Max	1	0	21.76	0.2518
Combination 20MHz+10MHz (100RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.40	0.2917
L	16QAM	1	Max	1	0	21.72	0.2495
Combination 10MHz+20MHz (50RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.40	0.2917
L	16QAM	1	Max	1	0	21.76	0.2518
Combination 15MHz+10MHz (75RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.38	0.2904
L	16QAM	1	Max	1	0	21.67	0.2466
Combination 10MHz+15MHz (50RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.37	0.2897
L	16QAM	1	Max	1	0	21.73	0.2500
Combination 20MHz+5MHz (100RB+25RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.33	0.2871
L	16QAM	1	Max	1	0	21.79	0.2535
Combination 5MHz+20MHz (25RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
M	QPSK	1	Max	1	0	22.39	0.2911
L	16QAM	1	Max	1	0	21.72	0.2495

**CA_66B_ANT 1**

Combination 10MHz+10MHz (50RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.81	0.4797
M	QPSK	1	Max	1	0	22.69	0.4667
H	QPSK	1	Max	1	0	22.71	0.4688
L	16QAM	1	Max	1	0	22.19	0.4159
M	16QAM	1	Max	1	0	22.12	0.4093
H	16QAM	1	Max	1	0	22.29	0.4256
L	64QAM	1	Max	1	0	20.63	0.2904
M	64QAM	1	Max	1	0	20.61	0.2891
H	64QAM	1	Max	1	0	20.60	0.2884
L	256QAM	1	Max	1	0	17.51	0.1416
M	256QAM	1	Max	1	0	17.51	0.1416
H	256QAM	1	Max	1	0	17.56	0.1432
Combination 15MHz+5MHz (75RB+25RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.67	0.4645
H	16QAM	1	Max	1	0	22.14	0.4111
Combination 5MHz+15MHz (25RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.69	0.4667
H	16QAM	1	Max	1	0	22.10	0.4074
Combination 10MHz+5MHz (50RB+25RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.63	0.4603
H	16QAM	1	Max	1	0	22.04	0.4018
Combination 5MHz+10MHz (25RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.61	0.4581
H	16QAM	1	Max	1	0	22.10	0.4074
Combination 5MHz+5MHz (25RB+25RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.69	0.4667
H	16QAM	1	Max	1	0	21.91	0.3899



CA_66C_ANT 1


Combination 20MHz+20MHz (100RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.84	0.4831
M	QPSK	1	Max	1	0	22.60	0.4571
H	QPSK	1	Max	1	0	22.73	0.4710
L	16QAM	1	Max	1	0	22.22	0.4188
M	16QAM	1	Max	1	0	22.25	0.4217
H	16QAM	1	Max	1	0	22.26	0.4227
L	64QAM	1	Max	1	0	20.69	0.2944
M	64QAM	1	Max	1	0	20.68	0.2938
H	64QAM	1	Max	1	0	20.66	0.2924
L	256QAM	1	Max	1	0	17.60	0.1445
M	256QAM	1	Max	1	0	17.47	0.1403
H	256QAM	1	Max	1	0	17.56	0.1432
Combination 20MHz+15MHz (100RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.70	0.4677
H	16QAM	1	Max	1	0	22.11	0.4083
Combination 15MHz+20MHz (75RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.62	0.4592
H	16QAM	1	Max	1	0	21.96	0.3945
Combination 15MHz+15MHz (75RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.60	0.4571
H	16QAM	1	Max	1	0	21.99	0.3972
Combination 20MHz+10MHz (100RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.62	0.4592
H	16QAM	1	Max	1	0	22.03	0.4009
Combination 10MHz+20MHz (50RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.59	0.4560
H	16QAM	1	Max	1	0	22.07	0.4046
Combination 15MHz+10MHz (75RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.57	0.4539
H	16QAM	1	Max	1	0	22.10	0.4074
Combination 10MHz+15MHz (50RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.66	0.4634
H	16QAM	1	Max	1	0	21.99	0.3972
Combination 20MHz+5MHz (100RB+25RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.62	0.4592
H	16QAM	1	Max	1	0	21.97	0.3954
Combination 5MHz+20MHz (25RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	22.68	0.4656
H	16QAM	1	Max	1	0	22.08	0.4055



LTE Band 25

Peak-to-Average Ratio

Mode	LTE Band 25 / 20MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	4.72	5.68	6.12	PASS






26dB Bandwidth

Mode	LTE Band 25 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.31	1.33	3.03	3.13	5.03	4.94	9.85	9.75	14.63	14.42	18.66	19.26




LTE Band 25

Middle Channel / 1.4MHz / QPSK




Date: 26 JUL 2024 11:11:39

Middle Channel / 1.4MHz / 16QAM




Date: 26 JUL 2024 11:12:19

Middle Channel / 3MHz / QPSK




Date: 26 JUL 2024 11:28:20

Middle Channel / 3MHz / 16QAM




Date: 26 JUL 2024 11:29:00

Middle Channel / 5MHz / QPSK



Date: 26 JUL 2024 11:45:00

Middle Channel / 5MHz / 16QAM




Date: 26 JUL 2024 11:45:40




LTE Band 25

Middle Channel / 10MHz / QPSK




Date: 26 JUL 2024 12:02:24

Middle Channel / 10MHz / 16QAM




Date: 26 JUL 2024 12:03:04

Middle Channel / 15MHz / QPSK




Date: 26 JUL 2024 12:19:04

Middle Channel / 15MHz / 16QAM




Date: 26 JUL 2024 12:19:44

Middle Channel / 20MHz / QPSK



Date: 26 JUL 2024 12:35:45

Middle Channel / 20MHz / 16QAM



Date: 26 JUL 2024 12:36:24




Occupied Bandwidth

Mode	LTE Band 25 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.10	1.09	2.74	2.74	4.51	4.51	9.05	9.05	13.46	13.52	17.90	17.90




LTE Band 25


Middle Channel / 1.4MHz / QPSK




Middle Channel / 1.4MHz / 16QAM




Middle Channel / 3MHz / QPSK




Middle Channel / 3MHz / 16QAM



Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM






LTE Band 25


Middle Channel / 10MHz / QPSK




Middle Channel / 10MHz / 16QAM




Middle Channel / 15MHz / QPSK




Middle Channel / 15MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM






Conducted Band Edge


LTE Band 25 / 1.4MHz / QPSK

Lowest Band Edge / 1RB




Date: 26 JUL 2024 11:04:01

Highest Band Edge / 1RB




Date: 26 JUL 2024 11:13:14

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:08:40

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:17:53




LTE Band 25 / 1.4MHz / 16QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 25 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:05:52

Highest Band Edge / 1 RB




Date: 26 JUL 2024 11:15:06

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:06:48

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:16:01




LTE Band 25 / 3MHz / QPSK


Lowest Band Edge / 1RB




Highest Band Edge / 1RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 25 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:21:37

Highest Band Edge / 1 RB




Date: 26 JUL 2024 11:30:51

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:24:24

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:33:38




LTE Band 25 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:22:33

Highest Band Edge / 1 RB




Date: 26 JUL 2024 11:31:46

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:23:28

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:32:42




LTE Band 25 / 5MHz / QPSK

Lowest Band Edge / 1RB




Date: 26 JUL 2024 11:37:22

Highest Band Edge / 1RB




Date: 26 JUL 2024 11:48:35

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:42:00

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:51:57




LTE Band 25 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:38:17

Highest Band Edge / 1 RB




Date: 26 JUL 2024 11:47:30

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:41:04

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:51:02




LTE Band 25 / 5MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:39:13

Highest Band Edge / 1 RB




Date: 26 JUL 2024 11:48:26

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:40:09

Highest Band Edge / Full RB




Date: 26 JUL 2024 11:49:22




LTE Band 25 / 10MHz / QPSK


Lowest Band Edge / 1RB




Highest Band Edge / 1RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 25 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 11:55:41

Highest Band Edge / 1 RB




Date: 26 JUL 2024 12:04:55

Lowest Band Edge / Full RB



Date: 26 JUL 2024 11:58:29

Highest Band Edge / Full RB




Date: 26 JUL 2024 12:07:42




LTE Band 25 / 10MHz / 64QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 25 / 15MHz / QPSK

Lowest Band Edge / 1RB




Date: 26 JUL 2024 12:11:26

Highest Band Edge / 1RB




Date: 26 JUL 2024 12:20:39

Lowest Band Edge / Full RB



Date: 26 JUL 2024 12:16:05

Highest Band Edge / Full RB




Date: 26 JUL 2024 12:25:18




LTE Band 25 / 15MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 12:12:22

Highest Band Edge / 1 RB




Date: 26 JUL 2024 12:21:35

Lowest Band Edge / Full RB



Date: 26 JUL 2024 12:15:09

Highest Band Edge / Full RB




Date: 26 JUL 2024 12:24:22




LTE Band 25 / 15MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 26 JUL 2024 12:13:17

Highest Band Edge / 1 RB




Date: 26 JUL 2024 12:22:31

Lowest Band Edge / Full RB



Date: 26 JUL 2024 12:14:13

Highest Band Edge / Full RB




Date: 26 JUL 2024 12:23:26




LTE Band 25 / 20MHz / QPSK

Lowest Band Edge / 1RB




Date: 26 JUL 2024 12:28:06

Highest Band Edge / 1RB




Date: 26 JUL 2024 12:37:19

Lowest Band Edge / Full RB



Date: 26 JUL 2024 12:32:45

Highest Band Edge / Full RB



Date: 26 JUL 2024 12:41:58