

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 1 of 47

Applicant : Ehong Technology Co.,Ltd
Address of Applicant : Room 501, No.485 Xingmei Road,
Minhang Dis,Shanghai, China.

Product Name : BLE Module
Brand Name : Ehong
Model Name : EH-MC33
Sample Acquisition Method : Sent by Client
Sample No. : E24060091-01#04(Radiation Sample)
E24060091-01#05(Conducted Sample)

FCC ID : 2ACCRM33
ISED Number : 20625-MC33

Standards : FCC CFR47 Part 15.247, Subpart C
RSS-Gen (Issue 5, Amd.2-Feb 2021)
RSS-247 (Issue 3, August 2023)

Date of Receipt : 2024-06-28
Date of Test : 2024-07-02~ 2024-07-09
Date of Issue : 2024-07-12

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by: Erik Yang (Erik Yang)
Reviewed by: Jennifer Zhou (Jennifer Zhou)
Approved by: Echo Mu (Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 2 of 47

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
3.3	SUPPORT SOFTWARE	8
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement</i>	11
4.1.2	<i>Maximum peak conducted output power and E.I.R.P</i>	12
4.1.3	<i>6dB Bandwidth and 99% Bandwidth</i>	16
4.1.4	<i>Maximum conducted output power spectral density</i>	23
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	27
4.1.6	<i>Radiated Emission</i>	39
4.1.7	<i>Band Edge (Restricted-band band-edge)</i>	40
4.2	MAINS EMISSIONS	41
4.2.1	<i>Conducted Emission on AC Mains</i>	41
5	APPENDIXES	44
5.1	PHOTOGRAPHS OF THE SAMPLE	44
5.2	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	46
5.3	SET-UP FOR CONDUCTED EMISSIONS	46
5.4	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	47
5.5	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	47

TEST REPORT

Report No.: SHE24060091-02CE Date: 2024-07-12 Page 3 of 47

1 General Information

1.1 Testing Laboratory

ISED CAB identifier #	CN0081
Company number #	25174
Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd.
Address	No.1298, Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	Ehong Technology Co.,Ltd
Address	Room 501, No.485 Xingmei Road, Minhang Dis,Shanghai, China.
Contact Person	Rik Tang
Telephone	02164769993
Email	rik.tang@ehonglink.com
Manufacturer Company Name	Ehong Technology Co.,Ltd
Address	Room 501, No.485 Xingmei Road, Minhang Dis,Shanghai, China.
Factory Company Name	Ehong Technology Co.,Ltd
Address	Room 501, No.485 Xingmei Road, Minhang Dis,Shanghai, China.

1.3 Details of EUT

Product Name	BLE Module
Brand Name	Ehong
Test Model Name	EH-MC33
FCC ID	2ACCRMC33
ISED Number	20625-MC33
Mode of Operation	Bluetooth BLE Version 5.3
Frequency Range	2402MHz ~ 2480MHz
Number of Channels	40 (at intervals of 2 MHz)
Modulation Type	BLE ☒ GFSK 1Mbps ☒ GFSK 2Mbps
Max RF Output Power-Conducted	2.713dBm
Antenna Type	PCB Antenna
Antenna Gain	1.20dBi
Extreme Temperature Range	-20°C~ +85°C
Test Voltage	DC 3.3V

TEST REPORT

Report No.: SHE24060091-02CE Date: 2024-07-12 Page 4 of 47

Hardware Version	V1.1
Software Version	V1.0
RF power setting in TEST SW	Atmosic RF Tool_v1.6.5_Power level setting_8(4dBm)

Note:

- 1. The above information was declared by the manufacture.
- 2. For more details, please refer to the User’s manual of the EUT.

Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2.402GHz	14	2.430GHz	28	2.458GHz
1	2.404GHz	15	2.432GHz	29	2.460GHz
2	2.406GHz	16	2.434GHz	30	2.462GHz
3	2.408GHz	17	2.436GHz	31	2.464GHz
4	2.410GHz	18	2.438GHz	32	2.466GHz
5	2.412GHz	19	2.440GHz	33	2.468GHz
6	2.414GHz	20	2.442GHz	34	2.470GHz
7	2.416GHz	21	2.444GHz	35	2.472GHz
8	2.418GHz	22	2.446GHz	36	2.474GHz
9	2.420GHz	23	2.448GHz	37	2.476GHz
10	2.422GHz	24	2.450GHz	38	2.478GHz
11	2.424GHz	25	2.452GHz	39	2.480GHz
12	2.426GHz	26	2.454GHz		
13	2.428GHz	27	2.456GHz		

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
RSS-Gen (Issue 5, Amd.2-Feb 2021)	General Requirements for Compliance of Radio Apparatus
RSS-247 (Issue 3, August 2023)	Digital Transmission Systems (DTSSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 5 of 47

1.5 Test Summary

Test Item	FCC Rules	ISED Rules	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	RSS-247 5.4(f) RSS-GEN 6.8	PASS
Maximum peak conducted output power and E.I.R.P	FCC Part 15.247(b)(3)	RSS-247 5.4(d)	PASS
6dB Bandwidth and 99% Bandwidth	FCC Part 15.247(a)(2)	RSS-247 5.2(a) RSS-Gen 6.7	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	RSS-247 5.2(b)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	RSS-247 5.5	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	RSS-GEN 8.9	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	RSS-GEN 8.10	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	RSS-Gen 8.8	PASS

TEST REPORT

Report No.:SHE24060091-02CE

Date:2024-07-12

Page 6 of 47

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	18-25
Humidity (%RH)	40-65
Barometric Pressure (mbar)	960-1060

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020B	MY59260184	2024-06-26	2025-06-25
Spectrum Analyzer	Keysight	N9020A	MY54101709	2024-06-26	2025-06-25
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2024-06-04	2025-06-03
Signal Generator	Rohde & Schwarz	SMR27	100184	2024-06-26	2025-06-25
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2024-06-05	2025-06-04
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2024-06-04	2025-06-03
V-network	SCHWARZBECK	NSLK 8127	8127-902	2024-06-05	2025-06-04
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2024-06-05	2025-06-04
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2023-03-22	2025-03-21
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2023-06-13	2025-06-12
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2023-06-09	2025-06-08
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2023-06-18	2025-06-17
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2024-06-04	2025-06-03
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2023-06-09	2025-06-08
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2023-06-09	2025-06-08
Test Software	BL	BL410_E	Version:2.1.1.436	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 7 of 47

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission	< 1GHz	± 1.5 dB
	> 1GHz	± 1.5 dB
Radiated Emission	9KHz – 30MHz	± 3.42 dB
	30 MHz – 1GHz	± 5.01 dB
	> 1GHz	± 5.21 dB
Conducted Emission on AC Mains	150kHz-30MHz	± 2.68 dB
Occupied Channel Bandwidth		± 5 %
Maximum Conducted Output Power and E.I.R.P		± 0.64 dB
Maximum Conducted Output Power Spectral Density		± 1.18 dB

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 8 of 47

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software was control EUT work in continuous transmitting mode. Select test channel as below:

Channel	Frequency
The lowest channel(CH00)	2402MHz
The middle channel(CH19)	2440MHz
The highest channel(CH39)	2480MHz

The basic operation modes are:

- A. On
1. BLE mode

a. Transmitting

i. Low Channel

ii. Middle Channel

iii. High Channel

b. Receiving
2. Normal working with Bluetooth on
- B. Standby
- C. Off

3.2 Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model Name	Serial No.
Laptop 1	Lenovo	TP00083A	PF-0PRDGN
AC Adapter	Lenovo	ADLX45NDC3A	8SSA10M42787D1SG81L0B9F
Laptop 2	HP	HP ZHAN 66 Pro G1	5CD7438R1J
USB Cable	N/A	N/A	1.00m Unshielded


3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	Atmosic RF Tool_v1.6.5

TEST REPORT


3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Conduction Measurement




TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 10 of 47

Diagram of Measurement Equipment Configuration for Transmitter Test



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 11 of 47

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard	: FCC Part 15.247(b)(4), Part 15.203 RSS-247 5.4(f), RSS-GEN 6.8
Requirement	: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, EH-MC33 model has an antenna with a directional gain of 1.20dBi. The antenna is PCB Antenna with no possibility of replacement with a non-approved antenna by the end-user. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 12 of 47

4.1.2 Maximum peak conducted output power and E.I.R.P

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3), RSS-247 5.4(d)

Requirement : ANSI C63.10-2013 clause 11.9.1.1,
KDB 558074 D01 v05r02, Clause 8.3.1

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 24.8°C

Relative humidity : 50%

Table 1: Maximum peak conducted output power

Test Mode	Test Channel (MHz)	Maximum peak conducted output power		Limit (W)
		(dBm)	(mW)	
BLE-1Mbps	2402	1.919	1.556	< 1
	2440	2.263	1.684	
	2480	2.696	1.860	
BLE-2Mbps	2402	1.923	1.557	< 1
	2440	2.277	1.689	
	2480	2.713	1.868	

Table 2: E.I.R.P

Test Mode	Test Channel (MHz)	E.I.R.P		Limit (W)
		(dBm)	(mW)	
BLE-1Mbps	2402	3.119	2.051	< 4
	2440	3.463	2.220	
	2480	3.896	2.452	
BLE-2Mbps	2402	3.123	2.053	
	2440	3.477	2.227	
	2480	3.913	2.462	

Note: The antenna gain is 1.20dBi
E.I.R.P= peak conducted output power+antenna gain

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 13 of 47

Figure 1: Peak Output Power, 2402MHz, BLE-1Mbps





Figure 2: Peak Output Power, 2440MHz, BLE-1Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 14 of 47

Figure 3: Peak Output Power, 2480MHz, BLE-1Mbps





Figure 4: Peak Output Power, 2402MHz, BLE-2Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 15 of 47

Figure 5: Peak Output Power, 2440MHz, BLE-2Mbps





Figure 6: Peak Output Power, 2480MHz, BLE-2Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 16 of 47

4.1.3 6dB Bandwidth and 99% Bandwidth

RESULT:

PASS

Test standard

: FCC Part 15.247(a)(2), RSS-247 5.2(a)
RSS-Gen 6.7

Requirement

: ANSI C63.10-2013 clause 11.8.1,
KDB 558074 D01 v05r02, Clause 8.2

Kind of test site

: Shielded room

Test setup

Test Channel

: Low/Middle/High

Operation Mode

: A.1.a

Ambient temperature

: 24.8°C

Relative humidity

: 50%

Table 3: 6dB Bandwidth and 99% Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	6dB Bandwidth Limit
BLE-1Mbps	2402	0.7190	1.0450	>0.5 MHz
	2440	0.6965	1.0448	
	2480	0.6932	1.0488	
BLE-2Mbps	2402	1.3770	2.1045	
	2440	1.3720	2.1087	
	2480	1.4100	2.1142	

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 17 of 47

Figure 7: 6dB Bandwidth, 2402MHz, BLE-1Mbps



99% Bandwidth, 2402MHz, BLE-1Mbps




TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 18 of 47

Figure 8: 6dB Bandwidth, 2440MHz, BLE-1Mbps



99% Bandwidth, 2440MHz, BLE-1Mbps




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 19 of 47

Figure 9: 6dB Bandwidth, 2480MHz, BLE-1Mbps



99% Bandwidth, 2480MHz, BLE-1Mbps




TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 20 of 47

Figure 10: 6dB Bandwidth, 2402MHz, BLE-2Mbps



99% Bandwidth, 2402MHz, BLE-2Mbps




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 21 of 47

Figure 11: 6dB Bandwidth, 2440MHz, BLE-2Mbps



99% Bandwidth, 2440MHz, BLE-2Mbps




TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 22 of 47

Figure 12: 6dB Bandwidth, 2480MHz, BLE-2Mbps



99% Bandwidth, 2480MHz, BLE-2Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 23 of 47

4.1.4 Maximum conducted output power spectral density

RESULT:

PASS

Test standard : FCC Part 15.247(e), RSS-247 5.2(b)

Requirement : ANSI C63.10-2013 clause 11.10.2,
KDB 558074 D01 v05r02, Clause 8.4

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 24.8°C

Relative humidity : 50%

Table 4: Maximum conducted output power spectral density

Test Mode	Test Channel (MHz)	Measured Result (dBm/3kHz)	Limit (dBm/3kHz)
BLE-1Mbps	2402	-14.263	8
	2440	-13.907	
	2480	-13.496	
BLE-2Mbps	2402	-19.596	
	2440	-19.355	
	2480	-18.854	

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 24 of 47

Figure 13: Power Spectral Density, 2402MHz, BLE-1Mbps



Figure 14: Power Spectral Density, 2440MHz, BLE-1Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 25 of 47

Figure 15: Power Spectral Density, 2480MHz, BLE-1Mbps



Figure 16: Power Spectral Density, 2402MHz, BLE-2Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 26 of 47

Figure 17: Power Spectral Density, 2440MHz, BLE-2Mbps



Figure 18: Power Spectral Density, 2480MHz, BLE-2Mbps



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 27 of 47

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard

: FCC Part 15.247(d), RSS-247 5.5

Requirement

: ANSI C63.10-2013, Clause 11.11.1(a)
KDB 558074 D01 v05r02, Clause 8.5

Kind of test site

: Shielded room

Test setup

Test Channel

: Low/Middle/High for spurious, Low/High for Band
Edge

Operation Mode

: A.1.a

Ambient temperature

: 24.8°C

Relative humidity

: 50%

For details refer to following test plot.


TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 28 of 47

Figure 19: Conducted Spurious Emission & Authorized-band band-edge, 2402MHz, BLE-1Mbps
Carrier Level



Band Edge





TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 29 of 47


Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE24060091-02CE Date: 2024-07-12 Page 30 of 47

Figure 20: Conducted Spurious Emission & Authorized-band band-edge, 2440MHz, BLE-1Mbps Carrier Level



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 31 of 47





Figure 21: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, BLE-1Mbps Carrier Level




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 32 of 47

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 33 of 47





Figure 22: Conducted Spurious Emission & Authorized-band band-edge, 2402MHz, BLE-2Mbps Carrier Level




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 34 of 47

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 35 of 47







Figure 23: Conducted Spurious Emission & Authorized-band band-edge, 2440MHz, BLE-2Mbps Carrier Level



TEST REPORT

Report No.: SHE24060091-02CE Date: 2024-07-12 Page 36 of 47

Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 37 of 47

Figure 24: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, BLE-2Mbps
Carrier Level





Band Edge



TEST REPORT

Report No.: SHE24060091-02CE Date: 2024-07-12 Page 38 of 47

Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 39 of 47

4.1.6 Radiated Emission

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.205, 15.209 RSS-GEN 8.9
Requirement	: ANSI C63.10-2013 clause 11.12, KDB 558074 D01 v05r02, Clause 8.6
Kind of test site	: 3m Semi-Anechoic Chamber

Test setup

Test Channel	: Low/Middle/High
Operation Mode	: A
Ambient temperature	: 23.9°C
Relative humidity	: 51%

Notes

Test plots please refer to the annex document "SHE24060091-02CE DATA BLE-TX EXHIBIT A".

1. For 9 kHz ~ 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported. In addition, During 30MHz to 1GHz test frequency range, only the worst mode data was reported in this report.
2. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.
3. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 40 of 47

4.1.7 Band Edge (Restricted-band band-edge)

RESULT:

PASS

Test standard

: FCC Part 15.247(d), 15.205, 15.209
RSS-GEN 8.10

Requirement

: ANSI C63.10-2013 clause 11.13,
KDB 558074 D01 v05r02, Clause 8.7

Kind of test site

: 3m Semi-Anechoic Chamber

Test setup

Test Channel

: Low/Middle/High

Operation Mode

: A.1

Ambient temperature

: 23.9°C

Relative humidity

: 51%

Notes

Test plots please refer to the annex document “SHE24060091-02CE DATA BLE-TX EXHIBIT A ”.

TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 41 of 47

4.2 Mains Emissions

4.2.1 Conducted Emission on AC Mains

RESULT:

PASS

Test standard	: FCC Part 15.207(a), RSS-Gen 8.8
Requirement	: ANSI C63.10-2013, Clause 6.2
Kind of test site	: Shielded room

Test setup

Input Voltage	: which received AC 120V, 60Hz Power
Operation Mode	: A.1.a
Earthing	: Connected to GND
Ambient temperature	: 23.7°C
Relative humidity	: 52%

For details refer to following test plot.

TEST REPORT


Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 42 of 47

Note: The all configurations were tested respectively, but only the worst data (at low channel) shown here.

Figure 25: Conducted Emission on AC Mains, L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.170	63.88	9.94	64.96	1.08	Peak	L	Pass
1*	0.170	59.41	9.94	64.96	5.55	QP	L	Pass
1**	0.170	46.21	9.94	54.96	8.75	AV	L	Pass
2	0.194	61.19	9.94	63.86	2.67	Peak	L	Pass
2*	0.194	56.05	9.94	63.86	7.81	QP	L	Pass
2**	0.194	36.93	9.94	53.86	16.93	AV	L	Pass
3	0.240	54.66	9.96	62.10	7.44	Peak	L	Pass
3*	0.240	49.65	9.96	62.10	12.45	QP	L	Pass
3**	0.240	43.67	9.96	52.10	8.43	AV	L	Pass
4	0.552	45.86	9.96	56.00	10.14	Peak	L	Pass
4*	0.552	43.12	9.96	56.00	12.88	QP	L	Pass
4**	0.552	36.73	9.96	46.00	9.27	AV	L	Pass
5	4.540	44.96	9.82	56.00	11.04	Peak	L	Pass
5*	4.540	38.04	9.82	56.00	17.96	QP	L	Pass
5**	4.540	30.55	9.82	46.00	15.45	AV	L	Pass
6	20.504	36.01	9.34	60.00	23.99	Peak	L	Pass
6*	20.504	29.07	9.34	60.00	30.93	QP	L	Pass
6**	20.504	26.54	9.34	50.00	23.46	AV	L	Pass


TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 43 of 47

Figure 26: Conducted Emission on AC Mains, N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.178	61.79	10.02	64.58	2.79	Peak	N	Pass
1*	0.178	54.18	10.02	64.58	10.40	QP	N	Pass
1**	0.178	37.92	10.02	54.58	16.66	AV	N	Pass
2	0.406	44.21	10.07	57.73	13.52	Peak	N	Pass
2*	0.406	39.77	10.07	57.73	17.96	QP	N	Pass
2**	0.406	33.08	10.07	47.73	14.65	AV	N	Pass
3	1.224	44.80	9.95	56.00	11.20	Peak	N	Pass
3*	1.224	40.90	9.95	56.00	15.10	QP	N	Pass
3**	1.224	31.35	9.95	46.00	14.65	AV	N	Pass
4	2.620	39.77	9.92	56.00	16.23	Peak	N	Pass
4*	2.620	32.76	9.92	56.00	23.24	QP	N	Pass
4**	2.620	28.86	9.92	46.00	17.14	AV	N	Pass
5	4.592	41.41	9.79	56.00	14.59	Peak	N	Pass
5*	4.592	34.84	9.79	56.00	21.16	QP	N	Pass
5**	4.592	29.80	9.79	46.00	16.20	AV	N	Pass
6	9.660	37.94	9.76	60.00	22.06	Peak	N	Pass
6*	9.660	31.94	9.76	60.00	28.06	QP	N	Pass
6**	9.660	28.06	9.76	50.00	21.94	AV	N	Pass

TEST REPORT


Report No.: SHE24060091-02CE

Date: 2024-07-12


Page 44 of 47

5 Appendixes

5.1 Photographs of the Sample




Front of the sample



Rear of the sample

TEST REPORT



Internal of the sample


TEST REPORT

Report No.: SHE24060091-02CE

Date: 2024-07-12

Page 46 of 47

5.2 Set-up for Conducted RF test at Antenna Port



5.3 Set-up for Conducted Emissions




TEST REPORT

Report No.: SHE24060091-02CE


Date: 2024-07-12

Page 47 of 47

5.4 Set-up for Spurious Emissions below 1GHz



5.5 Set-up for Spurious Emissions above 1GHz



End of the report