

TEST REPORT

Product Name : Active speaker
Model Number : Air XD Sub 15,
 Air XD Sub 18
FCC ID : 2ACCU-AIRSUB001

Prepared for : PreSonus Audio Electronics, Inc.
Address : 18011 Grand Bay Court Baton Rouge, LA 70809,
 United States of America

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
 Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2503310317W04401R
Date(s) of Tests : April 14, 2025 to May 20, 2025
Date of issue : July 02, 2025

\$二维码\$

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	3
2 EUT TECHNICAL DESCRIPTION	5
3 SUMMARY OF TEST RESULT	6
4 TEST METHODOLOGY	7
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
4.2 MEASUREMENT EQUIPMENT USED	7
4.3 DESCRIPTION OF TEST MODES	8
5 FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES	9
5.2 LABORATORY ACCREDITATIONS AND LISTINGS	9
6 TEST SYSTEM UNCERTAINTY	10
7 SETUP OF EQUIPMENT UNDER TEST	11
7.1 RADIO FREQUENCY TEST SETUP 1	11
7.2 RADIO FREQUENCY TEST SETUP 2	11
7.3 CONDUCTED EMISSION TEST SETUP	13
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	14
7.5 SUPPORT EQUIPMENT	14
8 FREQUENCY HOPPING SYSTEM REQUIREMENTS	15
8.1 Standard Applicable	15
8.2 EUT Pseudorandom Frequency Hopping Sequence	15
8.3 Equal Hopping Frequency Use	16
8.4 Frequency Hopping System	16
9 TEST REQUIREMENTS	17
9.1 20DB&99%BANDWIDTH	17
9.2 CARRIER FREQUENCY SEPARATION	29
9.3 NUMBER OF HOPPING FREQUENCIES	32
9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)	35
9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER	38
9.6 CONDUCTED SPURIOUS EMISSION	44
9.7 RADIATED SPURIOUS EMISSION	61
9.8 CONDUCTED EMISSIONS TEST	67
9.9 ANTENNA APPLICATION	69

1 TEST RESULT CERTIFICATION

Applicant : PreSonus Audio Electronics, Inc.
 Address : 18011 Grand Bay Court Baton Rouge, LA 70809, United States of America
 Manufacturer : PreSonus Audio Electronics, Inc.
 Address : 18011 Grand Bay Court Baton Rouge, LA 70809, United States of America
 Trade Mark : N/A
 EUT : Active speaker
 Model No. : Air XD Sub 15, Air XD Sub 18

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (NINGBO) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test : April 14, 2025 to May 20, 2025



Prepared by : Una Yu /Editor

Reviewer : Joe Xia /Supervisor



Approve & Authorized Signer : Lisa Wang/Manager

Modified Information

Version	Report No.	Revision Date	Summary
/	ENS2503310317W04401R	/	Original Report



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product Name	Active Speaker
Model number	Air XD Sub 15, Air XD Sub 18 Note: The difference between models only distinguishes the appearance shape and color, and the internal electrical principle is consistent.
Sample number	ENS2503310317W044-1-1
Device Type	Bluetooth V5.0
Data Rate	1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation 3Mbps for 8DPSK modulation
Modulation	GFSK pi/4-DQPSK 8DPSK
Operating Frequency Range	2402-2480MHz
Number of Channels	79 Channels
Max Transmit Power	11.05 dBm
Antenna Type	PCB Antenna
Gain	1.7 dBi
External cable loss	0.55 dB
Power supply	AC 100-120V or AC 220V-240V/50Hz or 60Hz
Temperature Range	-40°C to +85°C
Date of Received	April 14, 2025

Note: for more details, please refer to the user's manual of the EUT.

3 SUMMARY OF TEST RESULT

IC PartClause	Test Parameter	Verdict	Remark
15.247(a)(1)	20dB Bandwidth	PASS	
15.247(a)(1)	99% Occupied Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(b)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(a)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.203	Antenna Application	PASS	

NOTE1: N/A (Not Applicable)

NOTE2: According to RSS -247, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for IC: 282F-527300 filing to comply with Section A8 of the IC.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 KDB 558074 D01 15.247 Meas Guidance V05r02

4.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101384	2025/1/9	1Year
Coaxial Cable	TIMES	\	\	2025/1/9	1Year
AMN	Rohde & Schwarz	ENV216	101161	2025/1/9	1Year

For Spurious Emissions Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESU 26	100154	2025/1/9	1Year
Pre-Amplifie	Lunar EM	LNA30M3G-25	J10100000070	2025/1/9	1Year
Bilog Antenna	Schwarzbeck	VULB9163	661	2025/1/18	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1177	2023/8/28	2 Year
Pre-Amplifie	SKET	LNPA_0118G-45	SK2019051801	2025/1/9	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2025/1/13	2 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2025/1/9	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2025/1/9	1Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2025/1/9	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2025/1/13	2 Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2025/1/9	1Year

For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Signal Analyzer	KEYSIGHT	N9010B	MY60240204	2025/1/7	1Year
RF Control Unit (Power Meter)	Tonscend	JS0806-2	/	2025/1/9	1Year
RF Cable	Rosenberger	/	/	2025/1/9	1Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation(DH5); 2Mbps for $\pi/4$ -DQPSK modulation(2DH5); 3Mbps for 8DPSK modulation(3DH5)) were used for all tests.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	78	2480

Note: $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 79

Test Frequency and channel list:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01.

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Solar Speaker Lantern) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10- Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.
- (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 512$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their

corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB&99%BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth V5.0+EDR mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1%-5% OBW

Set the video bandwidth (VBW) $\geq 100\text{kHz}$.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdeltafunction, and move the marker to the other side of the emission, until it is (asclose as possible to) even with the reference marker level. The marker-delta reading atthis point is the 20 dB bandwidth of the emission.

If this value varies with differentmodes of operation (e.g., data rate, modulation format, etc.), repeat this test for eachvariation.

Measure and record the results in the test report.

Test Results

20dB Emission Bandwidth

Test Mode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.951	2401.514	2402.465	---	PASS
DH5	Ant1	2441	0.948	2440.511	2441.459	---	PASS
DH5	Ant1	2480	0.936	2479.517	2480.453	---	PASS
2DH5	Ant1	2402	1.254	2401.361	2402.615	---	PASS
2DH5	Ant1	2441	1.353	2440.304	2441.657	---	PASS
2DH5	Ant1	2480	1.323	2479.313	2480.636	---	PASS
3DH5	Ant1	2402	1.269	2401.343	2402.612	---	PASS
3DH5	Ant1	2441	1.260	2440.337	2441.597	---	PASS
3DH5	Ant1	2480	1.299	2479.328	2480.627	---	PASS











Occupied Channel Bandwidth (99%)

TestMode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.83439	2401.5580	2402.3924	---	---
DH5	Ant1	2441	0.84832	2440.5501	2441.3984	---	---
DH5	Ant1	2480	0.83827	2479.5549	2480.3931	---	---
2DH5	Ant1	2402	1.1764	2401.3881	2402.5645	---	---
2DH5	Ant1	2441	1.1911	2440.3847	2441.5758	---	---
2DH5	Ant1	2480	1.1989	2479.3791	2480.5780	---	---
3DH5	Ant1	2402	1.1697	2401.3943	2402.5640	---	---
3DH5	Ant1	2441	1.2040	2440.3720	2441.5760	---	---
3DH5	Ant1	2480	1.2276	2479.3575	2480.5851	---	---





DH5-Ant1-2402




DH5-Ant1-2441









9.2 CARRIER FREQUENCY SEPARATION

9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.2.4 Test Procedure

■ According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:
 Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test Results

Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

TestMode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.686	≥0.634	PASS
2DH5	Ant1	Hop	0.994	≥0.902	PASS
3DH5	Ant1	Hop	1.306	≥1.299	PASS





9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and 558074 D01 15.247 Meas Guidance V05r02

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.3.4 Test Procedure

■ According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2390-2440MHz) and (2440-2490MHz)

RBW = 100kHz

VBW \geq RBW

Sweep = auto

Detector function = peak


Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

Test Results

Temperature:	25° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

TestMode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS





3DH5-Ant1-Hop-PASS

9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and 558074 D01 15.247 Meas Guidance V05r02

9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the averagetime of occupancy on any channel shall not be greater than 0.4s within a period of 0.4smultiplied by the number of hopping channels employed.

9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.4.4 Test Procedure

■ According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:
 Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

9.4.5 Test Results

Note: TotalHops(DH1)=(1600/2/79)*31.6


TotalHops(DH3)=(1600/4/79)*31.6

TotalHops(DH5)=(1600/6/79)*31.6

Dwell Time= BurstWidth* TotalHops

All the channel and packet type were tested, the data of the worst mode are described in the following table.

TestMode	Antenna	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH5	Ant1	Hop	2.902	106.67	0.31	\leq 0.4	PASS
2DH5	Ant1	Hop	2.908	106.67	0.31	\leq 0.4	PASS
3DH5	Ant1	Hop	2.908	106.67	0.31	\leq 0.4	PASS





9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and 558074 D01 15.247 Meas Guidance V05r02

9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.5.4 Test Procedure

■ According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel(about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured(about 3MHz)

Set VBW \geq RBW

Set Sweep = auto

Set Detector function = peak


Set Trace = max hold


Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emissionto determine the peak amplitude level.

This power is tested according to the maximum power.

Test Results

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	9.66	\leq 20.97	PASS
DH5	Ant1	2441	10.58	\leq 20.97	PASS
DH5	Ant1	2480	10.42	\leq 20.97	PASS
2DH5	Ant1	2402	9.91	\leq 20.97	PASS
2DH5	Ant1	2441	10.79	\leq 20.97	PASS
2DH5	Ant1	2480	10.58	\leq 20.97	PASS
3DH5	Ant1	2402	10.36	\leq 30	PASS
3DH5	Ant1	2441	11.05	\leq 30	PASS
3DH5	Ant1	2480	10.78	\leq 30	PASS











9.6 CONDUCTED SUPRIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and 558074 D01 15.247 Meas Guidance V05r02

9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

Set the RBW = 100 kHz. Set the VBW \geq 3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximumconductedlevel.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW \geq 1% of the span=100kHzSet VBW \geq RBW

Set Sweep = autoSetDetector function = peakSetTrace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ ConductedSpurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz).Set RBW = 100 kHzSetVBW \geq RBW


Set Sweep = autoSetDetector function = peakSetTrace = max hold


Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


9.6.5 Test Results


TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	30~1000	9.30	-51.54	≤-10.7	PASS
DH5	Ant1	2402	1000~26500	9.30	-23.11	≤-10.7	PASS
DH5	Ant1	2441	30~1000	9.78	-51.12	≤-10.22	PASS
DH5	Ant1	2441	1000~26500	9.78	-21.56	≤-10.22	PASS
DH5	Ant1	2480	30~1000	9.86	-51.08	≤-10.14	PASS
DH5	Ant1	2480	1000~26500	9.86	-21.15	≤-10.14	PASS
2DH5	Ant1	2402	30~1000	8.98	-51.12	≤-11.02	PASS
2DH5	Ant1	2402	1000~26500	8.98	-27.57	≤-11.02	PASS
2DH5	Ant1	2441	30~1000	9.92	-42.3	≤-10.08	PASS
2DH5	Ant1	2441	1000~26500	9.92	-23.71	≤-10.08	PASS
2DH5	Ant1	2480	30~1000	9.90	-51.04	≤-10.1	PASS
2DH5	Ant1	2480	1000~26500	9.90	-21.71	≤-10.1	PASS
3DH5	Ant1	2402	30~1000	9.15	-51.67	≤-10.85	PASS
3DH5	Ant1	2402	1000~26500	9.15	-28.91	≤-10.85	PASS
3DH5	Ant1	2441	30~1000	10.22	-51.36	≤-9.78	PASS
3DH5	Ant1	2441	1000~26500	10.22	-25.49	≤-9.78	PASS
3DH5	Ant1	2480	30~1000	9.62	-51.1	≤-10.38	PASS
3DH5	Ant1	2480	1000~26500	9.62	-23.73	≤-10.38	PASS


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	9.30	-47.23	≤-10.7	PASS
DH5	Ant1	High	2480	9.86	-48.53	≤-10.14	PASS
DH5	Ant1	Low	Hop_2402	7.19	-48.82	≤-12.81	PASS
DH5	Ant1	High	Hop_2480	9.61	-44.13	≤-10.39	PASS
2DH5	Ant1	Low	2402	8.98	-46.38	≤-11.02	PASS
2DH5	Ant1	High	2480	9.90	-48.17	≤-10.1	PASS
2DH5	Ant1	Low	Hop_2402	4.25	-47.52	≤-15.75	PASS
2DH5	Ant1	High	Hop_2480	7.13	-46.4	≤-12.87	PASS
3DH5	Ant1	Low	2402	9.15	-46.71	≤-10.85	PASS
3DH5	Ant1	High	2480	9.62	-47.69	≤-10.38	PASS
3DH5	Ant1	Low	Hop_2402	1.10	-49.41	≤-18.9	PASS
3DH5	Ant1	High	Hop_2480	6.20	-44.59	≤-13.8	PASS










































9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance V05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

According to IC RSS-Gen 8.9, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Restricted Frequency(MHz)	Magnetic field strength (H-Field) (μ A/m)	Magnetic field strength (H-Field) (dB μ A/m)	Measurement Distance (m)
0.009~0.490	6.37/F (F in kHz)	20 log (μ A/m)	300
0.490~1.705	63.7/F (F in kHz)	20 log (μ A/m)	30
1.705~30.0	0.08	20 log (μ A/m)	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note 2: dB μ V/m = dB μ A/m + 51.5

9.7.3 Test Configuration

Test according to clause 6.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit. Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

Pass

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature:	25.7° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test mode:	GFSK	Frequency:	Channel 0: 2402MHz
------------	------	------------	--------------------

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Margin(dB)	Detector
4803.500	H	52.74	74.00	21.26	PEAK
7206.000	H	60.81	74.00	13.19	PEAK
7206.000	H	52.61	54.00	1.39	AVG
9608.000	H	54.10	74.00	19.90	PEAK
9608.000	H	47.82	54.00	6.18	AVG
4803.500	V	46.93	74.00	27.07	PEAK
5180.500	V	47.52	74.00	26.48	PEAK
7206.000	V	59.62	74.00	14.38	PEAK
7206.000	V	52.14	54.00	1.86	AVG
9608.000	V	52.27	74.00	21.73	PEAK

Test mode:	GFSK	Frequency:	Channel 39: 2441MHz
------------	------	------------	---------------------

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Margin(dB)	Detector
4882.000	H	53.78	74.00	20.22	PEAK
7322.500	H	58.91	74.00	15.09	PEAK
7322.500	H	51.64	54.00	2.36	AVG
9764.500	H	51.90	74.00	22.10	PEAK
4882.000	V	47.89	74.00	26.11	PEAK
7323.000	V	58.79	74.00	15.21	PEAK
7323.000	V	52.17	54.00	1.83	AVG
9764.000	V	52.57	74.00	21.43	PEAK

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Margin(dB)	Detector
4959.500	H	53.92	74.00	20.08	PEAK
7439.500	H	56.30	74.00	17.70	PEAK
7439.500	H	49.91	54.00	4.09	AVG
9606.500	H	52.65	74.00	21.35	PEAK
9920.000	H	52.02	74.00	21.98	PEAK
3418.000	V	47.21	74.00	26.79	PEAK
4960.000	V	50.23	74.00	23.77	PEAK
5185.000	V	48.27	74.00	25.73	PEAK
7439.500	V	53.18	74.00	20.82	PEAK
9920.000	V	51.70	74.00	22.30	PEAK

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(4) Only records the worst data in tabular form.

- Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz
 Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Margin(dB)	Detector
2357.263	H	58.49	74.00	15.51	PEAK
2357.263	H	51.68	54.00	2.32	AVG
2390.000	H	56.14	74.00	17.86	PEAK
2390.000	H	50.69	54.00	3.31	AVG
2384.670	V	58.20	74.00	15.80	PEAK
2384.670	V	51.16	54.00	2.84	AVG
2390.000	V	56.52	74.00	17.48	PEAK
2390.000	V	50.84	54.00	3.16	AVG

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Margin(dB)	Detector
2483.500	H	57.23	74.00	16.77	PEAK
2483.500	H	50.28	54.00	3.72	AVG
2497.668	H	58.87	74.00	15.13	PEAK
2497.668	H	51.05	54.00	2.95	AVG
2483.500	V	56.52	74.00	17.48	PEAK
2483.500	V	50.69	54.00	3.31	AVG
2497.448	V	59.24	74.00	14.76	PEAK
2497.448	V	51.85	54.00	2.15	AVG

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and RMS Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission below 1GHz(30MHz to 1GHz)

Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test mode:	GFSK	Frequency:	Channel 0: 2402MHz
------------	------	------------	--------------------

No.	Freq. (MHz)	Reading (dB μ V/m)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Pol.	Verdict
1	52.310	41.43	-24.55	16.88	40.00	23.12	QPK	H	PASS
2	86.163	57.12	-26.4	30.72	40.00	9.28	QPK	H	PASS
3	95.766	57.21	-25.62	31.59	43.50	11.91	QPK	H	PASS
4	117.591	48.69	-26.85	21.84	43.50	21.66	QPK	H	PASS
5	137.767	59.11	-27.99	31.12	43.50	12.38	QPK	H	PASS
6	188.692	48.65	-25.56	23.09	43.50	20.41	QPK	H	PASS

No.	Freq. (MHz)	Reading (dB μ V/m)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Pol.	Verdict
1	52.125	53.96	-24.52	29.44	40.00	10.56	QPK	V	PASS
2	89.504	63.11	-26.12	36.99	43.50	6.51	QPK	V	PASS
3	97.965	63.93	-25.44	38.49	43.50	5.01	QPK	V	PASS
4	138.123	64.07	-28.01	36.06	43.50	7.44	QPK	V	PASS
5	196.905	54.91	-24.92	29.99	43.50	13.51	QPK	V	PASS
6	236.914	49.74	-23.42	26.32	46.00	19.68	QPK	V	PASS

9.8 CONDUCTED EMISSIONS TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

Test mode:	GFSK	Frequency:	Channel 00: 2402 MHz				
------------	------	------------	----------------------	--	--	--	--

No.	Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V)	Limit (dB μ V)	Margin (dB)	Det.	Line	PE	Verdict
1	0.154	45.47	10.22	55.69	65.78	10.09	QPK	N	GND	PASS
2	0.154	20.31	10.22	30.53	55.78	25.25	AVG	N	GND	PASS
3	0.286	40.55	10.37	50.92	60.64	9.72	QPK	N	GND	PASS
4	0.286	35.20	10.37	45.57	50.64	5.07	AVG	N	GND	PASS
5	0.310	33.76	10.37	44.13	59.97	15.84	QPK	N	GND	PASS
6	0.310	33.27	10.37	43.64	49.97	6.33	AVG	N	GND	PASS
7	0.476	27.33	10.33	37.66	56.41	18.75	QPK	N	GND	PASS
8	0.476	26.01	10.33	36.34	46.41	10.07	AVG	N	GND	PASS
9	0.669	18.81	10.38	29.19	56.00	26.81	QPK	N	GND	PASS
10	0.669	18.12	10.38	28.50	46.00	17.50	AVG	N	GND	PASS
11	0.857	13.36	10.36	23.72	56.00	32.28	QPK	N	GND	PASS
12	0.857	12.75	10.36	23.11	46.00	22.89	AVG	N	GND	PASS

Test mode:	GFSK	Frequency:	Channel 00: 2402 MHz				
------------	------	------------	----------------------	--	--	--	--

No.	Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V)	Limit (dB μ V)	Margin (dB)	Det.	Line	PE	Verdict
1	0.155	45.01	10.2	55.21	65.73	10.52	QPK	L1	GND	PASS
2	0.155	20.19	10.2	30.39	55.73	25.34	AVG	L1	GND	PASS
3	0.190	40.18	10.32	50.50	64.04	13.54	QPK	L1	GND	PASS
4	0.190	28.32	10.32	38.64	54.04	15.40	AVG	L1	GND	PASS
5	0.286	41.27	10.34	51.61	60.64	9.03	QPK	L1	GND	PASS
6	0.286	38.92	10.34	49.26	50.64	1.38	AVG	L1	GND	PASS
7	0.309	34.23	10.37	44.60	60.00	15.40	QPK	L1	GND	PASS
8	0.309	33.88	10.37	44.25	50.00	5.75	AVG	L1	GND	PASS
9	0.476	28.62	10.42	39.04	56.41	17.37	QPK	L1	GND	PASS
10	0.476	26.24	10.42	36.66	46.41	9.75	AVG	L1	GND	PASS
11	0.669	19.35	10.32	29.67	56.00	26.33	QPK	L1	GND	PASS
12	0.669	17.99	10.32	28.31	46.00	17.69	AVG	L1	GND	PASS

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.9.2 Result

PASS

The EUT has 1 PCB Antenna: The PCB Antenna Gain is 1.7 dBi;

- Antenna use a permanently attached antenna which is not replaceable.
- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

Note: Please refer to the attached document Internal Photos to show the antenna connector.
 Which in accordance to section 15.203, please refer to the internal photos.

--- End of Report ---