

FCC Test Report FCC ID:2ACDFO3

Product: Mobile phone

Trade Mark: superinworld

Model Number: O3

Serial Model: N/A

Report No.: NTEK- 2016NT11169907F4

Prepared for

Superdigital Technology Co.,Limited F2104, 3C Building, Cloud Park, No.133 Xuegang North Road, Longgang District shenzhen, China, 518000

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599 Website:http://www.ntek.org.cn Applicant's name: Superdigital Technology Co.,Limited



TEST RESULT CERTIFICATION

Report No.: NTEK-2016NT11169907F4

| Address | 3C Building, Cloud Park, No.133 Xuegang North Road, ing District, shenzhen, China, 518000 | | | | |
|-----------------------------------|---|--|--|--|--|
| Manufacturer's Name: Superd | igital Technology Co.,Limited | | | | |
| Address | dress | | | | |
| Product description | | | | | |
| Product name: Mobile | phone | | | | |
| Model and/or type reference : N/A | | | | | |
| Standards FCC Pa | art15B: 21 Sep.2016 63.4:2014 | | | | |
| | rested by NTEK, and the test results show that the ance with Part 15 of FCC Rules. And it is applicable only to t. | | | | |
| | ept in full, without the written approval of NTEK, this NTEK, personnel only, and shall be noted in the revision of : | | | | |
| Date (s) of performance of tests | | | | | |
| Date of Issue | | | | | |
| Test Result | | | | | |
| Testing Engineer | : Eileen Wu. (Eileen Liu) | | | | |
| | Jason chen | | | | |
| Technical Manager | : (Jason Chen) | | | | |
| Authorized Signatory | : Sam . Chew (Sam Chen) | | | | |



| Table of Contents | Page |
|--|------|
| 1 . TEST SUMMARY | 4 |
| 1.1 TEST FACILITY | 5 |
| 1.2 MEASUREMENT UNCERTAINTY | 5 |
| 2 . GENERAL INFORMATION | 6 |
| 2.1 GENERAL DESCRIPTION OF EUT | 6 |
| 2.2 DESCRIPTION OF TEST SETUP | 8 |
| 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL | 9 |
| 2.4 MEASUREMENT INSTRUMENTS LIST | 10 |
| 3 . EMC EMISSION TEST | 11 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 11 |
| 3.1.1 POWER LINE CONDUCTED EMISSION | 11 |
| 3.1.2 TEST PROCEDURE | 12 |
| 3.1.3 TEST SETUP | 12 |
| 3.1.4 EUT OPERATING CONDITIONS | 12 |
| 3.1.5 TEST RESULTS | 13 |
| 3.1.7 LIMITS OF RADIATED EMISSION MEASUREMENT | 17 |
| 3.1.8 TEST PROCEDURE | 17 |
| 3.1.9 TEST SETUP | 18 |
| 3.1.10 TEST RESULTS | 19 |
| 3.1.11 TEST RESULTS(1000~12400MHz) | 21 |
| 4 FUT TEST PHOTO | 22 |



1. TEST SUMMARY

Test procedures according to the technical standards:

| EMC Emission | | | | | | | |
|--------------------------------------|--------------------|---------|----------|--------|--|--|--|
| Standard | Test Item | Limit | Judgment | Remark | | | |
| FCC Part15B:2016 ANSI C63.4: 2014 | Conducted Emission | Class B | PASS | | | | |
| | Radiated Emission | Class B | PASS | | | | |

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.



1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number: 463705; IC Registration Number: 9270A-1

CNAS Registration Number:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement:

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| NTEKC01 | ANSI | 150 KHz ~ 30MHz | 3.2 | |

B. Radiated Measurement:

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| NTEKA01 | ANSI | 30MHz ~ 1000MHz | 4.7 | |
| | | 1GHz ~12.4GHz | 5.0 | |



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| Z.1 GLINLINAL DESC | 1101101 201 | | | |
|---------------------|---|--|--|--|
| Equipment | Mobile phone | | | |
| Trade Mark | superinworld | | | |
| Model Name | O3 | | | |
| Serial Model | N/A | | | |
| Model Difference | N/A | | | |
| | The EUT is a Indus | strial Mobile phone. | | |
| | Connecting I/O port: | USB, Earphone | | |
| Product Description | Operation Frequency: Modulation Type: | BT:2402~2480MHz WIFI 802.11B/G/N20:2412~2462MHz; GSM850: TX824.2MHz~848.8MHz /RX869.2MHz~893.8MHz; PCS1900: TX1850.2MHz~1909.8MHz /RX1930.2MHz~1989.8MHz; UMTS FDD Band V : TX826.4MHz~846.6MHz /RX869MHz~894MHz; BT(1Mbps): GFSK BT EDR(2Mbps): π /4-DQPSK BT EDR(3Mbps): 8-DPSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n (HT20): OFDM (64QAM, 16QAM, QPSK, BPSK) GSM / DCS: GMSK WCDMA:QPSK | | |
| Power Source | DC 3.7V/1300mAh f | rom Battery or DC 5V from Adapter. | | |
| | Model: superinworld | | | |
| Adapter | Input:AC 100~240V | 50/60Hz 0.15A | | |
| | Output:DC 5V,700mA | | | |
| Battery | DC 3.7V, 1300mAh | DC 3.7V, 1300mAh | | |
| | | | | |



2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


| Pretest Mode | Description |
|--------------|---------------|
| Mode 1 | Connect to PC |
| Mode 2 | Camera |
| Mode 3 | TF card Play |

| For Conducted Test | | | |
|--------------------|---------------|--|--|
| Final Test Mode | Description | | |
| Mode 1 | Connect to PC | | |
| Mode 2 | Camera | | |
| Mode 3 | TF card Play | | |

| For Radiated Test | | | |
|-------------------|---------------|--|--|
| Final Test Mode | Description | | |
| Mode 1 | Connect to PC | | |
| Mode 2 | Camera | | |
| Mode 3 | TF card Play | | |

Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case. Only the worst case mode is recorded in the report.







2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Brand | Model/Type No. | Series No. | Note |
|------|-------------------|--------------|----------------|------------------------------|------|
| E-1 | Mobile phone | superinworld | О3 | N/A | EUT |
| E-2 | Printer | Canon | L11121E | LBP2900 | |
| E-3 | Monitor | DELL | IN2020MB | cn-0y6mhx-74261-11f-67e s | |
| E-4 | Personal computer | DELL | FT4Y23X | 34413561645 | |
| E-5 | Keyboard | DELL | SK-8185 | OY526KUS | |
| E-6 | Mouse | DELL | MS111-P | cn-011d3v-71581-11e-1th7 | |
| E-7 | Earphone | N/A | L662 | N/A | |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Cable Type | Shielded Type | Ferrite Core | Length | Note |
|------|-------------------|---------------|--------------|--------|------|
| C-1 | USB Cable | unshielded | NO | 1.2m | |
| C-2 | VGA | unshielded | NO | 1.0m | |
| C-3 | USB Cable | unshielded | NO | 1.2m | |
| C-4 | USB Cable | unshielded | NO | 1.0m | |
| C-5 | USB Cable | unshielded | NO | 1.0m | |
| C-6 | Power Line | unshielded | NO | 1.2m | |
| C-7 | Earphone Cable | unshielded | Yes | 1.0m | |
| | | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".



Page 10 of 23 Report No.: NTEK- 2016NT11169907F4

2.4 MEASUREMENT INSTRUMENTS LIST

Radiation Test equipment

| Item | | Manufacturer | Type No. | Serial No. | Last | Calibrated | Calibratio |
|------|-----------------------|--------------|-----------------|------------------|-------------|------------|------------|
| 4 | Equipment | | | NA)/4540004 | calibration | until | n period |
| 1 | Spectrum Analyzer | Agilent | E4407B | MY4510804 0 | 2016.07.06 | 2017.07.05 | 1 year |
| 2 | Test Receiver | R&S | ESPI | 101318 | 2016.06.07 | 2017.06.06 | 1 year |
| 3 | Bilog Antenna | TESEQ | CBL6111D | 31216 | 2016.07.06 | 2017.07.05 | 1 year |
| 4 | 50Ω Coaxial Switch | Anritsu | MP59B | 620026441 6 | 2016.06.07 | 2017.06.06 | 1 year |
| 5 | Spectrum Analyzer | ADVANTEST | R3132 | 150900201 | 2016.06.07 | 2017.06.06 | 1 year |
| 6 | Horn Antenna | EM | EM-AH-101 80 | 2011071402 | 2016.07.06 | 2017.07.05 | 1 year |
| 7 | Horn Ant | Schwarzbeck | BBHA 9170 | 9170-181 | 2016.07.06 | 2017.07.05 | 1 year |
| 8 | Amplifier | EM | EM-30180 | 060538 | 2015.12.22 | 2016.12.21 | 1 year |
| 9 | Loop Antenna | ARA | PLA-1030/B | 1029 | 2016.06.08 | 2017.06.07 | 1 year |
| 10 | Power Meter | R&S | NRVS | 100696 | 2016.07.06 | 2017.07.05 | 1 year |
| 11 | Power Sensor | R&S | URV5-Z4 | 0395.1619. 05 | 2016.07.06 | 2017.07.05 | 1 year |
| 12 | Test Cable | N/A | R-01 | N/A | 2016.07.06 | 2017.07.05 | 1 year |
| 13 | Test Cable | N/A | R-02 | N/A | 2016.07.06 | 2017.07.05 | 1 year |

Conduction Test equipment

| Item | Kind of Equipment | Manufactu rer | Type No. | Serial No. | Last calibration | Calibrated until | Calibratio n period |
|------|--------------------------|------------------|----------|----------------|------------------|------------------|---------------------|
| 1 | Test Receiver | R&S | ESCI | 101160 | 2016.07.06 | 2017.07.05 | 1 year |
| 2 | LISN | R&S | ENV216 | 101313 | 2016.08.24 | 2017.08.23 | 1 year |
| 3 | LISN | EMCO | 3816/2 | 00042990 | 2016.08.24 | 2017.08.23 | 1 year |
| 4 | 50Ω Coaxial Switch | Anritsu | MP59B | 620026441 7 | 2016.06.07 | 2017.06.06 | 1 year |
| 5 | Passive Voltage Probe | R&S | ESH2-Z3 | 100196 | 2016.06.07 | 2017.06.06 | 1 year |
| 6 | Absorbing clamp | R&S | MOS-21 | 100423 | 2016.06.08 | 2017.06.07 | 1 year |
| 7 | Test Cable | N/A | C01 | N/A | 2016.06.08 | 2017.06.07 | 1 year |
| 8 | Test Cable | N/A | C02 | N/A | 2016.06.08 | 2017.06.07 | 1 year |
| 9 | Test Cable | N/A | C03 | N/A | 2016.06.08 | 2017.06.07 | 1 year |



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) | | Class B (dBuV) | | |
|------------------|----------------|---------|----------------|-----------|--|
| FREQUENCT (MITZ) | Quasi-peak | Average | Quasi-peak | Average | |
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |



3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISM.

2.Both of LISMs (AMM) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.




3.1.5 TEST RESULTS

| EUT: | Mobile phone | Model Name. : | O3 | | |
|---------------|---------------------------------|--------------------|------------|--|--|
| Temperature: | 26 ℃ | Relative Humidity: | 54% | | |
| Pressure: | 1010hPa | Test Date: | 2016-11-16 | | |
| Test Mode: | Mode 1 Phase : L | | | | |
| Test Voltage: | DC 5V from Adapter AC 120V/60Hz | | | | |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz) | (dBµV) | (dB) | (dBµV) | (dBµV) | (dB) | Remark |
| 0.2020 | 32.93 | 10.20 | 43.13 | 63.52 | -20.39 | QP |
| 0.2020 | 28.95 | 10.20 | 39.15 | 53.52 | -14.37 | AVG |
| 0.8059 | 18.99 | 9.82 | 28.81 | 56.00 | -27.19 | QP |
| 0.8059 | 16.14 | 9.82 | 25.96 | 46.00 | -20.04 | AVG |
| 2.4180 | 24.32 | 9.86 | 34.18 | 56.00 | -21.82 | QP |
| 2.4180 | 17.32 | 9.86 | 27.18 | 46.00 | -18.82 | AVG |
| 15.8139 | 32.84 | 10.26 | 43.10 | 60.00 | -16.90 | QP |
| 15.8139 | 20.27 | 10.26 | 30.53 | 50.00 | -19.47 | AVG |
| 24.5700 | 29.59 | 10.47 | 40.06 | 60.00 | -19.94 | QP |
| 24.5700 | 18.26 | 10.47 | 28.73 | 50.00 | -21.27 | AVG |

Remark:



DC 5V from Adapter AC 120V/60Hz



Test Voltage:


EUT: Mobile phone Model Name.: О3 Relative Humidity: Temperature: 26 ℃ 54% Pressure: 1010hPa Test Date: 2016-11-16 Test Mode: Phase: Ν Mode 1

Report No.: NTEK-2016NT11169907F4

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz) | (dBµV) | (dB) | (dBµV) | (dBµV) | (dB) | Remark |
| 0.2020 | 34.10 | 10.20 | 44.30 | 63.52 | -19.22 | QP |
| 0.2020 | 29.51 | 10.20 | 39.71 | 53.52 | -13.81 | AVG |
| 0.4020 | 24.48 | 9.98 | 34.46 | 57.81 | -23.35 | QP |
| 0.4020 | 19.84 | 9.98 | 29.82 | 47.81 | -17.99 | AVG |
| 2.4140 | 24.74 | 9.86 | 34.60 | 56.00 | -21.40 | QP |
| 2.4140 | 17.98 | 9.86 | 27.84 | 46.00 | -18.16 | AVG |
| 15.7939 | 37.68 | 10.26 | 47.94 | 60.00 | -12.06 | QP |
| 15.7939 | 24.41 | 10.26 | 34.67 | 50.00 | -15.33 | AVG |
| 24.5339 | 31.62 | 10.47 | 42.09 | 60.00 | -17.91 | QP |
| 24.5339 | 17.61 | 10.47 | 28.08 | 50.00 | -21.92 | AVG |

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Insertion Loss + Cable Loss.






| EUT: | Mobile phone | Model Name.: | O3 | |
|---------------|---------------------------------|--------------------|------------|--|
| Temperature: | 26 ℃ | Relative Humidity: | 54% | |
| Pressure: | 1010hPa | Test Date: | 2016-11-16 | |
| Test Mode: | Mode 1 | Phase : | L | |
| Test Voltage: | DC 5V from Adapter AC 240V/60Hz | | | |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz) | (dBµV) | (dB) | (dBµV) | (dBµV) | (dB) | Remark |
| 0.2020 | 34.32 | 10.20 | 44.52 | 63.52 | -19.00 | QP |
| 0.2020 | 29.47 | 10.20 | 39.67 | 53.52 | -13.85 | AVG |
| 1.3700 | 22.78 | 9.82 | 32.60 | 56.00 | -23.40 | QP |
| 1.3700 | 20.46 | 9.82 | 30.28 | 46.00 | -15.72 | AVG |
| 2.2860 | 29.50 | 9.85 | 39.35 | 56.00 | -16.65 | QP |
| 2.2860 | 25.59 | 9.85 | 35.44 | 46.00 | -10.56 | AVG |
| 15.8697 | 29.57 | 10.26 | 39.83 | 60.00 | -20.17 | QP |
| 15.8697 | 21.13 | 10.26 | 31.39 | 50.00 | -18.61 | AVG |
| 25.1098 | 30.55 | 10.46 | 41.01 | 60.00 | -18.99 | QP |
| 25.1098 | 22.33 | 10.46 | 32.79 | 50.00 | -17.21 | AVG |

Remark:

1. All readings are Quasi-Peak and Average values.






| EUT: | Mobile phone | Model Name. : | O3 | | |
|---------------|---------------------------------|--------------------|------------|--|--|
| Temperature: | 26 ℃ | Relative Humidity: | 54% | | |
| Pressure: | 1010hPa | Test Date: | 2016-11-16 | | |
| Test Mode: | Mode 1 Phase : N | | | | |
| Test Voltage: | DC 5V from Adapter AC 240V/60Hz | | | | |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz) | (dBµV) | (dB) | (dBµV) | (dBµV) | (dB) | Remark |
| 0.2020 | 34.65 | 10.20 | 44.85 | 63.52 | -18.67 | QP |
| 0.2020 | 28.01 | 10.20 | 38.21 | 53.52 | -15.31 | AVG |
| 0.5020 | 27.60 | 9.88 | 37.48 | 56.00 | -18.52 | QP |
| 0.5020 | 20.64 | 9.88 | 30.52 | 46.00 | -15.48 | AVG |
| 1.7098 | 22.19 | 9.84 | 32.03 | 56.00 | -23.97 | QP |
| 1.7098 | 18.19 | 9.84 | 28.03 | 46.00 | -17.97 | AVG |
| 15.8899 | 35.51 | 10.26 | 45.77 | 60.00 | -14.23 | QP |
| 15.8899 | 24.80 | 10.26 | 35.06 | 50.00 | -14.94 | AVG |
| 24.7340 | 31.80 | 10.46 | 42.26 | 60.00 | -17.74 | QP |
| 24.7340 | 22.76 | 10.46 | 33.22 | 50.00 | -16.78 | AVG |

Remark:





B.1.6 RADIATED EMISSION MEASUREMENT

3.1.7 LIMITS OF RADIATED EMISSION MEASUREMENT

| FREQUENCY (MHz) | Class A (at 10m) | Class B (at 3m) | |
|------------------|------------------|-----------------|--|
| PREQUENCY (MINZ) | dBuV/m | dBuV/m | |
| 30 ~ 88 | 39.0 | 40.0 | |
| 88 ~ 216 | 43.5 | 43.5 | |
| 216 ~ 960 | 46.5 | 46.0 | |
| Above 960 | 49.5 | 54.0 | |

Notes:

- (1) The limit for radiated test was performed according to as following: FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.1.8 TEST PROCEDURE

Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: For the hand-held device, the EUT should be measured for all 3 axes and only the wors




case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


| Frequency Band (MHz) | Function | Resolution bandwidth | Video Bandwidth |
|-------------------------|----------|----------------------|-----------------|
| 30 to 1000 | QP | 120 kHz | 300 kHz |
| | Peak | 1 MHz | 1 MHz |
| Above 1000 | Avg | 1 MHz | 10 Hz |

3.1.9 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz





3.1.10 TEST RESULTS


TEST RESULTS (30~1000 MHz)

| EUT: | Mobile phone | Model Name.: | O3 | | |
|--------------|---------------------------------|--------------------|------------|--|--|
| Temperature: | 24 °C | Relative Humidity: | 54% | | |
| Pressure: | 1010 hPa | Test Date : | 2016-11-16 | | |
| Test Mode : | Mode 1 | Polarization : | Horizontal | | |
| Test Power : | DC 5V from Adapter AC 120V/60Hz | | | | |

| Pola r (H/V) | Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Remark |
|--------------------|-----------|------------------|--------|-------------------|----------|--------|--------|
| (H/V) | (MHz) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | Roman |
| Н | 182.5592 | 25.26 | 11.28 | 36.54 | 43.50 | -6.96 | QP |
| Н | 287.9904 | 25.46 | 15.94 | 41.40 | 46.00 | -4.60 | QP |
| Н | 312.1792 | 25.92 | 16.65 | 42.57 | 46.00 | -3.43 | QP |
| Н | 480.5276 | 21.12 | 21.18 | 42.30 | 46.00 | -3.70 | QP |
| Н | 962.1621 | 15.18 | 31.33 | 46.51 | 54.00 | -7.49 | QP |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.






| EUT: | Mobile phone | Model Name.: | O3 | | |
|--------------|---------------------------------|--------------------|------------|--|--|
| Temperature: | 24 ℃ | Relative Humidity: | 54% | | |
| Pressure: | 1010 hPa | Test Date : | 2016-11-16 | | |
| Test Mode: | Mode 1 | Polarization: | Vertical | | |
| Test Power: | DC 5V from Adapter AC 120V/60Hz | | | | |

| Polar (H/V) | Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Remark |
|----------------|-----------|------------------|--------|-------------------|----------|--------|--------|
| | (MHz) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | |
| V | 54.8348 | 32.85 | 7.15 | 40.00 | 40.00 | 0.00 | QP |
| V | 182.5592 | 26.35 | 11.28 | 37.63 | 43.50 | -5.87 | QP |
| V | 291.0360 | 23.22 | 16.06 | 39.28 | 46.00 | -6.72 | QP |
| V | 480.5276 | 19.51 | 21.18 | 40.69 | 46.00 | -5.31 | QP |
| V | 962.1621 | 14.48 | 31.33 | 45.81 | 54.00 | -8.19 | QP |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.





3.1.11 TEST RESULTS(1000~12400MHz)

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Remark |
|-----------|---|--|---|---|---|--|
| (MHz) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | |
| 1343.987 | 54.08 | -12.59 | 41.49 | 74.00 | -32.51 | peak |
| 1343.987 | 47.19 | -12.59 | 34.60 | 54.00 | -19.40 | AVG |
| 1838.956 | 49.14 | -10.76 | 38.38 | 74.00 | -35.62 | peak |
| 1838.956 | 41.26 | -10.76 | 30.50 | 54.00 | -23.50 | AVG |
| 2014.917 | 50.07 | -9.96 | 40.11 | 74.00 | -33.89 | peak |
| 2014.917 | 42.66 | -9.96 | 32.70 | 54.00 | -21.30 | AVG |
| 2688.682 | 49.30 | -9.14 | 40.16 | 74.00 | -33.84 | peak |
| 2688.682 | 41.24 | -9.14 | 32.10 | 54.00 | -21.90 | AVG |
| 1343.987 | 53.17 | -12.59 | 40.58 | 74.00 | -33.42 | peak |
| 1343.987 | 44.99 | -12.59 | 32.40 | 54.00 | -21.60 | AVG |
| 2014.917 | 48.58 | -9.96 | 38.62 | 74.00 | -35.38 | peak |
| 2014.917 | 40.86 | -9.96 | 30.90 | 54.00 | -23.10 | AVG |
| 2350.597 | 46.55 | -9.73 | 36.82 | 74.00 | -37.18 | peak |
| 2350.597 | 39.93 | -9.73 | 30.20 | 54.00 | -23.80 | AVG |
| | (MHz) 1343.987 1343.987 1838.956 1838.956 2014.917 2014.917 2688.682 2688.682 1343.987 1343.987 2014.917 2014.917 2350.597 | (MHz) (dBuV) 1343.987 54.08 1343.987 47.19 1838.956 49.14 1838.956 41.26 2014.917 50.07 2014.917 42.66 2688.682 49.30 2688.682 41.24 1343.987 53.17 1343.987 44.99 2014.917 48.58 2014.917 40.86 2350.597 46.55 2350.597 39.93 | (MHz) (dBuV) (dB) 1343.987 54.08 -12.59 1343.987 47.19 -12.59 1838.956 49.14 -10.76 1838.956 41.26 -10.76 2014.917 50.07 -9.96 2014.917 42.66 -9.96 2688.682 49.30 -9.14 2688.682 41.24 -9.14 1343.987 53.17 -12.59 1343.987 44.99 -12.59 2014.917 48.58 -9.96 2014.917 40.86 -9.96 2350.597 46.55 -9.73 2350.597 39.93 -9.73 | (MHz) (dBuV) (dB) (dBuV/m) 1343.987 54.08 -12.59 41.49 1343.987 47.19 -12.59 34.60 1838.956 49.14 -10.76 38.38 1838.956 41.26 -10.76 30.50 2014.917 50.07 -9.96 40.11 2014.917 42.66 -9.96 32.70 2688.682 49.30 -9.14 40.16 2688.682 41.24 -9.14 32.10 1343.987 53.17 -12.59 40.58 1343.987 44.99 -12.59 32.40 2014.917 40.86 -9.96 30.90 2350.597 46.55 -9.73 36.82 2350.597 39.93 -9.73 30.20 | (MHz) (dBuV) (dB) (dBuV/m) (dBuV/m) 1343.987 54.08 -12.59 41.49 74.00 1343.987 47.19 -12.59 34.60 54.00 1838.956 49.14 -10.76 38.38 74.00 1838.956 41.26 -10.76 30.50 54.00 2014.917 50.07 -9.96 40.11 74.00 2014.917 42.66 -9.96 32.70 54.00 2688.682 49.30 -9.14 40.16 74.00 2688.682 41.24 -9.14 32.10 54.00 1343.987 53.17 -12.59 40.58 74.00 1343.987 44.99 -12.59 32.40 54.00 2014.917 48.58 -9.96 38.62 74.00 2014.917 40.86 -9.96 30.90 54.00 2350.597 39.93 -9.73 36.82 74.00 2350.597 39.93 -9.73 30.20 5 | (MHz) (dBuV) (dB) (dBuV/m) (dBuV/m) (dBuV/m) (dB) 1343.987 54.08 -12.59 41.49 74.00 -32.51 1343.987 47.19 -12.59 34.60 54.00 -19.40 1838.956 49.14 -10.76 38.38 74.00 -35.62 1838.956 41.26 -10.76 30.50 54.00 -23.50 2014.917 50.07 -9.96 40.11 74.00 -33.89 2014.917 42.66 -9.96 32.70 54.00 -21.30 2688.682 49.30 -9.14 40.16 74.00 -33.84 2688.682 41.24 -9.14 32.10 54.00 -21.90 1343.987 53.17 -12.59 40.58 74.00 -33.42 1343.987 44.99 -12.59 32.40 54.00 -21.60 2014.917 48.58 -9.96 38.62 74.00 -35.38 2014.917 40.86 -9.96 |

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit







4. EUT TEST PHOTO











Conducted Measurement Photos

