

# TEST REPORT

### **FCC PART 15.225**

Report Reference No. ...... CTL1703068021-WF01

Compiled by: ( position+printed name+signature)

Allen Wang (File administrators)

Tested by:

( position+printed name+signature)

Nice Nong (Test Engineer)

Approved by: ( position+printed name+signature)

Ivan Xie (Manager)

Product Name...... RFID card reader

S3-P, S3-M, S3-D, S3-MP, S3-DT, S2-P, S2-M, S2-D, S2-MP,

S2-DT, S1-P, S1-M, S1-D, S1-MP, S1-DT, B1-P, B1-M, B1-D,

Model/Type reference ....... B1-MP, B1-DT, F1-P, F1-M, F1-D, F1-MP, F1-DT, F1G-P, F1G-M, F1G-D, F1G-MP, F1G-DT, F2-P, F2-M, F2-D, F2-MP, F2-DT,

F2G-P, F2G-M, F2G-D, F2G-MP, F2G-DT

Trade Mark...... INS

FCC ID ...... 2ACDGS3-P

Applicant's name ...... INS Global Pty Ltd

Address of applicant ...... Suite 8,166A The Entrance Rd, Erina NSW 2250, Australia

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Address of Test Firm ......

Nanshan District, Shenzhen, China 518055

Test specification.....

Standard...... FCC Part 15.225: Operation within the band 13.110–14.010 MHz.

TRF Originator ...... Shenzhen CTL Testing Technology Co., Ltd.

Master TRF ...... Dated 2011-01

**Date of Receipt**...... Mar. 06, 2017

Date of Test Date ...... Mar. 06, 2017–Apr. 20, 2017

**Data of Issue**...... Apr. 20, 2017

Result ..... Pass

#### Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# **TEST REPORT**

Test Report No. :	CTL1703068021-WF01	Apr. 20, 2017 Date of issue
-------------------	--------------------	--------------------------------

Equipment under Test : RFID card reader

Model /Type : S3-P, S3-M, S3-D, S3-MP, S3-DT, S2-P, S2-M, S2-D,

S2-MP, S2-DT, S1-P, S1-M, S1-D, S1-MP, S1-DT, B1-P, B1-M, B1-D, B1-MP, B1-DT, F1-P, F1-M, F1-D, F1-MP, F1-DT, F1G-P, F1G-M, F1G-D, F1G-MP, F1G-DT, F2-P, F2-M, F2-D, F2-MP, F2-DT, F2G-P,

Report No.: CTL1703068021-WF01

F2G-M, F2G-D, F2G-MP, F2G-DT

Applicant : INS Global Pty Ltd

Address : Suite 8,166A The Entrance Rd, Erina NSW 2250,

Australia

Manufacturer JAT Enterprise Co.,Limited

Address : 6F, ChuangCheng Building #2, TaiWan Industrial

Area, ShiYan, BaoAn, ShenZhen, China

Test result Pass \*

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified page 5.

# \*\* Modified History \*\*

Version	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2017-04-20	CTL1703068021-WF01	Tracy Qi



	Table of Contents	Page
1. SU	JMMARY	5
1.1.	Test Standards	
1.2.	TEST DESCRIPTION	5
1.3.	TEST FACILITY	
1.4.	STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
2. GE	ENERAL INFORMATION	7
2.1.	ENVIRONMENTAL CONDITIONS	7
2.2.	GENERAL DESCRIPTION OF EUT	7
2.3.	EQUIPMENTS USED DURING THE TEST	
2.4.	RELATED SUBMITTAL(S) / GRANT (S)	8
2.5.	Modifications	8
3. TE	ST CONDITIONS AND RESULTS	9
3.1.	CONDUCTED EMISSION (AC MAIN)	9
3.2.	Radiated Emission	12
3.3.	20dB Bandwidth	15
3.4.	Frequency Stability Test Data	
4. EU	JT TEST PHOTO	18
	TERNAL AND INTERNAL PHOTOS OF THE EUT	
J/	CLEAN LEVILLE TO LEVEL TO LOCATE TO LOCATE TO LANGUAGE	



# 1. SUMMARY

#### 1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.225: Operation within the band 13.110-14.010 MHz

ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices

ANSI C63.4: 2014: —American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

# 1.2. Test Description

FCC PART 15 .225		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.215	20dB Bandwidth	PASS
FCC Part 15.225(a) (b) (c)	In-band Emissions	PASS
FCC Part 15.225(d)/15.207	Out-of-band Emissions	PASS
FCC Part 15.225(e)	Frequency Stability Tolerance	PASS

Remark: The measurement uncertainty is not included in the test result.



V1.0 Page 6 of 23 Report No.: CTL1703068021-WF01

### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

#### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods — Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance0.15~30MHz	±3.20dB	(1)

<sup>(1)</sup> This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

V1.0 Page 7 of 23 Report No.: CTL1703068021-WF01

# 2. GENERAL INFORMATION

# 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

# 2.2. General Description of EUT

Product Name:	RFID card reader
Model/Type reference:	S3-P
Power supply:	DC 12V from battery
13.56MHz	
Operation frequency:	13.56MHz
Modulation :	ASK
No. of Channel :	1
Antenna type:	PCB Antenna
Antenna gain:	0 dBi
125.62KHz	No Contract of the Contract of
Operation frequency:	125.62KHz
Modulation :	ASK
No. of Channel :	
Antenna type:	LOOP Antenna
Antenna gain:	0 dBi

For more details, please refer to the user's manual of the EUT.

# 2.3. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.1 2	2016/06/02	2017/06/01
LISN	R&S	ESH2-Z5	860014/010	2016/06/02	2017/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2016/06/02	2017/06/01
EMI Test Receiver	R&S	ESCI	103710	2016/06/02	2017/06/01
Spectrum Analyzer	Agilent	N9020	US46220290	2017/01/17	2018/01/16
Controller	EM Electronics	Controller EM 1000	N/A	2016/05/21	2017/05/20

Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2016/05/19	2017/05/18
Active Loop Antenna	SCHWARZBE CK	FMZB1519	1519-037	2016/05/19	2017/05/18
Amplifier	Agilent	8349B	3008A02306	2016/05/19	2017/05/18
Amplifier	Agilent	8447D	2944A10176	2016/05/19	2017/05/18
Temperature/Humi dity Meter	Gangxing	CTH-608	02	2016/05/20	2017/05/19
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2016/05/20	2017/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2016/05/20	2017/05/19
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-10M	10m	2016/06/02	2017/06/01
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2016/06/02	2017/06/01
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2016/06/02	2017/06/01
Programmable constant temperature and humidity test chamber	Bolie	BL-225TH-40A	2022041015	2016/06/02	2017/06/01
DC source	QJE	QJ6003S	023457	2016/06/02	2017/06/01
RF Cable	Megalon	RF-A303	N/A	2016/06/02	2017/06/01

The calibration interval was one year

# 2.4. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ACDGS3-P filing to comply with Section 15.225 of the FCC Part 15, Subpart C Rules.

No modifications were implemented to meet testing criteria.

V1.0 Page 9 of 23 Report No.: CTL1703068021-WF01

### 3. TEST CONDITIONS AND RESULTS

### 3.1. Conducted Emission (AC Main)


#### <u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Fraguency range (MHz)	Limit (dBuV)		
Frequency range (MHz)	Quasi-peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **TEST CONFIGURATION**




#### TEST PROCEDURE

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a flood stand system; a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2. Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.

#### **TEST RESULTS**

#### SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



#### MEASUREMENT RESULT: "CTL170420610 fin"

4/20/2	2017 2	:51PM
--------	--------	-------

4/20/2017	Z.JIFN						
Frequenc MF	-		Limit dBµV	Margin dB	Detector	Line	PE
0.15000	0 54.30	10.2	66	11.7	QP	L1	GND
0.16200	0 50.00	10.2	65	15.4	Q̈́Ρ	L1	GND
0.41800	0 42.50	10.2	58	15.0	QP	L1	GND
0.50000	0 42.30	10.2	56	13.7	QP	L1	GND
1.76000	0 41.90	10.3	56	14.1	QP	L1	GND
2.15000	0 40.30	10.4	56	15.7	QP	L1	GND


#### MEASUREMENT RESULT: "CTL170420610\_fin2"

4/20/2017 2:51PM

4/20	)/201/ 2:5	DIPM						
I	requency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dBuV	dB	dBuV	dB			
	11112	az <sub>µ</sub> ,		app.	42			
	0 150000	20.00	10.0	F.C.	16.6	7.77	T 1	CINTE
	0.158000	39.00	10.2	56	16.6	AV	L1	GND
	1.106000	28.50	10.3	46	17.5	AV	L1	GND
	1.274000	29.30	10.3	46	16.7	AV	L1	GND
	1.412000	31.70	10.3	46	14.3	AV	L1	GND
	1.760000	32.50	10.3	46	13.5	AV	L1	GND
	2.180000	31.20	10.4	46	14.8	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



#### MEASUREMENT RESULT: "CTL170420611\_fin"

4/20/2017 2:	:54PM						
Frequency	Level				Detector	Line	PE
MHz	dΒμV	dB	dΒμV	dB			
0.154000	52.70	10.2	66	13.1	QP	N	GND
0.402000	42.90	10.2	58	14.9	QP	N	GND
0.478000	44.90	10.2	56	11.5	QP	N	GND
1.532000	42.60	10.3	56	13.4	QP	N	GND
2.198000	36.90	10.4	56	19.1	QP	N	GND
3.410000	33.80	10.4	56	22.2	QP	N	GND

#### MEASUREMENT RESULT: "CTL170420611\_fin2"

4/	20/2017 2:	54PM						
	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dBµ∇	dB	dΒμV	dB			
	0.486000	31.80	10.2	46	14.4	AV	N	GND
	0.872000	30.10	10.2	46	15.9	AV	N	GND
	0.884000	30.60	10.2	46	15.4	AV	N	GND
	0.998000	31.10	10.3	46	14.9	AV	N	GND
	1.214000	30.60	10.3	46	15.4	AV	N	GND
	1.370000	31.20	10.3	46	14.8	AV	N	GND

V1.0 Page 12 of 23 Report No.: CTL1703068021-WF01

#### 3.2. Radiated Emission

#### Limit

- a The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.
- b Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- c Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- d The field strength of any emissions appearing outside of the 13.110– 14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

exoced the general radiated emission infine in \$10.200.									
Frequency (MHz)	Distance (Meters)	Radiated (dBuV/m)	Radiated (µV/m)						
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)						
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)						
1.705-13.110	3	69.54	30						
13.110-13.410	3	80.50	106						
13410-13.553	3	90.47	334						
13.553-13.567	3	124.00	15848						
13.567-13.710	3	90.47	334						
13.710-14.010	3	80.50	106						
14.010-30.0	3	69.54	30						
30-88	3	40.0	100						
88-216	3	43.5	150						
216-960	3	46.0	200						
Above 960	3	54.0	500						

#### **Test Procedure**

- 1. The EUT was placed on 80cm wooden desk above ground plane which on a turn table.
- 2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measurements have been completed.

#### **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

#### FS = RA + AF + CL - AG


Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

#### For example


Frequency	FS	RA	AF	CL	AG	Transd
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(dB)	(dB)
150.00	40	58.1	12.2	1.6	31.90	

### **Test Configuration**

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



V1.0 Page 14 of 23 Report No.: CTL1703068021-WF01

#### **Test Results**

#### 3.2.1 In-band Emissions

	Frequency		13.56			olarity:	HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)	Detector	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Correction Factor (dB/m)
1	13.15	46.04	PK	80.50	34.46	41.34	5.26	-0.56	4.70
2	13.55	48.99	PK	90.47	41.48	44.20	5.36	-0.57	4.79
3	13.56	91.22	PK	124.00	32.78	86.34	5.45	-0.57	4.88
4	13.57	47.04	PK	90.47	43.43	41.90	5.49	-0.35	5.14
5	13.75	45.90	PK	80.50	34.60	40.57	5.63	-0.30	5.33

Frequency(MHz):				13.56			olarity:	VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Detector	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Correction Factor (dB/m)
1	13.15	47.12	PK	80.50	33.38	42.42	5.26	-0.56	4.70
2	13.55	49.47	PK	90.47	41.00	44.68	5.36	-0.57	4.79
3	13.56	92.08	PK	124.00	31.92	87.20	5.45	-0.57	4.88
4	13.57	47.35	PK	90.47	43.12	42.21	5.49	-0.35	5.14
5	13.75	46.04	PK	80.50	34.46	40.71	5.63	-0.30	5.33

#### **REMARKS**:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)
- 3. Margin value = Limit value- Emission level.
- 4. The other emission levels were very low against the limit.

#### 3.2.2 Out-of-band Emissions

Frequency(MHz):			13.56			Polarity:		HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Detector	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Correction Factor (dB/m)
1	27.12	42.86	PK	69.54	26.68	35.36	7.25	0.25	7.50
2	40.68	32.18	QP	40.00	7.82	23.37	8.25	0.56	8.81
3	54.24	31.09	QP	40.00	8.91	22.05	8.30	0.74	9.04
4	67.80	32.52	QP	40.00	7.48	22.99	8.55	0.98	9.53

Frequency(MHz):			13.56			Po	olarity:	VERTICAL				
No.	Frequency (MHz)	Emission Level (dBuV/m)	Detector	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Correction Factor (dB/m)			
1	27.12	43.91	PK	69.54	25.63	36.41	7.25	0.25	7.50			
2	40.68	33.08	QP	40.00	6.92	24.27	8.25	0.56	8.81			
3	54.24	30.87	QP	40.00	9.13	21.83	8.30	0.74	9.04			
4	67.80	30.45	QP	40.00	9.55	20.92	8.55	0.98	9.53			

#### REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)
- 3. Margin value = Limit value- Emission level.
- 4. The other emission levels were very low against the limit.

V1.0 Page 15 of 23 Report No.: CTL1703068021-WF01

#### 3.3. 20dB Bandwidth

#### **Limit**

No limit for 20dB bandwidth.

#### **Test Procedure**

The 20dB bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.


The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### **Test Configuration**



#### **Test Results**

Modulation	Frequency(MHz)	20dB bandwidth (KHz)	Result
ASK	13.56	2.68	Pass




Date: 24.MAR.2017 16:32:22

# 3.4. Frequency Stability Test Data

#### <u>LIMIT</u>

The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

#### **TEST CONFIGURATION**



Note: Measurement setup for testing on Antenna connector

#### **TEST PROCEDURE**


- 1. The equipment under test was connected to an external DC power supply and input rated voltage.
- 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
- 3. The EUT was placed inside the temperature chamber.
- 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20℃ operating frequency as reference frequency.
- 5. Turn EUT off and set the chamber temperature to −20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.
- 6. Repeat step measure with 10℃ increased per stage until the highest temperature of +50℃ reached.
- 7. Reduce the input voltage to specified extreme voltage variation (+/- 15%) or endpoint, record the maximum frequency change.

#### **TEST RESULTS**

	Refere	ence Frequency: 13.5	56MHz	
Voltage ( V )	Temperature (℃)	Frequency (Hz)	Frequency Deviation(Hz)	Deviation (%)
	+20(Ref)	13,559,994	-6	0.0000442
	-20	13,559,942	-58	0.0004277
	-10	13,559,970	-30	0.0002212
	0	13,559,923	-77	0.0005678
12.0	+10	13,559,985	-15	0.0001106
12.0	+20	13,559,994	-6	0.0000442
	+25	13,559,991	-9	0.0000664
	+30	13,559,985	-15	0.0001106
	+40	13,559,972	-28	0.0002065
	+50	13,559,949	-51	0.0003761
13.2	+20	13,559,962	-38	0.0002802
10.8	+20	13,559,951	-49	0.0003614



# 4. EUT TEST PHOTO




# 5. External and Internal Photos of the EUT

**External Photos EUT** 













V1.0

Internal Photos EUT

