



588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666

Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM180600474202

Page: 1 of 57

## TEST REPORT

<b>Application No.:</b>	SHEM1806004742CR
<b>FCC ID:</b>	2ACDZ-BL3335T-P
<b>IC:</b>	21239- BL3335T
<b>Applicant:</b>	Hangzhou Gubei Electronics Technoloy Co., Ltd
<b>Address of Applicant:</b>	Room106, No.1 Building, No. 611 Jianghong Road Binjiang, Hangzhou
<b>Manufacturer:</b>	Hangzhou Gubei Electronics Technoloy Co., Ltd
<b>Address of Manufacturer:</b>	Room106, No.1 Building, No. 611 Jianghong Road Binjiang, Hangzhou
<b>Factory:</b>	Hangzhou Gubei Electronics Technoloy Co., Ltd
<b>Address of Factory:</b>	Room106, No.1 Building, No. 611 Jianghong Road Binjiang, Hangzhou
<b>Equipment Under Test (EUT):</b>	
<b>EUT Name:</b>	WiFi Module
<b>Model No.:</b>	BL3335T-P
<b>Standard(s) :</b>	47 CFR Part 15, Subpart C 15.247 RSS-247 Issue 2, February 2017 RSS-Gen Issue 5, April 2018
<b>Date of Receipt:</b>	2018-06-12
<b>Date of Test:</b>	2018-06-19 to 2018-06-21
<b>Date of Issue:</b>	2018-06-27
<b>Test Result:</b>	<b>Pass*</b>

\* In the configuration tested, the EUT complied with the standards specified above.



Parlam Zhan  
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2018-06-27	/

Authorized for issue by:			
		Vincent Zhu	
		Vincent Zhu / Project Engineer	
		Parlam Zhan	
		Parlam Zhan /Reviewer	



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Customer Declaration

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
99% Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 Section 6.9.3	RSS-Gen Section 6.6	Pass



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY.....</b>	<b>3</b>
<b>3 CONTENTS.....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>6</b>
4.1 DETAILS OF E.U.T. .....	6
4.2 DESCRIPTION OF SUPPORT UNITS.....	6
4.3 MEASUREMENT UNCERTAINTY.....	6
4.4 TEST LOCATION .....	7
4.5 TEST FACILITY .....	7
4.6 DEVIATION FROM STANDARDS .....	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
<b>5 EQUIPMENT LIST .....</b>	<b>8</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>9</b>
6.1 ANTENNA REQUIREMENT .....	9
6.1.1 <i>Test Requirement:</i> .....	9
6.1.2 <i>Conclusion</i> .....	9
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>10</b>
7.1 MINIMUM 6DB BANDWIDTH .....	10
7.1.1 <i>E.U.T. Operation</i> .....	10
7.1.2 <i>Test Setup Diagram</i> .....	10
7.1.3 <i>Measurement Procedure and Data</i> .....	10
7.2 CONDUCTED PEAK OUTPUT POWER .....	11
7.2.1 <i>E.U.T. Operation</i> .....	11
7.2.2 <i>Test Setup Diagram</i> .....	11
7.2.3 <i>Measurement Procedure and Data</i> .....	11
7.3 POWER SPECTRUM DENSITY .....	12
7.3.1 <i>E.U.T. Operation</i> .....	12
7.3.2 <i>Test Setup Diagram</i> .....	12
7.3.3 <i>Measurement Procedure and Data</i> .....	12
7.4 CONDUCTED BAND EDGES MEASUREMENT .....	13
7.4.1 <i>E.U.T. Operation</i> .....	13
7.4.2 <i>Test Setup Diagram</i> .....	13
7.4.3 <i>Measurement Procedure and Data</i> .....	13
7.5 CONDUCTED SPURIOUS EMISSIONS .....	14
7.5.1 <i>E.U.T. Operation</i> .....	14
7.5.2 <i>Test Setup Diagram</i> .....	14
7.5.3 <i>Measurement Procedure and Data</i> .....	14
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	15
7.6.1 <i>E.U.T. Operation</i> .....	16
7.6.2 <i>Test Setup Diagram</i> .....	16
7.6.3 <i>Measurement Procedure and Data</i> .....	17
7.7 RADIATED SPURIOUS EMISSIONS .....	49
7.7.1 <i>E.U.T. Operation</i> .....	50
7.7.2 <i>Test Setup Diagram</i> .....	50



7.7.3	<i>Measurement Procedure and Data</i> .....	51
7.8	99% BANDWIDTH .....	56
7.8.1	<i>E.U.T. Operation</i> .....	56
7.8.2	<i>Test Setup Diagram</i> .....	56
7.8.3	<i>Measurement Procedure and Data</i> .....	56
8	<b>TEST SETUP PHOTOGRAPHS</b> .....	57
9	<b>EUT CONSTRUCTIONAL DETAILS</b> .....	57



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 3.3V
Antenna Gain	0 dBi
Antenna Type	PCB Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	/
Serial port adapter plate	/	Test Plate 3	/

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Timeout	2s
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	RF power density	2.84dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	4.5dB (Below 1GHz) 4.8dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz) 4.4dB (30MHz-1GHz) 4.6dB (1GHz-18GHz) 5.2dB (Above 18GHz)
10	Temperature test	1 °C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666      Fax: +86 21 6191 5678

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None



## 5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
<b>Conducted Test</b>					
Spectrum Analyzer	R&S	FSP-30	SHEMA002-1	2017-12-20	2018-12-19
Spectrum Analyzer	Agilent	N9020A	SHEMA181-1	2017-09-26	2018-09-25
Power meter	R&S	NRP	SHEMA057-1	2017-12-26	2018-12-25
Power Sensor	R&S	NRP-Z22	SHEMA136-1	2017-07-22	2018-07-21
Power Sensor	R&S	NRP-Z91	SHEMA057-2	2017-12-26	2018-12-25
Signal Generator	R&S	SMR40	SHEMA058-1	2017-07-03	2018-07-02
Signal Generator	Agilent	N5182A	SHEMA182-1	2017-09-26	2018-09-25
Communication Tester	R&S	CMW270	SHEMA183-1	2017-10-22	2018-10-21
Switcher	Tonscend	JS0806	SHEMA184-1	2017-09-26	2018-09-25
Splitter	Anritsu	MA1612A	SHEMA185-1	/	/
Coupler	e-meca	803-S-1	SHEMA186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEMA087-1	2017-09-26	2018-09-25
AC Power Stabilizer	WOCEN	6100	SHEMA045-1	2017-12-26	2018-12-25
DC Power Supply	QJE	QJ30003SII	SHEMA046-1	2017-12-26	2018-12-25
Conducted test Cable	/	RF01, RF 02	/	2017-12-26	2018-12-25
<b>Radiated Test</b>					
EMI test receiver	R&S	ESU40	SHEMA051-1	2017-12-20	2018-12-19
Spectrum Analyzer	R&S	FSP-30	SHEMA002-1	2017-12-20	2018-12-19
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEMA135-1	2017-04-10	2020-04-09
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEMA048-1	2017-02-28	2020-02-27
Antenna (25MHz-3GHz)	Schwarzbeck	HL562	SHEMA010-1	2017-02-28	2020-02-27
Horn Antenna (1-8GHz)	Schwarzbeck	HF906	SHEMA009-1	2017-10-24	2020-10-23
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEMA050-1	2017-01-14	2020-01-13
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEMA049-1	2017-12-03	2020-12-02
Pre-amplifier (9KHz-2GHz)	CLAVIIO	LNA-0001-412010	SHEMA164-1	2017-08-22	2018-08-21
Pre-amplifier (1-18GHz)	CLAVIIO	BDLNA-0118-352810	SHEMA050-2	2017-08-22	2018-08-21
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEMA049-2	2017-12-20	2018-12-19
Band filter	LORCH	9BRX-875/X150-SR	SHEMA156-1	/	/
Band filter	LORCH	13BRX-1950/X500-SR	SHEMA083-2	/	/
Band filter	LORCH	5BRX-2400/X200-SR	SHEMA155-1	/	/
Band filter	LORCH	5BRX-5500/X1000-SR	SHEMA157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G-100SS	SHEMA157-1	/	/
High pass Filter	Wainwright	WHKS1700-3SS	SHEMA157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEMA078-2	2017-07-22	2020-07-21
RE test Cable	/	RE01, RE02, RE06	/	2017-12-26	2018-12-25



## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

#### 6.1.2 Conclusion

Standard Requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 0dBi.



## 7 Radio Spectrum Matter Test Results

### 7.1 Minimum 6dB Bandwidth


Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar  
Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

#### 7.1.2 Test Setup Diagram



#### 7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202


### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission

#### 7.3.1 E.U.T. Operation

Operating Environment:  
Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar  
Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202




## 7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.13.3.2  
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

### 7.4.1 E.U.T. Operation

Operating Environment:  
Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar  
Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202




## 7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.11  
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

### 7.5.1 E.U.T. Operation

Operating Environment:  
Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar  
Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202



## 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C      Humidity: 45 % RH      Atmospheric Pressure: 1010 mbar

Test mode      b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.6.2 Test Setup Diagram






### 7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2388.15	66.60	26.03	6.47	37.36	61.74	74.00	-12.26	Peak
2 2390.00	66.02	26.03	6.47	37.36	61.16	74.00	-12.84	Peak
3 2410.63	105.03	26.06	6.50	37.35	100.24	74.00	26.24	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2388.88	42.31	26.03	6.47	37.36	37.45	54.00	-16.55	Average
2 2390.00	42.42	26.03	6.47	37.36	37.56	54.00	-16.44	Average
3 2411.12	100.45	26.06	6.50	37.35	95.66	54.00	41.66	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.24	60.19	26.03	6.47	37.36	55.33	74.00	-18.67	Peak
2 2390.00	60.33	26.03	6.47	37.36	55.47	74.00	-18.53	Peak
3 2410.63	100.74	26.06	6.50	37.35	95.95	74.00	21.95	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.24	36.97	26.03	6.47	37.36	32.11	54.00	-21.89	Average
2 2390.00	36.95	26.03	6.47	37.36	32.09	54.00	-21.91	Average
3 2411.24	96.13	26.08	6.50	37.36	91.35	54.00	37.35	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2463.37	106.30	26.15	6.68	37.46	101.67	74.00	27.67	Peak
2 2483.50	66.30	26.18	6.80	37.51	61.77	74.00	-12.23	Peak
3 2484.15	66.15	26.18	6.80	37.51	61.62	74.00	-12.38	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2463.17	101.51	26.15	6.68	37.46	96.88	54.00	42.88	Average
2 2483.50	44.99	26.18	6.80	37.51	40.46	54.00	-13.54	Average
3 2484.25	43.22	26.18	6.80	37.51	38.69	54.00	-15.31	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2460.61	99.87	26.15	6.68	37.46	95.24	74.00	21.24	Peak
2 2483.50	55.25	26.18	6.80	37.51	50.72	74.00	-23.28	Peak
3 2484.15	55.28	26.18	6.80	37.51	50.75	74.00	-23.25	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.24	73.79	26.03	6.47	37.36	68.93	74.00	-5.07	Peak
2 2390.00	76.51	26.03	6.47	37.36	71.65	74.00	-2.35	Peak
3 2412.10	106.82	26.08	6.50	37.36	102.04	74.00	28.04	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor



Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.48	52.15	26.03	6.47	37.36	47.29	54.00	-6.71	Average
2 2390.00	53.53	26.03	6.47	37.36	48.67	54.00	-5.33	Average
3 2410.02	95.25	26.06	6.50	37.35	90.46	54.00	36.46	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.48	66.52	26.03	6.47	37.36	61.66	74.00	-12.34	Peak
2 2390.00	68.41	26.03	6.47	37.36	63.55	74.00	-10.45	Peak
3 2409.54	101.62	26.06	6.50	37.35	96.83	74.00	22.83	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.48	44.88	26.03	6.47	37.36	40.02	54.00	-13.98	Average
2 2390.00	46.12	26.03	6.47	37.36	41.26	54.00	-12.74	Average
3 2408.56	91.30	26.06	6.50	37.35	86.51	54.00	32.51	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2465.14	102.37	26.15	6.74	37.46	97.80	74.00	23.80	Peak
2 2483.50	76.50	26.18	6.80	37.51	71.97	74.00	-2.03	Peak
3 2483.75	76.37	26.18	6.80	37.51	71.84	74.00	-2.16	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2465.83	93.01	26.15	6.74	37.46	88.44	54.00	34.44	Average
2 2483.50	57.55	26.18	6.80	37.51	53.02	54.00	-0.98	Average
3 2484.15	55.81	26.18	6.80	37.51	51.28	54.00	-2.72	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2458.94	101.45	26.14	6.68	37.45	96.82	74.00	22.82	Peak
2 2483.50	61.64	26.18	6.80	37.51	57.11	74.00	-16.89	Peak
3 2483.75	61.40	26.18	6.80	37.51	56.87	74.00	-17.13	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz								
1 2459.23	90.18	26.14	6.68	37.45	85.55	54.00	31.55	Average
2 2483.50	40.29	26.18	6.80	37.51	35.76	54.00	-18.24	Average
3 2483.95	39.36	26.18	6.80	37.51	34.83	54.00	-19.17	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.24	76.05	26.03	6.47	37.36	71.19	74.00	-2.81	Peak
2 2390.00	77.17	26.03	6.47	37.36	72.31	74.00	-1.69	Peak
3 2409.78	105.04	26.06	6.50	37.35	100.25	74.00	26.25	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Over Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2388.76	52.63	26.03	6.47	37.36	47.77	54.00	-6.23	Average
2 2390.00	55.29	26.03	6.47	37.36	50.43	54.00	-3.57	Average
3 2410.51	94.44	26.06	6.50	37.35	89.65	54.00	35.65	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor



Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.12	68.56	26.03	6.47	37.36	63.70	74.00	-10.30	Peak
2 2390.00	71.28	26.03	6.47	37.36	66.42	74.00	-7.58	Peak
3 2409.78	101.26	26.06	6.50	37.35	96.47	74.00	22.47	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.24	45.25	26.03	6.47	37.36	40.39	54.00	-13.61	Average
2 2390.00	46.61	26.03	6.47	37.36	41.75	54.00	-12.25	Average
3 2408.32	90.39	26.06	6.50	37.35	85.60	54.00	31.60	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor



Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2463.76	99.60	26.15	6.68	37.46	94.97	74.00	20.97	Peak
2 2483.50	73.38	26.18	6.80	37.51	68.85	74.00	-5.15	Peak
3 2484.05	75.79	26.18	6.80	37.51	71.26	74.00	-2.74	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2465.73	89.54	26.15	6.74	37.46	84.97	54.00	30.97	Average
2 2483.50	56.07	26.18	6.80	37.51	51.54	54.00	-2.46	Average
3 2484.25	54.55	26.18	6.80	37.51	50.02	54.00	-3.98	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2457.56	100.23	26.14	6.68	37.45	95.60	74.00	21.60	Peak
2 2483.50	61.12	26.18	6.80	37.51	56.59	74.00	-17.41	Peak
3 2484.05	61.10	26.18	6.80	37.51	56.57	74.00	-17.43	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2459.43	89.53	26.14	6.68	37.45	84.90	54.00	30.90	Average
2 2483.50	41.27	26.18	6.80	37.51	36.74	54.00	-17.26	Average
3 2484.25	39.95	26.18	6.80	37.51	35.42	54.00	-18.58	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2381.21	77.39	26.02	6.45	37.36	72.50	74.00	-1.50	Peak
2 2390.00	75.87	26.03	6.47	37.36	71.01	74.00	-2.99	Peak
3 2427.90	102.45	26.10	6.56	37.39	97.72	74.00	23.72	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2389.07	57.08	26.03	6.47	37.36	52.22	54.00	-1.78	Average
2 2390.00	57.48	26.03	6.47	37.36	52.62	54.00	-1.38	Average
3 2429.76	88.35	26.10	6.56	37.39	83.62	54.00	29.62	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor



Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2388.09	71.24	26.03	6.47	37.36	66.38	74.00	-7.62	Peak
2 2390.00	70.18	26.03	6.47	37.36	65.32	74.00	-8.68	Peak
3 2407.98	97.30	26.06	6.50	37.35	92.51	74.00	18.51	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2388.65	49.78	26.03	6.47	37.36	44.92	54.00	-9.08	Average
2 2390.00	50.24	26.03	6.47	37.36	45.38	54.00	-8.62	Average
3 2406.99	85.89	26.06	6.50	37.35	81.10	54.00	27.10	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2461.95	97.89	26.15	6.68	37.46	93.26	74.00	19.26	Peak
2 2483.50	75.36	26.18	6.80	37.51	70.83	74.00	-3.17	Peak
3 2484.12	75.80	26.18	6.80	37.51	71.27	74.00	-2.73	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2459.58	83.39	26.14	6.68	37.45	78.76	54.00	24.76	Average
2 2483.50	56.27	26.18	6.80	37.51	51.74	54.00	-2.26	Average
3 2484.48	55.75	26.18	6.80	37.51	51.22	54.00	-2.78	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2459.22	99.65	26.14	6.68	37.45	95.02	74.00	21.02	Peak
2 2483.52	76.90	26.18	6.80	37.51	72.37	74.00	-1.63	Peak
3 2484.48	77.51	26.18	6.80	37.51	72.98	74.00	-1.02	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor



Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 2459.82	83.64	26.14	6.68	37.45	79.01	54.00	25.01	Average
2 2483.50	56.49	26.18	6.80	37.51	51.96	54.00	-2.04	Average
3 2484.72	55.79	26.18	6.80	37.51	51.26	54.00	-2.74	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



## 7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C      Humidity: 45 % RH      Atmospheric Pressure: 1010 mbar

Test mode      b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.7.2 Test Setup Diagram





### **7.7.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown



Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	39.32	6.40	45.72	54	-8.28	peak
7236	39.72	10.76	50.48	54	-3.52	peak
9648	33.91	14.37	48.28	54	-5.72	peak

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	41.56	6.40	47.96	54	-6.04	peak
7236	36.38	10.76	47.14	54	-6.86	peak
9648	32.59	14.37	46.96	54	-7.04	peak

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	41.20	6.92	48.12	54	-5.88	peak
7311	35.30	11.08	46.38	54	-7.62	peak
9748	31.50	14.36	45.86	54	-8.14	peak

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	43.20	6.92	50.12	54	-3.88	peak
7311	34.18	11.08	45.26	54	-8.74	peak
9748	31.74	14.36	46.10	54	-7.90	peak

Mode:b; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	40.37	7.31	47.68	54	-6.32	peak
7386	36.09	11.41	47.50	54	-6.50	peak
9848	31.73	14.38	46.11	54	-7.89	peak

Mode:b; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	41.42	7.31	48.73	54	-5.27	peak
7386	34.00	11.41	45.41	54	-8.59	peak
9848	31.50	14.38	45.88	54	-8.12	peak



Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	40.45	6.40	46.85	54	-7.15	peak
7236	39.90	10.76	50.66	54	-3.34	peak
9648	33.55	14.37	47.92	54	-6.08	peak

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	40.33	6.40	46.73	54	-7.27	peak
7236	36.07	10.76	46.83	54	-7.17	peak
9648	30.43	14.37	44.80	54	-9.20	peak

Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	40.36	6.92	47.28	54	-6.72	peak
7311	37.50	11.08	48.58	54	-5.42	peak
9748	36.99	14.36	51.35	54	-2.65	peak

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	41.23	6.92	48.15	54	-5.85	peak
7311	36.29	11.08	47.37	54	-6.63	peak
9748	32.10	14.36	46.46	54	-7.54	peak

Mode:b; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	38.03	7.31	45.34	54	-8.66	peak
7386	37.34	11.41	48.75	54	-5.25	peak
9848	32.23	14.38	46.61	54	-7.39	peak

Mode:b; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	40.86	7.31	48.17	54	-5.83	peak
7386	37.27	11.41	48.68	54	-5.32	peak
9848	35.84	14.38	50.22	54	-3.78	peak



Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	39.02	6.40	45.42	54	-8.58	peak
7236	39.36	10.76	50.12	54	-3.88	peak
9648	36.31	14.37	50.68	54	-3.32	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4824	41.77	6.40	48.17	54	-5.83	peak
7236	37.33	10.76	48.09	54	-5.91	peak
9648	32.75	14.37	47.12	54	-6.88	peak

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	41.37	6.92	48.29	54	-5.71	peak
7311	36.87	11.08	47.95	54	-6.05	peak
9748	35.60	14.36	49.96	54	-4.04	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	43.12	6.92	50.04	54	-3.96	peak
7311	37.92	11.08	49.00	54	-5.00	peak
9748	35.18	14.36	49.54	54	-4.46	peak

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	42.74	7.31	50.05	54	-3.95	peak
7386	38.16	11.41	49.57	54	-4.43	peak
9848	33.20	14.38	47.58	54	-6.42	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4924	41.30	7.31	48.61	54	-5.39	peak
7386	35.23	11.41	46.64	54	-7.36	peak
9848	36.95	14.38	51.33	54	-2.67	peak



Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4844	41.60	6.60	48.20	54	-5.80	peak
7266	38.52	10.89	49.41	54	-4.59	peak
9688	35.72	14.35	50.07	54	-3.93	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4844	41.47	6.60	48.07	54	-5.93	peak
7266	39.04	10.89	49.93	54	-4.07	peak
9688	30.39	14.35	44.74	54	-9.26	peak

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	43.36	6.92	50.28	54	-3.72	peak
7311	34.23	11.08	45.31	54	-8.69	peak
9748	32.64	14.36	47.00	54	-7.00	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4874	41.26	6.92	48.18	54	-5.82	peak
7311	36.69	11.08	47.77	54	-6.23	peak
9748	36.50	14.36	50.86	54	-3.14	peak

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4904	42.84	7.22	50.06	54	-3.94	peak
7356	34.71	11.28	45.99	54	-8.01	peak
9808	36.44	14.37	50.81	54	-3.19	peak

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4904	39.10	7.22	46.32	54	-7.68	peak
7356	34.21	11.28	45.49	54	-8.51	peak
9808	35.26	14.37	49.63	54	-4.37	peak



## 7.8 99% Bandwidth


Test Requirement RSS-Gen Section 6.6  
Test Method: ANSI C63.10 Section 6.9.3

### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C      Humidity: 50 % RH      Atmospheric Pressure: 1002 mbar  
Test mode b:Engineering Mode\_Use test software to control EUT working in continuous transmitting, and select channel and modulation type.

### 7.8.2 Test Setup Diagram



### 7.8.3 Measurement Procedure and Data

The detailed test data see: Appendix A SHEM180600474202



## 8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

## 9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos>.

**- End of the Report -**