

FCC Test Report

Applicant : TELEPHONE EST (HK) CO., LTD

Address : Room709,7F, FuLi tianhe commercial
building,Linhe East Road and tianhe district,
Guangzhou, China

Product Name : Magnetic 15W Wireless Charger

Report Date : Jun. 25, 2024



Shenzhen Anbotech Compliance Laboratory Limited

Shenzhen Anbotech Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotech.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotech.com.cn



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Modes	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
1.9. Disclaimer	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
3.4. Test Data	11
4. Radiation Spurious Emission	14
4.1. Test Standard and Limit	14
4.2. Test Setup	14
4.3. Test Procedure	15
4.4. Test Data	15
5. 20dB Occupy Bandwidth Test	20
5.1. Test Standard and Limit	20
5.2. Test Setup	20
5.3. Test Procedure	20
5.4. Test Data	20
6. Antenna Requirement	22
6.1. Test Standard and Requirement	22
6.2. Antenna Connected Construction	22
APPENDIX I -- TEST SETUP PHOTOGRAPH	23
APPENDIX II -- EXTERNAL PHOTOGRAPH	23
APPENDIX III -- INTERNAL PHOTOGRAPH	23



TEST REPORT

Applicant : TELEPHONE EST (HK) CO., LTD
Manufacturer : Telephone Est Electronics Factory (Zhong Shan)
Product Name : Magnetic 15W Wireless Charger
Test Model No. : XYS-MAG15WHT
Reference Model No. : TS-N2701
Trade Mark : N/A
Rating(s) : Input: DC 5V/2A, 9V/2A
Wireless charging output: 5W/7.5W/10W/15W

Test Standard(s) : 47 CFR Part 15 Subpart C

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

May 08, 2024

Date of Test

May 08 ~ Jun. 25, 2024

Prepared By

Nian Xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Edward Pan

(Edward Pan)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jun. 25, 2024



1. General Information

1.1. Client Information

Applicant	:	TELEPHONE EST (HK) CO., LTD
Address	:	Room709,7F, FuLi tianhe commercial building,Linhe East Road and tianhe district, Guangzhou, China
Manufacturer	:	Telephone Est Electronics Factory (Zhong Shan)
Address	:	No.2 Heyuan Shengfeng Road,Xiaolan Town, Zhongshan, China
Factory	:	Telephone Est Electronics Factory (Zhong Shan)
Address	:	No.2 Heyuan Shengfeng Road,Xiaolan Town, Zhongshan, China

1.2. Description of Device (EUT)

Product Name	:	Magnetic 15W Wireless Charger
Test Model No.	:	XYS-MAG15WHT
Reference Model No.	:	TS-N2701 (Note: All samples are the same except the model number and appearance color, so we prepare "XYS-MAG15WHT" for test only.)
Trade Mark	:	N/A
Test Power Supply	:	AC 120V, 60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A

RF Specification

Operation Frequency	:	112-205kHz
Modulation Type	:	FSK
Antenna Type	:	Inductive loop coil Antenna

Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Adapter	Model: MDY-13-ES Input: 100-240V~, 50/60Hz, 1.7A Output: 5V---3A/ 9V---3A/ 11V---6.1A Max 12V---2.25A/ 15V---3A/ 20V---3.25A Max
Mobile Phone	iPhone 12



1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Modes	Descriptions
Mode 1	WTP Mode (5W 1% Load)
Mode 2	WTP Mode (5W 50% Load)
Mode 3	WTP Mode (5W 99% Load)
Mode 4	WTP Mode (7.5W 1% Load)
Mode 5	WTP Mode (7.5W 50% Load)
Mode 6	WTP Mode (7.5W 99% Load)
Mode 7	WTP Mode (10W 1% Load)
Mode 8	WTP Mode (10W 50% Load)
Mode 9	WTP Mode (10W 99% Load)
Mode 10	WTP Mode (15W 1% Load)
Mode 11	WTP Mode (15W 50% Load)
Mode 12	WTP Mode (15W 99% Load)
Mode 13	Standby Mode



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Jan. 18, 2024	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	Jan. 17, 2024	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jan. 17, 2024	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 23, 2024	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 12, 2023	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	Jan. 17, 2024	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 12, 2023	1 Year
10.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 12, 2023	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 17, 2024	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 12, 2023	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 12, 2023	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 12, 2023	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 20, 2023	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 16, 2023	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	May. 26, 2023	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission Test	PASS
15.205/15.209	Spurious Emission	PASS
15.215(c)	20dB Occupied Bandwidth	PASS




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

PASS


During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 12
Test Specification: AC 120V, 60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 23.5°C/57%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	1.2740	27.15	17.86	45.01	56.00	-10.99	QP	
2	1.6580	25.57	17.85	43.42	56.00	-12.58	QP	
3	2.0420	26.23	17.85	44.08	56.00	-11.92	QP	
4	2.0420	22.83	17.85	40.68	46.00	-5.32	AVG	
5	2.4219	24.95	17.85	42.80	56.00	-13.20	QP	
6	2.4219	23.02	17.85	40.87	46.00	-5.13	AVG	
7	2.8060	25.32	17.85	43.17	56.00	-12.83	QP	
8	2.8060	22.78	17.85	40.63	46.00	-5.37	AVG	
9	2.9340	22.34	17.85	40.19	46.00	-5.81	AVG	
10	3.5700	24.81	17.86	42.67	56.00	-13.33	QP	
11	3.5700	22.51	17.86	40.37	46.00	-5.63	AVG	
12	4.7180	23.27	17.86	41.13	46.00	-4.87	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 12
Test Specification: AC 120V, 60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 23.5°C/57%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	1.6580	26.26	17.85	44.11	56.00	-11.89	QP	
2	1.9140	26.03	17.85	43.88	56.00	-12.12	QP	
3	2.0420	26.87	17.85	44.72	56.00	-11.28	QP	
4	2.0420	23.76	17.85	41.61	46.00	-4.39	AVG	
5	2.4219	23.56	17.85	41.41	46.00	-4.59	AVG	
6	2.6780	25.90	17.85	43.75	56.00	-12.25	QP	
7	2.6780	23.76	17.85	41.61	46.00	-4.39	AVG	
8	2.8060	26.01	17.85	43.86	56.00	-12.14	QP	
9	3.0620	26.14	17.85	43.99	56.00	-12.01	QP	
10	3.0620	24.54	17.85	42.39	46.00	-3.61	AVG	
11	3.4420	23.93	17.85	41.78	46.00	-4.22	AVG	
12	3.8260	23.92	17.86	41.78	46.00	-4.22	AVG	



4. Radiation Spurious Emission

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.




Report No.: 18220WC40093401

FCC ID: 2ACE5-XYSMAG

Page 16 of 23

Test Results (Between 9KHz – 150KHz)

Test Mode: Mode 12
Distance: 3m
Power Source: AC 120V, 60Hz for Adapter
Temp.(°C)/Hum.(%RH): 23.5°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.0146	-5.49	20.25	14.76	124.13	-109.37	QP			
2	0.0240	-2.62	20.38	17.76	119.84	-102.08	QP			
3	0.0320	-1.45	20.56	19.11	117.36	-98.25	QP			
4	0.0350	0.71	20.49	21.20	116.58	-95.38	QP			
5	0.1000	-12.98	20.29	7.31	107.52	-100.21	QP			
6	0.1170	16.31	20.32	36.63	106.16	-69.53	QP			



Report No.: 18220WC40093401

FCC ID: 2ACE5-XYSMAG

Page 17 of 23


Test Results (Between 0.15MHz – 30MHz)

Test Mode: Mode 12

Distance: 3m

Power Source: AC 120V, 60Hz for Adapter

Temp.(°C)/Hum.(%RH): 23.5°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.3577	3.19	20.28	23.47	96.52	-73.05	QP			
2	1.2892	-0.64	20.26	19.62	65.42	-45.80	QP			
3	2.1213	-6.83	20.28	13.45	69.50	-56.05	QP			
4	3.4174	-10.41	20.33	9.92	69.50	-59.58	QP			
5	11.3170	-12.37	20.53	8.16	69.50	-61.34	QP			
6	16.5732	-9.58	20.55	10.97	69.50	-58.53	QP			

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.




Report No.: 18220WC40093401

FCC ID: 2ACE5-XYSMAG

Page 18 of 23

Test Results (Between 30MHz –1000 MHz)

Test Mode: Mode 12
Distance: 3m
Power Source: AC 120V, 60Hz for Adapter
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 20.3°C/46%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	55.0274	43.97	-17.63	26.34	40.00	-13.66	QP			
2	79.5209	50.52	-23.23	27.29	40.00	-12.71	QP			
3	91.1746	48.33	-22.30	26.03	40.00	-13.97	QP			
4	191.0738	57.73	-22.71	35.02	40.00	-4.98	QP			
5	263.8190	51.25	-20.30	30.95	47.00	-16.05	QP			
6	303.5437	45.58	-17.08	28.50	47.00	-18.50	QP			




Report No.: 18220WC40093401

FCC ID: 2ACE5-XYSMAG

Page 19 of 23

Test Results (Between 30MHz –1000 MHz)

Test Mode: Mode 12
Distance: 3m
Power Source: AC 120V, 60Hz for Adapter
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 20.3°C/46%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	47.8260	44.36	-15.45	28.91	40.00	-11.09	QP			
2	80.9275	52.76	-19.17	33.59	40.00	-6.41	QP			
3	128.5630	50.64	-21.25	29.39	40.00	-10.61	QP			
4	163.7550	51.11	-21.46	29.65	40.00	-10.35	QP			
5	263.8190	44.36	-17.47	26.89	47.00	-20.11	QP			
6	948.7610	33.38	-5.65	27.73	47.00	-19.27	QP			




5. 20dB Occupy Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.215(c)
Test Limit	N/A

5.2. Test Setup



5.3. Test Procedure


The bandwidth of the fundamental frequency was measured by spectrum analyzer with $RBW=1\%-5\%OBW$, $VBW\geq 3*RBW$. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.4. Test Data

Test Item	:	20dB Bandwidth	Test Mode	:	Continuously transmitting
Test Voltage	:	AC 120V, 60Hz for Adapter	Temperature	:	24.3℃
Test Result	:	PASS	Humidity	:	48%RH



Freq. (MHz)	Bandwidth (kHz)	Results
0.1257	1.272	PASS



6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

