# FCC PART 15.249

# EMI MEASUREMENT AND TEST REPORT

For

# Vina International Holdings Limited

1st,No.26 East Chang Long RD,FuChengAo,Pinghu Town, LongGang District, ShenZhen, China

**FCC ID: 2ACE8MS-319** 

May 16, 2014

This Report Concerns: **Equipment Type:** bluetooth speaker **Original Report** Lisa Chan Test Engineer: Lisa Chen Report No.: BSL13071011Y-1E4-15 May 12,2014 / Receive EUT May 12 - May 16, 2014 Date/Test Date: Stey Homa Reviewed By: Sky Zhang **BSL Testing Co.,LTD.** NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Prepared By: Tel: 86-755-26508703

**Note:** The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of BSL Testing Co.,LTD. This report must not be used by the client to claim product certification,approval,or endorsement by NVLAP, NIST or any agency of the US Government.

Fax: 86-755-26508703

# **TABLE OF CONTENTS**

1.	GENI	ERAL INFORMATION	3
	1.1.	Report information	3
	1.2.	Measurement Uncertainty	3
2.	PROI	DUCT DESCRIPTION	4
	2.1.	EUT Description	4
	2.2.	Block Diagram of EUT Configuration	
	2.3.	Support Equipment List	
	2.4.	Test Conditions	5
<b>3.</b>	TEST	RESULTS SUMMARY	6
	Modif	fications	6
4.	TEST	EQUIPMENT USED	7
5.	ANTI	ENNA REQUIREMENT	8
	5.1.	Standard Applicable	8
	5.2.	Antenna Connected Construction	
	5.3.	Result	8
6.	CON	DUCTED POWER LINE TEST	9
	6.1.	Test Equipment	9
	6.2.	Test Procedure	9
	6.3.	Test Setup	
	6.4.	Conducted Power line Emission Limits	
	6.5.	Conducted Power Line Test Result	0
7.	RAD]	IATED EMISSION TEST1	2
	7.1.	Test Equipment	2
	7.2.	Test Procedure1	2
	7.3.	Radiated Test Setup1	
	7.4.	Radiated Emission Limit	
	7.5.	Radiated Emission Test Result	
8.	BANI	D EDGE	
	8.1.	Test Equipment	
	8.2.	Test Procedure	
	8.3.	Band Edge FCC 15.249(d) Limit	
	8.4.	Band Edge Test Result	
9.	20-DI	3 BANDWIDTH2	2
	9.1.	Test Equipment	
	9.2.	Test Procedure	
	9.3.	Limit	
	9.4.	Test Result /Plots	.2

#### 1. GENERAL INFORMATION

#### 1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BSL approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BSL in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BSL therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3.Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BSL, unless the applicant has authorized BSL in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of

BSL Testing Co.,LTD.

(FCC Registered Test Site Number: 191509) on

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

The Test Site is constructed and calibrated to meet the FCC requirements.

#### 1.2. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	+/-1.25dB
2	RF Power, Conducted	+/-0.20dB
3	Spurious emissions, conducted	+/-0.33dB
4	All emissions, radiated (<1G)	+/-3.47dB
5	All emissions, radiated (>1G)	+/-3.82dB
6	Temperature	+/-0.5°CdB
7	Humidity	+/-2%

BSL13071011Y-1E4-15 Page 3/25

# 2. PRODUCT DESCRIPTION

# 2.1. EUT Description

Description : bluetooth speaker

Applicant : Vina International Holdings Limited

1st,No.26 East Chang Long RD,FuChengAo,Pinghu Town,

LongGang District, ShenZhen, China

Manufacturer : Vina International Holdings Limited

1st,No.26 East Chang Long RD,FuChengAo,Pinghu Town,

LongGang District, ShenZhen, China

Model Number : MS-319
Modulation type : GFSK
Antenna gain : 0dBi

Frequency : 2402-2480MHz Number of Channels : 79 Channels

Bluetooth version : 2.1

Power Supply : Transmitting:DC 3.7V By battery (The fully charged battery is used during the

measurement) charging: DC 5V By Adapter

		Chann	el List	Channel List									
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)								
00	2402	27	2429	54	2456								
01	2403	28	2430	55	2457								
02	2404	29	2431	56	2458								
03	2405	30	2432	57	2459								
04	2406	31	2433	58	2460								
05	2407	32	2434	59	2461								
06	2408	33	2435	60	2462								
07	2409	34	2436	61	2463								
08	2410	35	2437	62	2464								
09	2411	36	2438	63	2465								
10	2412	37	2439	64	2466								
11	2413	38	2440	65	2467								
12	2414	39	2441	66	2468								
13	2415	40	2442	67	2469								
14	2416	41	2443	68	2470								
15	2417	42	2444	69	2471								
16	2418	43	2445	70	2472								
17	2419	44	2446	71	2473								
18	2420	45	2447	72	2474								
19	2421	46	2448	73	2475								
20	2422	47	2449	74	2476								
21	2423	48	2450	75	2477								
22	2424	49	2451	76	2478								
23	2425	50	2452	77	2479								
24	2426	51	2453	78	2480								
25	2427	52	2454										
26	2428	53	2455										

BSL13071011Y-1E4-15 Page 4/25

# 2.2. Block Diagram of EUT Configuration

# **Radiated emissions test**

EUT

# **Conducted Emission test**




Figure 1 EUT Setup

# 2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used (Y/N)	
Adapter	CYSK05-050100	N/A	Yu Long	Y	

# 2.4. Test Conditions

Items	Required (IEC 68-1)	Actual
Temperature (℃)	15-35	20-25
Humidity (%RH)	25-75	50-63
Barometric pressure (mbar)	860-1060	950-1000

BSL13071011Y-1E4-15 Page 5/25

# 3. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249:2013

FCC Rules	<b>Description of Test</b>	Result
Section 15.207	Conducted Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant
Section 15.249	20dB Bandwidth	Compliant

Remark: "N/A" means "Not applicable".

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

## **Modifications**

No modification was made.

BSL13071011Y-1E4-15 Page 6/25

# 4. TEST EQUIPMENT USED

EQUIPMENT/FACIL ITIES	MANUFACTURE R	MODEL	SERIAL NO.	DATE OF CAL.	CAL. INTERV AL
3m Semi-Anechoic	Chengyu Electron	9 (L)*6	BSL086	Aug. 23 2013	1 Year
Chamber		(W)* 6 (H)			
EMI Test Receiver	Rohde & Schwarz	ESCI3	BSL001	Sep. 28 2013	1 Year
BiConiLog Antenna	Rohde & Schwarz	HL562	BSL009	Sep. 28 2013	1 Year
Double -ridged waveguide horn	Rohde & Schwarz	9120D	BSL008	Aug. 27 2013	1 Year
Horn Antenna	ETS-LINDGREN	3160	BSL072	Dec. 28 2013	1 Year
Cable	Rohde & Schwarz	N/A	BSL045	Aug. 27 2013	1 Year
Cable	Rohde & Schwarz	N/A	BSL046	Aug. 27 2013	1 Year
Cable	Rohde & Schwarz	N/A	BSL047	Aug. 27 2013	1 Year
Amplifier(100kHz-40G Hz)	R&S	SMR40	BSL007	Sep. 28 2013	1 Year
Band filter	Amindeon	82346	BSL049	Aug. 27 2013	1 Year
Active Loop Antenna	EMTES	EM15	BSL011	Sep. 28 2013	1 Year
Coaxial Switch	YUANFANG	TA218B	BSL004	Aug. 27 2013	1 Year
Spectrum analyzer	Rohde & Schwarz	FSP40	BSL049	Sep. 28 2013	1 Year
Shielding Room	zhongyu Electron	7.0(L)x3.0( W)x3.0(H)	BSL085	Sep. 28 2013	1 Year
EMI Test Receiver	R&S	ESPI	BSL002	Sep. 28 2013	1 Year
10dB Pulse Limita	R&S	N/A	BSL003	Sep. 28 2013	1 Year
Coaxial Switch	YUANFANG	TA218B	BSL004	Aug. 27 2013	1 Year
LISN	Rohde & Schwarz	ESH3-Y5	BSL005	Sep. 28 2013	1 Year
Coaxial Cable	YUANFANG	N/A	BSL048	Aug. 27 2013	1 Year
EMI TEST SOFTWARE	AUDIX	E3	N/A	N/A	N/A

BSL13071011Y-1E4-15 Page 7/25

# 5. ANTENNA REQUIREMENT

## 5.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 5.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is PCB antenna. The antenna is permanently attached. Refer to the product photo.

#### 5.3. Result

Compliance

BSL13071011Y-1E4-15 Page 8/25

#### 6. CONDUCTED POWER LINE TEST

#### **6.1. Test Equipment**


Please refer to section 4 this report.

#### **6.2. Test Procedure**

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uh coupling inpedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling inpedance with 50ohm termination.

Both sides of A.C. Line are check for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement. Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

### 6.3. Test Setup



For the actual test configuration, Please refer to the related items-Photos of testing

#### **6.4. Conducted Power line Emission Limits**

FCC Part 15 Paragraph 15.207 (dBuV)					
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV			
0.15-0.5	79/66	65-56/56-46			
0.5-5.0	73/60	56-46			
5.0-3.0	73/60	60-50			


**Note:** In the above table, the tighter limit applies at the band edges.

BSL13071011Y-1E4-15 Page 9/25


#### 6.5. Conducted Power Line Test Result

**PASS** 

## Link Mode



BSL13071011Y-1E4-15 Page 10/25



BSL13071011Y-1E4-15 Page 11/25

#### 7. RADIATED EMISSION TEST

#### 7.1. Test Equipment

Please refer to section 4 this report.

#### 7.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit. And X direction is worst mode


#### 7.3. Radiated Test Setup

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz




BSL13071011Y-1E4-15 Page 12/25

## (B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



#### (C) Radiated Emission Test Set-Up, Frequency above 1000MHz



BSL13071011Y-1E4-15 Page 13/25

#### 7.4. Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

A. Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency	Field as treng	th of Fundamental(3	3m)	Field as trength of Harmonics(3m)		
(MHZ)	mV/m	dBuV/m		uV/m	dBuV/m	
902-928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400-2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

- (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (3) The emission limit in this paragraph os based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

B. Spurious Radiated Emissions.

	Limit							
Frequency (MHz)	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dBµV/m)	Measurement distance (m)	The final measurement in band 9-90kHz,				
0.009 - 0.490	2400/F(kHz)	/	300	110-490kHz and above 1000MHz is				
0.490 - 1.705	24000/F(kHz)	/	30	performed with				
1.705-30	30	29.5	30	Average detector. Except those				
30 - 88	100	40	3	frequency bands mention above, the				
88 - 216	150	43.5	3	final measurement for frequencies				
216 - 960	200	46	3	below 1000MHz is				
Above 960	500	54	3	performed with Quasi Peak detector.				

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

- (2) In the Above Table, the tighter limit applies at the band edges.
- (3) Distagnce refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

BSL13071011Y-1E4-15 Page 14/25

# 7.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2402	74.94/90.38	27.47	5.42	30.17	77.66/93.1	VERT	94/114	-16.34/-20.9
2402	77.09/99.86	27.47	5.42	30.17	79.81/102.58	HORIZ	94/114	-14.19/-11.42

#### CH Middle

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2441	74.84/95.58	27.40	5.40	30.15	77.49/98.23	VERT	94/114	-16.51/-15.77
2441	76.67/101.89	27.40	5.40	30.15	79.32/104.54	HORIZ	94/114	-14.68/-9.46

#### CH High

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2480	71.53/95.3	27.50	5.46	29.98	74.51/98.28	VERT	94/114	-19.49/-15.72
2480	72.68/100.11	27.50	5.46	29.98	75.66/103.09	HORIZ	94/114	-18.34/-10.91

#### Remark:

 $Final\ Emission = Receiver\ Read\ level + Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$ 

BSL13071011Y-1E4-15 Page 15/25

#### B. General Radiated Emissions Data

## For below 9kHz-30MHz Spurious

Freq. (MHz)	Emission(dBuV/m) PK / AV	Limits(dBuV/m) PK / AV	Margin (dB)
-	-	-	-
-	-	-	-


1	Emissions	attenuated	more than	20 dR	helow the	permissible	value are no	ot reported

BSL13071011Y-1E4-15 Page 16/25

## For 30M-1000MHz Spurious

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

# 2441MHz Transmitting(Worst case mode)




Condition : FCC15 CLASS-B 3m HORIZONTAL

: RBW:120.000KHz VBW:300.000KHz SWT:Auto

	Freq	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	31.95	29.37	40.00	-10.63	QP	HORIZONTAL
2 max	40.13	32, 66	40.00	-7.34	QP	HORIZONTAL
3	148.44	32.64	43.50	-10.86	QP	HORIZONTAL
4	245.09	32.09	46.00	-13.91	QP	HORIZONTAL
5	336.04	27.52	46.00	-18.48	QP	HORIZONTAL
6	938.83	37.44	46.00	-8.56	QP	HORIZONTAL

BSL13071011Y-1E4-15 Page 17/25



Site

Site :
Condition : FCC15 CLASS-B 3m VERTICAL
: RBW:120.000KHz VBW:300.000KHz SWT:Auto

	. NOVI.120.000N12 VDVV.300.000N12 3VV1.Auto					
				Over		
	Freq	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dВ		
1 max	30, 32	36, 58	4U. UU	-3, 42	ŲP	VERTICAL
2	40.13	33.13	40.00	-6.87	QP	VERTICAL
3	66.73	31.50	40.00	-8.50	QP	VERTICAL
4 5	129.92	27.98	43.50	-15.52	QP	VERTICAL
5	252.95	27.66	46.00	-18.34	QP	VERTICAL
6	833.32	41.16	46.00	-4.84	QP	VERTICAL

BSL13071011Y-1E4-15 Page 18/25

## For 1000MHz-25000MHz Spurious

#### CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4804	35.66/51.38		54.0/74.0	-18.34/-22.62
7206	35.95/49.92	VERT	54.0/74.0	-18.05/-24.08
9608	35.11/49.39		54.0/74.0	-18.89/-24.61
4804	37.05/52.44		54.0/74.0	-16.95/-21.56
7206	36.21/51.49	HORIZ	54.0/74.0	-17.79/-22.51
9608	36.08/51.34		54.0/74.0	-17.92/-22.66

#### CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4882	38.06/50.49		54.0/74.0	-15.94/-23.51
7323	36.55/50.33	VERT	54.0/74.0	-17.45/-23.67
9764	36.95/51.36		54.0/74.0	-17.05/-22.64
4882	38.36/52.55		54.0/74.0	-15.64/-21.45
7323	37.68/51.42	HORIZ	54.0/74.0	-16.32/-22.58
9764	37.06/51		54.0/74.0	-16.94/-23

## CH High

ngn				
Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4960	36.56/52.22		54.0/74.0	-17.44/-21.78
7440	36.11/51.56	VERT	54.0/74.0	-17.89/-22.44
9920	36.39/50.91		54.0/74.0	-17.61/-23.09
4960	39.57/52.7		54.0/74.0	-14.43/-21.3
7440	38.38/52.02	HORIZ	54.0/74.0	-15.62/-21.98
9920	37.72/51.33		54.0/74.0	-16.28/-22.67

#### Note:

- 1. The average measurement was not performed when the peak measured data under the limit of average detection.
- 2. Emissions attenuated more than 20 dB below the permissible value are not reported.

BSL13071011Y-1E4-15 Page 19/25

## 8. BAND EDGE

## 8.1. Test Equipment

Please refer to Section 4 this report.

#### 8.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

## 8.3. Band Edge FCC 15.249(d) Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the specified frequency bands.	vel
of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.	

BSL13071011Y-1E4-15 Page 20/25

# 8.4. Band Edge Test Result

#### **Pass**

ALL of the restriction bands were tested, and only the data of worst case was exhibited.

#### CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2390	38.86/48.58		54.0/74.0	-15.14/-25.42
2400	49.15/65.12	VERT	54.0/74.0	-4.85/-8.88
2390	37.25/45.64		54.0/74.0	-16.75/-28.36
2400	48.41/64.69	HORIZ	54.0/74.0	-5.59/-9.31

CH High

1511				
Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2483.5	43.76/52.42		54.0/74.0	-10.24/-21.58
2500.00	39.31/51.76	VERT	54.0/74.0	-14.69/-22.24
2483.5	42.77/51.9		54.0/74.0	-11.23/-22.1
2500.00	38.58/50.22	HORIZ	54.0/74.0	-15.42/-23.78

#### Remark:

 $1.\ Factor = Antenna\ Factor + Cable\ Loss - Pre-amplifier.$ 

BSL13071011Y-1E4-15 Page 21/25

# 9. 20-DB BANDWIDTH

# 9.1. Test Equipment

Please refer to Section 4 this report.

#### 9.2. Test Procedure

- $1. \ Remove \ the \ antenna \ from \ the \ EUT \ and \ then \ connect \ a \ low \ loss \ RF \ cable \ from \ the \ antenna \ port \ to \ the \ spectrum \ analyzer.$
- 2. Set center frequency of spectrum analyzer = operating frequency.
- 3. The spectrum analyzer as RBW=30 KHz, VBW=100 KHz, Sweep=auto
- 4. Mark the peak frequency and -20 dB (upper and lower) frequency.


#### **9.3.** Limit

Please refer section 15.249


## 9.4. Test Result /Plots

Limit	Channel Frequency (MHz)	20dB Bandwidth (MHz)
/	2402	0.800
/	2441	0.796
/	2480	0.800


BSL13071011Y-1E4-15 Page 22/25



BSL13071011Y-1E4-15 Page 23/25



BSL13071011Y-1E4-15 Page 24/25



# **End Of The Report**

BSL13071011Y-1E4-15 Page 25/25