



The University of Michigan Radiation Laboratory
3228 EECS Building
Ann Arbor, Michigan 48109-2122 USA
Tel: (734) 483-4211
Fax: (734) 647-2106
e-mail: liepa@umich.edu

Testing of
Electromagnetic Emissions
per

USA: CFR Title 47, Part 15.231
Canada: IC RSS-210/GNe


are herein reported for

Apollo America, Inc.
51000-355


Test Report No.: 417124-150120-01
Copyright © 2015

Applicant/Provider:
Apollo America, Inc.
25 Corporate Drive, Auburn Hills Michigan 48326 USA
Phone: (248) 332-3900, Fax: 248) 332-8807
Contact Person: Andrew Frost; andrew.frost@apollo-fire.com


Measured by:


Valdis V. Liepa, Ph.D.

Report Approved by:


Valdis V. Liepa, Ph.D.

Report by:


Valdis V. Liepa, Ph.D.

Report Date of Issue:

January 20, 2015

Results of testing completed on (or before) December 16, 2014 are as follows.

Emissions: The transmitter intentional emissions **COMPLY** with the regulatory limit(s) by no less than 5.5 dB. Transmit chain spurious harmonic emissions **COMPLY** by no less than 3.3 dB.

Contents

1 Test Specifications, General Procedures, and Location	4
1.1 Test Specification and General Procedures	4
1.2 Test Location and Equipment Used	5
2 Configuration and Identification of the Equipment Under Test	6
2.1 Description and Declarations	6
2.1.1 EUT Configuration	6
2.1.2 Modes of Operation	6
2.1.3 Variants	7
2.1.4 Test Samples	7
2.1.5 Functional Exerciser	7
2.1.6 Modifications Made	7
2.1.7 Production Intent	7
2.1.8 Declared Exemptions and Additional Product Notes	7
3 Emissions	8
3.1 General Test Procedures	8
3.1.1 Radiated Test Setup and Procedures	8
3.1.2 Conducted Emissions Test Setup and Procedures	11
3.1.3 Power Supply Variation	11
3.2 Intentional Emissions	12
3.2.1 Fundamental Emission Pulsed Operation	12
3.2.2 Fundamental Emission Bandwidth	14
3.2.3 Fundamental Emission	15
3.3 Unintentional Emissions	16
3.3.1 Transmit Chain Spurious Emissions	16

List of Tables

1	The University of Michigan Radiation Laboratory Equipment List.	5
2	EUT Declarations.	6
3	Pulsed Emission Characteristics (Duty Cycle).	12
4	Intentional Emission Bandwidth.	14
5	Fundamental Radiated Emissions.	15
6	Transmit Chain Spurious Emissions.	16

List of Figures

1	Photos of EUT.	6
2	EUT Test Configuration Diagram.	7
3	Radiated Emissions Diagram of the EUT.	8
4	Radiated Emissions Test Setup Photograph(s).	10
5	Pulsed Emission Characteristics (Duty Cycle).	13
5	Pulsed Emission Characteristics (Duty Cycle).	13
6	Intentional Emission Bandwidth.	14

1 Test Specifications, General Procedures, and Location

1.1 Test Specification and General Procedures

The ultimate goal of Apollo America, Inc. is to demonstrate that the Equipment Under Test (EUT) complies with the Rules and/or Directives below. Detailed in this report are the results of testing the Apollo America, Inc. 51000-355 for compliance to:

Country/Region	Rules or Directive	Referenced Section(s)
United States	Code of Federal Regulations	CFR Title 47, Part 15.231
Canada	Industry Canada	IC RSS-210/GENe

Apollo America, Inc. has determined that the equipment under test is subject to the rules and directives above at the date of this testing. In conjunction with these rules and directives, the following specifications and procedures are followed herein to demonstrate compliance (in whole or in part) with these regulations.

ANSI C63.4-2009 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"
Industry Canada "The Measurement of Occupied Bandwidth"

1.2 Test Location and Equipment Used

Test Location The EUT was fully tested by **The University of Michigan Radiation Laboratory**, 3228 EECS Building, Ann Arbor, Michigan 48109-2122 USA. The Test Facility description and attenuation characteristics are on file with the FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057A-1).

Test Equipment Pertinent test equipment used for measurements at this facility is listed in Table 1. The quality system employed at The University of Michigan Radiation Laboratory has been established to ensure all equipment has a clearly identifiable classification, calibration expiry date, and that all calibrations are traceable to the SI through NIST, other recognized national laboratories, accepted fundamental or natural physical constants, ratio type of calibration, or by comparison to consensus standards.

Table 1: The University of Michigan Radiation Laboratory Equipment List.

Test Instrument	Manufacturer/Model	Q Number
Spectrum Analyzer (9kHz-26GHz)	Hewlett-Packard 8593E, SN: 3412A01131	HP8593E1
Spectrum Analyzer (10Hz-2.9GHz)	Hewlett-Packard 8593E, SN: 3412A01131	HP8560E1
Power Meter	Hewlett-Packard, 432A	HP432A1
Harmonic Mixer (26-40 GHz)	Hewlett-Packard 11970A, SN: 3003A08327	HP11970A1
Harmonic Mixer (40-60 GHz)	Hewlett-Packard 11970U, SN: 2332A00500	HP11970U1
Harmonic Mixer (75-110 GHz)	Hewlett-Packard 11970W, SN: 2521A00179	HP11970W1
Harmonic Mixer (140-220 GHz)	Pacific Millimeter Prod., GMA, SN: 26	PMPGMA1
S-Band Std. Gain Horn	S/A, Model SGH-2.6	SBAND1
C-Band Std. Gain Horn	University of Michigan, NRL design	CBAND1
XN-Band Std. Gain Horn	University of Michigan, NRL design	XNBAND1
X-Band Std. Gain Horn	S/A, Model 12-8.2	XBAND1
X-band horn (8.2- 12.4 GHz)	Narda 640	XBAND2
X-band horn (8.2- 12.4 GHz)	Scientific Atlanta , 12-8.2, SN: 730	XBAND3
K-band horn (18-26.5 GHz)	FXR, Inc., K638KF	KBAND1
Ka-band horn (26.5-40 GHz)	FXR, Inc., U638A	KABAND1
U-band horn (40-60 GHz)	Custom Microwave, HO19	UBAND1
W-band horn(75-110 GHz)	Custom Microwave, HO10	WBAND1
G-band horn (140-220 GHz)	Custom Microwave, HO5R	GBAND1
Bicone Antenna (30-250 MHz)	University of Michigan, RLBC-1	LBBIC1
Bicone Antenna (200-1000 MHz)	University of Michigan, RLBC-2	HBBIC1
Dipole Antenna Set (30-1000 MHz)	University of Michigan, RLDP-1,-2,-3	UMDIP1
Dipole Antenna Set (30-1000 MHz)	EMCO 3121C, SN: 992 (Ref. Antennas)	EMDIP1
Active Rod Antenna (30 Hz-50 MHz)	EMCO 3301B, SN: 3223	EMROD1
Active Loop Antenna (30 Hz-50 MHz)	EMCO 6502, SN:2855	EMLOOP1
Ridge-horn Antenna (300-5000 MHz)	University of Michigan	UMRH1
Magnetic Field Strength Probe	HP 11941A	HPMFSP1
Electric Field Strength Probe	EG&G ACD-4A(R)	EGGACD41
Amplifier (5-1000 MHz)	Avantek, A11-1, A25-1S	AVAMP1
Amplifier (5-4500 MHz)	Avantek	AVAMP2
Amplifier (4.5-13 GHz)	Avantek, AFT-12665	AVAMP3
Amplifier (6-16 GHz)	Trek	TRAMP1
Amplifier (16-26 GHz)	Avantek	AVAMP4
LISN Box	University of Michigan	UMLISN1
Signal Generator	Hewlett-Packard 8657B	HPSG1

2 Configuration and Identification of the Equipment Under Test

2.1 Description and Declarations

The EUT is a wireless smoke alarm. The EUT is approximately 16 x 16 x 4 cm in dimension, and is depicted in Figure 1. It is powered by a 3 x 1.5 VDC alkaline "AA" batteries. In use, this device is affixed in a residential setting. Table 2 outlines provider declared EUT specifications.



Figure 1: Photos of EUT.

Table 2: EUT Declarations.

General Declarations			
Equipment Type:	Wireless Smoke Alarm	Country of Origin:	USA
Nominal Supply:	3 x 1.5 VDC	Oper. Temp Range:	Not Declared
Frequency Range:	345.0 MHz	Antenna Dimension:	8 x 2 x 0.3 cm
Antenna Type:	PCB trace	Antenna Gain:	Not Declared (integral)
Number of Channels:	1	Channel Spacing:	Not Applicable
Alignment Range:	345.0 MHz	Type of Modulation:	ASK
United States			
FCC ID Number:	2ACE9-51000355A	Classification:	DSC
Canada			
IC Number:	12011A-51000355A	Classification:	Security Device / Alarm System, Remote Control Device

2.1.1 EUT Configuration

The EUT is configured for testing as depicted in Figure 2.

2.1.2 Modes of Operation

The EUT is capable of three key modes of operation: MANUAL mode, ALARM mode, and HEARTBEAT mode. In MANUAL mode the EUT transmits three packets of 6 frames when the batteries are first inserted, and two packets of 6 frames when the unit is attached to its mounting plate (via depression of a built-in switch). In HEARTBEAT mode (non-emergency system integrity mode) the EUT transmits a single packet of 6 frames approximately once every 65 minutes to ensure safety system integrity. In ALARM mode, the EUT transmits two packets of 6 frames approximately every 5 seconds during the alarm state.



Figure 2: EUT Test Configuration Diagram.

2.1.3 Variants

There is only a single variant of the EUT, as tested.

2.1.4 Test Samples

Two samples in total were provided. One normal sample capable of MANUAL, ALARM, and HEARTBEAT modes, and a second sample to take apart for photos.

2.1.5 Functional Exerciser

Normal operating EUT functionality was verified by observation of transmitted signal.

2.1.6 Modifications Made

There were no modifications made to the EUT by this laboratory.

2.1.7 Production Intent

The EUT appears to be a production ready sample.

2.1.8 Declared Exemptions and Additional Product Notes

The EUT employs some modes of operation that alert the user in the event of an emergency. Such alert modes fall under FCC 15.231(a)(4), and may operate during the pendency of the alarm condition. The EUT employs some modes of operation that are system integrity modes. Such alert modes fall under FCC 15.231(a)(3).

3 Emissions

3.1 General Test Procedures

3.1.1 Radiated Test Setup and Procedures

Radiated electromagnetic emissions from the EUT are first evaluated in our shielded fully anechoic chamber. Spectrum and modulation characteristics of all emissions are recorded, and emissions above 1 GHz are fully characterized. The anechoic chamber contains a set-up similar to that of our outdoor 3-meter site, with a turntable and antenna mast. Instrumentation, including spectrum analyzers and other test equipment as detailed in Section 1.2 are employed. After indoor pre-scans, emission measurements are made on our outdoor 3-meter Open Area Test Site (OATS). If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.4 / CISPR-22 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed if the resulting emissions appear to be worst-case in such a configuration. See Figure 3. All




Figure 3: Radiated Emissions Diagram of the EUT.

intentionally radiating elements that are not fixed-mounted in use are placed on the test table lying flat, on their side, and on their end (3-axes) and the resulting worst case emissions are recorded. If the EUT is fixed-mounted in use, measurements are made with the device oriented in the manner consistent with installation and then emissions are recorded.

If the EUT exhibits spurious emissions due to internal receiver circuitry, such emissions are measured with an appropriate carrier signal applied. For devices with intentional emissions below 30 MHz, a shielded loop antenna is used as the test antenna. It is placed at a 1 meter receive height and appropriate low frequency magnetic field extrapolation to the regulatory limit distance is employed. Emissions between 30 MHz and 1 GHz are measured using tuned dipoles and/or calibrated broadband antennas. For both horizontal and vertical polarizations, the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected. The EUT is then rotated through 360° in azimuth until the highest emission is detected. The test antenna is then raised and lowered one last time from 1 to 4 m and the worst case value is recorded. Emissions above 1 GHz are characterized using standard gain horn antennas or calibrated broadband ridge-horn antennas on our OATS with a 2.4m x 2.4m square of H-4 absorber placed over the ground screen between the EUT and the test antenna. Care is taken to ensure that test receiver resolution and video bandwidths meet the regulatory requirements, and that the emission bandwidth of the EUT is not reduced. Photographs of the test setup employed are depicted in Figure 4.

Where regulations allow for direct measurement of field strength, power values (dBm) measured on the test receiver / analyzer are converted to dB μ V/m at the regulatory distance, using

$$E_{dist} = 107 + P_R + K_A - K_G + K_E - C_F$$

where P_R is the power recorded on spectrum analyzer, in dBm, K_A is the test antenna factor in dB/m, K_G is the combined pre-amplifier gain and cable loss in dB, K_E is duty correction factor (when applicable) in dB, and C_F is

a distance conversion (employed only if limits are specified at alternate distance) in dB. This field strength value is then compared with the regulatory limit. If effective isotropic radiated power (EIRP) is compute, it is computed as

$$EIRP(dBm) = E_{3m}(dB\mu V/m) - 95.2.$$

When presenting data at each frequency, the highest measured emission under all possible EUT orientations (3-axes) is reported.



Figure 4: Radiated Emissions Test Setup Photograph(s).

3.1.2 Conducted Emissions Test Setup and Procedures

Battery Power Conducted Spurious The EUT is not subject to measurement of power line conducted emissions as it is powered solely by its internal battery.

3.1.3 Power Supply Variation

Tests at extreme supply voltages are made if required by the the procedures specified in the test standard, and results of this testing are detailed in this report.

In the case the EUT is designed for operation from a battery power source, the extreme test voltages are evaluated over the range specified in the test standard; no less than $\pm 10\%$ of the nominal battery voltage declared by the manufacturer. For all battery operated equipment, worst case intentional and spurious emissions are re-checked employing a new (fully charged) battery.

3.2 Intentional Emissions

3.2.1 Fundamental Emission Pulsed Operation

The details and results of testing the EUT for pulsed operation are summarized in Table 3. Plots showing the measurements made to obtain these values are provided in Figure 5.

Table 3: Pulsed Emission Characteristics (Duty Cycle).

In MANUAL mode the EUT transmits three packets of 6 frames when the battery is inserted, and two packets of 6 frames when mounted to the ceiling. Only a single frame may occur in any given 100ms window. Each frame consists of 15.75 ms of Manchester encoded ASK data with an duty of 0.140 ms / 0.260 ms. (See subfigure (a).) In HEARTBEAT mode the EUT transmits a single packet of the same 6 frames approximately once every 65 minutes to ensure safety system integrity. (See subfigure (b).) In ALARM mode, the EUT transmits the same two packets of 6 frames approximately every 5 seconds during the alarm state.

Duty Cycle Computation		Apollo Smoke; FCC/IC
1 KE = (15.75 ms x 0.140 ms / 0.260 ms) / 100 ms = 0.085 < -20 dB		
2 HEARTBEAT On-Time / Hr = 6 frames x (15.75ms x 0.140 ms / 0.260 ms) / Hr = 50.9 ms / Hr		Meas. U of Mich.; 08/06/2014




Figure 5(a): Pulsed Emission Characteristics (Duty Cycle).




Figure 5(b): Pulsed Emission Characteristics (Duty Cycle).

3.2.2 Fundamental Emission Bandwidth

Emission bandwidth (EBW) of the EUT is measured with the device placed in the test mode(s) with the shortest available frame length and minimum frame spacing. Radiated emissions are recorded following the test procedures listed in Section 1.1. The 20 dB EBW is measured as the max-held peak-detected signal when the IF bandwidth is greater than or equal to 1% of the receiver span. For complex modulations other than ASK and FSK, the 99% emission bandwidth per IC test procedures has a different result, and is also separately reported. The results of EBW testing are summarized in Table 4. Plots showing measurements employed to obtain the emission bandwidth reported are provided in Figure 6.

Table 4: Intentional Emission Bandwidth.

The emission bandwidth of the signal is shown in the following Figure. The allowed 99% bandwidth is 0.25% of 345 MHz, or 862.5 kHz.

Measured Emission Bandwidth						Apollo Smoke; FCC/IC	
#	EBW meas. (kHz)						
1	65.0						

Meas. U of Mich.; 08/06/2014




Figure 6: Intentional Emission Bandwidth.

3.2.3 Fundamental Emission

Following the test procedures listed in Section 1.1, radiated emissions measurements are made on the EUT for both Horizontal and Vertical polarized fields. Table 5 details the results of these measurements.


Table 5: Fundamental Radiated Emissions.

Frequency Range	Det	IF Bandwidth	Video Bandwidth
25 MHz $f < 1000$ MHz	Pk/QPk	120 kHz	300 kHz
$f > 1000$ MHz	Pk	1 MHz	3 MHz
$f > 1000$ MHz	Avg	1 MHz	10kHz

Fundamental Radiated Emission											Apollo Smoke; FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dB μ V/m	E3lim dB μ V/m	Pass dB	Comments
1	345.0	Dip	H	-14.0	Pk	19.5	20.7	71.8	77.3	5.5	flat
2	345.0	Dip	V	-17.3	Pk	19.5	20.7	68.5	77.3	8.8	end
3											
4											
5											
6											
7											
8	* Includes 20 dB Duty Cycle										
9											

Equipment Used: HP8593E1, UMDIP1, UMRH1

Meas. U of Mich.; 08/06/2014



3.3 Unintentional Emissions

3.3.1 Transmit Chain Spurious Emissions

The results for the measurement of transmit chain spurious emissions at the nominal voltage and temperature are provided in Table 6. Measurements are performed to 10 times the highest fundamental operating frequency.

Table 6: Transmit Chain Spurious Emissions.

Frequency Range	Det	IF Bandwidth	Video Bandwidth
25 MHz $f < 1000$ MHz	Pk/QPk	120 kHz	300 kHz
$f > 1000$ MHz	Pk	1 MHz	3 MHz
$f > 1000$ MHz	Avg	1 MHz	10kHz

Spurious Radiated Emissions											Apollo Smoke; FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dB μ V/m	E3lim dB μ V/m	Pass dB	Comments
1	690.0	Dip	H	-51.8	Pk	25.2	17.5	42.9	57.3	14.3	flat
2	690.0	Dip	V	-55.7	Pk	25.2	17.5	39.0	57.3	18.2	side
3	1035.0	Dip	H	-37.9	Pk	19.8	28.0	40.8	54.0	13.2	side
4	1380.0	Dip	V	-43.8	Pk	21.0	28.1	36.1	54.0	17.9	end
5	1725.0	Horn	H	-30.1	Pk	21.8	28.1	50.7	54.0	3.3	end
6	2070.0	Horn	H	-34.3	Pk	22.7	26.5	48.8	57.3	8.4	flat
7	2415.0	Horn	H	-46.3	Pk	23.6	26.3	38.0	57.3	19.3	flat
8	2760.0	Horn	H	-50.4	Pk	24.6	25.1	36.1	57.3	21.1	flat
9	3105.0	Horn	H	-52.1	Pk	25.7	19.6	40.9	54.0	13.1	flat
10	3450.0	Horn	H	-55.2	Pk	26.8	19.3	39.3	57.3	18.0	flat
11											
12											
13											
14											
15											
16											
17	* Includes 20 dB Duty Cycle.										
18											

Equipment Used: HP8593E1, UMDIP1, UMRH1

Meas. U of Mich.; 08/06/2014