

RF EXPOSURE REPORT

REPORT NO.: SA140612E04A

MODEL NO.: KT-6160

FCC ID: 2ACEXKT6160

RECEIVED: June 12, 2014

TESTED: July 01, 2014

ISSUED: Sep. 29, 2014

APPLICANT: Keystone Microtech Corporation

ADDRESS: 9F., No.255 Dong Sec. 1, Guangming 6th Rd.,

Jhubei City, Hsinchu County 302

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: SA140612E04A Reference No.: 140818E02



TABLE OF CONTENTS

REL	LEASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	5
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Report No.: SA140612E04A Reference No.: 1140818E02 2 of 6



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140612E04A	Original release	Sep. 29, 2014

Report No.: SA140612E04A Reference No.: 140818E02



1. CERTIFICATION

PRODUCT: EZ-Extender

BRAND NAME: Keystone Microtech Corporation

MODEL NO.: KT-6160

TEST SAMPLE: MASS-PRODUCTION

APPLICANT: Keystone Microtech Corporation

TESTED DATE: July 01, 2014

STANDARDS: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment (Model: KT-6160) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: , DATE: Sep. 29, 2014

(Elsie Hsu, Specialist)

APPROVED BY : , DATE: Sep. 29, 2014

(May Chen, Manager)



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	~	AVERAGE TIME (minutes)			
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE							
300-1500			F/1500	30			
1500-100,000			1.0	30			

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antenna provided to the EUT, please refer to the following table:

Manufacture	Model name	Antenna Gain(dBi) Including cable loss	Antenna Type	Connecter Type	Frequency range (MHz to MHz)
Keystone	F1B_00340 4-MMP	2	Dipole	SMA	2400~2500

Report No.: SA140612E04A Reference No.: 140818E02



6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The maximum conducted power was refer to the radio test report (Report No.: RF140612E04).

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2407 - 2477	12.050	2	20	0.0038	1.00

--- END ---

Report No.: SA140612E04A Reference No.: 140818E02 6 of 6