

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059 Email: ee.guangzhou@sgs.com Report No.: GZEM140200071601

Page: 1 of 49 FCC ID: 2ACFO-TREK

# TEST REPORT

Application No.:	GZEM1402000716RF
Applicant:	TREK limited
FCC ID:	2ACFO-TREK
Product Name:	Heart Rate Belt
<b>Product Description:</b>	Bluetooth transmitter with 2.4 GHz as carrier.
Model No.:	HR-001-BLE4.0
Trade mark:	TREK
Standards:	CFR 47 FCC PART 15 SUBPART C:2013 section 15.247
Date of Receipt:	2014-02-27
Date of Test:	2014-05-09
Date of Issue:	2014-05-19
Test Result :	Pass*

In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms and conditions.htm">www.sgs.com/terms and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms e-document.htm">www.sgs.com/terms e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only"



Report No.: GZEM140200071601

Page: 2 of 49

#### 2 Version

Revision Record							
Version	Chapter	Date	Modifier	Remark			
00		2014-05-19		Original			

Authorized for issue by:		
Tested By	Jack Liens	2014-05-09
	(Jack Liang) /Project Engineer	Date
Prepared By	Twe Chen	2014-05-19
	(June Chen) /Clerk	Date
Checked By	Storn shu	2014-05-19
	(Storm Shu)/Reviewer	Date



Report No.: GZEM140200071601

Page: 3 of 49

## 3 Test Summary

TEST	TEST REQUIREMENT	TEST METHOD	RESULT
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	FCC/KDB-558074 D01 v03r01 Clause 9.1.2	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6.11.2.3	PASS
Conducted Spurious Emission	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.7	PASS
Radiated Spurious Emission	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: Clause 6.9.2	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	N/A

#### Remark:

N/A: not applicable. Refer to the relative section for the details. EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.



Report No.: GZEM140200071601

Page: 4 of 49

### 4 Contents

1	COVE	ER PAGE	1
2	VERS	SION	2
3	TEST	SUMMARY	3
4	CON	TENTS	4
5	GENE	ERAL INFORMATION	5
	5.1	Client Information	5
	5.2	General Description of E.U.T.	5
	5.3	Details of E.U.T.	5
	5.4	Description of Support Units	5
	5.5	Deviation from Standards	5
	5.6	Abnormalities from Standard Conditions	5
	5.7	Other Information Requested by the Customer	5
	5.8	Test Location	5
	5.9	Test Facility	6
6	EQUI	IPMENT USED DURING TEST	7
7	TEST	TRESULTS	8
	7.1	E.U.T. test conditions	8
	7.2	Antenna Requirement	10
	7.3	6 dB Bandwidth	11
	7.4	Maximum Peak Output Power	15
	7.5	Peak Power Spectral Density	20
	7.6	Conducted Spurious Emissions	24
	7.7	Radiated Spurious Emissions	30
	7.8	Band Edges Requirement	47



Report No.: GZEM140200071601

Page: 5 of 49

#### 5 General Information

#### 5.1 Client Information

Applicant: TREK limited

Address of Applicant: No. 14 NingJiang Road, Daning Village, HuMen Town, DongGuan city,

G.D, CHINA

#### 5.2 General Description of E.U.T.

Product Name: Heart Rate Belt Model No.: HR-001-BLE4.0

#### 5.3 Details of E.U.T.

Operating Frequency 2402 MHz to 2480 MHz

Type of Modulation: GFSK,  $(\pi/4)$ DQPSK, 8DPSK

Number of Channels 40 Channels

Channel Separation: 2 MHz

Antenna Type Integral antenna

Antenna gain: 0 dBi

Speciality: Bluetooth 4.0 Smart (Single mode)

Function: BT function to transmit and receive data.

Power Supply: DC 3V lithium battery

#### 5.4 Description of Support Units

The EUT has been tested as an independent unit for fixed frequency by testing lab.

#### 5.5 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

#### 5.6 Abnormalities from Standard Conditions

None.

#### 5.7 Other Information Requested by the Customer

None.

#### 5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,

Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Report No.: GZEM140200071601

Page: 6 of 49

#### 5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

#### ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

#### SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

#### CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

#### • FCC (Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

#### Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

#### VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

#### CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.



Report No.: GZEM140200071601

Page: 7 of 49

## 6 Equipment Used during Test

RE in Cha	RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM-DD)	Calibration Interval	
EMC0525	Compact Semi- Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y	
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2015-04-19	1Y	
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2015-03-03	1Y	
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2015-05-09	1Y	
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS- ELEKTRONIK	VULB 9163	9163-450	2016-08-31	3Y	
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-08-31	3Y	
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2016-05-04	2Y	
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS- ELEKTRONIK	BBHA 9120D	9120D-841	2016-08-31	3Y	
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y	
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2015-03-03	1Y	
EMC2065	Amplifier	HP	8447F	N/A	2014-08-31	1Y	
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2014-07-29	1Y	
EMC0075	310N Amplifier	Sonama	310N	272683	2015-03-03	1Y	
EMC0523	Active Loop Antenna	EMCO	6502	42963	2016-03-03	2Y	
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS- ELEKTRONI	BBHA 9170	9170-375	2014-06-01	3Y	
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2015-04-19	1Y	
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2016-05-03	2Y	

General u	General used equipment						
No.	Test Equipment	Manufacturer	rer Model No. Serial No. Cal.Due date		Manufacturer Model No Serial No Cal.De	Cal.Due date	Calibration
NO.	rest Equipment	Manufacturei	manufacturer   Model No.   Serial No.	(YYYY-MM-DD)	Interval		
EMC0006	DMM	Fluke	73	70681569	2014-09-13	1Y	
EMC0007	DMM	Fluke	73	70671122	2014-09-13	1Y	



Report No.: GZEM140200071601

8 of 49 Page:

#### **Test Results**

#### E.U.T. test conditions

Test Voltage: DC 3V

Temperature: 20.0 -25.0 °C **Humidity:** 38-50 % RH

1000 -1010 mbar **Atmospheric Pressure:** 

15.31(e): For intentional radiators, measurements of the variation of Requirements:

> the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the

equipment tests shall be performed using a new battery.

15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall

be tested as follows: Testing shall be in accordance with the

procedures specified in Section 15.31 of this part.

Test frequencies and

frequency range:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency

shown in the following table:

#### Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of	Location in frequency range
device operates	frequencies	of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
Mayo thora 10 MHz	2	1 near top, 1 near middle and 1
More than 10 MHz	3	near bottom



Report No.: GZEM140200071601

Page: 9 of 49

#### Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz,
9 KHZ to below to GHZ	whichever is lower
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to 100 GHz,
30 GHz	whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz,
At or above 30 GHZ	whichever is lower, unless otherwise specified

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Test frequencies are the lowest channel: 0 channel(2402MHz), middle channel: 20 channel(2442 MHz) and highest channel: 39 channel(2480 MHz)



Report No.: GZEM140200071601

Page: 10 of 49

#### 7.2 Antenna Requirement

#### Standard requirement

15.203 requirement:


For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna**

The antenna is an integral antenna. The best case gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.



Report No.: GZEM140200071601

Page: 11 of 49

#### 7.3 6 dB Bandwidth

Test Requirement: FCC Part 15 C section 15.247

(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The

minimum 6 dB bandwidth shall be at least 500 kHz.


Test Method: ANSI C63.10: Clause 6.9.1

Test Status: Pre-Scan has been conducted to determine the worst-case mode from

all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed

below.

#### **Test Configuration:**



**Ground Reference Plane** 

#### Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =1.5dB) from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW=100KHz. VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
- 3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
- 4. Repeat until all the test status is investigated.
- 5. Report the worse case.



Report No.: GZEM140200071601

Page: 12 of 49

Observati	<b>5</b>	Measured 6dB		
Channel	Frequency	bandwidth	Limit	Result
No.	(MHz)	(MHz)		
0	2402	0.802		Pass
20	2442	0.721	≥500KHz	Pass
39	2480	0.762		Pass

Test result: The unit does meet the FCC requirements.




Report No.: GZEM140200071601


Page: 13 of 49

#### Result plot as follows:

#### Lowest Channel(2.402 GHz):



#### Middle Channel(2.442 GHz):






Report No.: GZEM140200071601

Page: 14 of 49

### Highest Channel(2.480 GHz):





Report No.: GZEM140200071601

Page: 15 of 49

#### 7.4 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247

(b)(3) For systems using digital modulation in the 902-928 MHz,

2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna

exceeds 6 dBi.

Test Method: FCC/KDB-558074 D01 v03r01


9.1.2 Integrated band power method

Test Status: Pre-Scan has been conducted to determine the worst-case mode from

all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed

below.

**Test Configuration:** 





Report No.: GZEM140200071601

Page: 16 of 49

#### Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable

(Cable loss =2.0dB) from the antenna port to the spectrum.

- 2. Set the RBW = 1 MHz.
- 3. Set the VBW ≥ 3 x RBW
- 4. Set the span  $\ge$  1.5 x DTS bandwidth.
- Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.

Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

- 10. Measure the channel power of the test frequency with special test status.
- 11. Repeat until all the test status is investigated.
- 12. Report the worse case.



Report No.: GZEM140200071601

Page: 17 of 49

#### Test result:

Channel	Frequency	Measured Channel Power	l innit	Daguit
No.	(MHz)	(dBm)	Limit	Result
0	2402	1.67		Pass
20	2442	2.82	1W(30dBm)	Pass
39	2480	2.07		Pass

Remark: Level = Read Level + Cable Loss. The unit does meet the FCC requirements.




Report No.: GZEM140200071601


Page: 18 of 49

#### Result plot as follows:

#### Lowest Channel(2.402 GHz):



#### Middle Channel(2.442 GHz):






Report No.: GZEM140200071601

Page: 19 of 49

#### Highest Channel(2.480 GHz):





Report No.: GZEM140200071601

Page: 20 of 49

#### 7.5 Peak Power Spectral Density

Test Requirement:

FCC Part 15 C section 15.247

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the

power spectral density.


Test Method: ANSI C63.10: Clause 6.11.2.3

Test Status: Pre-Scan has been conducted to determine the worst-case mode from

all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed

below.

Test Configuration:





Report No.: GZEM140200071601

Page: 21 of 49

#### Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =1.5dB) from the antenna port to the spectrum analyzer or power meter.
- 2. Set the spectrum analyzer:
  - a) Set CENTER FREQUENCY = Frequency from Power Spectral Density Test Matrix (see 6.10.2)
  - b) Set SPAN = 20 MHz (For devices with a nominal 40 MHz BW, 50 MHz span will be needed)
  - c) Set REFERENCE LEVEL = 20 dBm
  - d) Set ATTENUATION = 0 dB (add internal attenuation, if necessary)
  - e) Set SWEEP TIME = Coupled
  - f) Set RBW = 3 kHz
  - g) Set VBW = 10 kHz
  - h) Set DETECTOR = Peak
  - i) Set MKR = Center Frequency
  - i) Set TRACE = CLEAR WRITE

Place the radio in continuous transmit mode. Set the TRACE to MAX HOLD, and after the trace stabilizes, the TRACE to VIEW. Set the marker on the peak of the signal and then adjust the center frequency of the spectrum analyzer to the marker frequency.

After viewing the EUT waveform on the spectrum analyzer, perform the following spectrum analyzer functions to capture the trace:

Set SPAN = 300 kHz

Set SWEEP TIME = 100 s

Set TRACE = MAX HOLD

Set MKR = PEAK SEARCH

- 3. Measure the Power Spectral Density of the test frequency with special test status.
- 4. Repeat until all the test status is investigated.
- 5. Report the worse case.




Report No.: GZEM140200071601


Page: 22 of 49

#### Result plot as follows:

#### Lowest Channel(2.402 GHz):



#### Middle Channel(2.442 GHz):






Report No.: GZEM140200071601

Page: 23 of 49

#### Highest Channel(2.480 GHz):





Report No.: GZEM140200071601

Page: 24 of 49

### 7.6 Conducted Spurious Emissions

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all

possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

**Test Configuration:** 



**Ground Reference Plane** 

#### Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
- 2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
- 3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
- 4. Repeat until all the test status is investigated.
- 5. Report the worse case.




Report No.: GZEM140200071601

Page: 25 of 49


#### Result plot as follows:

Lowest Channel(2.402 GHz):

#### 30 MHz to 1 GHz



#### 1 G to 5 GHz






Report No.: GZEM140200071601


Page: 26 of 49

#### 5 G to 25 GHz



#### Middle Channel(2.442 GHz):

#### 30 M to 1 GHz







Report No.: GZEM140200071601

Page: 27 of 49

#### 1 G to 5 GHz



#### 5 G to 25 GHz






Report No.: GZEM140200071601


Page: 28 of 49

#### Highest Channel(2.480 GHz):

#### 30 M to 1 GHz



#### 1 G to 5 GHz






Report No.: GZEM140200071601

Page: 29 of 49

#### 5 G to 25 GHz





Report No.: GZEM140200071601

Page: 30 of 49

### 7.7 Radiated Spurious Emissions

Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all

possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Detector: For PK value:

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW Sweep = auto

Detector function = peak

Trace = max hold For AV value:

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW =10Hz Sweep = auto

Detector function = peak

Trace = max hold

15.209 Limit:  $40.0 \text{ dB}\mu\text{V/m}$  between 30MHz & 88MHz

 $43.5 \text{ dB}\mu\text{V/m}$  between 88MHz & 216MHz  $46.0 \text{ dB}\mu\text{V/m}$  between 216MHz & 960MHz

54.0 dBµV/m above 960MHz




Report No.: GZEM140200071601


Page: 31 of 49

#### **Test Configuration:**

1) 30 MHz to 1 GHz emissions:



2) 1 GHz to 40 GHz emissions:





Report No.: GZEM140200071601

Page: 32 of 49

#### **Test Procedure:**

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver scanned from the lowest frequency generated within the EUT to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit.



Report No.: GZEM140200071601

Page: 33 of 49

### 7.7.1 Harmonic and other spurious emissions

Test at Channel 0 (2.402 GHz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

#### Vertical:

Peak scan

Level (dBµV/m)



Quasi-peak measurement

Freq			Cable Preamp Loss Factor				0ver Limit	Remark
MHz	dBu∨	dB/m	dB	dB	dBu∀/m	dBu√/m	dB	
66.733	47.76	10.02	1.20	31.60	27.38	40.00	-12.62	QP
83.230	48.74	9.72	1.30	31.60	28.16	40.00	-11.84	QP
94.098	47.86	12.67	1.37	31.60	30.30	43.50	-13.20	QP
130.379	48.97	8.93	1.61	31.51	28.00	43.50	-15.50	QP
665.804	47.33	18.69	3.48	31.23	38.27	46.00	-7.73	QP
804.603	40.73	20.10	3.92	31.20	33.55	46.00	-12.45	QP




Report No.: GZEM140200071601

Page: 34 of 49

#### Horizontal:

Peak scan Level (dBµV/m)



Quasi-peak measurement

Freq	ReadAntenna Level Factor						0∨er Limit	Remark
MHz	dBu∀	dB/m	dB	dB	dBu√/m	dBu√/m	dB	
95.093	43.20	12.84	1.38	31.60	25.82	43.50	-17.68	QP
119.856	47.11	10.48	1.56	31.55	27.60	43.50	-15.90	QP
198.588	47.45	10.57	1.88	31.30	28.60	43.50	-14.90	QP
304.610	42.97	13.13	2.37	31.29	27.18	46.00	-18.82	QP
504.706	37.99	16.68	3.09	31.20	26.56	46.00	-19.44	QP
798.980	35.50	20.06	3.91	31.20	28.27	46.00	-17.73	OP



Report No.: GZEM140200071601

Page: 35 of 49

#### 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
4804.00	31.53	11.11	49.30	54.36	47.70	74	V
7206.00	36.47	12.90	49.69	49.62	49.30	74	V
9608.00	38.08	15.16	49.88	49.17	52.53	74	V
4804.00	31.53	11.11	49.30	53.74	47.08	74	Н
7206.00	36.47	12.90	49.69	50.21	49.89	74	Н
9608.00	38.08	15.16	49.88	51.85	55.21	74	Н

#### **Average Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
4804.00	31.53	11.11	49.30	49.23	42.57	54	٧
7206.00	36.47	12.90	49.69	45.82	45.50	54	V
9608.00	38.08	15.16	49.88	45.06	48.42	54	V
4804.00	31.53	11.11	49.30	48.83	42.17	54	Н
7206.00	36.47	12.90	49.69	44.76	44.44	54	Н
9608.00	38.08	15.16	49.88	46.52	49.88	54	Н



Report No.: GZEM140200071601

Page: 36 of 49

Test at Channel20 2.442Hz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

#### Vertical:

Peak scan

Level (dBµV/m)



#### Quasi-peak measurement

Freq			Cable Preamp Loss Factor					Remark
MHz	dBu∀	dB/m	dB	dB	dBu∀/m	dBu∨/m	dB	
42.302	46.89	13.57 9.87		31.60 31.60				-
300.367			2.35	31.30	36.60	46.00	-9.40	QР
392.095 459.114				31.11 31.17				-
670.489	45.52	18.71	3.48	31.22	36.49	46.00	-9.51	OP




Report No.: GZEM140200071601

Page: 37 of 49

#### Horizontal:

Peak scan Level (dBµV/m)



Quasi-peak measurement

Freq		Antenna Factor				Limit Line		Remark
MHz	dBu∀	dB/m	dB	dB	dBu∀/m	dBu√/m	dB	
98.487	48.50	13.06	1.42	31.60	31.38	43.50	-12.12	QP
171.393	49.29	9.03	1.79	31.34	28.77	43.50	-14.73	QP
300.367	49.30	13.06	2.35	31.30	33.41	46.00	-12.59	QP
392.095	47.79	14.87	2.69	31.11	34.24	46.00	-11.76	QP
535.707	41.18	17.31	3.09	31.23	30.35	46.00	-15.65	QP
625.078	39.46	18.54	3.37	31.27	30.10	46.00	-15.90	OP



Report No.: GZEM140200071601

Page: 38 of 49

#### 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
4882.00	31.58	11.26	49.30	54.57	48.11	74.00	V
7323.00	36.50	13.28	49.71	50.05	50.12	74.00	V
9764.00	38.46	15.05	49.89	51.49	55.11	74.00	V
4882.00	31.58	11.26	49.30	55.43	48.97	74.00	Н
7323.00	36.50	13.28	49.71	54.70	54.77	74.00	Н
9764.00	38.46	15.05	49.89	50.50	54.12	74.00	Н

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
4882.00	31.58	11.26	49.30	47.92	41.46	54.00	V
7323.00	36.50	13.28	49.71	44.27	44.34	54.00	V
9764.00	38.46	15.05	49.89	43.68	47.30	54.00	V
4882.00	31.58	11.26	49.30	48.09	41.63	54.00	Н
7323.00	36.50	13.28	49.71	46.95	47.02	54.00	Н
9764.00	38.46	15.05	49.89	44.95	48.57	54.00	Н



Report No.: GZEM140200071601

Page: 39 of 49

Test at Channel39 (2.480 GHz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

#### Vertical:

Peak scan

Level (dBµV/m)



#### Quasi-peak measurement

Freq		ntenna Factor				Limit Line	0∨er Limit	Remark
MHz	dBu∀	dB/m	dB	dB	dBu√/m	dBu√/m	dB	
41.422		13.57			29.10			-
84.999	51.44	10.31	1.31	31.60	31.46	40.00	-8.54	QP
300.367	52.08	13.06	2.35	31.30	36.19	46.00	-9.81	QP
392.095	51.49	14.87	2.69	31.11	37.94	46.00	-8.06	QP
459.114	51.32	15.59	2.96	31.17	38.70	46.00	-7.30	QP
665.804	43.86	18.69	3.48	31.23	34.80	46.00	-11.20	QP




Report No.: GZEM140200071601

Page: 40 of 49

#### Horizontal:

Peak scan Level (dBµV/m)



Quasi-peak measurement

Freq		Antenna Factor						Remark
MHz	dBu∀	dB/m	dB	dB	dBu∨/m	dBu∨/m	dB	
97.798 143.830		13.03		31.60 31.44				-
199.986	48.36	10.57	1.88	31.30	29.51	43.50	-13.99	QP
300.367 392.095			2.69		31.57	46.00	-14.43	QP
665. 804	38.47	18.69	3.48	31.23	29.41	46.00	-16.59	OP



Report No.: GZEM140200071601

Page: 41 of 49

### 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4960.00	31.70	11.39	49.30	54.73	48.52	74.00	V
7440.00	36.60	13.60	49.72	49.16	49.64	74.00	V
9920.00	38.65	14.92	49.90	50.46	54.13	74.00	V
4960.00	31.70	11.39	49.30	53.93	47.72	74.00	Н
7440.00	36.60	13.60	49.72	49.60	50.08	74.00	Н
9920.00	38.65	14.92	49.90	50.01	53.68	74.00	Н

**Average Measurement:** 

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4960.00	31.70	11.39	49.30	49.18	42.97	54.00	V
7440.00	36.60	13.60	49.72	46.68	47.16	54.00	V
9920.00	38.65	14.92	49.90	45.21	48.88	54.00	V
4960.00	31.70	11.39	49.30	48.62	42.41	54.00	Н
7440.00	36.60	13.60	49.72	44.97	45.45	54.00	Н
9920.00	38.65	14.92	49.90	45.79	49.46	54.00	Н

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

#### Remark:

- 1) .For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3<sup>rd</sup> harmonic.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



Report No.: GZEM140200071601

Page: 42 of 49

#### 7.7.2 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part 15 C section 15.247

(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission

limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all

possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit: 40.0 dBµV/m between 30MHz & 88MHz;

43.5 dB $\mu$ V/m between 88MHz & 216MHz;

46.0 dBµV/m between 216MHz & 960MHz;

54.0 dBµV/m above 960MHz.

Detector: For PK value:

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW Sweep = auto

Detector function = peak

Trace = max hold For AV value:

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW =10Hz Sweep = auto

Detector function = peak

Trace = max hold



Report No.: GZEM140200071601

Page: 43 of 49

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		



Report No.: GZEM140200071601

Page: 44 of 49

#### **Test Result:**

### 7.7.2.1 802.11b mode with 11Mbps data rate

Test at Channel 0 (2.402 GHz) in transmitting status

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	57.21	42.19	74.00	Vertical
2390.00	27.63	6.55	49.45	57.73	42.46	74.00	V
2483.50	27.55	6.99	49.42	57.07	42.19	74.00	V
2500.00	27.55	7.02	49.42	57.25	42.40	74.00	V
2310.00	27.93	6.52	49.47	57.06	42.04	74.00	Horizontal
2390.00	27.63	6.55	49.45	57.12	41.85	74.00	Н
2483.50	27.55	6.99	49.42	57.13	42.25	74.00	Н
2500.00	27.55	7.02	49.42	58.79	43.94	74.00	Н

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	51.26	36.24	54.00	Vertical
2390.00	27.63	6.55	49.45	53.10	37.83	54.00	V
2483.50	27.55	6.99	49.42	51.47	36.59	54.00	V
2500.00	27.55	7.02	49.42	52.88	38.03	54.00	V
2310.00	27.93	6.52	49.47	52.33	37.31	54.00	Horizontal
2390.00	27.63	6.55	49.45	52.32	37.05	54.00	Н
2483.50	27.55	6.99	49.42	52.47	37.59	54.00	Н
2500.00	27.55	7.02	49.42	53.79	38.94	54.00	Н



Report No.: GZEM140200071601

Page: 45 of 49

Test at Channel 20 (2.442 GHz) in transmitting status

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	57.34	42.32	74.00	Vertical
2390.00	27.63	6.55	49.45	56.72	41.45	74.00	V
2483.50	27.55	6.99	49.42	57.24	42.36	74.00	V
2500.00	27.55	7.02	49.42	58.15	43.30	74.00	V
2310.00	27.93	6.52	49.47	57.34	42.32	74.00	Horizontal
2390.00	27.63	6.55	49.45	58.39	43.12	74.00	Н
2483.50	27.55	6.99	49.42	58.12	43.24	74.00	Н
2500.00	27.55	7.02	49.42	57.45	42.60	74.00	Н

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	52.63	37.61	54.00	Vertical
2390.00	27.63	6.55	49.45	53.25	37.98	54.00	V
2483.50	27.55	6.99	49.42	52.62	37.74	54.00	V
2500.00	27.55	7.02	49.42	53.43	38.58	54.00	V
2310.00	27.93	6.52	49.47	51.81	36.79	54.00	Horizontal
2390.00	27.63	6.55	49.45	51.39	36.12	54.00	Н
2483.50	27.55	6.99	49.42	52.82	37.94	54.00	Н
2500.00	27.55	7.02	49.42	51.34	36.49	54.00	Н



Report No.: GZEM140200071601

Page: 46 of 49

Test at Channel 39 (2.480 GHz) in transmitting status

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	56.03	41.01	74.00	Vertical
2390.00	27.63	6.55	49.45	57.39	42.12	74.00	V
2483.50	27.55	6.99	49.42	58.28	43.40	74.00	V
2500.00	27.55	7.02	49.42	58.42	43.57	74.00	V
2310.00	27.93	6.52	49.47	56.94	41.92	74.00	Horizontal
2390.00	27.63	6.55	49.45	58.80	43.53	74.00	Н
2483.50	27.55	6.99	49.42	58.32	43.44	74.00	Н
2500.00	27.55	7.02	49.42	58.35	43.50	74.00	Н

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2310.00	27.93	6.52	49.47	52.26	37.24	54.00	Vertical
2390.00	27.63	6.55	49.45	51.91	36.64	54.00	V
2483.50	27.55	6.99	49.42	54.15	39.27	54.00	V
2500.00	27.55	7.02	49.42	51.79	36.94	54.00	V
2310.00	27.93	6.52	49.47	51.62	36.60	54.00	Horizontal
2390.00	27.63	6.55	49.45	51.44	36.17	54.00	Н
2483.50	27.55	6.99	49.42	52.15	37.27	54.00	Н
2500.00	27.55	7.02	49.42	53.03	38.18	54.00	Н



Report No.: GZEM140200071601

Page: 47 of 49

### 7.8 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.


Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10: Clause 6.9.2

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all

possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

**Test Configuration:** 



**Ground Reference Plane** 

#### Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
- 2. Set RBW=100 kHz , VBW=100KHz ,suitable frequency span including 100 kHz bandwidth from band edge..
- 3. Measure the Conducted Spurious Emissions and Radiated Emissions of the test frequency with special test status.
- 4. Repeat until all the test status is investigated.
- 5. Report the worse.



Report No.: GZEM140200071601

Page: 48 of 49

### Test result with plots as follows:

The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.




Report No.: GZEM140200071601


Page: 49 of 49

#### Result plot as follows:

### Lowest Channel(2.402 GHz):



### Highest Channel(2.480 GHz):



#### -- End of Report--