

FCC RADIO TEST REPORT FCC ID: 2ACFWRL-0313B

Product: Lndutive light and Alarm

Trade Name: RL

Model Name: RL-0313B

Serial Model: N/A

Report No.: NTEK-2015NT0319468F

Prepared for

GUANGDONG ROULE ELECTRONICS CO.,LTD.

No.12, Pingdong 3rd Road, Nanping Industry Community, Zhuhai, Guangdong China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



Applicant's name: GUANGDONG ROULE ELECTRONICS CO.,LTD.



TEST RESULT CERTIFICATION

Address: No.12, Pingdong 3rd Road, Nanping Industry Community, Zhuhai,

Report No.: NTEK-2015NT0319468F

	Guanguong China			
Manufacture's Name:	GUANGDONG ROULE ELECTRONICS CO.,LTD.			
Address:	No.12, Pingdong 3rd Road, Nanping Industry Community, Zhuhai,			
	Guangdong China			
Product description				
Product name:	-			
Model and/or type reference :	RL-0313B			
Serial Model:	N/A			
Standards:	FCC Part15.231 01 Oct. 2014			
Test procedure	ANSI C63.4-2009			
	s been tested by NTEK, and the test results show that the compliance with the FCC requirements. And it is applicable only the report.			
This report shall not be reproduc	ced except in full, without the written approval of NTEK, this			
document may be altered or rev	rised by NTEK, personal only, and shall be noted in the revision of			
the document.				
Date of Test	:			
Date (s) of performance of tests	: 19 Mar. 2015 ~ 13 Apr. 2015			
Date of Issue	: 13 Apr. 2015			
Test Result	Pass			
Testing Engine	eer: Donny Grany			
	Denny Huang			
Technical Man	ager: Brown Ln			
	(Brown Lu)			
Authorized Sig				
	(Bill Yao)			



Table of Contents	Page
4 OUMMARY OF TEST RESULTS	
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . ANTENNA REQUIREMENT	11
3.1 STANDARD REQUIREMENT	11
3.2 EUT ANTENNA	11
3.3 CONDUCTED EMISSION MEASUREMENT	12
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.3.2 TEST PROCEDURE	13
3.3.3 DEVIATION FROM TEST STANDARD 3.3.4 TEST SETUP	13 13
3.2.5 TEST RESULT	14
3.4 RADIATED EMISSION MEASUREMENT	15
3.4.1 RADIATED EMISSION LIMITS	15
3.4.2 TEST PROCEDURE	16
3.4.3 DEVIATION FROM TEST STANDARD	16
3.4.4 TEST SETUP 3.4.5 TEST RESULTS (BELOW 30MHZ)	17 19
3.4.6 TEST RESULTS (BETWEEN 30 – 5000 MHZ)	20
4 . BANDWIDTH TEST	23
4.1 TEST PROCEDURE	23
4.2 DEVIATION FROM STANDARD	23
4.3 TEST SETUP 4.4 TEST RESULTS	23 24
5 . TRANSMITTER TIMEOUT	25
5.1 REQUIREMENTS	25
6 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	26



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.231)					
Standard Section	Test Item	Judgment	Remark		
15.207	Conducted Emission	N/A	Note(1)		
15.203	Antenna Requirement	Pass			
15.231	Radiated Spurious Emission	Pass			
15.231	15.231 Occupied Bandwidth				
15.231	Transmitter Timeout	Pass			

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.



1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,

Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

•



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Lndutive light and Alarm				
Trade Name	RL				
Model Name	RL-0313B				
Serial Model	N/A				
Model Difference	N/A				
Product Description	The EUT is a Lndutive light and Alarm Operation Frequency: 433.92MHz Modulation Type: ASK Number Of Channel 1CH. Antenna Designation: PCB antenna Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as a ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.				
Channel List	Refer to below				
Adapter	N/A				
Battery	1.5V*3 button cell				

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)		
01	433.92		



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission			
Final Test Mode	Description		
Mode 1	TX		

For Radiated Emission				
Final Test Mode Description				
Mode 1	TX			

Note:

(1) The EUT use new battery.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

E-1 EUT



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Lndutive light and Alarm	RL	RL-0313B	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>『Length』</code> column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufactu rer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Test Receiver	R&S	ESCI	101160	2014.06.07	2015.06.06	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2014.07.06	2015.07.05	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.07.06	2015.07.05	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year



3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is permar	nent attached antenna. It c	mply with	n the standard	i requirement.
---------------------------	-----------------------------	-----------	----------------	----------------

•



3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

	Class A	(dBuV) Class B (dBuV)		Standard		
FREQUENCY (MHz)	Quasi-peak	Average	Quasi-peak	Average	Standard	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR	
0.50 -5.0			56.00	46.00	CISPR	
5.0 -30.0			60.00	50.00	CISPR	

0.15 -0.5		66 - 56 *	56 - 46 *	LP002.
0.50 -5.0		56.00	46.00	LP002.
5.0 -30.0		60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes



3.2.5 TEST RESULT

EUT:	Lndutive light and Alarm	Model Name. :	RL-0313B
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N/A
Test Voltage :	N/A	Test Mode:	N/A

•



3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.231)

,				
Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)		
40.66 - 40.70	2250.00	225.00		
70 - 130	1250.00	125.00		
130 - 174	1,250 to 3,750 **	125 to 375 **		
174 - 260	3750.00	375.00		
260 - 470	3,750 to 12,500 **	375 to 1,250 **		
Above 470	12500.00	1250.00		

Notes:

(1) ** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = 56.81818(F) - 6136.3636; for the band 260-470 MHz, uV/m at 3 meters = 41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in 93 Section 15.209, whichever limit permits a higher field strength.



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.4.3 DEVIATION FROM TEST STANDARD

No deviation




3.4.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



Page 18 of 26

•



3.4.5 TEST RESULTS (BELOW 30MHz)

EUT:	Lndutive light and Alarm	Model Name. :	RL-0313B
Temperature :	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.4.6 TEST RESULTS (BETWEEN 30 - 5000 MHZ)

EUT:	Lndutive light and Alarm	Model Name :	RL-0313B
Temperature:	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	TX	Polarization :	Horizontal

Report No.: NTEK-2015NT0319468F

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.92	-17.07	93.59	76.52	100.83	80.83	pass
867.84	-17.07	60.33	43.26	80.83	60.83	pass
1301.76	-17.07	52.41	35.34	74.00	54.00	pass
1843.14	-17.07	48.66	31.59	74.00	54.00	pass
2347.92	-17.07	44.25	27.18	74.00	54.00	pass

EUT:	Lndutive light and Alarm	Model Name :	RL-0313B
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	TX	Polarization :	Vertical

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	Stata
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.92	-17.07	85.88	68.81	100.83	80.83	pass
867.84	-17.07	57.23	40.16	80.83	60.83	pass
1301.76	-17.07	50.47	33.4	74.00	54.00	pass
1745.23	-17.07	46.38	29.31	74.00	54.00	pass
2159.67	-17.07	42.42	25.35	74.00	54.00	pass

Note: 1. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report(Y orientation).

2. *Calculate Average value based on Duty Cycle correction factor:

Duty Cycle=Ton/(Ton+Toff)= 6.5828ms/18.20ms = 0.14 = 14%

Duty Cycle factor= 20lg (Duty Cycle) =20lg (0.14) = -17.07dB

Average=Peak+ Duty Cycle factor

- 2. FCC Limit for Average Measurement = 41.6667(433.92)-7083.3333 = 10996.681164uV/m = 80.83dBuV/m
- 3. Pulse Desensitization Correction Factor

Pulse Width(PW)=18.20ms

2/PW=2/18.20ms=0.11kHz

RBW(100kHz) > 2/PW (0.11kHz),

Therefore PDCF is not needed.



3.4.7 DUTY CYCLE


The duty cycle is simply the on time divided by the period:


The duration of one cycle = 18.20ms


Effective period of the cycle = 0.45ms×9+0.1583ms×16=6.5828ms

Duty Cycle = 6.5828ms/18.20ms = 0.14

The duration of one cycle







•



4. BANDWIDTH TEST

4.1 TEST PROCEDURE

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit: 433.92MHz*0.25%=1084.8KHz

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP


EUT	SPECTRUM
	ANALYZER



4.4 TEST RESULTS

EUT:	Lndutive light and Alarm	Model Name :	RL-0313B
Temperature :	26 ℃	Relative Humidity:	53%
Pressure :	1020 hPa	Test Power :	DC 4.5V
Test Mode :	TX CH 1		

Test Channel	Frequency	20 dBc Bandwidth	Limit
	(MHz)	(kHz)	(kHz)
CH01	433.92	52.628	1084.8





5. TRANSMITTER TIMEOUT

5.1 REQUIREMENTS

1 A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result: The EUT has a manually activated transmitter, please refer to below detail data

2 A transmitter activated automatically shall cease transmission within 5 seconds after activation.


Result: The EUT does not have a manually activated transmitter,

Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour

Result: The EUT does not employ periodic transmission.

4 Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result: The section is not applicable to EUT.



THE DURATION OF EACH TRANSMISSION	LIMIT	RESULT	
1.783s	<5s	PASS	



6. EUT TEST PHOTO



