

FCC ID: 2ACGF-MA00A

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Frequency Electric Field		Power	Average		
Range(MHz)	Strength(V/m)	Field Density(mW/cm ²)		Time		
		Strength(A/m)				
(A) Limits for Occupational/Control Exposures						
300-1500	/		F/300	6		
1500-	// I		5	6		
100000						
(B) Limits for General Population/Uncontrol Exposures						
300-1500		/	F/1500	6		
1500-			1	30		
100000						

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.



11.2 Measurement Result

Module 1

Antenna gain: 5.12 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
0.47	0 to 1	1	3.25	0.00081	1

Module 2

Antenna gain: 5.12 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
1.03	1 to 2	2	3.25	0.00103	1

Module 3

Antenna gain: 5.12 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
0.91	0 to 1	1	3.25	0.00081	1

Three modules can work simultaneously MAX RF EXPOSURE EVALUATION

	Module 2 (mW/cm2)	Module 3 (mW/cm2)	Summation of Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
0.00081	0.00103	0.00081	0.00265	1