

Report No.: AGC01883140502FE04 Page 1 of 48

FCC Test Report

Report No.: AGC01883140502FE04

FCC ID : 2ACGKWIRELESSSENSOR

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Wireless Sensor

BRAND NAME : ServersCheck

MODEL NAME : Wireless Sensor

CLIENT : ServersCheck Europe

DATE OF ISSUE : June 26, 2014

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report No.: AGC01883140502FE04 Page 2 of 48

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June 26, 2014	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. TEST STANDARDS	7
2.4. RELATED SUBMITTAL(S) / GRANT (S)	7
2.5. TEST METHODOLOGY	7
2.6. SPECIAL ACCESSORIES	7
2.7. EQUIPMENT MODIFICATIONS	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	8
4. DESCRIPTION OF TEST MODES	8
5. SYSTEM TEST CONFIGURATION	9
5.1. CONFIGURATION OF EUT SYSTEM	9
5.2. EQUIPMENT USED IN EUT SYSTEM	9
5.3. SUMMARY OF TEST RESULTS	9
6. TEST FACILITY	10
7. 15.203 - ANTENNA REQUIREMENT	10
7.1. STANDARD APPLICABLE	10
7.2. TEST RESULT	10
8. PEAK OUTPUT POWER	11
8.1. MEASUREMENT PROCEDURE	11
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3. LIMITS AND MEASUREMENT RESULT	13
9. 6DB BANDWIDTH	
9.1. MEASUREMENT PROCEDURE	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
9.3. LIMITS AND MEASUREMENT RESULTS	16
10. CONDUCTED SPURIOUS EMISSION	18
10.1. MEASUREMENT PROCEDURE	18
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	18
10.3. MEASUREMENT EQUIPMENT USED	18
10.4. LIMITS AND MEASUREMENT RESULT	
11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	25

11.1 MEASUREMENT PROCEDURE	25
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
11.3 MEASUREMENT EQUIPMENT USED	25
10.4 LIMITS AND MEASUREMENT RESULT	25
12. RADIATED EMISSION	28
12.1. MEASUREMENT PROCEDURE	28
12.2. TEST SETUP	29
12.3. LIMITS AND MEASUREMENT RESULT	30
11.4. TEST RESULT	30
13. BAND EDGE EMISSION	38
13.1. MEASUREMENT PROCEDURE	38
13.2. TEST SET-UP	38
13.3. TEST RESULT	39
14. FCC LINE CONDUCTED EMISSION TEST	40
14.1. LIMITS OF LINE CONDUCTED EMISSION TEST	40
14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	40
14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	42
N/A	42
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	43
APPENDIX B: PHOTOGRAPHS OF EUT	44

Page 5 of 48

1. VERIFICATION OF CONFORMITY

Applicant	ServersCheck Europe			
Address	Leuvensesteenweg 613 Unit 4, 1930 ZAVENTEM BELGIUM			
Manufacturer	Design Gateway Co., Ltd.			
Address	54 BB Building, 13th Floor (Room 1302), Sukhumvit 21 Rd. (Asoke Klongtoey-Nua, Wattana, Bangkok 10110, Thailand			
Product Designation	Wireless Sensor			
Brand Name	ServersCheck			
Test Model	Wireless Sensor			
Date of test	June 05,2014 to June 25,2014			
Deviation	None			
Condition of Test Sample	Normal			
Report Template	AGCRT-US-BGN/RF (2013-03-01)			

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

Reviewed By:

Bart Xie June 26, 2014

Reviewed By:

Kidd Yang June 26, 2014

Approved By:

Solger Zhang June 26, 2014

Page 6 of 48

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as "Wireless Sensor". It is designed by way of utilizing the DSSS technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2405.00-2480.00MHz, (Channel Number: 16, Channel
Operation Frequency	Frequency=2405+5(K-1), K=1, 2, 316)
RF Output Power	13.27dBm(Max)
Channel Spacing	5MHz
Modulation	OQPSK
Number of channels	16
Hardware Version	1.00
Software Version	1.00
Antenna Designation	Integrated Antenna
Antenna Gain	0dBi(Max.)
Power Supply	DC3V by button cell

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2405MHZ
	1	2410MHZ
	:	:
	8	2440 MHZ
2400~2483.5MHZ	9	2445 MHZ
	10	2450 MHZ
	:	:
	14	2475 MHZ
	15	2480 MHZ

Page 7 of 48

2.3. TEST STANDARDS

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 is required to be used for this kind of FCC 15.247 digital modulation device.

The following report of is prepared on behalf of the Attestation of Global Compliance Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commission rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commission rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ACGKWIRELESSSENSOR** filing to comply with the FCC Part 15 requirements.

2.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

2.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Attestation of Global Compliance (Shenzhen) Co., Ltd.

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.

FCC register No.: 259865

Page 8 of 48

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

4. DESCRIPTION OF TEST MODES

4. DESCRIPTION OF TEST MODES

No.	TEST MODES	
1	2405MHZ TX	
2	2440MHZ TX	
3	2480MHZ TX	
Note: Above 2 modes have performed at maximum emission conditions 2 axis have been tested and		

Note: Above 3 modes have performed at maximum emission conditions.3 axis have been tested and only the worst mode data recorded in the test report.

Note:


- 1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency individually.
- 2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

Page 9 of 48

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless Sensor	Wireless Sensor	Wireless Sensor	EUT
3	USB Cable	N/A	N/A	Accessory
4	Laptop	Dell	INSPIRON	A.E

Note: All the accessories have been used during the test in conduction emission test.

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirements	Compliant
§15.247	Peak Output Power	Compliant
§15.247	6dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	N/A

Note: The EUT received power from DC3.0V lithium button cell.

Page 10 of 48

6. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China		
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.		

ALL TEST EQUIPMENT LIST

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Probe	R&S	NRP-Z23	100323	07/17/2013	07/16/2014
RF attenuator	N/A	RFA20db	68	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	US41421290	07/17/2013	07/16/2014
EXA Signal Analyzer	Agilent	N9020A	MY52091009	06/20/2014	06/19/2015
Amplifier	EM	EM30180	0607030	02/27/2014	02/26/2015
Horn Antenna	EM	EM-AH-10180	67	04/19/2014	04/18/2015
Horn Antenna	A.H. Systems Inc.	SAS-574		07/17/2013	07/16/2014
EMI Test Receiver	Rohde & Schwarz	ESCI	100694	07/17/2013	07/16/2014
Biological Antenna	A.H. Systems Inc.	SAS-521-4	26	06/07/2013	06/06/2014
Loop Antenna	A.H.	SAS-526B	264	07/14/2013	07/13/2014
LISN	R&S	ESH3-Z5	8389791009	07/17/2013	07/16/2014

7. 15.203 - ANTENNA REQUIREMENT

7.1. STANDARD APPLICABLE

According to FCC 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

7.2. TEST RESULT

This product has a permanent antenna, fulfill the requirement of this section.

Page 11 of 48

8. PEAK OUTPUT POWER

8.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, middle and the bottom operation frequency individually.
- 4. Use the following spectrum analyzer settings:

Set the RBW ≥ DTS bandwidth.

Set the VBW ≥ 3 x RBW

Set the span \ge 3 x RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

- 5. Allow the trace to stabilize. Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges.
- 6. Record the result form the Spectrum Analyzer.


For average power test:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to power probe through an RF attenuator.
- 3. Connect the power probe to the PC.
- 4. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 5. Record the maximum power from the software.
- 6. The maximum peak power shall be less 1 Watt (30dBm).


Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Page 12 of 48

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP



AVERAGE POWER SETUP




Page 13 of 48

8.3. LIMITS AND MEASUREMENT RESULT

TEST ITEM	PEAK POWER
TEST MODE	802.11b with data rate 1


LIMITS AND MEASUREMENT RESULT								
Frequency (GHz)	(15)							
2.405	10.03	13.27	30	Pass				
2.440	9.86	13.16	30	Pass				
2.480	9.47	12.67	30	Pass				

CH1




Page 14 of 48

CH₆



CH11



Page 15 of 48


9. 6DB BANDWIDTH

9.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set SPA Centre Frequency = Operation Frequency, RBW = 100 KHz, VBW ≥ RBW.
- 5. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



Page 16 of 48

9.3. LIMITS AND MEASUREMENT RESULTS

LIMITS AND MEASUREMENT RESULT						
Applicable Limits						
Applicable Limits	Test Da	ta (MHz)	Criteria			
	Low Channel	1.547	PASS			
>500KHZ	Middle Channel	1.537	PASS			
	High Channel	1.557	PASS			

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



Page 17 of 48

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 18 of 48

10. CONDUCTED SPURIOUS EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW > RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW > RBW) are conform to the requirement.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

10.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.


10.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT						
Annilia alda di insita	Measurement Result					
Applicable Limits	Test Data	Criteria				
In any 100 KHz Bandwidth Outside the	At least -20dBc than the limit					
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS				
intentional radiator is operating, the radio frequency	Channel					
power that is produce by the intentional radiator						
shall be at least 20 dB below that in 100KHz						
bandwidth within the band that contains the highest						
level of the desired power.	At least -20dBc than the limit	PASS				
In addition, radiation emissions which fall in the	Specified on the TOP Channel	PASS				
restricted bands, as defined in §15.205(a), must also						
comply with the radiated emission limits specified						
in§15.209(a))						


Page 19 of 48


TEST PLOT OF OUT OF BAND EMISSIONS LOW CHANNEL






Page 20 of 48







Page 21 of 48


TEST PLOT OF OUT OF BAND EMISSIONS MODULATION IN MIDDLE CHANNEL






Page 22 of 48







Page 23 of 48

TEST PLOT OF OUT OF BAND EMISSIONS MODULATION IN HIGH CHANNEL



Page 24 of 48





Page 25 of 48

11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

11.1 MEASUREMENT PROCEDURE

- (1). The EUT was placed on a turn table which is 0.8m above ground plane.
- (2). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (3). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (4). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

11.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

TEST ITEM	POWER PECTRAL DENSITY
TEST MODE	802.11b with data rate 1

Channel No.	PSD (dBm)	Limit (dBm)	Result
Low Channel	-10.02	8	Pass
Middle Channel	-9.57	8	Pass
High Channel	-8.97	8	Pass

Page 26 of 48

TEST RESULT
TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



Page 27 of 48

TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



Page 28 of 48

12. RADIATED EMISSION


12.1. MEASUREMENT PROCEDURE

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.


Page 29 of 48

12.2. TEST SETUP


RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 30 of 48

12.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,

the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

Page 31 of 48

RADIATED EMISSION BELOW 1GHZ

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	2405MHZ	Antenna	Horizontal



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Wireless Sensor M/N: Wireless Sensor Mode: Low channel TX

Note:


Polarization: Horizontal Temperature: 26 Power: Humidity: 60 %

Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit Over	Over	Limit Over	Detector	Antenna Height	Table Degree	Comment
	*	MHz	dBuV	dB/m	dBuV/m		dBuV/m		cm:	degree		
1	*	73.6500	25.12	10.09	35.21	40.00	-4.79	peak				
2		198.1331	25.23	11.91	37.14	43.50	-6.36	peak				
3	1	222.3831	28.14	12.85	40.99	46.00	-5.01	peak				
4		371.1166	16.47	18.88	35.35	46.00	-10.65	peak				
5		445.4832	14.76	20.45	35.21	46.00	-10.79	peak				
6		668.5833	13.51	24.35	37.86	46.00	-8.14	peak				

Page 32 of 48

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	2405MHZ	Antenna	Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT: Wireless Sensor Distance:

M/N: Wireless Sensor Distance:


Note:

Mode: Low channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	nt Limit dBu∀/m	Dete	Detector	Antenna Height	Table Degree	Comment
	. 1	MHz	dBuV	dB/m	dBuV/m				cm	degree	
1	1	39.7000	25.51	8.51	34.02	40.00	-5.98	peak			
2	*	73.6500	32.57	3.36	35.93	40.00	-4.07	peak			
3	1	131.8497	26.31	11.80	38.11	43.50	-5.39	peak			
4		222.3831	28.13	11.19	39.32	46.00	-6.68	peak			
5		458.4166	11.92	20.68	32.60	46.00	-13.40	peak			
6		668.5833	8.69	24.35	33.04	46.00	-12.96	peak			

Page 33 of 48

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	2440MHZ	Antenna	Horizontal



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Wireless Sensor M/N: Wireless Sensor Mode: Middle channel TX


Note:

Polarization: Horizontal Temperature: 26
Power: Humidity: 60 %

Distance:

No.	Mk	Freq.	Reading	Factor dB/m	Measurement dBuV/m	Limit		Detector	Antenna Height cm	Table Degree	Comment
	*	* MHz	dBuV			dBuV/m					
1	*	73.6500	24.62	10.09	34.71	40.00	-5.29	peak			
2		198.1331	24.23	11.91	36.14	43.50	-7.36	peak			
3	!	222.3831	27.64	12.85	40.49	46.00	-5.51	peak			
4		445.4832	15.26	20.45	35.71	46.00	-10.29	peak			
5		668.5833	14.01	24.35	38.36	46.00	-7.64	peak			
6		817.3165	11.20	27.32	38.52	46.00	-7.48	peak			
		The state of the s			A Committee of the Comm			***************************************			

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	2440MHZ	Antenna	Vertical



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Wireless Sensor

M/N: Wireless Sensor Mode: Middle channel TX

Note:

Polarization: Vertical Temperature: 26
Power: Humidity: 60 %


Distance:

No.	Mk	5000167707	Reading dBuV	Factor		TOTAL STATE	Over	Detector	Antenna Height	Comment
	∂3.			dB/m			dΒ	A-17-10-10-10-10-10-10-10-10-10-10-10-10-10-	cm	
1	ļ	39.7000	26.01	8.51	34.52	40.00	-5.48	peak		
2	*	73.6500	33.07	3.36	36.43	40.00	-3.57	peak		
3	1	131.8497	26.81	11.80	38.61	43.50	-4.89	peak		
4		222.3831	28.63	11.19	39.82	46.00	-6.18	peak		
5		371.1166	14.33	18.88	33.21	46.00	-12.79	peak		
6		812.4664	7.81	27.32	35.13	46.00	-10.87	peak		

Temperature: 26

Page 35 of 48

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	2480MHZ	Antenna	Horizontal



Site: site #1

Limi EUT

M/N: Wireless Sensor Mode: High channel TX

Note:

nit: FCC Class B 3M Radiation	Power:	Humidity: 60 %
T: Wireless Sensor	Distance:	
N: Mireless Sensor		

Polarization: Horizontal


No.	Mk		Reading	Factor dB/m	Measurement dBuV/m	Limit		Detector	Antenna Height cm	Table Degree degree	Comment
	5¥		dBuV			dBu√/m					
1	*	73.6500	25.12	10.09	35.21	40.00	-4.79	peak			
2		222.3831	27.14	12.85	39.99	46.00	-6.01	peak			
3		371.1166	16.47	18.88	35.35	46.00	-10.65	peak			
4		445.4832	15.26	20.45	35.71	46.00	-10.29	peak			
5		668.5833	14.01	24.35	38.36	46.00	-7.64	peak			
6		817.3165	11.20	27.32	38.52	46.00	-7.48	peak			

Temperature: 26

Humidity: 60 %

Page 36 of 48

EUT	Wireless Sensor	Model Name	Wireless Sensor
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Vertical



Polarization: Vertical

Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Wireless Sensor

M/N: Wireless Sensor Mode: High channel TX

Note:

No.	Mk	Mk Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	35		dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	73.6500	32.07	3.36	35.43	40.00	-4.57	peak			
2	1	131.8497	26.31	11.80	38.11	43.50	-5.39	peak			
3		222.3831	28.63	11.19	39.82	46.00	-6.18	peak			
4		371.1166	14.33	18.88	33.21	46.00	-12.79	peak			
5		458.4166	12.42	20.68	33.10	46.00	-12.90	peak			
6		668.5833	9.19	24.35	33.54	46.00	-12.46	peak			

Power:

Distance:

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 37 of 48

RADIATED EMISSION ABOVE 1GHZ

Channel 0

Freq. MHz	Reading Level dBuV	Ant Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4810.04	47.32	33.06	35.04	3.94	49.28	74	-24.72	Peak	Horizontal
4810.07	38.23	33.06	35.04	3.94	40.19	54	-13.81	Average	Horizontal
4810.04	47.97	33.06	35.04	3.94	49.93	74	-24.07	Peak	Vertical
4810.07	38.86	33.06	35.04	3.94	40.82	54	-13.18	Average	Vertical

Channel 7

Freq.	Reading Level	Ant Fac.	Pre. Fac.	Cab. Loss	Measured	Limit	Margin	Remark	Pol.
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
4890.08	46.71	33.16	35.15	3.96	48.68	74	-25.32	Peak	Horizontal
4890.14	37.08	33.16	35.15	3.96	39.05	54	-14.95	Average	Horizontal
4890.08	47.90	33.16	35.15	3.96	49.87	74	-24.13	Peak	Vertical
4890.14	38.71	33.16	35.15	3.96	40.68	54	-13.32	Average	Vertical

Channel 15

Freq. MHz	Reading Level dBuV	Ant Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4960.32	46.42	33.26	35.14	3.98	48.52	74	-25.48	Peak	Horizontal
4960.37	36.45	33.26	35.14	3.98	38.55	54	-15.45	Average	Horizontal
4960.32	47.26	33.26	35.14	3.98	49.36	74	-24.64	Peak	Vertical
4960.38	38.38	33.26	35.14	3.98	40.48	54	-13.52	Average	Vertical

Notes:

- 1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30 MHz.
- 2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
- 3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Page 38 of 48

13. BAND EDGE EMISSION

13.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the bottom operation frequency individually.
- 2. Set SPA Start or Stop Frequency = Operation Frequency, RBW>=1%span, VBW>=RBW
- 3. The band edges was measured and recorded.

13.2. TEST SET-UP

Radiated same as 11.2

Report No.: AGC01883140502FE04 Page 39 of 48

13.3. TEST RESULT

(Radiated) Channel 0 Tx-2405

Freq.	Reading Level dBuV	Ant Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/ m	Margin dB	Remark	Pol.
2370.05	44.66	32.89	35.16	3.51	45.90	74	-28.10	Peak	Horizontal
2370.13	34.87	32.90	35.16	3.51	36.12	54	-17.88	Average	Horizontal
2400.00	48.82	32.92	35.16	3.54	50.12	74	-23.88	Peak	Horizontal
2400.01	39.47	32.92	35.16	3.54	40.77	54	-13.23	Average	Horizontal
2370.18	45.22	32.89	35.16	3.51	46.46	74	-27.54	Peak	Vertical
2370.22	36.32	32.90	35.16	3.51	37.57	54	-16.43	Average	Vertical
2400.01	49.26	32.92	35.16	3.54	50.56	74	-23.44	Peak	Vertical
2400.00	39.06	32.92	35.16	3.54	40.36	54	-13.64	Average	Vertical

Channel 15 Tx-2480

Freq.	Reading Level dBuV	Ant Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/ m	Margin dB	Remark	Pol.
2483.50	45.68	33.06	35.18	3.60	47.16	74	26.84	Peak	Horizontal
2483.49	35.73	33.08	35.18	3.60	37.23	54	-16.77	Average	Horizontal
2486.87	46.22	33.08	35.18	3.62	50.12	74	-26.26	Peak	Horizontal
2486.94	36.14	33.08	35.18	3.62	37.66	54	-16.34	Average	Horizontal
2483.50	46.55	33.08	35.18	3.60	48.03	74	-25.97	Peak	Vertical
2483.51	35.79	33.08	35.18	3.60	37.29	54	-16.71	Average	Vertical
2486.83	46.76	33.08	35.18	3.62	48.28	74	-25.72	Peak	Vertical
2486.91	36.77	33.08	35.18	3.62	38.29	54	-15.71	Average	Vertical

RESULT: PASS

Page 40 of 48

14. FCC LINE CONDUCTED EMISSION TEST


14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francis	Maximum RF Line Voltage					
Frequency	Q.P.(dBuV)	Average(dBuV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 41 of 48

14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Page 42 of 48

14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: N.A. The test not applicable, battery operated equipment.

Report No.: AGC01883140502FE04 Page 43 of 48

APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC RADIATED EMISSION TEST SETUP




Page 44 of 48

APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT




Report No.: AGC01883140502FE04 Page 45 of 48

FRONT VIEW OF EUT



BACK VIEW OF EUT




Page 46 of 48

LEFT VIEW OF EUT



RIGHT VIEW OF EUT




Page 47 of 48


OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----