



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666

Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM180400246702

Page: 1 of 85

TEST REPORT

| | |
|------------------------------------|---|
| Application No.: | SHEM1804002467CR |
| FCC ID: | 2ACHK-01070189 |
| Applicant: | iRay Technology Co. Ltd. |
| Address of Applicant: | RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China |
| Manufacturer: | iRay Technology Co. Ltd. |
| Address of Manufacturer: | RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China |
| Factory: | iRay Technology Co. Ltd. |
| Address of Factory: | RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China |
| Equipment Under Test (EUT): | |
| EUT Name: | WiFi Module |
| Model No.: | WIFI-2-V897EA1 |
| Standard(s) : | 47 CFR Part 15, Subpart E 15.407 |
| Date of Receipt: | 2018-04-04 |
| Date of Test: | 2018-04-04 to 2018-06-21 |
| Date of Issue: | 2018-07-20 |
| Test Result: | Pass* |

* In the configuration tested, the EUT complied with the standards specified above.




Parlam Zhan
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

| Revision Record | | | |
|-----------------|-------------|------------|--------|
| Version | Description | Date | Remark |
| 00 | Original | 2018-07-20 | / |
| | | | |
| | | | |

| | | | |
|--------------------------|--|--|--|
| Authorized for issue by: | | | |
| | |  | |
| | | Vincent Zhu / Project Engineer | |
| | |  | |
| | | Parlam Zhan /Reviewer | |

2 Test Summary

| Radio Spectrum Technical Requirement | | | | |
|--------------------------------------|----------------------------------|--------|--------------------------------------|--------|
| Item | Standard | Method | Requirement | Result |
| Antenna Requirement | 47 CFR Part 15, Subpart E 15.407 | N/A | 47 CFR Part 15, Subpart C 15.203 | Pass |
| Transmission in the Absence of Data | 47 CFR Part 15, Subpart E 15.407 | N/A | 47 CFR Part 15, Subpart C 15.407 (c) | Pass |

N/A: Not applicable

| Radio Spectrum Matter Part | | | | |
|---|----------------------------------|--------------------------------|--|--------|
| Item | Standard | Method | Requirement | Result |
| 99% Bandwidth | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 II D | N/A* | Pass |
| 26dB Emission bandwidth | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II C 1 | 47 CFR Part 15, Subpart C 15.407 (a) | Pass |
| Minimum 6 dB bandwidth (5.725-5.85 GHz band) | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II C 2 | 47 CFR Part 15, Subpart C 15.407 (e) | Pass |
| Maximum Conducted output power | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II E | 47 CFR Part 15, Subpart C 15.407 (a) | Pass |
| Peak Power spectrum density | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II F | 47 CFR Part 15, Subpart C 15.407 (a) | Pass |
| Radiated Emissions | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II G | 47 CFR Part 15, Subpart C 15.209 & 15.407(b) | Pass |
| Radiated Emissions which fall in the restricted bands | 47 CFR Part 15, Subpart E 15.407 | KDB 789033 D02 II G | 47 CFR Part 15, Subpart C 15.209 & 15.407(b) | Pass |
| Frequency Stability | 47 CFR Part 15, Subpart E 15.407 | ANSI C63.10 (2013) Section 6.8 | 47 CFR Part 15, Subpart C 15.407 (g) | Pass |

3 Contents

| | Page |
|--|------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS..... | 4 |
| 4 GENERAL INFORMATION | 6 |
| 4.1 DETAILS OF E.U.T. | 6 |
| 4.2 DESCRIPTION OF SUPPORT UNITS..... | 6 |
| 4.3 MEASUREMENT UNCERTAINTY..... | 7 |
| 4.4 TEST LOCATION | 8 |
| 4.5 TEST FACILITY | 8 |
| 4.6 DEVIATION FROM STANDARDS | 8 |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS..... | 8 |
| 5 EQUIPMENT LIST | 9 |
| 6 RADIO SPECTRUM TECHNICAL REQUIREMENT | 10 |
| 6.1 ANTENNA REQUIREMENT | 10 |
| 6.1.1 Test Requirement:..... | 10 |
| 6.1.2 Conclusion..... | 10 |
| 6.2 TRANSMISSION IN THE ABSENCE OF DATA | 11 |
| 6.2.1 Test Requirement:..... | 11 |
| 6.2.2 Conclusion..... | 11 |
| 7 RADIO SPECTRUM MATTER TEST RESULTS | 12 |
| 7.1 26dB EMISSION BANDWIDTH..... | 12 |
| 7.1.1 E.U.T. Operation | 12 |
| 7.1.2 Test Setup Diagram | 12 |
| 7.1.3 Measurement Procedure and Data | 12 |
| 7.2 MINIMUM 6 DB BANDWIDTH (5.725-5.85 GHZ BAND)..... | 13 |
| 7.2.1 E.U.T. Operation | 13 |
| 7.2.2 Test Setup Diagram | 13 |
| 7.2.3 Measurement Procedure and Data | 13 |
| 7.3 MAXIMUM CONDUCTED OUTPUT POWER | 14 |
| 7.3.1 E.U.T. Operation | 14 |
| 7.3.2 Test Setup Diagram | 14 |
| 7.3.3 Measurement Procedure and Data | 15 |
| 7.4 PEAK POWER SPECTRUM DENSITY | 16 |
| 7.4.1 E.U.T. Operation | 16 |
| 7.4.2 Test Setup Diagram | 16 |
| 7.4.3 Measurement Procedure and Data | 16 |
| 7.5 RADIATED EMISSIONS | 17 |
| 7.5.1 E.U.T. Operation | 17 |
| 7.5.2 Test Setup Diagram | 17 |
| 7.5.3 Measurement Procedure and Data | 18 |
| 7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS..... | 31 |
| 7.6.1 E.U.T. Operation | 32 |
| 7.6.2 Test Setup Diagram | 32 |
| 7.6.3 Measurement Procedure and Data | 33 |
| 7.7 FREQUENCY STABILITY..... | 84 |

| | | |
|----------|---|-----------|
| 7.7.1 | <i>E.U.T. Operation</i> | 84 |
| 7.7.2 | <i>Test Setup Diagram</i> | 84 |
| 7.7.3 | <i>Measurement Procedure and Data</i> | 84 |
| 8 | TEST SETUP PHOTOGRAPHS | 85 |
| 9 | EUT CONSTRUCTIONAL DETAILS | 85 |

4 General Information

4.1 Details of E.U.T.

| | |
|-----------------------|---|
| Power supply: | DC 3.3V |
| Test voltage: | DC3.3V |
| Antenna Gain | Antenna 0: 6dBi, Antenna 1: 6dBi |
| Antenna Type | Connector Antenna |
| Operation Frequency: | 802.11a/n(HT20)/ac(HT20): 5180-5240MHz, 5745MHz-5825MHz 802.11n(HT40)/ac(HT40): 5190-5230MHz, 5755MHz-5795MHz |
| Modulation Technique: | OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK) Remark: 256QAM for 802.11 ac only |
| | 802.11a: 6/9/12/18/24/36/48/54Mbps |
| Data Rate: | 802.11n: MCS0-15 802.11ac: MCS0-9 |
| Number of Channel: | 802.11 a/n(HT20)/ac(HT20): 9 Channel 36, 40, 44, 48, 149, 153, 157, 161, 165 802.11 n(HT40)/ac(HT40): 4 Channel 38, 46, 151, 159 |

4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|--------------|--------------|----------------|------------|
| Laptop | Lenovo | ThinkPad X100e | / |
| Test Fixture | / | / | / |

4.3 Measurement Uncertainty

| No. | Item | Measurement Uncertainty |
|-----|---------------------------------|--|
| 1 | Radio Frequency | 7.25 x 10-8 |
| 2 | Timeout | 2s |
| 3 | Duty cycle | 0.37% |
| 4 | Occupied Bandwidth | 3% |
| 5 | RF conducted power | 0.75dB |
| 6 | RF power density | 2.84dB |
| 7 | Conducted Spurious emissions | 0.75dB |
| 8 | RF Radiated power | 4.5dB (Below 1GHz) 4.8dB (Above 1GHz) |
| 9 | Radiated Spurious emission test | 4.2dB (Below 30MHz) 4.4dB (30MHz-1GHz) 4.6dB (1GHz-18GHz) 5.2dB (Above 18GHz) |
| 10 | Temperature test | 1°C |
| 11 | Humidity test | 3% |
| 12 | Supply voltages | 1.5% |
| 13 | Time | 3% |

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|---------------------------|--------------|--------------------|--------------|------------|--------------|
| Conducted Test | | | | | |
| Spectrum Analyzer | R&S | FSP-30 | SHEM002-1 | 2017-12-20 | 2018-12-19 |
| Spectrum Analyzer | Agilent | N9020A | SHEM181-1 | 2017-09-26 | 2018-09-25 |
| Power meter | R&S | NRP | SHEM057-1 | 2017-12-26 | 2018-12-25 |
| Power Sensor | R&S | NRP-Z22 | SHEM136-1 | 2017-07-22 | 2018-07-21 |
| Power Sensor | R&S | NRP-Z91 | SHEM057-2 | 2017-12-26 | 2018-12-25 |
| Signal Generator | R&S | SMR40 | SHEM058-1 | 2017-07-03 | 2018-07-02 |
| Signal Generator | Agilent | N5182A | SHEM182-1 | 2017-09-26 | 2018-09-25 |
| Communication Tester | R&S | CMW270 | SHEM183-1 | 2017-10-22 | 2018-10-21 |
| Switcher | Tonscend | JS0806 | SHEM184-1 | 2017-09-26 | 2018-09-25 |
| Splitter | Anritsu | MA1612A | SHEM185-1 | / | / |
| Coupler | e-meca | 803-S-1 | SHEM186-1 | / | / |
| High-low Temp Cabinet | Suzhou Zhihe | TL-40 | SHEM087-1 | 2017-09-26 | 2018-09-25 |
| AC Power Stabilizer | WOCEN | 6100 | SHEM045-1 | 2017-12-26 | 2018-12-25 |
| DC Power Supply | QJE | QJ30003SII | SHEM046-1 | 2017-12-26 | 2018-12-25 |
| Conducted test Cable | / | RF01, RF 02 | / | 2017-12-26 | 2018-12-25 |
| Radiated Test | | | | | |
| EMI test receiver | R&S | ESU40 | SHEM051-1 | 2017-12-20 | 2018-12-19 |
| Spectrum Analyzer | R&S | FSP-30 | SHEM002-1 | 2017-12-20 | 2018-12-19 |
| Loop Antenna (9kHz-30MHz) | Schwarzbeck | FMZB1519 | SHEM135-1 | 2017-04-10 | 2020-04-09 |
| Antenna (25MHz-2GHz) | Schwarzbeck | VULB9168 | SHEM048-1 | 2017-02-28 | 2020-02-27 |
| Antenna (25MHz-3GHz) | Schwarzbeck | HL562 | SHEM010-1 | 2017-02-28 | 2020-02-27 |
| Horn Antenna (1-8GHz) | Schwarzbeck | HF906 | SHEM009-1 | 2017-10-24 | 2020-10-23 |
| Horn Antenna (1-18GHz) | Schwarzbeck | BBHA9120D | SHEM050-1 | 2017-01-14 | 2020-01-13 |
| Horn Antenna (14-40GHz) | Schwarzbeck | BBHA 9170 | SHEM049-1 | 2017-12-03 | 2020-12-02 |
| Pre-amplifier (9KHz-2GHz) | CLAVIIO | BDLNA-0001-412010 | SHEM164-1 | 2017-08-22 | 2018-08-21 |
| Pre-amplifier (1-18GHz) | CLAVIIO | BDLNA-0118-352810 | SHEM050-2 | 2017-08-22 | 2018-08-21 |
| High-amplifier (14-40GHz) | Schwarzbeck | 10001 | SHEM049-2 | 2017-12-20 | 2018-12-19 |
| Band filter | LORCH | 9BRX-875/X150-SR | SHEM156-1 | / | / |
| Band filter | LORCH | 13BRX-1950/X500-SR | SHEM083-2 | / | / |
| Band filter | LORCH | 5BRX-2400/X200-SR | SHEM155-1 | / | / |
| Band filter | LORCH | 5BRX-5500/X1000-SR | SHEM157-2 | / | / |
| High pass Filter | Wainwright | WHK3.0/18G-100SS | SHEM157-1 | / | / |
| High pass Filter | Wainwright | WHKS1700-3SS | SHEM157-3 | / | / |
| Semi/Fully Anechoic | ST | 11*6*6M | SHEM078-2 | 2017-07-22 | 2020-07-21 |
| RE test Cable | / | RE01, RE02, RE06 | / | 2017-12-26 | 2018-12-25 |

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203


6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Connector Antenna and no consideration of replacement. The best case gain of the antenna0 is 6dBi and antenna1 is 6dBi



6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.407 (c)

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip (Marvell 88W8897) support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.

7 Radio Spectrum Matter Test Results

7.1 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)


Test Method: KDB 789033 D02 II C 1

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEMA180400246702

7.2 Minimum 6 dB bandwidth (5.725-5.85 GHz band)

Test Requirement 47 CFR Part 15, Subpart C 15.407 (e)

Test Method: KDB 789033 D02 II C 2


Limit: ≥ 500 kHz

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEMA180400246702

7.3 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

| Frequency band(MHz) | Limit |
|---------------------|---|
| 5150-5250 | $\leq 1W(30dBm)$ for master device |
| | $\leq 250mW(24dBm)$ for client device |
| 5250-5350 | $\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$ |
| 5470-5725 | $\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$ |
| 5725-5850 | $\leq 1W(30dBm)$ |


Remark: 1.*Where B is the 26dB emission bandwidth in MHz.
2.The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
3. The two antennas completely correlated with each other, so the directional gain of the two antenna in MIMO mode is 9dBi, the directional antenna gains greater than 6dBi, so the limit of conducted peak output power for 5150MHz to 5250MHz must reduce to 21dBm; the limit of conducted peak output power for 5725MHz to 5850MHz must reduce to 27dBm

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEMA180400246702

7.4 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

| Frequency band(MHz) | Limit |
|---------------------|----------------------------------|
| 5150-5250 | ≤17dBm in 1MHz for master device |
| | ≤11dBm in 1MHz for client device |
| 5250-5350 | ≤11dBm in 1MHz for client device |
| 5470-5725 | ≤11dBm in 1MHz for client device |
| 5725-5850 | ≤30dBm in 500 kHz |

Remark: 1. The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.


2. The two antennas completely correlated with each other, so the directional gain of the two antenna in MIMO mode is 9dBi, the directional antenna gains greater than 6dBi, so the limit of conducted PSD for 5150MHz to 5250MHz must reduce to 8dBm; the limit of conducted PSD for 5725MHz to 5850MHz must reduce to 27dBm

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEMA180400246702

7.5 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.407(b)

Test Method: KDB 789033 D02 II G

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode b: TX mode (Band 1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

c: TX mode (Band 3)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
5. Peak limit for Band 1 is -27dBm/MHz, according $EIRP[dBm] = E[dB\mu V/m] - 95.2$, So the converted "E" value is 68.2dB μ V/m
6. This test item was investigated while operating in SISO and MIMO mode, however, it was determined that SISO antenna 1 operation for a modulation and MIMO antenna operation for n/ac modulation produced the worst emissions. So the emissions produced from other operation are not report.

Below 1GHz


Mode:b; Polarization:Horizontal

**Antenna Polarity :HORIZONTAL****Test mode :b**

| | Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|--------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| | MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 | 35.25 | 40.11 | 15.86 | 0.20 | 42.61 | 13.56 | 40.00 | -26.44 | QP |
| 2 | 160.91 | 49.21 | 12.93 | 0.64 | 42.59 | 20.19 | 43.50 | -23.31 | QP |
| 3 | 250.30 | 53.22 | 11.50 | 0.77 | 42.46 | 23.03 | 46.00 | -22.97 | QP |
| 4 | 378.58 | 53.88 | 14.73 | 0.96 | 42.16 | 27.41 | 46.00 | -18.59 | QP |
| 5 | 434.07 | 47.72 | 15.87 | 1.06 | 42.11 | 22.54 | 46.00 | -23.46 | QP |
| 6 | 737.07 | 42.74 | 20.87 | 1.85 | 42.53 | 22.93 | 46.00 | -23.07 | QP |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical

**Antenna Polarity :VERTICAL****Test mode :b**

| | Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|--------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| | MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 | 35.62 | 53.28 | 15.90 | 0.21 | 42.61 | 26.78 | 40.00 | -13.22 | QP |
| 2 | 44.12 | 48.44 | 13.81 | 0.24 | 42.63 | 19.86 | 40.00 | -20.14 | QP |
| 3 | 71.58 | 48.98 | 10.86 | 0.34 | 42.67 | 17.51 | 40.00 | -22.49 | QP |
| 4 | 107.51 | 54.43 | 9.58 | 0.49 | 42.70 | 21.80 | 43.50 | -21.70 | QP |
| 5 | 160.91 | 52.21 | 12.93 | 0.64 | 42.59 | 23.19 | 43.50 | -20.31 | QP |
| 6 | 250.30 | 45.51 | 11.50 | 0.77 | 42.46 | 15.32 | 46.00 | -30.68 | QP |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Above 1GHz

Mode:b; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 32.97 | 14.28 | 47.25 | 68.2 | -20.95 | peak |
| 15540 | 30.12 | 21.58 | 51.70 | 54 | -2.30 | peak |
| 20720 | 26.03 | 23.16 | 49.19 | 54 | -4.81 | peak |

Mode:b; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 33.17 | 14.28 | 47.45 | 68.2 | -20.75 | peak |
| 15540 | 28.02 | 21.58 | 49.60 | 54 | -4.40 | peak |
| 20720 | 30.10 | 23.16 | 53.26 | 54 | -0.74 | peak |

Mode:b; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 34.75 | 14.14 | 48.89 | 68.2 | -19.31 | peak |
| 15660 | 29.46 | 21.22 | 50.68 | 54 | -3.32 | peak |
| 20880 | 26.40 | 23.24 | 49.64 | 54 | -4.36 | peak |

Mode:b; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 35.83 | 14.14 | 49.97 | 68.2 | -18.23 | peak |
| 15660 | 25.90 | 21.22 | 47.12 | 54 | -6.88 | peak |
| 20880 | 29.52 | 23.24 | 52.76 | 54 | -1.24 | peak |

Mode:b; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 32.98 | 14.08 | 47.06 | 68.2 | -21.14 | peak |
| 15720 | 32.15 | 21.10 | 53.25 | 54 | -0.75 | peak |
| 20960 | 25.94 | 23.64 | 49.58 | 54 | -4.42 | peak |

Mode:b; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 33.38 | 14.08 | 47.46 | 68.2 | -20.74 | peak |
| 15720 | 27.60 | 21.10 | 48.70 | 54 | -5.30 | peak |
| 20960 | 27.31 | 23.64 | 50.95 | 54 | -3.05 | peak |

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 29.32 | 14.28 | 43.60 | 68.2 | -24.60 | peak |
| 15540 | 26.01 | 21.58 | 47.59 | 54 | -6.41 | peak |
| 20720 | 26.67 | 23.16 | 49.83 | 54 | -4.17 | peak |

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 34.32 | 14.28 | 48.60 | 68.2 | -19.60 | peak |
| 15540 | 29.08 | 21.58 | 50.66 | 54 | -3.34 | peak |
| 20720 | 27.44 | 23.16 | 50.60 | 54 | -3.40 | peak |

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 30.90 | 14.14 | 45.04 | 68.2 | -23.16 | peak |
| 15660 | 28.94 | 21.22 | 50.16 | 54 | -3.84 | peak |
| 20880 | 27.20 | 23.24 | 50.44 | 54 | -3.56 | peak |

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 34.06 | 14.14 | 48.20 | 68.2 | -20.00 | peak |
| 15660 | 26.56 | 21.22 | 47.78 | 54 | -6.22 | peak |
| 20880 | 27.62 | 23.24 | 50.86 | 54 | -3.14 | peak |

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 30.29 | 14.08 | 44.37 | 68.2 | -23.83 | peak |
| 15720 | 26.82 | 21.10 | 47.92 | 54 | -6.08 | peak |
| 20960 | 29.99 | 23.64 | 53.63 | 54 | -0.37 | peak |

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 31.80 | 14.08 | 45.88 | 68.2 | -22.32 | peak |
| 15720 | 27.92 | 21.10 | 49.02 | 54 | -4.98 | peak |
| 20960 | 27.04 | 23.64 | 50.68 | 54 | -3.32 | peak |

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10380 | 30.89 | 14.25 | 45.14 | 68.2 | -23.06 | peak |
| 15570 | 30.68 | 21.49 | 52.17 | 54 | -1.83 | peak |
| 20760 | 28.36 | 23.16 | 51.52 | 54 | -2.48 | peak |

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10380 | 31.14 | 14.25 | 45.39 | 68.2 | -22.81 | peak |
| 15570 | 31.22 | 21.49 | 52.71 | 54 | -1.29 | peak |
| 20760 | 29.14 | 23.16 | 52.30 | 54 | -1.70 | peak |

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10460 | 32.82 | 14.11 | 46.93 | 68.2 | -21.27 | peak |
| 15690 | 28.83 | 21.14 | 49.97 | 54 | -4.03 | peak |
| 20920 | 25.01 | 23.31 | 48.32 | 54 | -5.68 | peak |

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10460 | 33.04 | 14.11 | 47.15 | 68.2 | -21.05 | peak |
| 15690 | 30.58 | 21.14 | 51.72 | 54 | -2.28 | peak |
| 20920 | 26.84 | 23.31 | 50.15 | 54 | -3.85 | peak |

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 30.33 | 14.28 | 44.61 | 68.2 | -23.59 | peak |
| 15540 | 29.36 | 21.58 | 50.94 | 54 | -3.06 | peak |
| 20720 | 29.22 | 23.16 | 52.38 | 54 | -1.62 | peak |

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10360 | 29.39 | 14.28 | 43.67 | 68.2 | -24.53 | peak |
| 15540 | 27.62 | 21.58 | 49.20 | 54 | -4.80 | peak |
| 20720 | 29.92 | 23.16 | 53.08 | 54 | -0.92 | peak |

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 30.39 | 14.14 | 44.53 | 68.2 | -23.67 | peak |
| 15660 | 27.36 | 21.22 | 48.58 | 54 | -5.42 | peak |
| 20880 | 29.66 | 23.24 | 52.90 | 54 | -1.10 | peak |

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10440 | 30.72 | 14.14 | 44.86 | 68.2 | -23.34 | peak |
| 15660 | 30.47 | 21.22 | 51.69 | 54 | -2.31 | peak |
| 20880 | 27.15 | 23.24 | 50.39 | 54 | -3.61 | peak |

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 32.68 | 14.08 | 46.76 | 68.2 | -21.44 | peak |
| 15720 | 27.29 | 21.10 | 48.39 | 54 | -5.61 | peak |
| 20960 | 27.04 | 23.64 | 50.68 | 54 | -3.32 | peak |

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10480 | 35.74 | 14.08 | 49.82 | 68.2 | -18.38 | peak |
| 15720 | 26.72 | 21.10 | 47.82 | 54 | -6.18 | peak |
| 20960 | 30.00 | 23.64 | 53.64 | 54 | -0.36 | peak |

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10380 | 30.54 | 14.25 | 44.79 | 68.2 | -23.41 | peak |
| 15570 | 28.11 | 21.49 | 49.60 | 54 | -4.40 | peak |
| 20760 | 27.60 | 23.16 | 50.76 | 54 | -3.24 | peak |

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10380 | 31.96 | 14.25 | 46.21 | 68.2 | -21.99 | peak |
| 15570 | 29.16 | 21.49 | 50.65 | 54 | -3.35 | peak |
| 20760 | 28.87 | 23.16 | 52.03 | 54 | -1.97 | peak |

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10460 | 32.41 | 14.11 | 46.52 | 68.2 | -21.68 | peak |
| 15690 | 27.91 | 21.14 | 49.05 | 54 | -4.95 | peak |
| 20920 | 28.40 | 23.31 | 51.71 | 54 | -2.29 | peak |

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 10460 | 35.35 | 14.11 | 49.46 | 68.2 | -18.74 | peak |
| 15690 | 27.94 | 21.14 | 49.08 | 54 | -4.92 | peak |
| 20920 | 27.44 | 23.31 | 50.75 | 54 | -3.25 | peak |

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11490 | 34.58 | 14.41 | 48.99 | 54 | -5.01 | peak |
| 17235 | 25.89 | 22.57 | 48.46 | 68.2 | -19.74 | peak |
| 22980 | 27.34 | 24.45 | 51.79 | 54 | -2.21 | peak |

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11490 | 32.93 | 14.41 | 47.34 | 54 | -6.66 | peak |
| 17235 | 28.71 | 22.57 | 51.28 | 68.2 | -16.92 | peak |
| 22980 | 27.59 | 24.45 | 52.04 | 54 | -1.96 | peak |

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 33.15 | 14.25 | 47.40 | 54 | -6.60 | peak |
| 17355 | 26.93 | 21.86 | 48.79 | 68.2 | -19.41 | peak |
| 23140 | 26.50 | 24.68 | 51.18 | 68.2 | -17.02 | peak |

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 34.57 | 14.25 | 48.82 | 54 | -5.18 | peak |
| 17355 | 25.97 | 21.86 | 47.83 | 68.2 | -20.37 | peak |
| 23140 | 27.27 | 24.68 | 51.95 | 68.2 | -16.25 | peak |

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 32.15 | 14.06 | 46.21 | 54 | -7.79 | peak |
| 17475 | 25.15 | 21.15 | 46.30 | 68.2 | -21.90 | peak |
| 23300 | 24.98 | 25.11 | 50.09 | 68.2 | -18.11 | peak |

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 33.96 | 14.06 | 48.02 | 54 | -5.98 | peak |
| 17475 | 27.00 | 21.15 | 48.15 | 68.2 | -20.05 | peak |
| 23300 | 23.57 | 25.11 | 48.68 | 68.2 | -19.52 | peak |

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11490 | 31.04 | 14.41 | 45.45 | 54 | -8.55 | peak |
| 17235 | 28.30 | 22.57 | 50.87 | 68.2 | -17.33 | peak |
| 22980 | 27.36 | 24.45 | 51.81 | 54 | -2.19 | peak |

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11490 | 33.72 | 14.41 | 48.13 | 54 | -5.87 | peak |
| 17235 | 26.73 | 22.57 | 49.30 | 68.2 | -18.90 | peak |
| 22980 | 26.61 | 24.45 | 51.06 | 54 | -2.94 | peak |

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 33.91 | 14.25 | 48.16 | 54 | -5.84 | peak |
| 17355 | 26.20 | 21.86 | 48.06 | 68.2 | -20.14 | peak |
| 23140 | 25.20 | 24.68 | 49.88 | 68.2 | -18.32 | peak |

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 31.06 | 14.25 | 45.31 | 54 | -8.69 | peak |
| 17355 | 28.16 | 21.86 | 50.02 | 68.2 | -18.18 | peak |
| 23140 | 25.08 | 24.68 | 49.76 | 68.2 | -18.44 | peak |

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 32.60 | 14.06 | 46.66 | 54 | -7.34 | peak |
| 17475 | 29.81 | 21.15 | 50.96 | 68.2 | -17.24 | peak |
| 23300 | 27.54 | 25.11 | 52.65 | 68.2 | -15.55 | peak |

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 34.73 | 14.06 | 48.79 | 54 | -5.21 | peak |
| 17475 | 29.86 | 21.15 | 51.01 | 68.2 | -17.19 | peak |
| 23300 | 27.60 | 25.11 | 52.71 | 68.2 | -15.49 | peak |

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11510 | 34.36 | 14.40 | 48.76 | 54 | -5.24 | peak |
| 17265 | 26.04 | 22.40 | 48.44 | 68.2 | -19.76 | peak |
| 23020 | 25.10 | 24.68 | 49.78 | 54 | -4.22 | peak |

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11510 | 32.20 | 14.40 | 46.60 | 54 | -7.40 | peak |
| 17265 | 28.75 | 22.40 | 51.15 | 68.2 | -17.05 | peak |
| 23020 | 28.03 | 24.68 | 52.71 | 54 | -1.29 | peak |

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11590 | 33.34 | 14.20 | 47.54 | 54 | -6.46 | peak |
| 17385 | 26.87 | 21.68 | 48.55 | 68.2 | -19.65 | peak |
| 23180 | 24.62 | 24.72 | 49.34 | 68.2 | -18.86 | peak |

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11590 | 33.00 | 14.20 | 47.20 | 54 | -6.80 | peak |
| 17385 | 27.47 | 21.68 | 49.15 | 68.2 | -19.05 | peak |
| 23180 | 29.00 | 24.72 | 53.72 | 68.2 | -14.48 | peak |

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector | |
|-----------|-------|--------|----------|--------|--------|----------|--|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 11490 | 34.74 | 14.41 | 49.15 | 54 | -4.85 | peak | |
| 17235 | 28.48 | 22.57 | 51.05 | 68.2 | -17.15 | peak | |
| 22980 | 29.04 | 24.45 | 53.49 | 54 | -0.51 | peak | |
| | | | | | | | |
| | | | | | | | |

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11490 | 36.82 | 14.41 | 51.23 | 54 | -2.77 | peak |
| 17235 | 25.98 | 22.57 | 48.55 | 68.2 | -19.65 | peak |
| 22980 | 26.51 | 24.45 | 50.96 | 54 | -3.04 | peak |

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 35.89 | 14.25 | 50.14 | 54 | -3.86 | peak |
| 17355 | 27.52 | 21.86 | 49.38 | 68.2 | -18.82 | peak |
| 23140 | 28.41 | 24.68 | 53.09 | 68.2 | -15.11 | peak |

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11570 | 36.16 | 14.25 | 50.41 | 54 | -3.59 | peak |
| 17355 | 29.84 | 21.86 | 51.70 | 68.2 | -16.50 | peak |
| 23140 | 29.28 | 24.68 | 53.96 | 68.2 | -14.24 | peak |

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 33.55 | 14.06 | 47.61 | 54 | -6.39 | peak |
| 17475 | 28.58 | 21.15 | 49.73 | 68.2 | -18.47 | peak |
| 23300 | 27.28 | 25.11 | 52.39 | 68.2 | -15.81 | peak |

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11650 | 33.34 | 14.06 | 47.40 | 54 | -6.60 | peak |
| 17475 | 27.31 | 21.15 | 48.46 | 68.2 | -19.74 | peak |
| 23300 | 29.66 | 25.11 | 54.77 | 68.2 | -13.43 | peak |

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11510 | 30.97 | 14.40 | 45.37 | 54 | -8.63 | peak |
| 17265 | 28.19 | 22.40 | 50.59 | 68.2 | -17.61 | peak |
| 23020 | 26.89 | 24.68 | 51.57 | 54 | -2.43 | peak |

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11510 | 31.61 | 14.40 | 46.01 | 54 | -7.99 | peak |
| 17265 | 27.72 | 22.40 | 50.12 | 68.2 | -18.08 | peak |
| 23020 | 28.23 | 24.68 | 52.91 | 54 | -1.09 | peak |

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

| Frequency | RX_R | Factor | Emission | Limit | Margin | Detector |
|-----------|-------|--------|----------|--------|--------|----------|
| MHz | dBuV | dB | dBuV/m | dBuV/m | dB | |
| 11590 | 35.06 | 14.20 | 49.26 | 54 | -4.74 | peak |
| 17385 | 28.01 | 21.68 | 49.69 | 68.2 | -18.51 | peak |
| 23180 | 23.30 | 24.72 | 48.02 | 68.2 | -20.18 | peak |

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

| Frequency MHz | RX_R dBuV | Factor dB | Emission dBuV/m | Limit dBuV/m | Margin dB | Detector |
|------------------|--------------|--------------|--------------------|-----------------|--------------|----------|
| 11590 | 33.88 | 14.20 | 48.08 | 54 | -5.92 | peak |
| 17385 | 25.81 | 21.68 | 47.49 | 68.2 | -20.71 | peak |
| 23180 | 27.72 | 24.72 | 52.44 | 68.2 | -15.76 | peak |

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode

b: TX mode (Band 1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

c: TX mode (Band 3)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram




7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

- h. This test item was investigated while operating in SISO and MIMO mode, however, it was determined that SISO antenna 1 operation for a modulation and MIMO antenna operation for n/ac modulation produced the worst emissions. So the emissions produced from other operation are not report.

Mode:b; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5015.28 | 44.43 | 31.42 | 9.81 | 38.88 | 46.78 | 74.00 | -27.22 | Peak |
| 2 5150.00 | 45.75 | 31.61 | 9.06 | 38.81 | 47.61 | 74.00 | -26.39 | Peak |
| 3 5187.91 | 91.83 | 31.68 | 8.86 | 38.79 | 93.58 | 74.00 | 19.58 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5142.51 | 47.53 | 31.61 | 9.06 | 38.81 | 49.39 | 74.00 | -24.61 | Peak |
| 2 5150.00 | 46.78 | 31.61 | 9.06 | 38.81 | 48.64 | 74.00 | -25.36 | Peak |
| 3 5187.15 | 95.91 | 31.68 | 8.86 | 38.79 | 97.66 | 74.00 | 23.66 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5238.04 | 93.84 | 31.74 | 8.68 | 38.77 | 95.49 | 74.00 | 21.49 | Peak |
| 2 5350.00 | 42.12 | 31.89 | 9.20 | 38.70 | 44.51 | 74.00 | -29.49 | Peak |
| 3 5411.89 | 44.06 | 31.97 | 9.44 | 38.67 | 46.80 | 74.00 | -27.20 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:b; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5239.10 | 98.35 | 31.74 | 8.68 | 38.77 | 100.00 | 74.00 | 26.00 | Peak |
| 2 5350.00 | 41.75 | 31.89 | 9.20 | 38.70 | 44.14 | 74.00 | -29.86 | Peak |
| 3 5404.22 | 45.00 | 31.97 | 9.44 | 38.67 | 47.74 | 74.00 | -26.26 | Peak |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5087.81 | 45.61 | 31.53 | 9.44 | 38.84 | 47.74 | 74.00 | -26.26 | Peak |
| 2 5150.00 | 46.41 | 31.61 | 9.06 | 38.81 | 48.27 | 74.00 | -25.73 | Peak |
| 3 5187.91 | 91.30 | 31.68 | 8.86 | 38.79 | 93.05 | 74.00 | 19.05 | Peak |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

| | Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| | MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 | 5145.52 | 48.67 | 31.61 | 9.06 | 38.81 | 50.53 | 74.00 | -23.47 | Peak |
| 2 | 5150.00 | 50.60 | 31.61 | 9.06 | 38.81 | 52.46 | 74.00 | -21.54 | Peak |
| 3 | 5171.98 | 97.06 | 31.65 | 8.86 | 38.80 | 98.77 | 74.00 | 24.77 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5242.55 | 96.27 | 31.74 | 8.68 | 38.77 | 97.92 | 74.00 | 23.92 | Peak |
| 2 5350.00 | 42.37 | 31.89 | 9.20 | 38.70 | 44.76 | 74.00 | -29.24 | Peak |
| 3 5416.00 | 44.54 | 31.97 | 9.34 | 38.67 | 47.18 | 74.00 | -26.82 | Peak |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:b; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5247.33 | 100.97 | 31.76 | 8.68 | 38.76 | 102.65 | 74.00 | 28.65 | Peak |
| 2 5350.00 | 42.36 | 31.89 | 9.20 | 38.70 | 44.75 | 74.00 | -29.25 | Peak |
| 3 5424.50 | 44.98 | 31.99 | 9.34 | 38.66 | 47.65 | 74.00 | -26.35 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5131.87 | 46.74 | 31.59 | 9.06 | 38.82 | 48.57 | 74.00 | -25.43 | Peak |
| 2 5150.00 | 49.52 | 31.61 | 9.06 | 38.81 | 51.38 | 74.00 | -22.62 | Peak |
| 3 5204.12 | 92.45 | 31.70 | 8.66 | 38.78 | 94.03 | 74.00 | 20.03 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq MHz | Read Level dBuv | Antenna Factor dB/m | Cable Loss dB | Preamp Factor dB | Emission Level dBuv/m | Limit Line dBuv/m | Over Limit dB | Remark |
|-------------|-----------------------|---------------------------|---------------------|------------------------|-----------------------------|-------------------------|---------------------|--------|
| | ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- |
| 1 5143.45 | 51.24 | 31.61 | 9.06 | 38.81 | 53.10 | 74.00 | -20.90 | Peak |
| 2 5150.00 | 51.32 | 31.61 | 9.06 | 38.81 | 53.18 | 74.00 | -20.82 | Peak |
| 3 5193.96 | 95.41 | 31.68 | 8.86 | 38.79 | 97.16 | 74.00 | 23.16 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- |
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5245.47 | 92.37 | 31.74 | 8.68 | 38.77 | 94.02 | 74.00 | 20.02 | Peak |
| 2 5350.00 | 42.82 | 31.89 | 9.20 | 38.70 | 45.21 | 74.00 | -28.79 | Peak |
| 3 5406.68 | 44.49 | 31.97 | 9.44 | 38.67 | 47.23 | 74.00 | -26.77 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:b; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| 1 5245.47 | 97.37 | 31.74 | 8.68 | 38.77 | 99.02 | 74.00 | 25.02 | Peak |
| 2 5350.00 | 41.79 | 31.89 | 9.20 | 38.70 | 44.18 | 74.00 | -29.82 | Peak |
| 3 5411.89 | 44.83 | 31.97 | 9.44 | 38.67 | 47.57 | 74.00 | -26.43 | Peak |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5065.49 | 45.23 | 31.48 | 9.44 | 38.86 | 47.29 | 74.00 | -26.71 | Peak |
| 2 5150.00 | 47.00 | 31.61 | 9.06 | 38.81 | 48.86 | 74.00 | -25.14 | Peak |
| 3 5177.28 | 93.67 | 31.65 | 8.86 | 38.80 | 95.38 | 74.00 | 21.38 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:b; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5141.76 | 49.63 | 31.59 | 9.06 | 38.82 | 51.46 | 74.00 | -22.54 | Peak |
| 2 5150.00 | 50.39 | 31.61 | 9.06 | 38.81 | 52.25 | 74.00 | -21.75 | Peak |
| 3 5183.35 | 95.28 | 31.65 | 8.86 | 38.80 | 96.99 | 74.00 | 22.99 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5241.49 | 95.65 | 31.74 | 8.68 | 38.77 | 97.30 | 74.00 | 23.30 | Peak |
| 2 5350.00 | 42.68 | 31.89 | 9.20 | 38.70 | 45.07 | 74.00 | -28.93 | Peak |
| 3 5434.67 | 45.78 | 32.02 | 9.34 | 38.65 | 48.49 | 74.00 | -25.51 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| 1 5244.94 | 100.13 | 31.74 | 8.68 | 38.77 | 101.78 | 74.00 | 27.78 | Peak |
| 2 5350.00 | 41.63 | 31.89 | 9.20 | 38.70 | 44.02 | 74.00 | -29.98 | Peak |
| 3 5431.10 | 45.22 | 31.99 | 9.34 | 38.66 | 47.89 | 74.00 | -26.11 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5144.22 | 49.52 | 31.61 | 9.06 | 38.81 | 51.38 | 74.00 | -22.62 | Peak |
| 2 5150.00 | 50.76 | 31.61 | 9.06 | 38.81 | 52.62 | 74.00 | -21.38 | Peak |
| 3 5197.86 | 92.62 | 31.68 | 8.86 | 38.79 | 94.37 | 74.00 | 20.37 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:b; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5145.77 | 50.12 | 31.61 | 9.06 | 38.81 | 51.98 | 74.00 | -22.02 | Peak |
| 2 5150.00 | 50.23 | 31.61 | 9.06 | 38.81 | 52.09 | 74.00 | -21.91 | Peak |
| 3 5198.65 | 94.13 | 31.68 | 8.86 | 38.79 | 95.88 | 74.00 | 21.88 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:b; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5242.82 | 89.65 | 31.74 | 8.68 | 38.77 | 91.30 | 74.00 | 17.30 | Peak |
| 2 5350.00 | 42.38 | 31.89 | 9.20 | 38.70 | 44.77 | 74.00 | -29.23 | Peak |
| 3 5414.90 | 44.61 | 31.97 | 9.34 | 38.67 | 47.25 | 74.00 | -26.75 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:b; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5225.33 | 96.17 | 31.72 | 8.66 | 38.78 | 97.77 | 74.00 | 23.77 | Peak |
| 2 5350.00 | 43.32 | 31.89 | 9.20 | 38.70 | 45.71 | 74.00 | -28.29 | Peak |
| 3 5415.18 | 44.96 | 31.97 | 9.34 | 38.67 | 47.60 | 74.00 | -26.40 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5723.92 | 65.22 | 32.15 | 9.00 | 38.75 | 67.62 | 74.00 | -6.38 | Peak |
| 2 5725.00 | 63.24 | 32.15 | 9.00 | 38.75 | 65.64 | 74.00 | -8.36 | Peak |
| 3 5742.15 | 96.27 | 32.15 | 9.00 | 38.76 | 98.66 | 74.00 | 24.66 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| | Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|---------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| | MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 | 5722.78 | 44.68 | 32.15 | 9.00 | 38.75 | 47.08 | 54.00 | -6.92 | Average |
| 2 | 5725.00 | 46.31 | 32.15 | 9.00 | 38.75 | 48.71 | 54.00 | -5.29 | Average |
| 3 | 5742.53 | 83.61 | 32.15 | 9.00 | 38.76 | 86.00 | 54.00 | 32.00 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5723.54 | 61.17 | 32.15 | 9.00 | 38.75 | 63.57 | 74.00 | -10.43 | Peak |
| 2 5725.00 | 58.59 | 32.15 | 9.00 | 38.75 | 60.99 | 74.00 | -13.01 | Peak |
| 3 5747.48 | 94.85 | 32.15 | 9.00 | 38.76 | 97.24 | 74.00 | 23.24 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5723.54 | 42.45 | 32.15 | 9.00 | 38.75 | 44.85 | 54.00 | -9.15 | Average |
| 2 5725.00 | 43.92 | 32.15 | 9.00 | 38.75 | 46.32 | 54.00 | -7.68 | Average |
| 3 5742.53 | 84.22 | 32.15 | 9.00 | 38.76 | 86.61 | 54.00 | 32.61 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5827.40 | 96.63 | 32.17 | 8.87 | 38.77 | 98.90 | 74.00 | 24.90 | Peak |
| 2 5850.00 | 49.48 | 32.17 | 8.90 | 38.75 | 51.80 | 74.00 | -22.20 | Peak |
| 3 5860.08 | 48.28 | 32.17 | 8.90 | 38.74 | 50.61 | 74.00 | -23.39 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5724.67 | 64.78 | 32.15 | 9.00 | 38.75 | 67.18 | 74.00 | -6.82 | Peak |
| 2 5725.00 | 62.13 | 32.15 | 9.00 | 38.75 | 64.53 | 74.00 | -9.47 | Peak |
| 3 5743.29 | 97.26 | 32.15 | 9.00 | 38.76 | 99.65 | 74.00 | 25.65 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5723.92 | 46.74 | 32.15 | 9.00 | 38.75 | 49.14 | 54.00 | -4.86 | Average |
| 2 5725.00 | 45.25 | 32.15 | 9.00 | 38.75 | 47.65 | 54.00 | -6.35 | Average |
| 3 5743.68 | 86.41 | 32.15 | 9.00 | 38.76 | 88.80 | 54.00 | 34.80 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5722.02 | 62.75 | 32.14 | 9.00 | 38.74 | 65.15 | 74.00 | -8.85 | Peak |
| 2 5725.00 | 62.23 | 32.15 | 9.00 | 38.75 | 64.63 | 74.00 | -9.37 | Peak |
| 3 5745.96 | 98.48 | 32.15 | 9.00 | 38.76 | 100.87 | 74.00 | 26.87 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| | Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|---------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| | MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 | 5722.02 | 45.06 | 32.14 | 9.00 | 38.74 | 47.46 | 54.00 | -6.54 | Average |
| 2 | 5725.00 | 46.18 | 32.15 | 9.00 | 38.75 | 48.58 | 54.00 | -5.42 | Average |
| 3 | 5746.34 | 88.67 | 32.15 | 9.00 | 38.76 | 91.06 | 54.00 | 37.06 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5822.46 | 94.14 | 32.17 | 8.87 | 38.77 | 96.41 | 74.00 | 22.41 | Peak |
| 2 5850.00 | 48.37 | 32.17 | 8.90 | 38.75 | 50.69 | 74.00 | -23.31 | Peak |
| 3 5857.70 | 48.86 | 32.17 | 8.90 | 38.74 | 51.19 | 74.00 | -22.81 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5827.20 | 99.91 | 32.17 | 8.87 | 38.77 | 102.18 | 74.00 | 28.18 | Peak |
| 2 5850.00 | 58.84 | 32.17 | 8.90 | 38.75 | 61.16 | 74.00 | -12.84 | Peak |
| 3 5853.73 | 60.93 | 32.17 | 8.90 | 38.75 | 63.25 | 74.00 | -10.75 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5822.26 | 88.33 | 32.17 | 8.87 | 38.77 | 90.60 | 54.00 | 36.60 | Average |
| 2 5850.00 | 37.29 | 32.17 | 8.90 | 38.75 | 39.61 | 54.00 | -14.39 | Average |
| 3 5856.71 | 36.31 | 32.17 | 8.90 | 38.74 | 38.64 | 54.00 | -15.36 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5722.17 | 62.34 | 32.15 | 9.00 | 38.75 | 64.74 | 74.00 | -9.26 | Peak |
| 2 5725.00 | 59.00 | 32.15 | 9.00 | 38.75 | 61.40 | 74.00 | -12.60 | Peak |
| 3 5760.60 | 93.49 | 32.15 | 8.93 | 38.78 | 95.79 | 74.00 | 21.79 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5719.77 | 45.70 | 32.14 | 9.00 | 38.74 | 48.10 | 54.00 | -5.90 | Average |
| 2 5725.00 | 46.18 | 32.15 | 9.00 | 38.75 | 48.58 | 54.00 | -5.42 | Average |
| 3 5759.40 | 83.12 | 32.15 | 8.93 | 38.78 | 85.42 | 54.00 | 31.42 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5723.76 | 63.66 | 32.15 | 9.00 | 38.75 | 66.06 | 74.00 | -7.94 | Peak |
| 2 5725.00 | 58.82 | 32.15 | 9.00 | 38.75 | 61.22 | 74.00 | -12.78 | Peak |
| 3 5760.60 | 94.38 | 32.15 | 8.93 | 38.78 | 96.68 | 74.00 | 22.68 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5720.97 | 47.68 | 32.14 | 9.00 | 38.74 | 50.08 | 54.00 | -3.92 | Average |
| 2 5725.00 | 47.01 | 32.15 | 9.00 | 38.75 | 49.41 | 54.00 | -4.59 | Average |
| 3 5760.20 | 85.57 | 32.15 | 8.93 | 38.78 | 87.87 | 54.00 | 33.87 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5797.04 | 92.93 | 32.16 | 8.87 | 38.80 | 95.16 | 74.00 | 21.16 | Peak |
| 2 5850.00 | 47.17 | 32.17 | 8.90 | 38.75 | 49.49 | 74.00 | -24.51 | Peak |
| 3 5857.22 | 49.98 | 32.17 | 8.90 | 38.74 | 52.31 | 74.00 | -21.69 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5802.48 | 93.01 | 32.16 | 8.87 | 38.80 | 95.24 | 74.00 | 21.24 | Peak |
| 2 5850.00 | 48.80 | 32.17 | 8.90 | 38.75 | 51.12 | 74.00 | -22.88 | Peak |
| 3 5857.46 | 50.34 | 32.17 | 8.90 | 38.74 | 52.67 | 74.00 | -21.33 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5722.78 | 58.35 | 32.15 | 9.00 | 38.75 | 60.75 | 74.00 | -13.25 | Peak |
| 2 5725.00 | 58.94 | 32.15 | 9.00 | 38.75 | 61.34 | 74.00 | -12.66 | Peak |
| 3 5741.77 | 94.86 | 32.15 | 9.00 | 38.76 | 97.25 | 74.00 | 23.25 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5721.64 | 42.61 | 32.14 | 9.00 | 38.74 | 45.01 | 54.00 | -8.99 | Average |
| 2 5725.00 | 44.93 | 32.15 | 9.00 | 38.75 | 47.33 | 54.00 | -6.67 | Average |
| 3 5738.73 | 84.43 | 32.15 | 9.00 | 38.76 | 86.82 | 54.00 | 32.82 | Average |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5722.78 | 60.00 | 32.15 | 9.00 | 38.75 | 62.40 | 74.00 | -11.60 | Peak |
| 2 5725.00 | 60.06 | 32.15 | 9.00 | 38.75 | 62.46 | 74.00 | -11.54 | Peak |
| 3 5745.96 | 97.64 | 32.15 | 9.00 | 38.76 | 100.03 | 74.00 | 26.03 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low



| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5722.78 | 45.02 | 32.15 | 9.00 | 38.75 | 47.42 | 54.00 | -6.58 | Average |
| 2 5725.00 | 47.05 | 32.15 | 9.00 | 38.75 | 49.45 | 54.00 | -4.55 | Average |
| 3 5747.48 | 86.85 | 32.15 | 9.00 | 38.76 | 89.24 | 54.00 | 35.24 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5817.13 | 95.28 | 32.16 | 8.87 | 38.78 | 97.53 | 74.00 | 23.53 | Peak |
| 2 5850.00 | 49.09 | 32.17 | 8.90 | 38.75 | 51.41 | 74.00 | -22.59 | Peak |
| 3 5856.51 | 50.25 | 32.17 | 8.90 | 38.74 | 52.58 | 74.00 | -21.42 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5821.08 | 99.89 | 32.16 | 8.87 | 38.78 | 102.14 | 74.00 | 28.14 | Peak |
| 2 5850.00 | 50.91 | 32.17 | 8.90 | 38.75 | 53.23 | 74.00 | -20.77 | Peak |
| 3 5854.13 | 50.79 | 32.17 | 8.90 | 38.75 | 53.11 | 74.00 | -20.89 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5721.37 | 57.13 | 32.14 | 9.00 | 38.74 | 59.53 | 74.00 | -14.47 | Peak |
| 2 5725.00 | 54.80 | 32.15 | 9.00 | 38.75 | 57.20 | 74.00 | -16.80 | Peak |
| 3 5749.77 | 91.19 | 32.15 | 9.00 | 38.76 | 93.58 | 74.00 | 19.58 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5720.97 | 43.27 | 32.14 | 9.00 | 38.74 | 45.67 | 54.00 | -8.33 | Average |
| 2 5725.00 | 43.59 | 32.15 | 9.00 | 38.75 | 45.99 | 54.00 | -8.01 | Average |
| 3 5751.77 | 82.21 | 32.15 | 8.93 | 38.76 | 84.53 | 54.00 | 30.53 | Average |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- |
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5721.37 | 60.17 | 32.14 | 9.00 | 38.74 | 62.57 | 74.00 | -11.43 | Peak |
| 2 5725.00 | 59.44 | 32.15 | 9.00 | 38.75 | 61.84 | 74.00 | -12.16 | Peak |
| 3 5759.40 | 92.13 | 32.15 | 8.93 | 38.78 | 94.43 | 74.00 | 20.43 | Peak |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|---------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5721.37 | 45.81 | 32.14 | 9.00 | 38.74 | 48.21 | 54.00 | -5.79 | Average |
| 2 5725.00 | 46.53 | 32.15 | 9.00 | 38.75 | 48.93 | 54.00 | -5.07 | Average |
| 3 5749.77 | 83.22 | 32.15 | 9.00 | 38.76 | 85.61 | 54.00 | 31.61 | Average |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5800.35 | 91.54 | 32.16 | 8.87 | 38.80 | 93.77 | 74.00 | 19.77 | Peak |
| 2 5850.00 | 47.17 | 32.17 | 8.90 | 38.75 | 49.49 | 74.00 | -24.51 | Peak |
| 3 5857.22 | 49.98 | 32.17 | 8.90 | 38.74 | 52.31 | 74.00 | -21.69 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :VERTICAL**

| Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz | dBuv | dB/m | dB | dB | dBuv/m | dBuv/m | dB | |
| 1 5801.06 | 94.03 | 32.16 | 8.87 | 38.80 | 96.26 | 74.00 | 22.26 | Peak |
| 2 5850.00 | 44.84 | 32.17 | 8.90 | 38.75 | 47.16 | 74.00 | -26.84 | Peak |
| 3 5856.02 | 46.76 | 32.17 | 8.90 | 38.74 | 49.09 | 74.00 | -24.91 | Peak |

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

7.7 Frequency Stability


Test Requirement 47 CFR Part 15, Subpart C 15.407 (g)
Test Method: ANSI C63.10 (2013) Section 6.8
Limit: The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 35 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEM180400246702

8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

- End of the Report -