



RF TEST REPORT

Applicant iRay Technology Co. Ltd.
FCC ID 2ACHK-01070189
Product Wireless Digital Flat Panel Detector
Model Mars1417X
Report No. R2006A0398-R1
Issue Date November 11, 2020

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2019)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the test report.....	5
1.2. Test facility	5
1.3. Testing Location	5
2. General Description of Equipment under Test.....	6
2.1. Applicant and Manufacturer Information.....	6
2.2. General information.....	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case Results	10
5.1. Unwanted Emission	10
5.2. Conducted Emission	42
6. Main Test Instruments.....	45
ANNEX A: The EUT Appearance	46
ANNEX B: Test Setup Photos	47

Summary of measurement results

Number	Test Case	Clause in FCC rules	Verdict
1	Maximum output power	15.247(b)(3)	Refer to the module report: R1905A0235-R3
2	6 dB bandwidth	15.247(a)(2)	Refer to the module report: R1905A0235-R3
3	Power spectral density	15.247(e)	Refer to the module report: R1905A0235-R3
4	Band Edge	15.247(d)	Refer to the module report: R1905A0235-R3
5	Spurious RF Conducted Emissions	15.247(d)	Refer to the module report: R1905A0235-R3
6	Unwanted Emissions	15.247(d),15.205,15.209	PASS
7	Conducted Emissions	15.207	PASS
Date of Testing: September 24, 2020 ~November 4, 2020			
Date of Sample Received: June 23, 2020			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			



Mars1417X (Report No. R2006A0398-R1) is a variant model of WIFI-2-V897EA1 (Report No. R1905A0235-R3). Test items tested see the table below. The detailed product change description please refers to the *Mars1417X Product Change Description*.

Test Case	Original WIFI-2-V897EA1 (R1905A0235-R3)	Variant Mars1417X (R2006A0398-R1)
Maximum Average conducted output power	Only test 802.11g CH1 802.11n HT20 CH 1 802.11n HT40 CH 3/9	Refer to the module report: R1905A0235-R3
6 dB bandwidth	Only test 802.11g CH1 802.11n HT20 CH 1 802.11n HT40 CH 3/9	Refer to the module report: R1905A0235-R3
Power spectral density	Only test 802.11g CH1 802.11n HT20 CH 1 802.11n HT40 CH 3/9	Refer to the module report: R1905A0235-R3
Band Edge	Only test 802.11g CH1 802.11n HT20 CH 1 802.11n HT40 CH 3/9	Refer to the module report: R1905A0235-R3
Spurious RF Conducted Emissions	Only test 802.11g CH1 802.11n HT20 CH 1 802.11n HT40 CH 3/9	Refer to the module report: R1905A0235-R3
Unwanted Emissions	Pass	Pass
Conducted Emissions	Pass	Pass

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	iRay Technology Co. Ltd.
Applicant address	RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China
Manufacturer	iRay Technology Co. Ltd.
Manufacturer address	RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China

2.2. General information

EUT Description	
Model	Mars1417X
IMEI	/
Hardware Version	A0
Software Version	SDK:4.1.0.7574 ARM: Core: 2.1.10.69 Kernel: 1.0.4.0 FPGA: main: 2.10.6.6 MCU: 2.10.0.19
Power Supply	Battery/AC adapter
Antenna Type	Internal Antenna
Antenna Connector	A permanently attached antenna (meet with the standard FCC Part 15.203 requirement)
Antenna Gain	2.76dBi for Wi-Fi antenna 1 2.76dBi for Wi-Fi antenna 2 2.76dBi for Wi-Fi MIMO
additional beamforming gain	NA
Test Mode	802.11b 802.11g, 802.11n(HT20/HT40);
Modulation Type	802.11b: DSSS; 802.11g/n(HT20/HT40): OFDM
Operating Frequency Range(s)	802.11b/g/n(HT20): 2412 ~ 2462 MHz 802.11n(HT40): 2422 ~ 2452 MHz
EUT Accessory	
Battery	Manufacturer: iRay Technology Taicang Ltd. Model: BATTERY-KX Ratings:11.55Vdc,4700mAh



Adapter	Manufacturer: Shenzhen Longxc Power Supply Co., LTD Model: LXCP61-024300
Charger	Manufacturer: iRay Technology Taicang Ltd. Model: CHARGER-COMBO
DC cable	Manufacturer: iRay Technology Co. Ltd.
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.	

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15C (2019) Radio Frequency Devices

ANSI C63.10 (2013)

Reference standard:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the loop antenna is vertical, the others are vertical and horizontal. and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Test Mode	Data Rate		
	Antenna 1	Antenna 2	MIMO
802.11b	1 Mbps	1 Mbps	/
802.11g	6 Mbps	6 Mbps	/
802.11n HT20	MCS0	MCS0	MCS8
802.11n HT40	MCS0	MCS0	MCS8

The worst case Antenna mode for each of the following tests for Wi-Fi:

Test Cases	Antenna 1	Antenna 2	MIMO
Unwanted Emissions	802.11b/g	-	802.11n HT20 802.11n HT40
Conducted Emission	802.11b/g	-	802.11n HT20 802.11n HT40
Note: "O": test all bands			

According to RF Output power results in Original Report, MIMO was selected as the worst antenna for 802.11n HT20/ HT40. SISO Antenna 1 was selected as the worst SISO antenna for 802.11b/g.

5. Test Case Results

5.1. Unwanted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	102.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10-2013.

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. Sweep the Restricted Band and the emissions less than 20 dB below the permissible value are reported.

The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

This method refer to ANSI C63.10-2013.

The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:

Set the spectrum analyzer in the following:

9kHz~150 kHz

RBW=200Hz, VBW=1kHz/ Sweep=AUTO

150 kHz~30MHz

RBW=9KHz, VBW=30KHz,/ Sweep=AUTO

Below 1GHz

RBW=100kHz / VBW=300kHz / Sweep=AUTO

a) Peak emission levels are measured by setting the instrument as follows:

Above 1GHz

PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

b) Average emission levels are measured by setting the instrument as follows:

Above 1GHz

AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

c) Detector: The measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands

are based on measurements employing an average detector.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.


2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.


The test is in transmitting mode.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 15.247(d) specifies that “In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).”

Limit in restricted band

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30–88	100	40
88–216	150	43.5
216–960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Peak Limit=74 dBuV/m

Average Limit=54 dBuV/m

Spurious Radiated Emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

**Measurement Uncertainty**


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.17 dB
200MHz-1GHz	4.84 dB
1-18GHz	4.35 dB
18-26.5GHz	5.90 dB
26.5GHz~40GHz	5.92 dB




Test Results:


SISO Antenna 1




802.11b-Channel 1 Peak




802.11b-Channel 1 Average




802.11b-Channel 11 Peak




802.11b-Channel 11 Average




802.11g-Channel 1 Peak



802.11g-Channel 1 Average




802.11g-Channel 11 Peak




802.11g-Channel 11 Average


MIMO Antenna 1& Antenna 2




802.11n HT20 -Channel 1 Peak




802.11n HT20 -Channel 1 Average




802.11n HT20 -Channel 11 Peak




802.11n HT20 -Channel 11 Average




802.11n HT40 -Channel 3 Peak



802.11n HT40 -Channel 3 Average



802.11n HT40 -Channel 9 Peak



802.11n HT40 -Channel 9 Average

Result of RE

Test result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the Emissions in the frequency band 9kHz-30MHz and 18GHz-26.5GHz are more than 20dB below the limit are not reported.


The following graphs display the maximum values of horizontal and vertical by software.

For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

After the pretest, MIMO was selected as the worst antenna for 802.11n HT20/ HT40. SISO Antenna 1 was selected as the worst SISO antenna for 802.11b/g.

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Continuous TX mode:



Radiates Emission from 30MHz to 1GHz


Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
46.285000	22.38	175.0	V	323.0	-0.5	17.62	40.00
56.838750	21.19	100.0	V	153.0	-2.3	18.81	40.00
112.858750	18.79	109.0	V	192.0	-6.3	24.71	43.50
235.515000	22.06	109.0	H	270.0	-5.5	23.94	46.00
306.080000	23.27	100.0	H	263.0	-4.3	22.73	46.00
537.476250	29.19	109.0	V	23.0	0.2	16.81	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak


SISO Antenna 1

802.11b CH1



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1130.500000	40.40	---	74.00	33.60	500.0	200.0	H	206.0	-8.2
1144.750000	---	29.53	54.00	24.47	500.0	200.0	H	76.0	-8.1
1261.500000	41.42	---	74.00	32.58	500.0	200.0	H	337.0	-7.5
1414.750000	---	30.33	54.00	23.67	500.0	200.0	H	135.0	-6.6
1475.250000	40.99	---	74.00	33.01	500.0	200.0	V	189.0	-6.3
1555.250000	---	30.59	54.00	23.41	500.0	200.0	V	258.0	-5.9
1697.500000	---	31.45	54.00	22.55	500.0	100.0	H	26.0	-5.0
1720.000000	43.18	---	74.00	30.82	500.0	100.0	V	269.0	-4.9
1974.750000	43.75	---	74.00	30.25	500.0	200.0	H	0.0	-3.5
1993.750000	---	32.88	54.00	21.12	500.0	100.0	V	185.0	-3.4
2826.250000	45.25	---	74.00	28.75	500.0	200.0	V	292.0	0.2
2847.000000	---	34.83	54.00	19.17	500.0	100.0	V	53.0	0.4

802.11b CH6



Note: The signal beyond the limit is carrier.


Radiates Emission from 1GHz to 3GHz



Radiates Emission from 3GHz to 18GHz


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1108.250000	---	29.59	54.00	24.41	500.0	100.0	H	322.0	-8.3
1132.250000	41.02	---	74.00	32.98	500.0	100.0	H	65.0	-8.2
1367.250000	41.95	---	74.00	32.05	500.0	200.0	V	313.0	-6.9
1409.750000	---	30.51	54.00	23.49	500.0	100.0	H	173.0	-6.7
1526.250000	41.18	---	74.00	32.82	500.0	200.0	V	217.0	-6.0
1554.000000	---	30.53	54.00	23.47	500.0	200.0	H	22.0	-5.9
1680.000000	42.44	---	74.00	31.56	500.0	100.0	V	253.0	-5.1
1728.250000	---	31.49	54.00	22.51	500.0	200.0	H	306.0	-4.9
1998.000000	44.19	---	74.00	29.81	500.0	100.0	V	13.0	-3.4
1998.000000	---	32.96	54.00	21.04	500.0	100.0	V	13.0	-3.4
2907.000000	---	35.08	54.00	18.92	500.0	100.0	H	336.0	0.6
2994.500000	46.72	---	74.00	27.28	500.0	100.0	V	0.0	1.1

802.11b CH11



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1062.500000	---	32.39	54.00	21.61	500.0	100.0	H	58.0	-8.5
1164.000000	43.30	---	74.00	30.70	500.0	100.0	H	129.0	-8.0
1312.750000	---	32.99	54.00	21.01	500.0	200.0	V	268.0	-7.2
1332.250000	45.36	---	74.00	28.64	500.0	200.0	V	276.0	-7.1
1514.750000	---	31.08	54.00	22.92	500.0	100.0	V	186.0	-6.1
1599.250000	43.64	---	74.00	30.36	500.0	200.0	V	82.0	-5.6
1710.750000	---	31.78	54.00	22.22	500.0	100.0	V	340.0	-5.0
1829.500000	42.89	---	74.00	31.11	500.0	100.0	H	87.0	-4.2
2024.500000	---	32.91	54.00	21.09	500.0	200.0	V	0.0	-3.3
2264.750000	43.15	---	74.00	30.85	500.0	200.0	V	356.0	-2.3
2665.250000	---	38.63	54.00	15.37	500.0	100.0	V	27.0	-0.7
2665.500000	48.98	---	74.00	25.02	500.0	100.0	V	27.0	-0.7

802.11g CH1



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1145.500000	40.43	---	74.00	33.57	500.0	200.0	V	0.0	-8.1
1177.000000	---	32.46	54.00	21.54	500.0	200.0	H	220.0	-7.9
1347.250000	40.62	---	74.00	33.38	500.0	100.0	H	207.0	-7.0
1363.500000	---	29.97	54.00	24.03	500.0	200.0	V	303.0	-6.9
1558.750000	41.56	---	74.00	32.44	500.0	100.0	V	83.0	-5.8
1697.250000	---	31.47	54.00	22.53	500.0	200.0	V	48.0	-5.0
1720.500000	43.19	---	74.00	30.81	500.0	200.0	H	242.0	-4.9
1979.500000	43.97	---	74.00	30.03	500.0	200.0	V	107.0	-3.5
1997.500000	---	32.88	54.00	21.12	500.0	200.0	V	20.0	-3.4
2216.500000	---	32.32	54.00	21.68	500.0	100.0	H	297.0	-2.6
2889.500000	46.31	---	74.00	27.69	500.0	100.0	H	90.0	0.5
2901.500000	---	34.24	54.00	19.76	500.0	100.0	V	0.0	0.5

802.11g CH6



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1094.750000	41.20	---	74.00	32.80	500.0	100.0	H	251.0	-8.4
1199.500000	---	29.69	54.00	24.31	500.0	200.0	H	27.0	-7.8
1388.750000	---	30.28	54.00	23.72	500.0	100.0	H	158.0	-6.8
1417.250000	41.32	---	74.00	32.68	500.0	100.0	H	94.0	-6.6
1538.250000	42.57	---	74.00	31.43	500.0	100.0	V	225.0	-6.0
1680.750000	---	31.41	54.00	22.59	500.0	200.0	H	143.0	-5.1
1788.750000	42.96	---	74.00	31.04	500.0	200.0	V	278.0	-4.5
1832.000000	---	31.69	54.00	22.31	500.0	200.0	V	298.0	-4.2
2019.500000	---	32.67	54.00	21.33	500.0	100.0	V	60.0	-3.3
2074.000000	44.37	---	74.00	29.63	500.0	200.0	H	14.0	-3.1
2967.750000	46.11	---	74.00	27.89	500.0	200.0	H	0.0	0.9
2995.000000	---	35.15	54.00	18.85	500.0	200.0	H	317.0	1.1

802.11g CH11



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1063.500000	44.71	---	74.00	29.29	500.0	200.0	H	140.0	-8.5
1066.250000	---	32.70	54.00	21.30	500.0	100.0	H	139.0	-8.5
1329.750000	46.26	---	74.00	27.74	500.0	200.0	V	101.0	-7.1
1336.500000	---	33.44	54.00	20.56	500.0	100.0	V	157.0	-7.0
1478.750000	41.40	---	74.00	32.60	500.0	100.0	V	191.0	-6.3
1531.500000	---	30.72	54.00	23.28	500.0	100.0	V	191.0	-6.0
1715.000000	---	32.02	54.00	21.98	500.0	100.0	H	299.0	-5.0
1753.750000	42.48	---	74.00	31.52	500.0	100.0	V	0.0	-4.7
2020.500000	---	33.14	54.00	20.86	500.0	200.0	V	7.0	-3.3
2185.000000	43.65	---	74.00	30.35	500.0	200.0	H	294.0	-2.7
2807.500000	---	34.11	54.00	19.89	500.0	100.0	V	219.0	0.1
2841.500000	45.84	---	74.00	28.16	500.0	100.0	H	190.0	0.3

MIMO Antenna 1& Antenna 2

802.11n (HT20) CH1



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1141.750000	40.60	---	74.00	33.40	500.0	200.0	H	168.0	-8.1
1168.000000	---	29.44	54.00	24.56	500.0	200.0	H	0.0	-8.0
1414.750000	---	30.52	54.00	23.48	500.0	200.0	H	76.0	-6.6
1428.750000	41.51	---	74.00	32.49	500.0	200.0	V	58.0	-6.6
1605.000000	42.81	---	74.00	31.19	500.0	200.0	H	331.0	-5.6
1689.750000	---	31.41	54.00	22.59	500.0	100.0	H	99.0	-5.1
1840.000000	42.34	---	74.00	31.66	500.0	100.0	V	186.0	-4.3
1993.250000	---	32.98	54.00	21.02	500.0	200.0	V	359.0	-3.4
2052.500000	44.33	---	74.00	29.67	500.0	200.0	V	120.0	-3.1
2182.750000	---	32.03	54.00	21.97	500.0	200.0	V	359.0	-2.7
2941.750000	46.41	---	74.00	27.59	500.0	200.0	V	42.0	0.8
2981.750000	---	35.03	54.00	18.97	500.0	200.0	H	168.0	1.0

802.11n (HT20) CH6



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1188.500000	41.21	---	74.00	32.79	500.0	100.0	V	53.0	-7.8
1199.000000	---	29.61	54.00	24.39	500.0	100.0	V	130.0	-7.8
1402.250000	41.91	---	74.00	32.09	500.0	100.0	V	187.0	-6.7
1402.500000	---	30.40	54.00	23.60	500.0	100.0	H	164.0	-6.7
1546.250000	---	30.11	54.00	23.89	500.0	100.0	V	108.0	-6.0
1637.250000	42.89	---	74.00	31.11	500.0	100.0	V	10.0	-5.4
1721.750000	---	31.66	54.00	22.34	500.0	100.0	V	3.0	-4.9
1890.750000	42.25	---	74.00	31.75	500.0	200.0	V	106.0	-4.0
2016.750000	---	33.33	54.00	20.67	500.0	100.0	V	187.0	-3.3
2126.000000	44.62	---	74.00	29.38	500.0	100.0	V	73.0	-2.9
2814.250000	46.21	---	74.00	27.79	500.0	100.0	V	280.0	0.2
2819.000000	---	34.47	54.00	19.53	500.0	100.0	V	101.0	0.2

802.11n (HT20) CH11



Note: The signal beyond the limit is carrier.


Radiates Emission from 1GHz to 3GHz



Radiates Emission from 3GHz to 18GHz


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1064.000000	42.76	---	74.00	31.24	500.0	100.0	V	176.0	-8.5
1077.250000	---	31.72	54.00	22.28	500.0	100.0	H	132.0	-8.5
1329.250000	45.78	---	74.00	28.22	500.0	200.0	H	170.0	-7.1
1331.500000	---	33.37	54.00	20.63	500.0	100.0	V	154.0	-7.1
1597.500000	43.98	---	74.00	30.02	500.0	100.0	V	249.0	-5.6
1721.500000	---	31.92	54.00	22.08	500.0	100.0	V	270.0	-4.9
1915.000000	44.20	---	74.00	29.80	500.0	200.0	V	17.0	-3.9
1998.000000	---	33.18	54.00	20.82	500.0	100.0	V	249.0	-3.4
2231.500000	44.12	---	74.00	29.88	500.0	200.0	V	120.0	-2.6
2238.000000	---	32.72	54.00	21.28	500.0	100.0	V	140.0	-2.5
2664.250000	---	35.73	54.00	18.27	500.0	200.0	V	337.0	-0.7
2665.000000	47.48	---	74.00	26.52	500.0	200.0	V	337.0	-0.7

802.11n (HT40) CH3



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1123.250000	40.32	---	74.00	33.68	500.0	100.0	H	259.0	-8.2
1194.000000	---	28.69	54.00	25.31	500.0	200.0	V	191.0	-7.8
1331.250000	41.20	---	74.00	32.80	500.0	100.0	V	43.0	-7.1
1421.000000	---	30.47	54.00	23.53	500.0	100.0	V	1.0	-6.6
1518.500000	40.93	---	74.00	33.07	500.0	200.0	H	128.0	-6.0
1693.250000	---	31.66	54.00	22.34	500.0	100.0	V	7.0	-5.1
1770.500000	41.81	---	74.00	32.19	500.0	200.0	V	142.0	-4.6
1951.250000	---	32.95	54.00	21.05	500.0	100.0	V	50.0	-3.6
1968.750000	43.90	---	74.00	30.10	500.0	100.0	H	344.0	-3.5
2165.000000	---	32.65	54.00	21.35	500.0	100.0	V	43.0	-2.7
2774.750000	44.72	---	74.00	29.28	500.0	200.0	V	341.0	-0.1
2857.250000	---	35.03	54.00	18.97	500.0	100.0	V	110.0	0.4

802.11n (HT40) CH6



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz




Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1182.250000	---	29.78	54.00	24.22	500.0	100.0	V	0.0	-7.9
1183.250000	41.03	---	74.00	32.97	500.0	200.0	V	194.0	-7.9
1406.000000	41.91	---	74.00	32.09	500.0	200.0	H	176.0	-6.7
1425.500000	---	30.66	54.00	23.34	500.0	100.0	V	18.0	-6.6
1561.750000	---	30.81	54.00	23.19	500.0	100.0	V	52.0	-5.8
1575.250000	41.89	---	74.00	32.11	500.0	100.0	V	122.0	-5.7
1700.250000	---	31.65	54.00	22.35	500.0	100.0	V	157.0	-5.0
1744.000000	42.39	---	74.00	31.61	500.0	100.0	V	38.0	-4.8
1997.750000	44.30	---	74.00	29.70	500.0	100.0	V	38.0	-3.4
1997.750000	---	33.84	54.00	20.16	500.0	100.0	V	38.0	-3.4
2817.500000	46.01	---	74.00	27.99	500.0	100.0	V	73.0	0.2
2823.500000	---	34.79	54.00	19.21	500.0	100.0	V	3.0	0.2

802.11n (HT40) CH9



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz



Radiates Emission from 3GHz to 18GHz



Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1061.500000	---	31.62	54.00	22.38	500.0	100.0	H	132.0	-8.5
1171.750000	42.32	---	74.00	31.68	500.0	100.0	V	95.0	-8.0
1329.500000	45.38	---	74.00	28.62	500.0	200.0	H	0.0	-7.1
1329.750000	---	34.34	54.00	19.66	500.0	100.0	V	157.0	-7.1
1508.750000	---	31.75	54.00	22.25	500.0	100.0	H	167.0	-6.1
1595.500000	42.79	---	74.00	31.21	500.0	100.0	V	0.0	-5.6
1743.250000	---	31.43	54.00	22.57	500.0	100.0	H	97.0	-4.8
1925.750000	44.16	---	74.00	29.84	500.0	200.0	V	114.0	-3.9
2029.000000	---	33.73	54.00	20.27	500.0	200.0	V	3.0	-3.3
2202.750000	44.16	---	74.00	29.84	500.0	100.0	V	95.0	-2.6
2780.000000	---	34.72	54.00	19.28	500.0	200.0	V	30.0	-0.1
2785.000000	45.43	---	74.00	28.57	500.0	200.0	V	332.0	0.0

5.2. Conducted Emission

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10-2013. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50


*: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:


Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes (WIFI 2.4G) with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.33	---	38.17	49.51	11.34	1000.0	9.000	L1	ON	19
0.33	44.45	---	59.45	15.00	1000.0	9.000	L1	ON	19
0.36	---	31.77	48.64	16.87	1000.0	9.000	L1	ON	19
0.36	37.38	---	58.64	21.26	1000.0	9.000	L1	ON	19
1.85	---	30.08	46.00	15.92	1000.0	9.000	L1	ON	19
1.95	33.98	---	56.00	22.02	1000.0	9.000	L1	ON	19
2.13	---	29.51	46.00	16.49	1000.0	9.000	L1	ON	19
4.22	35.09	---	56.00	20.91	1000.0	9.000	L1	ON	19
6.04	34.06	---	60.00	25.94	1000.0	9.000	L1	ON	19
6.04	---	28.57	50.00	21.43	1000.0	9.000	L1	ON	19
15.08	28.04	---	60.00	31.96	1000.0	9.000	L1	ON	20
15.43	---	23.28	50.00	26.72	1000.0	9.000	L1	ON	19

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.32	44.51	---	59.62	15.11	1000.0	9.000	N	ON	19
0.33	---	38.58	49.57	10.99	1000.0	9.000	N	ON	19
0.37	---	29.73	48.59	18.86	1000.0	9.000	N	ON	19
0.37	36.47	---	58.49	22.02	1000.0	9.000	N	ON	19
1.95	---	25.52	46.00	20.48	1000.0	9.000	N	ON	19
1.98	32.96	---	56.00	23.04	1000.0	9.000	N	ON	19
4.29	---	30.62	46.00	15.38	1000.0	9.000	N	ON	19
4.49	36.51	---	56.00	19.49	1000.0	9.000	N	ON	19
6.24	---	29.61	50.00	20.39	1000.0	9.000	N	ON	19
6.31	35.01	---	60.00	24.99	1000.0	9.000	N	ON	19
19.71	---	40.62	50.00	9.38	1000.0	9.000	N	ON	19
19.71	44.11	---	60.00	15.89	1000.0	9.000	N	ON	19

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 KHz to 30 MHz

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Spectrum Analyzer	R&S	FSV30	100815	2019-12-15	2020-12-14
EMI Test Receiver	R&S	ESCI	100948	2020-05-18	2021-05-17
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	102723	2018-08-11	2021-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2021-06-19
EMI Test Receiver	R&S	ESR	101667	2020-05-18	2021-05-17
LISN	R&S	ENV216	101171	2018-12-15	2021-12-14
Spectrum Analyzer	Agilent	N9010A	MY47191109	2020-05-18	2021-05-17
Power Meter	R&S	NRP2	104306	2020-05-18	2021-05-17
Power Sensor	R&S	NRP-Z21	104799	2020-05-18	2021-05-17
20dB Attenuator	Star River Highlight	UCL-TS2S-20	18013001	2019-12-15	2020-12-14
RF Cable	Agilent	SMA 15cm	0001	2020-06-12	2020-12-11
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.