

MRT Technology (Suzhou) Co., Ltd

Phone: +86-512-66308358 +86-512-66308368 www.mrt-cert.com

Report No.: 1406RSU00601 Report Version: Issue Date: 06-13-2014

MEASUREMENT REPORT

FCC PART 15.247 Bluetooth

FCC ID: **2ACIT-SB1213**

APPLICANT: **AIIA Limited**

Certification **Application Type:**

Product: Bluetooth Silicon Speaker

Model No.: SB1213 Ssssspeaker Bluetooth

FCC Classification: FCC Part 15 Spread Spectrum Transmitter(DSS)

FCC Rule Part(s): Part 15.247

Test Procedure(s): ANSI C63.10-2009, DA 00-705

Test Date: June 03 ~ 13, 2014

(Robin Wu) Reviewed By

Approved By

(Marlin Chen)

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009 and DA 00-705. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

FCC ID: 2ACIT-SB1213 Page Number: 1 of 70



Revision History

Report No.	Version	Description	Issue Date
1406RSU00601	Rev. 01	Initial report	06-07-2014
1406RSU00601	Rev. 02	Modify the §7.7 item name and add hopping mode test data	06-13-2014

FCC ID: 2ACIT-SB1213 Page Number: 2 of 70



CONTENTS

De	scriptio	on	Page
1.	INTR	ODUCTION	7
	1.1.	Scope	7
	1.2.	MRT Test Location	7
2.	PROI	DUCT INFORMATION	8
	2.1.	Equipment Description	8
	2.2.	Frequency / Channel Opreation	9
	2.3.	Pseudorandom Frequency Hopping Sequence	10
	2.4.	Device Capabilities	10
	2.5.	Test Configuration	10
	2.6.	Test Software	10
	2.7.	Description of Support Units	11
	2.8.	EMI Suppression Device(s)/Modifications	11
	2.9.	Labeling Requirements	11
3.	DESC	CRIPTION OF TEST	12
	3.1.	Evaluation Procedure	12
	3.2.	AC Line Conducted Emissions	12
	3.3.	Radiated Emissions	13
4.	ANTE	ENNA REQUIREMENTS	14
5.	TEST	EQUIPMENT CALIBRATION DATA	15
6.	MEAS	SUREMENT UNCERTAINTY	16
7.	TEST	RESULT	17
	7.1.	Summary	17
	7.2.	20dB Bandwidth Measurement	18
	7.2.1.	Test Limit	18
	7.2.2.	Test Procedure used	18
	7.2.3.	Test Setting	18
	7.2.4.	Test Setup	19
	7.2.5.	Test Result	20
	7.3.	Output Power Measurement	23
	7.3.1.	Test Limit	23
	7.3.2.	Test Procedure Used	23
	7.3.3.	Test Setting	23
	7.3.4.	Test Setup	23



7.3.5.	Test Result	. 24
7.4.	Carrier Frequency Separation Measurement	. 27
7.4.1.	Test Limit	. 27
7.4.2.	Test Procedure Used	. 27
7.4.3.	Test Setting	. 27
7.4.4.	Test Setup	. 27
7.4.5.	Test Result	. 28
7.5.	Number of Hopping Channels Measurement	. 31
7.5.1.	Test Limit	. 31
7.5.2.	Test Procedure Used	. 31
7.5.3.	Test Settitng	. 31
7.5.4.	Test Setup	. 31
7.5.5.	Test Result	. 32
7.6.	Time of Occupancy Measurement	. 35
7.6.1.	Test Limit	. 35
7.6.2.	Test Procedure Used	. 35
7.6.3.	Test Settitng	. 35
7.6.4.	Test Setup	. 36
7.6.5.	Test Result	. 37
7.7.	Operation Frequency Range of 20dB Bandwidth	. 39
7.7.1.	Test Limit	. 39
7.7.2.	Test Procedure Used	. 39
7.7.3.	Test Setting	. 39
7.7.4.	Test Setup	. 40
7.7.5.	Test Result	. 41
7.8.	Conducted Spurious Emissions Measurement	. 44
7.8.1.	Test Limit	. 44
7.8.2.	Test Procedure Used	. 44
7.8.3.	Test Setting	. 44
7.8.4.	Test Setup	. 45
7.8.5.	Test Result	. 46
7.9.	Radiated Spurious Emission Measurement	. 49
7.9.1.	Test Limit	
7.9.2.	Test Procedure Used	
7.9.3.	Test Setting	. 49
7.9.4.	Test Setup	
7.9.5.	Test Result	
7.10.	Radiated Restricted Band Edge Measurement	





8.	CONCLU	ISION	70
	7.11.3.	Test Result	68
	7.11.2.	Test Setup	67
	7.11.1.	Test Limit	67
	7.11. A	C Conducted Emissions Measurement	67
	7.10.1.	Test Result	59



§2.1033 General Information

Applicant:	AIIA Limited
Applicant Address:	Room 16A02, Jue Shi Building, 4018# Jia Bin Road, Luo Hu area,
	Shenzhen, China
Manufacturer:	AllA Limited
Manufacturer Address:	Room 16A02, Jue Shi Building, 4018# Jia Bin Road, Luo Hu area,
	Shenzhen, China
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong
	Economic Development Zone, Suzhou, China
MRT Registration No.:	809388
FCC Rule Part(s):	Part 15.247
Model No.	Bluetooth Silicon Speaker
FCC ID:	2ACIT-SB1213
Test Device Serial No.:	N/A ☐ Production ☐ Pre-Production ☐ Engineering
FCC Classification:	FCC Part 15 Spread Spectrum Transmitter (DSS)
Method/System:	Frequency Hopping Spread Spectrum (FHSS)
Date(s) of Test:	June 03 ~ 06, 2014
Test Report S/N:	1406RSU00601

FCC ID: 2ACIT-SB1213 Page Number: 6 of 70



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



FCC ID: 2ACIT-SB1213 Page Number: 7 of 70



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Bluetooth Silicon Speaker
Model No.	SB1213 Ssssspeaker Bluetooth
Bluetooth (1x, EDR)	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.1
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Type	PCB Antenna
Antenna Gain	0 dBi

The equipment under test (EUT) is the **Bluetooth Silicon Speaker FCC ID: 2ACIT-SB1213**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate
 its channels selection/ hopping sequence with other frequency hopping systems for the
 express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by
 multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

FCC ID: 2ACIT-SB1213 Page Number: 8 of 70



2.2. Frequency / Channel Opreation

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A


FCC ID: 2ACIT-SB1213 Page Number: 9 of 70



2.3. Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

2.4. Device Capabilities

Bluetooth (1x, EDR)

2.5. Test Configuration

The **Bluetooth Silicon Speaker FCC ID: 2ACIT-SB1213** was tested per the guidance of ANSI C63.10-2009 and DA 00-705. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. Test Software

The test utility software used during testing was engineering order by applicant.

FCC ID: 2ACIT-SB1213 Page Number: 10 of 70



2.7. Description of Support Units

The EUT has been tested with associated equipment below:

Description	Manufacturer	Model No.
Adapter	Supply by MRT	HSU50600F

2.8. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.9. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not

practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: 2ACIT-SB1213 Page Number: 11 of 70



3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009), and the "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" (DA 00-705) were used in the measurement of the **Bluetooth Silicon Speaker FCC ID: 2ACIT-SB1213.**

Deviation from measurement procedure......None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50$ uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2009 at Clause 4.3.

Line conducted emissions test results are shown in Section 7.11.

FCC ID: 2ACIT-SB1213 Page Number: 12 of 70



3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GH absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beamwidth of horn antenna, the horn antenna should be always directed to the EUT when rising height.

FCC ID: 2ACIT-SB1213 Page Number: 13 of 70



4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the Bluetooth Silicon Speaker is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **Bluetooth Silicon Speaker FCC ID: 2ACIT-SB1213** unit complies with the requirement of §15.203.

FCC ID: 2ACIT-SB1213 Page Number: 14 of 70



5. TEST EQUIPMENT CALIBRATION DATA

Conducted Emissions

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	101209	1 year	2014/11/08
Two-Line V-Network	R&S	ENV216	101683	1 year	2014/11/08
Two-Line V-Network	R&S	ENV216	101684	1 year	2014/11/08
Temperature/ Meter Humidity	Anymetre	TH101B	SR2-01	1 year	2014/11/15

Radiated Emission

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9010A	MY5144016A	1 year	2015/01/04
Preamplifier	MRT	AP01G18	1310002	1 year	2014/10/07
Loop Antenna	Schwarzbeck	FMZB1519	1519-041	1 year	2014/11/24
TRILOG Antenna	Schwarzbeck	VULB9162	9162-047	1 year	2014/11/24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1167	1 year	2014/11/24
Broadband Horn Antenna	Schwarzbeck	BBHA9170	9170-549	1 year	2014/12/11
Temperature/Humidity Meter	Anymetre	TH101B	AC1-01	1 year	2014/11/15

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9010A	MY5144016A	1 year	2015/01/04
Power Sensor	Agilent	U2021XA	MY52450003	1 year	2014/12/14
Temperature/Humidity Meter	Anymetre	TH101B	TR3-01	1 year	2014/11/15

FCC ID: 2ACIT-SB1213 Page Number: 15 of 70



6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

150kHz~30MHz: ± 3.46dB

Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

9kHz ~ 1GHz: ± 4.18dB 1GHz ~ 25GHz: ± 4.76dB

FCC ID: 2ACIT-SB1213 Page Number: 16 of 70



7. TEST RESULT

7.1. Summary

Company Name: <u>AllA Limited</u>
FCC ID: <u>2ACIT-SB1213</u>

Method/System: Frequency Hopping Spread Spectrum (FHSS)

Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)	20dB Bandwidth	N/A		PASS	Section 7.2
15.247(b)(1)	Peak Transmitter Output Power	<1 Watt if > 75 non- overlapping channels used	Conducted	PASS	Section 7.3
15.247(a)(1)	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.4
15.247(a)(1)(iii)	Number of Channels	> 15 Channels		PASS	Section 7.5
15.247(a)(1)(iii)	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6
15.215(c) 15.247(d)	Operation Frequency Range of 20dB Bandwidth /out-of-Band Emissions	Conducted ≥ 20dBc		PASS	Section 7.7, Section 7.8
4-00-	General Field Strength	Emissions in restricted			0 11 -0
15.205 15.209	Limits (Restricted Bands and Radiated Emission Limits)	bands must meet the radiated limits detailed in 15.209	Radiated	PASS	Section 7.9, Section 7.10
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.11

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

FCC ID: 2ACIT-SB1213 Page Number: 17 of 70



7.2. 20dB Bandwidth Measurement

7.2.1. Test Limit

The maximum permissible 20dB bandwidth is 1 MHz, unless more than 15 non-overlapping channels are employed.

7.2.2. Test Procedure used

ANSI C63.10-2009 - Section 6.9.1


7.2.3. Test Setting

- 1. Set RBW ≥ 1% of the 20dB bandwidth
- 2. $VBW \ge 3 \times RBW$
- 3. Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

FCC ID: 2ACIT-SB1213 Page Number: 18 of 70



7.2.4. Test Setup




FCC ID: 2ACIT-SB1213 Page Number: 19 of 70




7.2.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	20dB Bandwidth (KHz)	Result
DH5	00	2402	926.6	Pass
DH5	39	2441	926.5	Pass
DH5	78	2480	926.4	Pass
2DH5	00	2402	1261.0	Pass
2DH5	39	2441	1258.0	Pass
2DH5	78	2480	1259.0	Pass
3DH5	00	2402	1264.0	Pass
3DH5	39	2441	1270.0	Pass
3DH5	78	2480	1266.0	Pass




FCC ID: 2ACIT-SB1213 Page Number: 20 of 70





FCC ID: 2ACIT-SB1213 Page Number: 21 of 70





FCC ID: 2ACIT-SB1213 Page Number: 22 of 70



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power permissible output power is 1 Watt for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.


7.3.2. Test Procedure Used

ANSI C63.10-2009 - Section 6.10.1

7.3.3. Test Setting

- 1. Set RBW ≥ the 20 dB bandwidth of the emission being measured.
- 2. VBW \geq 3 x RBW
- 3. Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace to stabilize, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss)

7.3.4. Test Setup




FCC ID: 2ACIT-SB1213 Page Number: 23 of 70




7.3.5. Test Result

Test Mode	Channel No.	Frequency	Peak Power	
		(MHz)	(dBm)	(mW)
DH5	00	2402	4.079	2.558
DH5	39	2441	3.218	2.098
DH5	78	2480	3.897	2.453
2DH5	00	2402	2.604	1.821
2DH5	39	2441	3.238	2.108
2DH5	78	2480	3.772	2.383
3DH5	00	2402	2.783	1.898
3DH5	39	2441	3.359	2.167
3DH5	78	2480	3.895	2.452




FCC ID: 2ACIT-SB1213 Page Number: 24 of 70





FCC ID: 2ACIT-SB1213 Page Number: 25 of 70





FCC ID: 2ACIT-SB1213 Page Number: 26 of 70



7.4. Carrier Frequency Separation Measurement

7.4.1. Test Limit

The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


7.4.2. Test Procedure Used

ANSI C63.10-2009 - Section 7.7.2

7.4.3. Test Setting

- 1. Span = wide enough to capture the peaks of two adjacent channels.
- 2. RBW ≥ 1 % of the span
- 3. VBW ≥ RBW
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

7.4.4. Test Setup




FCC ID: 2ACIT-SB1213 Page Number: 27 of 70




7.4.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit (kHz)	Result
DH5	00	2402	≥ 617.7	Pass
DH5	39	2441	≥ 617.7	Pass
DH5	78	2480	≥ 617.6	Pass
2DH5	00	2402	≥ 840.7	Pass
2DH5	39	2441	≥ 838.7	Pass
2DH5	78	2480	≥ 839.3	Pass
3DH5	00	2402	≥ 842.7	Pass
3DH5	39	2441	≥ 846 7	Pass
3DH5	78	2480	≥ 844.0	Pass



FCC ID: 2ACIT-SB1213 Page Number: 28 of 70






2DH5 Carrier Frequency Separation

Channel 00 (2402MHz)

Channel 39 (2441MHz)




Channel 78 (2480MHz)



FCC ID: 2ACIT-SB1213 Page Number: 29 of 70





FCC ID: 2ACIT-SB1213 Page Number: 30 of 70