

FCC Test Report

Product Name : FiberGateway
Trade Name : ALTICE, ALTICE LABS
Model No. : GR140DG
FCC ID : 2ACJF-FGW-GR140DG

Applicant : Altice Labs, S.A.

Address : Rua Eng. Ferreira Pinto Basto, 3810-106, Aveiro, Portugal

Date of Receipt : Jul. 23, 2020
Issued Date : Dec. 17, 2020
Report No. : 2070864R-E3032110123
Report Version : V2.0



The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Nov. 27, 2020
V2.0	Add UNII-3 test data	Dec. 17, 2020

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description.....	6
1.2. Test Mode.....	9
1.3. Tested System Details.....	10
1.4. Configuration of tested System.....	10
1.5. EUT Exercise Software.....	10
1.6. Comments and Remarks	11
1.7. Test Facility.....	12
1.8. List of Test Equipment.....	13
1.9. Duty Cycle	16
1.10. Uncertainty.....	21
2. Conducted Emission.....	22
2.1. Test Setup	22
2.2. Limits	22
2.3. Test Procedure	23
2.4. Test Specification	23
2.5. Test Result.....	24
3. 26dB & 99% & DTS Bandwidth	28
3.1. Test Setup	28
3.2. Limits	28
3.3. Test Procedure	28
3.4. Test Result.....	29
4. Maximum conducted output power.....	165
4.1. Test Setup	165
4.2. Limits	165
4.3. Test Procedure	166
4.4. Test Result.....	167
5. Maximum power spectral density	174
5.1. Test Setup	174
5.2. Limits	174
5.3. Test Procedure	175

5.4. Test Result.....	176
6. Radiated Emission.....	201
6.1. Test Setup	201
6.2. Limits	202
6.3. Test Procedure	203
6.4. Test Result.....	204
7. Band Edge	292
7.1. Test Setup	292
7.2. Limits	292
7.3. Test Procedure	294
7.4. Test Result.....	295
Attachment 1	385
Test Setup Photograph.....	385
Attachment 2.....	388
EUT External Photograph.....	388

ANT-TX / RX & Bandwidth


ANT-TX / RX	TX			RX		
Mode/ Channel Bandwidth	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz
IEEE802.11a	✓			✓		
IEEE802.11n	✓	✓		✓	✓	
IEEE802.11ac/ax	✓	✓	✓	✓	✓	✓

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
1 Notebook PC	Lenove	80XL	PF0SXXY1	DoC	Shielded, 2m

1.4. Configuration of tested System



1.5. EUT Exercise Software

1	Setup the EUT as shown in Section 1.4.
2	Execute the Broadcom command.
3	Configure the test mode, the test channel, and the data rate.
4	Press "Start TX" to start the continuous Transmit.
5	Verify that the EUT works properly.

1.6. Comments and Remarks

The product specification and testing instructions for the EUT declared in the report are provided by the manufacturer who will take all responsibilities for the accuracy.

1.9. Duty Cycle

Mode	On Time(ms)	On+Off Time(ms)	Duty Cycle(%)	Duty Factor(dB) linear voltage	Duty Factor(dB) Power	1/T Minimum VBW (kHz)
11A (SISO Mode)	2.053	2.083	98.56%	0.126006	0.06	0.010
VHT20 (CDD Mode)	1.913	1.952	98.00%	0.175297	0.09	0.010
VHT40 (CDD Mode)	0.944	0.972	97.12%	0.253885	0.13	1.059
VHT80 (CDD Mode)	0.444	0.479	92.72%	0.656952	0.33	2.251
HE20 (CDD Mode)	1.509	1.548	97.48%	0.221634	0.11	0.663
HE40 (CDD Mode)	0.767	0.794	96.52%	0.307221	0.15	1.304
HE80 (CDD Mode)	0.397	0.428	92.71%	0.657123	0.33	2.519

Note:

Offset = $20 \log(1/\text{duty cycle})$

Accotding to KDB 789033

If power averaging (rms) mode was used in step (iv) above, the correction factor is $10 \log (1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB must be added to the measured emission levels.

If linear voltage averaging mode was used in step (iv) above, the correction factor is $20 \log (1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB must be added to the measured emission levels.

