

## TEST REPORT

**Report Number: 103224477MPK-003D**

**Project Number: G103224477**

**December 27, 2017**

**Testing performed on the  
FIBERGATEWAY  
Model Number: GR240BG  
FCC ID: 2ACJF-FGW-GR240BG**

**to  
FCC Part 15, Subpart E**

**For**

**Altice Labs, SA**

**Test Performed by:**

Intertek

1365 Adams Court

Menlo Park, CA 94025 USA

**Test Authorized by:**

Altice Labs, SA

Rua Eng. Ferreira Pinto Basto

3810-106 Aveiro, Portugal

Prepared by:

  
Minh Ly

**Date:** December 27, 2017

Reviewed by:

  
Krishna K Vemuri

**Date:** December 27, 2017

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.*

## VERIFICATION OF COMPLIANCE

### Report No. 103224477MPK-003D

Verification is hereby issued to the named APPLICANT and is VALID ONLY for the equipment identified hereon for use under the rules and regulations listed below.

**Equipment Under Test:**

FIBERGATEWAY

**Trade Name:**

Altice Labs, SA

**Model No.:**

GR240BG

**Applicant:**

Altice Labs, SA

**Contact:**

Ricardo Cunha

**Address:**Rua Eng. Ferreira Pinto Basto  
3810-106 Aveiro**Country**

Portugal

**Tel. Number:**

351234403200

**Email:**

Rcunha@ptinovacao.pt

**Applicable Regulation:**

FCC Part 15, Subpart E

**Date of Test:**

December 04 to 13, 2017

*We attest to the accuracy of this report:*

Minh Ly  
EMC Project Engineer



Krishna K Vemuri  
Engineering Team Lead

**TABLE OF CONTENTS**

<b>1.0</b>	<b>Introduction.....</b>	<b>4</b>
1.1	Summary of Tests.....	4
<b>2.0</b>	<b>General Description .....</b>	<b>5</b>
2.1	Product Description.....	5
2.2	Related Submittal(s) Grants .....	6
2.3	Test Methodology .....	6
2.4	Test Facility.....	6
2.5	Measurement Uncertainty .....	6
<b>3.0</b>	<b>System Test Configuration.....</b>	<b>7</b>
3.1	Support Equipment .....	7
3.2	Block Diagram of Test Setup .....	7
3.3	Justification .....	8
3.4	Mode of Operation During Test .....	8
3.5	Modifications required for Compliance .....	8
3.6	Additions, deviations and exclusions from standards.....	8
<b>4.0</b>	<b>Measurement Results.....</b>	<b>9</b>
4.1	Emission Bandwidth and 99% Occupied Bandwidth.....	9
4.1.1	Procedure .....	9
4.1.2	Test Result .....	10
4.2	Maximum Conducted Output Power.....	23
4.2.1	Requirement .....	23
4.2.2	Procedure .....	23
4.2.3	Test Results.....	24
4.3	Peak Power Spectral Density.....	74
4.3.1	Requirement .....	74
4.3.2	Procedure .....	74
4.3.3	Test Result .....	75
4.4	Frequency stability .....	77
4.4.1	Requirement .....	77
4.4.2	Procedure .....	77
4.4.3	Result .....	78
4.5	Transmitter Radiated Emissions.....	79
4.5.1	Requirement .....	79
4.5.2	Procedure .....	80
4.5.3	Field Strength Calculation.....	81
4.5.4	Test Results.....	81
4.5.5	Test setup photographs.....	114
<b>5.0</b>	<b>List of Test Equipment .....</b>	<b>116</b>
<b>6.0</b>	<b>Document History .....</b>	<b>117</b>

## 1.0 Introduction

### 1.1 Summary of Tests

Test	Reference FCC	Result
26 dB Emission Band width and 99% Occupied Bandwidth	15.407(a)(1)(2)(3)	Complies
Conducted Output Power	15.407(a)(1)(2)(3)	Complies
Peak Power Spectral Density	15.407(a)(1)(2)(3)	Complies
Undesirable Emissions	15.407(b)(1-8)	Complies
Transmitter Radiated Emissions	15.407(b)(1-8) 15.209, 15.205	Complies
Frequency stability	15.407(g)	Complies
Dynamic Frequency Selection (DFS)	15.407(h)	Complies*
Antenna Requirement	15.203	Complies. The EUT uses internal antenna.

\*see test results in report #103224477MPK-006

**EUT receive date:** September 18, 2017

**EUT receive condition:** The pre-production version of the EUT was received in good condition with no apparent damage. As declared by the Applicant, it is identical to the production units.

**Test start date:** December 04, 2017

**Test completion date:** December 13, 2017

The test results in this report pertain only to the item tested.

## 2.0 General Description

### 2.1 Product Description

Altice Labs, SA supplied the following description of the EUT:

The FiberGateway GR240BG is an ONT (Optical Network Terminal) solution based on Rec. ITU-T G.984.x that supports triple play services (high speed internet, voice and video) which are deployed over Ethernet and Wi-Fi interfaces. GEM (GPON encapsulation method) is employed to adapt technologies. This system can be used in triple play service delivery network solutions. It includes Home Gateway functionalities, 4 GbE ports and Wi-Fi Dual-Band Concurrent (2.4 GHz bgn 4x4 + 5 GHz anac 4x4) for internet access and IPTV, 2 FXS ports for voice and 1 USB 2.0 port.

For more information, see user's manual provided by the manufacturer.

The information about the 5GHz radio, installed in the model GR240BG, is presented below.

<b>Applicant</b>	Altice Labs, SA
<b>Model No.</b>	GR240BG
<b>FCC ID</b>	2ACJF-FGW-GR240BG
<b>Rated RF Output</b>	802.11a: 21.59 dBm 802.11n 20MHz: 21.62 dBm 802.11n 40MHz: 22.03 dBm 802.11ac 80MHz: 20.79 dBm
<b>Frequency Range</b>	U-NII 2C: 5470 – 5725 MHz
<b>Type of modulation</b>	OFDM
<b>Antenna(s) &amp; Gain</b>	Internal Antenna, 4.95 dBi calculated peak gain Ant 0 – DB1: 4.8dBi, Vertical Ant 1 – DB2: 3.4dBi, Horizontal Ant 2 – DB3: 4.0dBi, Horizontal Ant 3 – DB4: 5.1dBi, Vertical
<b>Manufacturer Name &amp; Address</b>	Altice Labs, SA Rua Eng. Ferreira Pinto Basto 3810-106 Aveiro Portugal

The EUT supports a wide range of data rates in the U-NII-2A band:

- IEEE 802.11a
- IEEE 802.11n 20MHz
- IEEE 802.11n 40MHz
- IEEE 802.11ac 20MHz
- IEEE 802.11ac 40MHz
- IEEE 802.11ac 80MHz

## 2.2 Related Submittal(s) Grants

None.

## 2.3 Test Methodology

Antenna conducted measurements were performed according to the FCC documents "Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E" (789033 D02 General U-NII Test Procedures New Rules v01r04 & 905462 D02 UNII DFS Compliance Procedures New Rules v02).

Both AC mains line-conducted and radiated emissions measurements were performed according to the procedures in ANSI C63.4. Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Data Sheet**" of this Application.

All other measurements were made in accordance with the procedures in part 2 of CFR 47.

## 2.4 Test Facility

The test site used to collect the radiated data is site 1 (10-m semi-anechoic chamber). This test facility and site measurement data have been fully placed on file with the FCC, IC and A2LA accredited.

## 2.5 Measurement Uncertainty

Compliance with the limits was based on the results of the measurements and doesn't take into account the measurement uncertainty.

### Estimated Measurement Uncertainty

Measurement	Expanded Uncertainty (k=2)		
	0.15 MHz – 1 GHz	1 GHz – 6 GHz	> 6 GHz
RF Power and Power Density – antenna conducted	1.1 dB	1.5 dB	–
Unwanted emissions - antenna conducted	1.2 dB	1.7 dB	2.0 dB
Bandwidth – antenna conducted	50 Hz	100 Hz	–
Radiated emissions	4.2 dB	5.4 dB	
AC mains conducted emissions	2.4 dB	–	–

### 3.0 System Test Configuration


#### 3.1 Support Equipment

Description	Manufacturer	Model No./ Part No.
Laptop	HP	EliteBook 8470p
Optical Line Termination	Cisco	Cisco ME 4600 Series
Flash Drive	Kingston	DT101G2 8GB
Telephone	TKT	1700137823
Telephone	Alcatel	N/A
Router	Linksys	BEFSR81

#### 3.2 Block Diagram of Test Setup

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
FiberGateway (Radiated Unit)	Altice Labs, SA	GR240BG	5054494E912154CF
AC/DC Power Adapter	Airline mechanical Co Ltd	EOSA+4B120-4000	AB1708240092570
FiberGateway (Conducted Unit)	Altice Labs, SA	GR240BG	5054494E9121874F

Antenna was removed and co-axial connector with a cable was installed for Conducted Measurements.



**S** = Shielded  
**U** = Unshielded

**F** = With Ferrite  
**m** = Meter

### 3.3 Justification

Preliminary testing was performed for all modulation/data rate modes. The following modes, in which the highest power was detected, were selected for final measurements:

OFDM, 6MB/s – for 802.11a (Power Setting on test firmware: 15)  
OFDM, MCS0 – for 802.11n 20MHz (Power Setting on test firmware: 15)  
OFDM, MCS0 – for 802.11n 40MHz (Power Setting on test firmware: 16)  
OFDM, MCS0 – for 802.11ac 80MHz (Power Setting on test firmware: 15)

According to the manufacturer, the FiberGateway utilizes cross-polarized antennas with two vertical (Ant 1 & Ant 4) and two Horizontal (Ant 2 & Ant 3). Per FCC KDB “662911 D01 Multiple Transmitter Output v02r01”, the directional gain of the antenna is calculated as below:

$$\text{Directional gain} = 10 \log[(10G_1/10 + 10G_2/10 + \dots + 10G_N/10)/N_{\text{ANT}}] \text{ dBi}$$

$$\text{Vertical Gain} = 10 \log[(10^{(4.8/10)} + 10^{(5.1/10)})/2] = 4.9 \text{ dBi}$$

$$\text{Horizontal Gain} = 10 \log[(10^{(3.4/10)} + 10^{(4/10)})/2] = 3.7 \text{ dBi}$$

### 3.4 Mode of Operation During Test

During transmitter testing, the transmitter was setup to transmit continuously using the maximum RF power setting. Their corresponding output power in dBm can be found in section 4.2 of this report.

### 3.5 Modifications required for Compliance

The following modification was made by the manufacturer to the EUT in order to bring the EUT into compliance:

Added a ferrite with double loop (Manufacturer: Wurth Electronics, Part Number: 74271633S) at the DC input of the FiberGateway (See below).



### 3.6 Additions, deviations and exclusions from standards

No additions, deviations or exclusion have been made from standard.

**4.0 Measurement Results****4.1 Emission Bandwidth and 99% Occupied Bandwidth**

15.407(a)(2)

**4.1.1 Procedure**

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically Section C for Emission Bandwidth and Minimum Emission Bandwidth for the band 5.725-5.850 GHz. Section D was used for 99% Occupied Bandwidth.

The antenna port of the EUT was connected to the input of a spectrum analyzer (SA). For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier.

The Occupied bandwidth was measured using the build-in spectrum analyzer facility for 99% power bandwidth measurement.


<b>Tested By:</b>	Minh Ly
<b>Test Date:</b>	December 12, 2017

#### 4.1.2 Test Result

Refer to the following plots for the test result:


<b>Mode</b>	<b>Channel</b>	<b>Frequency, MHz</b>	<b>26-dB Bandwidth, MHz</b>	<b>Occupied Bandwidth, MHz</b>	<b>Plot #</b>
802.11a	100	5500	21.794	17.243	1.1
	116	5580	21.858	17.243	1.2
	144	5720	21.730	17.307	1.3
802.11n 20MHz	100	5500	22.115	18.333	1.4
	116	5580	22.115	18.333	1.5
	144	5720	22.115	18.333	1.6
802.11n 40MHz	102	5510	40.897	36.666	1.7
	118	5590	40.897	36.666	1.8
	142	5710	40.769	36.666	1.9
802.11ac 80MHz	106	5530	83.076	75.961	1.10
	122	5610	82.692	75.961	1.11
	138	5690	82.884	76.153	1.12

**Plot 1.1**  
**802.11a 5500MHz**




Date: 11.DEC.2017 11:15:16

**Plot 1.2**  
**802.11a 5580MHz**




Date: 11.DEC.2017 11:41:05

## Plot 1.3




Date: 11.DEC.2017 11:43:02

**Plot 1.4**  
**802.11n 20MHz, 5500MHz**




Date: 11.DEC.2017 11:51:04

**Plot 1.5**  
**802.11n 20MHz, 5580MHz**




Date: 11.DEC.2017 11:52:32

**Plot 1.6**  
**802.11n 20MHz, 5720MHz**




Date: 11.DEC.2017 11:55:06

**Plot 1.7**  
**802.11n 40MHz, 5510MHz**



Date: 11.DEC.2017 12:03:48


**Plot 1.8**  
**802.11n 40MHz, 5590MHz**



Date: 11.DEC.2017 12:05:41

## Plot 1.9


802.11n 40MHz, 5710MHz



Date: 11.DEC.2017 12:07:06

Plot 1.10


802.11ac 80MHz, 5530MHz



Date: 11.DEC.2017 12:11:47

Plot 1.11


802.11ac 80MHz, 5610MHz



Date: 11.DEC.2017 12:14:40

Plot 1.12

802.11ac 80MHz, 5690MHz



Date: 11.DEC.2017 12:16:19

4.2 Maximum Conducted Output Power  
FCC Rule 15.407(a)(1)(iv)

4.2.1 Requirement

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2.2 Procedure

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically Section E (2) (c) Method SA-1 Alternative for Maximum Conducted Output Power

The antenna port output of the EUT was connected to the input of a spectrum analyzer to measure the Maximum Conducted Transmitter Output Power.

<b>Tested By:</b>	Minh Ly
<b>Test Date:</b>	December 12, 2017

#### 4.2.3 Test Results

Refer to the following plots for the test result:

##### 802.11a (6Mbps) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
100	5500	15.14	2.1	15.58	2.4	15.06	2.7	15.12	2.10
116	5580	15.04	2.2	15.42	2.5	15.01	2.8	15.00	2.11
144	5720	15.60	2.3	15.66	2.6	15.36	2.9	15.64	2.12

##### 802.11n 20MHz (MCS0) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
100	5500	14.99	2.13	15.46	2.16	15.16	2.19	14.97	2.22
116	5580	15.14	2.14	15.45	2.17	15.01	2.20	14.95	2.23
144	5720	15.69	2.15	15.79	2.18	15.21	2.21	15.70	2.24


##### 802.11n 40MHz (MCS0) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
102	5510	15.99	2.25	16.29	2.28	15.86	2.31	15.90	2.34
118	5590	15.71	2.26	16.14	2.29	15.64	2.32	15.86	2.35
142	5710	16.40	2.27	16.79	2.30	16.16	2.33	16.59	2.36

##### 802.11ac 80MHz (MCS0) – Conducted Average Power


CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
106	5530	14.31	2.37	14.79	2.40	14.21	2.43	14.28	2.46
122	5610	14.38	2.38	14.82	2.41	14.37	2.44	14.48	2.47
138	5690	14.71	2.39	14.95	2.42	14.50	2.45	14.91	2.48

CH	Frequency (MHz)	Summed power (dBm)	Summed power (W)
802.11a			
100	5500	21.25	0.133
116	5580	21.14	0.130
144	5720	21.59	0.144
802.11n 20MHz			
100	5500	21.17	0.131
116	5580	21.16	0.131
144	5720	21.62	0.145
802.11n 40MHz			
102	5510	22.03	0.160
118	5590	21.86	0.154
142	5710	22.51	0.178
802.11ac 80MHz			
106	5530	20.42	0.110
122	5610	20.54	0.113
138	5690	20.79	0.120


**Plot 2.1**

Date: 12.DEC.2017 11:37:37

Plot 2.2




Date: 12.DEC.2017 11:39:16

**Plot 2. 3**


Date: 12.DEC.2017 11:48:49

Plot 2.4




Date: 12.DEC.2017 11:36:40

Plot 2.5




Date: 12.DEC.2017 11:40:02

Plot 2.6




Date: 12.DEC.2017 11:48:04

**Plot 2.7**


Date: 12.DEC.2017 11:35:43

Plot 2.8




Date: 12.DEC.2017 11:41:00

Plot 2.9




Date: 12.DEC.2017 11:47:18

**Plot 2. 10**


Date: 12.DEC.2017 11:34:42

Plot 2.11




Date: 12.DEC.2017 11:41:48

Plot 2.12




Date: 12.DEC.2017 11:43:22

Plot 2.13




Date: 12.DEC.2017 13:12:56

Plot 2.14




Date: 12.DEC.2017 13:14:41

Plot 2.15




Date: 12.DEC.2017 13:24:52

Plot 2.16




Date: 12.DEC.2017 13:11:17

Plot 2.17




Date: 12.DEC.2017 13:15:33

Plot 2.18




Date: 12.DEC.2017 13:25:56

Plot 2.19




Date: 12.DEC.2017 13:09:01

Plot 2.20




Date: 12.DEC.2017 13:16:24

Plot 2.21




Date: 12.DEC.2017 13:27:04

Plot 2.22




Date: 12.DEC.2017 13:08:12

Plot 2.23




Date: 12.DEC.2017 13:17:18

Plot 2.24




Date: 12.DEC.2017 13:28:01

Plot 2.25




Date: 12.DEC.2017 13:49:12

Plot 2.26




Date: 12.DEC.2017 13:50:22

Plot 2.27




Date: 12.DEC.2017 13:57:51

Plot 2.28




Date: 12.DEC.2017 13:48:25

Plot 2.29




Date: 12.DEC.2017 13:51:55

Plot 2.30




Date: 12.DEC.2017 13:57:08

Plot 2.31




Date: 12.DEC.2017 13:47:38

Plot 2.32




Date: 12.DEC.2017 13:52:40

Plot 2.33




Date: 12.DEC.2017 13:56:23

Plot 2.34




Date: 12.DEC.2017 13:46:48

Plot 2.35




Date: 12.DEC.2017 14:28:37

Plot 2.36




Date: 12.DEC.2017 13:55:19

Plot 2.37




Date: 12.DEC.2017 14:09:21

Plot 2.38




Date: 12.DEC.2017 14:10:47

Plot 2.39




Date: 12.DEC.2017 14:17:58

Plot 2.40




Date: 12.DEC.2017 14:08:32

Plot 2.41




Date: 12.DEC.2017 14:11:36

Plot 2.42




Date: 12.DEC.2017 14:17:12

Plot 2.43




Date: 12.DEC.2017 14:07:45

Plot 2.44




Date: 12.DEC.2017 14:20:07

Plot 2.45




Date: 12.DEC.2017 14:15:12

Plot 2.46




Date: 12.DEC.2017 14:06:43

Plot 2.47



Date: 12.DEC.2017 14:13:00

Plot 2.48



Date: 12.DEC.2017 14:14:40

4.3 Peak Power Spectral Density  
FCC Rule 15.407(a)(1)(iv)

4.3.1 Requirement

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2 Procedure

Each antenna port of the EUT was connected to the input of a spectrum analyzer to measure the Peak Power Spectral Density (PPSD) and recorded.

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically procedure from Section F was utilized for Maximum Power Spectral Density (PSD).

<b>Tested By:</b>	Minh Ly
<b>Test Date:</b>	December 12, 2017

#### 4.3.3 Test Result

Refer to the following plots for the test result:

##### 802.11a (6Mbps) – Peak Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
100	5500	3.97	2.1	4.42	2.4	4.09	2.7	4.26	2.10
116	5580	3.98	2.2	4.33	2.5	4.03	2.8	3.97	2.11
144	5720	4.52	2.3	4.71	2.6	4.39	2.9	4.66	2.12

##### 802.11n 20MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
100	5500	3.61	2.13	4.05	2.16	3.74	2.19	3.71	2.22
116	5580	3.87	2.14	4.14	2.17	3.64	2.20	3.58	2.23
144	5720	4.39	2.15	4.42	2.18	3.93	2.21	4.30	2.24

##### 802.11n 40MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
102	5510	1.70	2.25	1.93	2.28	1.61	2.31	1.67	2.34
118	5590	1.45	2.26	1.72	2.29	1.23	2.32	1.50	2.35
142	5710	2.11	2.27	2.42	2.30	1.92	2.33	2.19	2.36

##### 802.11n 40MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
106	5530	-3.06	2.37	-2.66	2.40	-3.29	2.43	-2.93	2.46
122	5610	-2.88	2.38	-2.56	2.41	-2.91	2.44	-2.77	2.47
138	5690	-2.71	2.39	-2.41	2.42	-2.95	2.45	-2.33	2.48

## MIMO - Power Spectral Density

CH	Frequency (MHz)	Summed PSD (dBm)	Limit (dBm)	Margin (dB)
802.11a				
100	5500	10.21	11	-0.79
116	5580	10.10	11	-0.90
144	5720	10.59	11	-0.41
802.11n 20MHz				
100	5500	9.80	11	-1.20
116	5580	9.83	11	-1.17
144	5720	10.28	11	-0.72
802.11n 40MHz				
102	5510	7.75	11	-3.25
118	5590	7.50	11	-3.50
142	5710	8.18	11	-2.82
802.11ac 80MHz				
106	5530	3.04	11	-7.96
122	5610	3.24	11	-7.76
138	5690	3.43	11	-7.57

4.4 Frequency stability  
FCC 15.407(g)

4.4.1 Requirement

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

4.4.2 Procedure

The EUT was placed in a temperature chamber and setup to transmit. Procedures for frequency stability in ANSIC63.10:2013 section 6.8 was utilized.

The carrier frequency was measured with the spectrum analyzer with resolution bandwidth of 1 kHz. The temperature was varied from 0°C to 50°C, as stated in the user manual.

The EUT in this report is powered by 120.0VAC which was varied to 85% and 115% for testing. Testing was performed at a temperature of 20°C.

After the temperature stabilized for approximately 20 minutes, the transmitting frequency was measured.

<b>Tested By:</b>	Minh Ly
<b>Test Date:</b>	December 13, 2017

## 4.4.3 Result

Temperature, $^{\circ}\text{C}$	<b>-26dB Band Edge at nominal voltage, (MHz)</b>	<b>Maximum deviation from frequency at 20°C, ppm</b>
Nominal Frequency: 5500 MHz		
50	5489.038462	11.659
40	5489.166667	11.697
30	5489.102564	0.019
20	5489.102462	0.000
10	5489.112453	1.820
0	5489.131555	5.300
Voltage at 20 $^{\circ}\text{C}$	<b>-26dB Band Edge at nominal voltage, (MHz)</b>	<b>Maximum deviation from frequency at 20°C, ppm</b>
120V - 15%	5489.102440	0.004
120V + 15%	5489.110657	1.493

4.5 Transmitter Radiated Emissions  
FCC Rule 15.407(b) (1-8) 15.209, 15.205

4.5.1 Requirement

(b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

Emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

Note: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

#### 4.5.2 Procedure

Radiated emission measurements were performed from 30 MHz to 40 GHz according to the procedure described in ANSI C64.10. Spectrum Analyzer Resolution Bandwidth is 100 kHz or greater for frequencies 30 MHz to 1000 MHz, 1 MHz for frequencies above 1000 MHz. Above 1000 MHz Peak and Average measurements were performed.

The EUT is placed on a plastic turntable that is 80 cm in height for below 1000MHz and 1.5m in height for above 1GHz. If the EUT attaches to peripherals, they are connected and operational (as typical as possible). During testing, all cables were manipulated to produce worst-case emissions. The signal is maximized through rotation. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters.

Radiated emissions are taken at 1 meter for Band Edge measurements. Radiated spurious emissions are taken at 3 meters for frequencies above 1 GHz and at 10 meters for frequencies below 1 GHz.

The 2.4GHz and 5GHz radio can transmit simultaneously; both of the transmitters are turned on during spurious emission to investigate for inter-modulation emission. Measurements made from 1 GHz to 18 GHz had a 2.4-2.5GHz and 5GHz notch filter in place. A preamp was used from 30MHz to 40GHz.

All measurements were made with a Peak Detector and compared to QP limits for 30MHz – 1GHz and Average limits for 1GHz – 40 GHz.

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels).

#### 4.5.3 Field Strength Calculation

##### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG; if measurement is performed at a distance other than specified in the rule, a Distance Correction Factor (DCF) shall be added.

Where FS = Field Strength in dB( $\mu$ V/m)

RA = Receiver Amplitude (including preamplifier) in dB( $\mu$ V); AF = Antenna Factor in dB(1/m)

CF = Cable Attenuation Factor in dB; AG = Amplifier Gain in dB

Assume a receiver reading of 52.0 dB( $\mu$ V) is obtained. The antennas factor of 7.4 dB(1/m) and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving field strength of 32 dB( $\mu$ V/m). This value in dB( $\mu$ V/m) was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB( $\mu$ V)

AF = 7.4 dB(1/m)

CF = 1.6 dB

AG = 29.0 dB

FS = 52.0+7.4+1.6-29.0 = 32 dB( $\mu$ V/m).

Level in  $\mu$ V/m = Common Antilogarithm [(32 dB $\mu$ V/m)/20] = 39.8  $\mu$ V/m.


#### 4.5.4 Test Results

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance where emissions are within 3dB of the limit.


Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz.

**Test Results: 15.209/15.205 Restricted Band Emissions at Antenna Port**

<b>Tested By:</b>	Minh Ly
<b>Test Date:</b>	December 05 - 08, 2017

**Out-of-Band Spurious Emissions at the Band Edge @1m Distance  
802.11a, 5500 MHz**

FCC Part 15/FCC Part 15.109 30M-40GHz B - Average/3.0m/  
 FCC Part 15/FCC Part 15.109 30M-40GHz B - QPeak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Average ) (Horizontal)  
 Peak (Peak /Lim. Average ) (Vertical)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Horizontal)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/06/2017 10:01

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5456.650	50.5	54.0	-3.5	1.6	315	Horizontal	29.1
5420.410	52.1	54.0	-1.9	1.6	0	Vertical	29.0
5426.357	53.5	54.0	-0.5	1.6	360	Vertical	29.0
5456.677	52.3	54.0	-1.7	1.6	0	Vertical	29.1


**Out-of-Band Spurious Emissions at the Band Edge @1m Distance  
802.11n 20MHz, 5500 MHz**

— FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/  
— Meas.Peak (Horizontal)  
— Meas.Peak (Vertical)  
✖ Peak (Peak /Lim. Peak ) (Horizontal)  
✖ Peak (Peak /Lim. Peak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/06/2017 13:05

FCC Part 15/FCC Part 15.109 30M-40GHz B - Average/3.0m/  
 FCC Part 15/FCC Part 15.109 30M-40GHz B - QPeak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Average ) (Horizontal)  
 Peak (Peak /Lim. Average ) (Vertical)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Horizontal)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/06/2017 10:25

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5458.638	50.2	54.0	-3.9	1.8	310	Horizontal /	29.1
5459.758	51.2	54.0	-2.8	1.6	348	Vertical /	29.1


**Out-of-Band Spurious Emissions at the Band Edge @1m Distance  
802.11n 40MHz, 5510 MHz**

FCC Part 15/FCC Part 15.109 30M-40GHz B - Average/3.0m/  
 FCC Part 15/FCC Part 15.109 30M-40GHz B - QPeak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Average ) (Horizontal)  
 Peak (Peak /Lim. Average ) (Vertical)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Horizontal)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/06/2017 10:54

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5457.543	49.9	54.0	-4.1	1.8	0	Horizontal	29.1
5458.246	52.1	54.0	-1.9	1.6	360	Vertical	29.1
5460.000	50.5	54.0	-3.5	1.6	360	Vertical	29.1

**Out-of-Band Spurious Emissions at the Band Edge @1m Distance  
802.11ac 80MHz, 5530 MHz**

FCC Part 15/FCC Part 15.109 30M-40GHz B - Average/3.0m/  
 FCC Part 15/FCC Part 15.109 30M-40GHz B - QPeak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Average ) (Horizontal)  
 Peak (Peak /Lim. Average ) (Vertical)  
 Meas.CISPR.AVG (Max Hold Manual meas.) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/06/2017 11:23

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5453.429	51.1	54.0	-3.0	1.5	348	Vertical	29.1
5459.749	51.3	54.0	-2.7	1.6	348	Vertical	29.1

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,**
**Tx at 802.11g 2412MHz, and 802.11a 5500MHz**
Radiated Spurious Emissions - 30 MHz to 1000 MHz


— FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. QPeak ) (Horizontal)  
 ✕ Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 10:46

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

— FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. Peak ) (Horizontal)  
 ✕ Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:02


Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit

Model: ; Client: ; Comments: ; Test Date: 12/06/2017 14:17

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz.

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,**
**Tx at 802.11g 2437MHz, and 802.11a 5580MHz**
Radiated Spurious Emissions - 30 MHz to 1000 MHz


— FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. QPeak ) (Horizontal)  
 ✕ Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 10:58

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

— FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. Peak ) (Horizontal)  
 ✕ Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:27

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:21

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
4006.733	32.8	54.0	-21.2	2.5	298	Horizontal	4.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,**
**Tx at 802.11g 2462MHz, and 802.11a 5720MHz**
Radiated Spurious Emissions - 30 MHz to 1000 MHz


— FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. QPeak ) (Horizontal)  
 ✕ Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 11:10

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

— FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. Peak ) (Horizontal)  
 ✕ Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:42

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:34

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 20MHz 2412MHz, and 802.11n 20MHz 5500MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 11:57

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:59

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/06/2017 15:53


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
6110.767	42.0	54.0	-12.0	1.5	273	Vertical	10.5

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 20MHz 2437MHz, and 802.11n 20MHz 5580MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 12:41

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 16:12

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/06/2017 16:06


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
4007.867	33.8	54.0	-20.2	2.5	299	Horizontal	4.3

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 20MHz 2462MHz, and 802.11n 20MHz 5720MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 12:53

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 16:25

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 16:19

Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
4007.867	33.4	54.0	-20.6	2.5	18	Horizontal	4.3



Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz


**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2437MHz, and 802.11n 40MHz 5510MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
6122.100	47.1	54.0	-6.9	1.5	297	Horizontal	10.5

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2462MHz, and 802.11n 40MHz 5590MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


— FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. QPeak ) (Horizontal)  
 ✕ Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 13:40

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

— FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 — Meas.Peak (Horizontal)  
 — Meas.Peak (Vertical)  
 ✕ Peak (Peak /Lim. Peak ) (Horizontal)  
 ✕ Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/06/2017 17:00

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/06/2017 16:54


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
6211.067	47.4	54.0	-6.6	1.5	0	Vertical	10.5

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2412MHz, and 802.11n 40MHz 5710MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 13:52

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 10:28

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/07/2017 10:11


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1878.333	47.8	54.0	-6.2	1.5	343	Vertical	-2.9
4016.933	44.7	54.0	-9.3	2.5	134	Horizontal	4.3

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2437MHz, and 802.11ac 80MHz 5530MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 14:15

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 11:08

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/07/2017 10:36


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1028.900	48.3	54.0	-5.7	1.5	0	Horizontal	-6.2
1860.767	44.7	54.0	-9.3	1.5	132	Vertical	-3.0

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2462MHz, and 802.11ac 80MHz 5610MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 14:28

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 11:01

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Model: ; Client: ; Comments: ; Test Date: 12/07/2017 10:52


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1028.900	47.8	54.0	-6.2	1.5	0	Horizontal	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

**Test Results: 15.209 Radiated Spurious Emissions Low Channel,  
Tx at 802.11n 40MHz 2412MHz, and 802.11ac 80MHz 5690MHz**

Radiated Spurious Emissions - 30 MHz to 1000 MHz


 FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. QPeak ) (Horizontal)  
 Peak (Peak /Lim. QPeak ) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 12/08/2017 14:40

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit

 FCC Part 15/15.407 UNII Peak 1GHz - 40GHz B - Peak/3.0m/  
 Meas.Peak (Horizontal)  
 Meas.Peak (Vertical)  
 Peak (Peak /Lim. Peak ) (Horizontal)  
 Peak (Peak /Lim. Peak ) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 11:24

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit


Frequency (MHz)	Average (dB $\mu$ V/m)	Lim. Avg (dB $\mu$ V/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1006.233	46.3	54.0	-7.7	2.5	227	Vertical	-6.4
1034.000	47.6	54.0	-6.4	2.5	227	Vertical	-6.2



Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

#### 4.5.5 Test setup photographs

**The following photographs show the testing configurations used.**



#### 4.5.6 Test Setup Photographs



## 5.0 List of Test Equipment

Measurement equipment used for emission compliance testing utilized the equipment on the following list:

Equipment	Manufacturer	Model/Type	Asset #	Cal Int	Cal Due
Spectrum Analyzer	Rohde and Schwarz	FSU	ITS 00913	12	01/12/18
EMI Receiver	Rohde and Schwarz	ESU	ITS 00961	12	07/10/18
Pyramidal Horn Antenna	EMCO	3160-09	ITS 00571	#	#
Pyramidal Horn Antenna	EMCO	3160-10	ITS 00572	#	#
Horn Antenna	ETS-Lindgren	3117	ITS 00982	12	02/03/18
BI-Log Antenna	Teseq	CBL 6111D	ITS 01058	12	08/11/18
Pre-Amplifier (18-40GHz)	Miteq	TTA1840-35-S-M	ITS 01393	12	04/18/18
Pre-Amplifier (1-18GHz)	Miteq	AMF-4D-001180-24-10P	ITS 00526	12	01/04/18
Pre-Amplifier	Sonoma Instrument	310	ITS 00942	12	01/19/18
Notch Filter	Micro-Tronics	BRM50702	ITS 01166	12	02/08/18
Notch Filter	Micro-Tronics	BRM50703	ITS 01167	12	01/19/18
Notch Filter	Micro-Tronics	BRM50705	ITS 01169	12	01/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01462	12	08/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01465	12	08/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01470	12	08/19/18
Attenuator	Mini Circuits	BW-N3W5+	ITS 01316	12	11/29/18
Attenuator	Narda	FSCM99899	ITS 01583	12	08/31/18
RF Cable	Megaphase	EMC1-K1K1-236	ITS 01538	12	06/13/18
RF Cable	Megaphase	TM40-K1K1-19	ITS 01154	12	01/26/18
RF Cable	Megaphase	TM40-K1K1-59 RF	ITS 01156	12	01/26/18

# No Calibration required

Software used for emission compliance testing utilized the following:

Name	Manufacturer	Version	Template/Profile
BAT-EMC	Nexio	3.16.0.64	Altice, ML_12-08-2017.bpp Altice, ML_12-05-2017.bpp
RS Commander	Rohde Schwarz	1.6.4	Not Applicable (Screen grabber)

## 6.0 Document History

Revision/ Job Number	Writer Initials	Reviewer Initials	Date	Change
1.0 / G103224477	ML	KV	December 27, 2017	Original document