



FCC RF EXPOSURE REPORT

| | | |
|--------------------------------|---|---|
| Applicant | : | Rayrun Technology Co., Ltd. |
| Address of Applicant | : | 5th Floor, Building 2, Haitian Lanyu Industrial Park, Shilong Community, Shiyan Street, Baoan District, Shenzhen, China |
| Manufacturer | : | Rayrun Technology Co., Ltd. |
| Address of Manufacturer | : | 5th Floor, Building 2, Haitian Lanyu Industrial Park, Shilong Community, Shiyan Street, Baoan District, Shenzhen, China |
| Equipment under Test | : | Remote Controller |
| Model No. | : | ATP01, ATP02, ATP03, ATP04, ATP05, ATP06, ATP07, ATP08, ATP09 |
| FCC ID | : | 2ACJPATP06 |
| Test Standard(s) | : | KDB447498 D01 General RF Exposure Guidance v06 |
| Report No. | : | DDT-RE24110531-1E02 |
| Issue Date | : | 2024/12/04 |
| Issue By | : | Guangdong Dongdian Testing Service Co., Ltd. |
| Address of Laboratory | : | Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808 |

REPORT

Table of Contents

| | |
|---|---|
| Test report declares..... | 3 |
| 1. General Information | 5 |
| 1.1. Description of equipment | 5 |
| 1.2. Assess laboratory..... | 5 |
| 2. RF Exposure evaluation for FCC | 6 |

Test Report Declare

| | | |
|--------------------------------|---|---|
| Applicant | : | Rayrun Technology Co., Ltd. |
| Address of Applicant | : | 5th Floor, Building 2, Haitian Lanyu Industrial Park, Shilong Community, Shiyan Street, Baoan District, Shenzhen, China |
| Equipment under Test | : | Remote Controller |
| Model No. | : | ATP01, ATP02, ATP03, ATP04, ATP05, ATP06, ATP07, ATP08, ATP09 |
| Manufacturer | : | Rayrun Technology Co., Ltd. |
| Address of Manufacturer | : | 5th Floor, Building 2, Haitian Lanyu Industrial Park, Shilong Community, Shiyan Street, Baoan District, Shenzhen, China |

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

| | | | |
|-------------------------|---------------------|----------------------|-----------------------|
| Report No.: | DDT-RE24110531-2E02 | | |
| Date of Receipt: | 2024/11/19 | Date of Test: | 2024/11/19~2024/12/04 |

Prepared By:



Johnson Huang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

| Rev. | Revisions | Issue Date | Revised By |
|------|---------------|------------|------------|
| --- | Initial issue | 2024/12/04 | |
| | | | |

1. General Information

1.1. Description of equipment

| | |
|----------------------------|---|
| EUT Name | : Remote Controller |
| Model Number | : ATP01, ATP02, ATP03, ATP04, ATP05, ATP06, ATP07, ATP08, ATP09 |
| Difference of model number | : All models are identical except the appearance, software and model name, therefore the test performed on the model ATP06. |
| EUT function description | : Please reference user manual of this device |
| Power supply | : DC 3V From Button cell |
| Operation frequency | : 433.79MHz |
| Modulation | : OOK |
| Antenna Type | : Internal antenna |
| Sample Number | : S24110531-002 |

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

SRD

| GFSK (Peak) | |
|----------------------|---------------|
| Frequency (MHz) | 433.79 |
| Target (dBm) | -31.85 |
| Tolerance \pm (dB) | 2 |

Note:

PK Output Power=63.35dBuV/m@3m-95.2=-31.85dBm

Please refer to the test report "DDT-RE24110531-1E01"

Estimation Result

Worse case is as below: [433.79 MHz, -29.85 dBm, (0.001 mW) output power]

$(0.001 / 5) \cdot [\sqrt{0.43379(\text{GHz})}] = 0.00001 < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required.

END OF REPORT