Equipment : Myo Blue Tooth Dongle

Brand Name : Thalmic Labs Inc.

Model No. : BT-420

FCC ID : 2ACKV-TLD1B

Standard : 47 CFR FCC Part 15.247 Operating Band : 2400 MHz – 2483.5 MHz

FCC Classification: DTS

Applicant : Thalmic Labs Inc.

24 Charles St W., Kitchener, Ontario,

Canada N2G1H2

Manufacturer : CC&C Technologies, Inc.

8F, No.150, Jian Yi Rd, Zhonghe District,

New Taipei City, 235, Taiwan

The product sample received on Mar. 10, 2014 and completely tested on Mar. 14, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Vic Hsiao / Supervisor

Testing Laboratory 1190

Report No.: FR422023-02

SPORTON INTERNATIONAL INC. Page No. : 1 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01



Table of Contents

I	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Support Equipment	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter	9
2.3	The Worst Case Measurement Configuration	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	6dB Bandwidth	16
3.3	RF Output Power	18
3.4	Power Spectral Density	20
3.5	Transmitter Bandedge Emissions	22
3.6	Transmitter Unwanted Emissions	25
ļ	TEST EQUIPMENT AND CALIBRATION DATA	36

APPENDIX A. TEST PHOTOS

APPENDIX B. PHOTOGRAPHS OF EUT

Report No.: FR422023-02



Summary of Test Result

Report No.: FR422023-02

	Conformance Test Specifications								
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result				
1.1.3	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied				
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.2018130MHz 44.34 (Margin 9.20dB) - AV 53.70 (Margin 9.84dB) - QP	FCC 15.207	Complied				
3.2	15.247(a)	6dB Bandwidth	LE: 712 kHz	≥500kHz	Complied				
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm] LE: 1.38	Power [dBm] LE:30	Complied				
3.4	15.247(e)	Power Spectral Density	PSD [dBm/100kHz] LE: -15.77	PSD [dBm/3kHz]: 8	Complied				
3.5	15.247(d)	Transmitter Bandedge Emissions	Restricted Bands [dBuV/m at 3m]: 2483.760 MHz 57.19 (Margin 16.81dB) - PK 45.70 (Margin 8.30dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied				
3.6	15.247(d)	Transmitter Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 797.270 MHz 38.73 (Margin 7.27dB) - PK	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied				

SPORTON INTERNATIONAL INC. Page No. : 3 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01



Revision History

Report No. : FR422023-02

Report No.	Version	Description	Issued Date
FR422023-02	Rev. 01	Initial issue of report	Oct. 08, 2014

SPORTON INTERNATIONAL INC. Page No. : 4 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

1 General Description

1.1 Information

1.1.1 Product Details

The equipment is Myo Blue Tooth Dongle. The equipment contains three exterior appearances. One is back and the others are blue. There are also two types of Balan Filters in this equipment. The difference between two Balan Filters is the supply company. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Report No.: FR422023-02

1.1.2 RF General Information

RF General Information							
Frequency Range (MHz)	Bluetooth Version	Ch. Frequency (MHz)	Channel Number	RF Output Power (dBm)			
2400-2483.5	v4.0 LE	2402-2480	0-39 [40]	1.38			

Note 1: Bluetooth LE (Low Energy) using GFSK modulation for DTS digital modulation. Note 2: RF output power specifies that Maximum Peak Conducted Output Power.

1.1.3 Antenna Information

	Antenna Category								
\boxtimes	Integral antenna (antenna permanently attached)								
	☐ Temporary RF connector provided								
		No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.							

	Antenna General Information						
No.	No. Ant. Cat. Ant. Type Gain (dBi)						
1	Integral	PIFA	1.80				

SPORTON INTERNATIONAL INC. : 5 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



1.1.4 Type of EUT

		ldenti	ify EUT			
EU	EUT Serial Number N/A					
Pre	sentation of Equipment	□ Production ; □ Production : □ Production	re-Production; Prototyp	e		
		Туре	of EUT			
\boxtimes	Stand-alone					
	Combined (EUT where t	he radio part is fully integ	grated within another device	e)		
	Combined Equipment –	Brand Name / Model No	.:			
	Plug-in radio (EUT inten	ded for a variety of host	systems)			
	Host System – Brand Na	ame / Model No.:				
	Other:					
1.1.	.5 Test Signal Duty	Cycle				
		Operated Mode fo	or Worst Duty Cycle			
\boxtimes	Operated test mode for	worst duty cycle				
	Test Signal Du	ty Cycle (x)		uty Factor 0 log 1/x)		
\boxtimes						
1.1.	1.1.6 EUT Operational Condition					
Sup	oply Voltage	AC mains	□ DC	System		
Typ	e of DC Source	Internal DC supply		☐ Battery		

Report No. : FR422023-02

SPORTON INTERNATIONAL INC. Page No. : 6 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

1.2 Support Equipment

Support Equipment – RF Conducted						
No.	No. Equipment Brand Name Model Name					
1	Notebook	DELL	E5520			

Report No.: FR422023-02

	Support Equipment – AC Conduction & Radiated Emission						
No.	No. Equipment Brand Name Model Name						
1	Notebook	DELL	E5530				

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15
- ANSI C63.10-2009
- FCC KDB 558074

1.4 Testing Location Information

	Testing Location							
\boxtimes	HWA YA	ADD	:	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.				
	TEL: 886-3-327-3456 FAX: 886-3-327-0973							
Test Condition			Test Site No.	Test Engineer	Test Environment			
	AC Conduc	ction		CO04-HY	Zeus	22°C / 55%		
RF Conducted		TH06-HY	Wei	23°C / 64%				
F	Radiated Emission			03CH03-HY	Leo	22°C / 55%		

SPORTON INTERNATIONAL INC. Page No. : 7 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Report No.: FR422023-02

Measurement Uncertainty						
Test Item	Uncertainty					
AC power-line conducted emissions		±2.2 dB				
Emission bandwidth, 6dB bandwidth		±1.4 %				
RF output power, conducted		±0.6 dB				
Power density, conducted		±0.8 dB				
Unwanted emissions, conducted	30 – 1000 MHz	±0.5 dB				
	1 – 18 GHz	±0.6 dB				
	18 – 40 GHz	±0.8 dB				
	40 – 200 GHz	N/A				
All emissions, radiated	30 – 1000 MHz	±2.5 dB				
	1 – 18 GHz	±3.5 dB				
	18 – 40 GHz	±3.8 dB				
	40 – 200 GHz	N/A				
Temperature		±0.8 °C				
Humidity		±3 %				
DC and low frequency voltages		±3 %				
Time		±1.4 %				
Duty Cycle		±1.4 %				

SPORTON INTERNATIONAL INC. Page No. : 8 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing						
Bluetooth Version	Transmit Chains (N _{TX})	Data Rate	Modulation Mode			
LE	1	1 Mbps	LE-1Mbps			

Report No.: FR422023-02

Note 1: Bluetooth LE (Low Energy) using GFSK modulation for DTS digital modulation.

Note 2: Modulation modes consist below configuration:

DSSS LE-1Mbps: GFSK (1Mbps)

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter			
Test Software Version	BTool-Bluetooth Low Energy PC Application		
Modulation Mode	2402 MHz	2440 MHz	2480 MHz
LE,1Mbps	Default	Default	Default

SPORTON INTERNATIONAL INC. Page No. : 9 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests		
Tests Item AC power-line conducted emissions		
Condition AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz		
Operating Mode	Operating Mode Description	
1	EUT with Notebook & Transmitting	

Report No.: FR422023-02


The Worst Case Mode for Following Conformance Tests		
Tests Item	RF Output Power, Power Spectral Density, 6 dB Bandwidth	
Test Condition	Conducted measurement at transmit chains	
Modulation Mode	LE-1Mbps	

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
Test Condition	Radiated measurement		
User Position	EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes.		
	EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.		
Operating Mode	Operating Mode Description		
1	EUT with Notebook & Transmitting		
Modulation Mode	LE-1Mbps		
	X Plane		
Orthogonal Planes of EUT			

SPORTON INTERNATIONAL INC. Page No. : 10 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



2.4 Test Setup Diagram



Report No.: FR422023-02

SPORTON INTERNATIONAL INC. Page No. : 11 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

Test Setup Diagram - Radiated Emission Below 1GHz Test 120 Vac / 60 Hz Adapter Notebook Test Setup Diagram - Radiated Emission Above 1GHz Test 120 Vac / 60 Hz Adapter Notebook

Report No.: FR422023-02

SPORTON INTERNATIONAL INC. Page No. : 12 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Powe	er-line Conducted Emissions L	imit
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Report No.: FR422023-02


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

	Test Method
\boxtimes	Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.


3.1.4 Test Setup



SPORTON INTERNATIONAL INC. Page No. : 13 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

Report No.: FR422023-02

3.1.5 Test Result of AC Power-line Conducted Emissions



Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

SPORTON INTERNATIONAL INC. Page No. : 14 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

AC Power-line Conducted Emissions Result Operating Mode Power Phase Line **Operating Function EUT with Notebook & Transmitting** Date: 2014-03-13 Level (dBuV) NCC/IC/FCC-B NCC/IC/FCC-B AV 0.15 0.2 0.5 5 10 30 Frequency (MHz) Read LISN Cable Over Limit Freq Level Limit Line Level Factor Loss Remark dB dBuV MHz dBuV dBuV 1 0.1944650 54.21 -9.63 63.84 53.69 0.03 0.49 QP 2 0.1944650 44.04 -9.80 53.84 43.52 0.03 0.49 Ave 0.49 Average 0.2094380 52.02 -11.21 63.23 51.48 0.03 0.51 QP 0.2094380 42.09 -11.14 53.23 41.55 0.03 0.51 Average 5 0.3520120 40.10 -18.81 58.91 39.49 0.03 0.58 OP

Report No.: FR422023-02

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

0.03

0.03

0.03

0.03

0.03

0.39

0.39

0.58 Average

0.59 Average

0.62 Average

0.58 Average

0.59 QP

0.62 QP

0.58 QP

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

6 0.3520120 26.20 -22.71 48.91 25.59

8 0.3791160 43.28 -15.02 58.30 42.66

10 0.4305230 32.01 -15.23 47.24 31.36

0.3791160 30.24 -18.06 48.30 29.62

0.4305230 42.97 -14.27 57.24 42.32

26.140 32.01 -17.99 50.00 31.04 26.140 39.13 -20.87 60.00 38.16

SPORTON INTERNATIONAL INC. Page No. : 15 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973

9

11 12

3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit		
Systems using digital modulation techniques:		
6 dB bandwidth ≥ 500 kHz.		

Report No.: FR422023-02

3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

		Test Method
\boxtimes	For	the emission bandwidth shall be measured using one of the options below:
	\boxtimes	Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
		Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
		Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
\boxtimes	For	conducted measurement.
	\boxtimes	The EUT supports single transmit chain and measurements performed on this transmit chain.
		The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.2.4 Test Setup


Emission Bandwidth Spectrum Analyzer		
	Emission Bandwidth	

SPORTON INTERNATIONAL INC. Page No. : 16 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result				
Modulation Mode Freq. (MHz)		99% Bandwidth (kHz)	6dB Bandwidth (kHz)	
LE-1Mbps	2402	1102.7496	712.0000	
LE-1Mbps	2440	1102.7496	720.7000	
LE-1Mbps	2480	1098.4081	712.0000	
Limit		N/A	≥500 kHz	
Result		Com	plied	

Report No.: FR422023-02



SPORTON INTERNATIONAL INC. Page No. : 17 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

3.3 RF Output Power

3.3.1 RF Output Power Limit

		RF Output Power Limit for Digital Modulation Systems	
Max	Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit		
\boxtimes	240	0-2483.5 MHz Band:	
	\boxtimes	If $G_{TX} \le 6$ dBi, then $P_{Out} \le 30$ dBm (1 W)	
		Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm	
e.i.r.	р. Р	ower Limit:	
\boxtimes	240	0-2483.5 MHz Band	
	\boxtimes	Point-to-multipoint systems (P2M): P _{eirp} ≤ 36 dBm (4 W)	
GTX	 Pout = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm. 		

Report No.: FR422023-02


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

		Test Method
\boxtimes	Max	ximum Peak Conducted Output Power
	\boxtimes	Refer as ANSI C63.10, clause 6.10.2.1 a) for peak power meter.
		Refer as ANSI C63.10, clause 6.10.2.1 a) for spectrum analyzer - (RBW ≥ EBW).
\boxtimes	For	conducted measurement.
	\boxtimes	The EUT supports single transmit chain and measurements performed on this transmit chain.
		The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.3.4 Test Setup



SPORTON INTERNATIONAL INC. Page No. : 18 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



FCC Test Report No.: FR422023-02

3.3.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result								
Condition		RF Output Power (dBm)						
Modulation Mode Freq. (MHz)		RF Output Power	Power Limit	Antenna Gain (dBi)	EIRP Power	EIRP Limit		
LE-1Mbps	2402	1.38	30	1.80	3.18	36		
LE-1Mbps	2440	0.68	30	1.80	2.48	36		
LE-1Mbps	2480	-0.07	30	1.80	1.73	36		
Result	Complied							

3.3.6 Test Result of Maximum Average Conducted Output Power

Maximum Average Conducted Output Power Result								
Condition			RF Output Power (dBm)					
Modulation Mode Freq. (MHz)		Average Power	Duty Factor (dB)	RF Output Power	Antenna Gain (dBi)	EIRP Power		
LE-1Mbps	2402	1.17	0.00	1.17	1.80	2.97		
LE-1Mbps	2440	0.46	0.00	0.46	1.80	2.26		
LE-1Mbps	2480	-0.31	0.00	-0.31	1.80	1.49		
Result	Complied							

SPORTON INTERNATIONAL INC. Page No. : 19 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

FCC Test Report No.: FR422023-02

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

	Power Spectral Density Limit
\boxtimes	Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

	Test Method
\boxtimes	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
	Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak)
	[duty cycle ≥ 98% or external video / power trigger]
	Refer as FCC KDB 558074, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
	Refer as FCC KDB 558074, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
	Refer as FCC KDB 558074, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
	Refer as FCC KDB 558074, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
\boxtimes	For conducted measurement.
	☐ The EUT supports single transmit chain and measurements performed on this transmit chain.
	☐ The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.4.4 Test Setup




SPORTON INTERNATIONAL INC. Page No. : 20 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result								
Modulation Mode	Freq. (MHz)	PSD (dBm/100kHz)	PSD Limit (dBm/3kHz)					
LE-1Mbps	2402	-15.77	8					
LE-1Mbps	2440	-16.50	8					
LE-1Mbps 2480		-17.11	8					
Res	sult	Com	plied					

Report No.: FR422023-02




SPORTON INTERNATIONAL INC. Page No. : 21 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



3.5 Transmitter Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit



Report No.: FR422023-02

3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


SPORTON INTERNATIONAL INC. Page No. : 22 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

3.5.3 Test Procedures

		Test Method									
\boxtimes	The	average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].									
\boxtimes		er as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency and highest frequency channel within the allowed operating band.									
\boxtimes	For	or the transmitter unwanted emissions shall be measured using following options below:									
	\boxtimes	Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.									
	\boxtimes	Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.									
		Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle ≥98%)									
		Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).									
		Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW≥1/T).									
		Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW ≥ 1/T, where T is pulse time.									
		Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.									
		Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.									
\boxtimes	For	the transmitter bandedge emissions shall be measured using following options below:									
		Refer as FCC KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).									
	\boxtimes	Refer as ANSI C63.10, clause 6.9.2 for band-edge testing.									
		Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.									
\boxtimes	For	radiated measurement, refer as FCC KDB 558074, clause 12.2.7.									
	For	conducted measurement, refer as FCC KDB 558074, clause 12.2.2.									

Report No.: FR422023-02

3.5.4 Test Setup



SPORTON INTERNATIONAL INC. Page No. : 23 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



Transmitter Radiated Bandedge Emissions

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Non-restricted Band)									
Modulation	N _{TX}	Test Freq. (MHz)	In-band PSD [i] Freq. (MHz)		Out-band PSD [o] (dBuV/100kHz)	PSD [o] [i] - [o] (dB)		Pol.	
LE-1Mbps	1	2402	88.64	2396.290	60.40	28.24	20	V	
LE-1Mbps 1 2480 88.95 2529.520 60.55 28.40 20 V									
Note 1: Measure	ment wo	rst emission	s of receive ante	nna polarization	I				

Report No.: FR422023-02

	2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Restricted Band)										
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.	
LE-1Mbps	1	2402	3	2322.040	56.76	74	2389.870	44.96	54	V	
LE-1Mbps	1	2480	3	2487.520	57.19	74	2483.760	45.70	54	V	

Note 1: Measurement worst emissions of receive antenna polarization.

Note 2: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us, VBW=3kHz.

SPORTON INTERNATIONAL INC. Page No. : 24 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

3.6 Transmitter Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit								
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)					
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300					
0.490~1.705	24000/F(kHz)	33.8 - 23	30					
1.705~30.0	30	29	30					
30~88	100	40	3					
88~216	150	43.5	3					
216~960	200	46	3					
Above 960	500	54	3					

Report No.: FR422023-02

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit						
RF output power procedure	Limit (dB)					
Peak output power procedure	20					
Average output power procedure	30					

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

SPORTON INTERNATIONAL INC. Page No. : 25 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01




3.6.3 Test Procedures

	Test Method
perfe equi extra dista	surements may be performed at a distance other than the limit distance provided they are not bring or the near field and the emissions to be measured can be detected by the measurement pment. When performing measurements at a distance other than that specified, the results shall be applated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear ince for field-strength measurements, inverse of linear distance-squared for power-density surements).
\boxtimes	Measurements in the frequency range 10 GHz - 18GHz are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
\boxtimes	Measurements in the frequency range above 18 GHz - 25GHz are typically made at a closer distance 0.5m, because the instrumentation noise floor is typically close to the radiated emission limit.
The	average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].
For	the transmitter unwanted emissions shall be measured using following options below:
\boxtimes	Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
\boxtimes	Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
	☐ Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle ≥98%)
	Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
	Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW≥1/T).
	☐ Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW ≥ 1/T, where T is pulse time.
	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
	Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
	Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
For	radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
\boxtimes	Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
\boxtimes	Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
\boxtimes	Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.
For	conducted and cabinet radiation measurement, refer as FCC KDB 558074, clause 12.2.2.

Report No. : FR422023-02

SPORTON INTERNATIONAL INC. Page No. : 26 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

3.6.4 Test Setup



Report No.: FR422023-02


Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna and the frequency range of 1 GHz to 40 GHz using a calibrated horn antenna.

3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)


All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

SPORTON INTERNATIONAL INC. Page No. : 27 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

Transmitter Radiated Unwanted Emissions (Below 1GHz)



Report No.: FR422023-02



	Freq	Level	Over Limit		200	Antenna Factor	1000	Preamp Factor	Remark	Ant Pos	Table Pos
-	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		com	deg
1	97.900	27.05	-16.45	43.50	42.18	10.69	1.57	27.39	Peak		
2	164.830	28.24	-15.26	43.50	43.33	9.92	2.12	27.13	Peak		
3	365.620	30.25	-15.75	46.00	39.44	14.72	3.19	27.10	Peak		
4	547.980	30.59	-15.41	46.00	36.04	18.57	3.91	27.93	Peak		-
5	661.470	30.60	-15.40	46.00	35.37	18.79	4.40	27.96	Peak		
6 0	797.270	38.73	-7.27	46.00	41.98	19.65	4.90	27.80	Peak		

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).

Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.


SPORTON INTERNATIONAL INC. Page No. : 28 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

Transmitter Radiated Unwanted Emissions

Operating Mode 1 Polarization H

Operating Function EUT with Notebook & Transmitting

Report No.: FR422023-02



			Over	Limit	Readi	Antenna	Cable	Preamp		Ant	Table
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
-	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		con	deg
1	238.550	30.05	-15.95	46.00	42.77	11.60	2.55	26.87	Peak		
2	296.750	32.81	-13.19	46.00	43.41	13.18	2.88	26.66	Peak		
3	365.620	36.76	-9.24	46.00	45.95	14.72	3.19	27.10	Peak		1944
4	431.580	33.18	-12.82	46.00	40.93	16.32	3.44	27.51	Peak		
5	598.420	30.46	-15.54	46.00	35.90	18.41	4.14	27.99	Peak		
6 @	797.270	37.20	-8.80	46.00	40.45	19.65	4.90	27.80	Peak		

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).


Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 29 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)



Report No.: FR422023-02




		Freq	Level	Over Limit	0000		Antenna Factor		Preamp Factor	Remark	Ant Pos	Table Pos
	-	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	-	can	deg
	1	4808.000	46.42	-27.58	74.00	40.09	33.06	5.71	32.44	Peak		
	2	4808.000	37.43	-16.57	54.00	31.10	33.06	5.71	32.44	Average		
	3	7202.000	51.47			41.11	35.80	7.20	32.64	Peak		
1	4	9608.000	54.48			40.54	38.23	8.81	33.10	Peak		
		The second secon										

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (88.68 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us, VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 30 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

FCC Test Report Report No.: FR422023-02

	Transmitter Radiated Unwanted Emissions									
Modulation Mode	LE-1Mbps	Test Freq. (MHz)	2402							
Operating Mode	1	Polarization	Н							




	Freq	Level	Over Limit			Antenna Factor		Preamp Factor	Remark	Ant Pos	Table Pos
	MKz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		can	deg
1	4804.000	46.42	-27.58	74.00	40.09	33.06	5.71	32.44	Peak		
2	4804.000	35.86	-18.14	54.00	29.53	33.06	5.71	32.44	Average		
3	7206.000	51.34			40.98	35.80	7.20	32.64	Peak		
4	9608.000	55.06			41.12	38.23	8.81	33.10	Peak		

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (88.68 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us. VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 31 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

	Transmitter Radiated Unwanted Emissions								
Modulation Mode	LE-1Mbps	Test Freq. (MHz)	2440						
Operating Mode	1	Polarization	V						

Report No.: FR422023-02




	Freq	Level	Over Limit			Intenna Factor		Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		con	deg
1	4880.000	39.08	-14.92	54.00	32.60	33.18	5.72	32.42	Average		
2	4880.000	48.99	-25.01	74.00	42.51	33.18	5.72	32.42	Peak		
3	7320.000	38.74	-15.26	54.00	28.04	36.09	7.28	32.67	Average		
4	7320.000	51.02	-22.98	74.00	40.32	36.09	7.28	32.67	Peak		
5	9760.000	53.33			39.08	38.57	8.76	33.08	Peak		

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (89.36 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us, VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 32 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

	Transmitter Radiated	Unwanted Emissions	
Modulation Mode	LE-1Mbps	Test Freq. (MHz)	2440


Report No.: FR422023-02




	Freq	Level	Over Limit	Define a		Antenna Factor		Preamp Factor		Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		con.	deg
1	4880.000	47.46	-26.54	74.00	40.98	33.18	5.72	32.42	Peak		
2	4880.000	36.09	-17.91	54.00	29.61	33.18	5.72	32.42	Average		
3	7320.000	50.41	-23.59	74.00	39.71	36.09	7.28	32.67	Peak		
4	7320.000	39.61	-14.39	54.00	28.91	36.09	7.28	32.67	Average		
5	9760.000	54.04			39.79	38.57	8.76	33.08	Peak		

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (89.36 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us, VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 33 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01



Report No.: FR422023-02




	Freq	Level	Over Limit			Antenna Factor		Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		com	deg
1	4960.000	48.68	-25.32	74.00	42.00	33.34	5.75	32.41	Peak		
2	4960.000	38.79	-15.21	54.00	32.11	33.34	5.75	32.41	Average		
3	7440.000	39.94	-14.06	54.00	28.90	36.38	7.37	32.71	Average		
4	7440.000	50.90	-23.10	74.00	39.86	36.38	7.37	32.71	Peak		
5	9920.000	55.50			40.91	38.95	8.71	33.07	Peak		

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (89.16 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us, VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 34 of 37
TEL: 886-3-327-3456 Report Version : Rev. 01

FCC Test Report Report No.: FR422023-02

	Transmitter Radiated Unwanted Emissions									
Modulation Mode	LE-1Mbps	Test Freq. (MHz)	2480							
Operating Mode	1	Polarization	Н							



			Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		can	deg
1	4960.000	35.70	-18.30	54.00	29.02	33.34	5.75	32.41	Average		
2	4960.000	47.12	-26.88	74.00	40.44	33.34	5.75	32.41	Peak		
3	7440.000	40.34	-13.66	54.00	29.30	36.38	7.37	32.71	Average		
4	7440.000	51.73	-22.27	74.00	40.69	36.38	7.37	32.71	Peak		200
5	9920.000	55.37			40.78	38.95	8.71	33.07	Peak		

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (89.16 dBuV/m).
- Note 5: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is "Pulse On Time", e.g., LE VBW≥1/625us. VBW=3kHz.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

SPORTON INTERNATIONAL INC. Page No. : 35 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01

4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 25, 2013	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	JAN. 21, 2014	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	Oct. 30, 2013	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Report No.: FR422023-02

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101013	9KHz~40GHz	Jan. 25, 2014	Conducted (TH06-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 27, 2013	Conducted (TH06-HY)
Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	Sep. 11, 2013	Conducted (TH06-HY)
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	Sep. 11, 2013	Conducted (TH06-HY)

Note: Calibration Interval of instruments listed above is one year.

SPORTON INTERNATIONAL INC. Page No. : 36 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	Nov. 30, 2013	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	May. 03, 2013	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	Aug. 20, 2013	Radiation (03CH03-HY)
Spectrum	R&S	FSV40	101514	10Hz ~ 40GHz	Apr. 15, 2013	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30MHz ~ 1GHz	Sep. 21, 2013	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 31, 2013	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jan. 10, 2014	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 16, 2013	Radiation (03CH03-HY)
RF Cable-high	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz ~ 40GHz	Dec. 11, 2013	Radiation (03CH03-HY)
Turn Table	EM Electronics	EM Electronics	060615	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	MF	MF-7802	MF780208179	1 ~ 4 m	N/A	Radiation (03CH03-HY)

Report No.: FR422023-02

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9kHz ~ 30MHz	Dec. 02, 2012	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

SPORTON INTERNATIONAL INC. Page No. : 37 of 37 TEL: 886-3-327-3456 Report Version : Rev. 01