



Radio Frequency Exposure

EUT INFORMATION

FCC ID	2ACLCECNSDSBC330J60
EUT	Embedded computer
Frequency band (Operating)	2412 MHz ~ 2462 GHz
Max. output power	23.37 dBm
Antenna gain (Max)	2.7 dBi

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency Radiation as specified in §1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

TEST RESULT

The EUT use shall be at least 20cm distance away from human body.

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \cdot P \cdot G}}{d}$$

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = E^2 / 3770$$

Combine these two formulas can be changed to

$$P_d = (30 \cdot P \cdot G) / (3770 \cdot d^2)$$

**Note:**

1. "E" means Electric field (V/m).
2. "P" means Peak RF output power (W).
3. "G" means EUT Antenna numeric gain (numeric).
4. "d" means the minimum mobile separation distance is 0.2m between radiator and human body.

$$G=10^{(2.7/10)} = 1.86$$

Modulation Type	Channel	Frequency (MHz)	Output Power to Antenna (dBm)	Tune-up power (dBm)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
802.11b	1	2412	22.08	23	0.0738	1
	6	2437	22.17	23	0.0738	1
	11	2462	21.99	22	0.0586	1
802.11g	1	2412	23.05	24	0.0929	1
	6	2437	23.37	24	0.0929	1
	11	2462	23.11	24	0.0929	1
802.11n HT20	1	2412	22.13	23	0.0738	1
	6	2437	22.39	23	0.0738	1
	11	2462	22.19	23	0.0738	1

Tested By:**Reviewed by:**

Jun. 07, 2022

(Date)

Bing/Engineer

Jun. 07, 2022

(Date)

Bell/Manager

FCC Designation Number: TW2954