### RF EXPOSURE EVALUATION

## **EUT Specification**

Report No.: NTC1406804F

EUT	PORTABLE BLUETOOTH WIRELESS STEREO SPEAKER				
Frequency band	□WLAN: 2.412GHz ~ 2.462GHz				
(Operating)	□WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz				
	□WLAN: 5.745GHz ~ 5825GHz				
	⊠Others(Bluetooth: 2.402GHz ~ 2.480GHz)				
Device category	⊠Portable (<20cm separation)				
	☐Mobile (>20cm separation)				
	Others				
Antenna diversity	⊠Single antenna				
	☐Multiple antennas				
	☐Tx diversity				
	☐Rx diversity				
	☐Tx/Rx diversity				
Max. output power	-2.92dBm (0.51mW)				
Antenna gain	0 dBi				
Evaluation applied	☐MPE Evaluation				
	⊠SAR Evaluation				

# **Standard Requirement**

#### **Portable Device**

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [ $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation17
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

### **Measurement Result**

Report No.: NTC1406804F

Channel	Channel Frequency	Max Output AVG power	Max Output AVG power	Calculation Value <sup>(Note 1)</sup>	Threshold Value	
	(MHz)	(dBm)	(mW)			
GFSK						
Low	2402.00	-3.72	0.42	0.13	3.0	
Middle	2441.00	-3.09	0.49	0.15	3.0	
High	2480.00	-2.92	0.51	0.16	3.0	
π/4-DQPSK						
Low	2402.00	-5.15	0.31	0.10	3.0	
Middle	2441.00	-4.31	0.37	0.12	3.0	
High	2480.00	-4.20	0.38	0.12	3.0	
8DPSK						
Low	2402.00	-4.81	0.33	0.10	3.0	
Middle	2441.00	-4.10	0.39	0.12	3.0	
High	2480.00	-3.99	0.40	0.13	3.0	

Note 1: Calculation Value =[(max. power of channel, mW)/(min.

test separation distance, mm)] • [ $\sqrt{f(GHz)}$ ]. Fox example:  $0.42/5*\sqrt{2.402}=0.13 \le 3.0$ 

According to KDB447498 D01 v05, threshold at which no SAR required is  $\leq$ 3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.