

FCC RF Test Report

For

Condeco Ltd

Test Standards: Part 15C Subpart C §15.247

Product Name: V3 Desk Screen

Tested Model: 201850

FCC ID: 2ACML-201850

Classification: Digital Spread Spectrum (DSS)

Report No.: EC1911039RF03

Tested Date: 2019-12-10 to 2019-12-30

Issued Date: 2019-12-30

Prepared By:

Jerry Wang

Jerry Wang / Engineer

Approved By:

Bacon Wu

Bacon Wu / RF Manager

Hunan Ecloud Testing Technology Co., Ltd.

Building A1, Changsha E Center, No. 18 Xiangtai Avenue, Liuyang Economic and
Technological Development Zone, Hunan, P.R.C

Tel.: +86-731-89634887 Fax.: +86-731-89634887

www.hn-ecloud.com

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Hunan Ecloud Testing Technology Co., Ltd., the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2019.12.30	Valid	Original Report

TABLE OF CONTENTS

1	TEST LABORATORY	6
1.1	Test facility	6
2	GENERAL DESCRIPTION.....	7
2.1	Applicant	7
2.2	Manufacturer	7
2.3	General Description Of EUT	7
2.4	Modification of EUT	8
2.5	Applicable Standards.....	8
3	TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
3.1	Descriptions of Test Mode	9
3.2	Test Mode	10
3.3	Support Equipment	11
3.4	Test Setup	11
3.5	Measurement Results Explanation Example.....	13
4	TEST RESULT	14
4.1	20dB and 99% Bandwidth Measurement	14
4.2	Hopping Channel Separation Measurement	15
4.3	Number of Channel Measurement	16
4.4	Average Time of Occupancy Measurement	17
4.5	Peak Output Power Measurement	18
4.6	Conducted Band Edges Measurement	19
4.7	Conducted Spurious Emission Measurement	20
4.8	Radiated Band Edges and Spurious Emission Measurement	21
4.9	AC Conducted Emission Measurement.....	51
4.10	Antenna Requirements.....	54
5	LIST OF MEASURING EQUIPMENT.....	55
6	UNCERTAINTY OF EVALUATION.....	57
	APPENDIX A: 20DB EMISSION BANDWIDTH	58
	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	64
	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	70
	APPENDIX D: CARRIER FREQUENCY SEPARATION.....	76
	APPENDIX E: TIME OF OCCUPANCY	79
	APPENDIX F: NUMBER OF HOPPING CHANNELS	107

APPENDIX G: BAND EDGE MEASUREMENTS.....	110
APPENDIX H: CONDUCTED SPURIOUS EMISSION.....	117
APPENDIX I: DUTY CYCLE	132
APPENDIX J: SETUP PHOTOGRAPHS.....	138

Summary of Test Result

FCC Rule	Description	Limit	Result	Remark
15.247(a)(1)	20dB Bandwidth	NA	Pass	-
-	99% Bandwidth	-	Pass	-
15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
15.247(a)(1)	Number of Channels	≥ 15 Chs	Pass	-
15.247(a)(1)	Average Time of Occupancy	≤ 0.4 sec in 31.6sec period	Pass	-
15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
15.247(d)	Conducted Band Edges	≤ 20 dBc	Pass	-
15.247(d)	Conducted Spurious Emission	≤ 20 dBc	Pass	-
15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.22 dB at 215.27 MHz
15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 20.43 dB at 0.442 MHz
15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 Test Laboratory

1.1 Test facility

CNAS (accreditation number: L11138)

Hunan Ecloud Testing Technology Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1244 , Test Firm Registration Number: 793308)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

ISED(CAB identifier: CN0012, ISED# :24347)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the Wireless Device Testing Laboratories list of innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

A2LA (Certificate Code : 4895.01)

Hunan Ecloud Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

2 General Description

2.1 Applicant

Condeco Ltd

8th Floor Exchange Tower, 2 Harbour Exchange Square. London. E14 9GE London United Kingdom

2.2 Manufacturer

Condeco Ltd

8th Floor Exchange Tower, 2 Harbour Exchange Square. London. E14 9GE London United Kingdom

2.3 General Description Of EUT

Product	V3 Desk Screen
Model No.	201850
Additional No.	N/A
Difference Description	N/A
FCC ID	2ACML-201850
Power Supply	DC 5V
Modulation Technology	FHSS
Modulation Type	GFSK, 8DPSK, $\pi/4$ DQPSK
Operating Frequency	2402MHz~2480MHz
Number Of Channel	79
Max. Output Power	Bluetooth BR(1Mbps) : 1.25 dBm (0.0013 W) Bluetooth EDR (2Mbps) : 1.21 dBm (0.0013 W) Bluetooth EDR (3Mbps) : 1.57 dBm (0.0014 W)
Antenna Type	Ceramics Antenna with -0.92dBi gain
HW Version	201850R14
SW Version	V8.1.0
I/O Ports	Refer to user's manual
Cable Supplied	USB cable: Unshielded, detachable, 2.0m

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.4 Modification of EUT

No modifications are made to the EUT during all test items.

2.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 15.247 Meas Guidance v05r02

Remark:

1. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 Test Configuration of Equipment Under Test

3.1 Descriptions of Test Mode

The transmitter has a maximum peak conducted output power as follows:

Channel	Frequency	Mode	Bluetooth RF Output Power
Ch00	2402MHz	GFSK	1.25
		4 π -DQPSK	1.21
		8PSK	1.57
Ch39	2441MHz	GFSK	0.43
		4 π -DQPSK	0.29
		8PSK	0.71
Ch78	2480MHz	GFSK	0.46
		4 π -DQPSK	0.35
		8PSK	0.7

Remark:

- 1.All the test data for each data rate were verified, but only the worst case was reported.
- 2.The data rate was set in 3Mbps for all the test items due to the highest RF output power.

3.2 Test Mode

3.2.1 Antenna Port Conducted Measurement

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz

3.2.2 Radiated Emission Test (Below 1GHz)

Radiated	Bluetooth EDR 3Mbps 8-DPSK
Test Cases	Mode 1: CH00_2402 MHz

- Note : 1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type. Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.
2. Following channel(s) was (were) selected for the final test as listed above

3.2.3 Radiated Emission Test (Above 1GHz)

Radiated	Bluetooth EDR 3Mbps 8-DPSK
Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz

- Note : 1. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.
2. Following channel(s) was (were) selected for the final test as listed above
3. For frequency above 18GHz, the measured value is much lower than the limit, therefore, it is not reflected in the report.

3.2.4 Power Line Conducted Emission Test:

AC Conducted Emission	Mode 1 : BT Tethering+WLAN Link+NFC+RFID+Charging from Adapter
-----------------------------	--

3.3 Support Equipment


Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	E470C	FCC DoC	N/A	shielded cable DC O/P 1.8 m unshielded AC I/P cable1.2 m
2.	USB Power Adapter	Apple	A1401	FCC DoC	N/A	N/A

3.4 Test Setup


The EUT is continuously communicating to the Bluetooth tester during the tests.

EUT was set in the Hidden menu mode to enable BT communications.


Setup diagram for Conducted Test




Setup diagram for Raidation(9KHz~30MHz) Test




Setup diagram for Raidation(Below 1G) Test



Setup diagram for Raidation(Above1G) Test



Setup diagram for AC Conducted Emission Test



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5 + 10 = 15 (dB)

For all radiated test items:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Over Limit (dB μ V/m) = Level(dB μ V/m) - Limit Level (dB μ V/m)

4 Test Result

4.1 20dB and 99% Bandwidth Measurement

4.1.1 Limit of 20dB and 99% Bandwidth

None; for reporting purposes only.

4.1.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
4. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 99% bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = sample;
Trace = max hold.

4.1.3 Test Result of 20dB Bandwidth

Refer to Appendix A of this test report.

4.1.4 Test Result of 99% Bandwidth

Refer to Appendix B of this test report.

4.2 Hopping Channel Separation Measurement

4.2.1 Limit of Hopping Channel Separation

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

4.2.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

4.2.3 Test Result of Hopping Channel Separation

Refer to Appendix C of this test report.

4.3 Number of Channel Measurement

4.3.1 Limits of Number of Hopping Frequency

FCC§15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.3.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

4.3.3 Test Result of Number of Hopping Frequency

Refer to Appendix D of this test report.

4.4 Average Time of Occupancy Measurement

4.4.1 Limit of Average Time of Occupancy

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.
4. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow:

DH1 time slot= Burst Width (ms)*(1600/ (2*79))*31.6

DH3 time slot= Burst Width (ms)*(1600/ (4*79))*31.6

DH5 time slot= Burst Width (ms)*(1600/ (6*79))*31.6

4.4.3 Test Result of Time of occupancy

Refer to Appendix E of this test report.

4.4.4 Test Result of Dwell Time

Refer to Appendix I of this test report.

4.5 Peak Output Power Measurement

4.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

4.5.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

4.5.3 Test Result of Peak Output Power

Refer to Appendix F of this test report.

4.6 Conducted Band Edges Measurement

4.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

4.6.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 1~3.

4.6.3 Test Result of Conducted Band Edges

Refer to Appendix G of this test report.

4.7 Conducted Spurious Emission Measurement

4.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

4.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.7.3 Test Result of Conducted Spurious Emission

Refer to Appendix H of this test report.

4.8 Radiated Band Edges and Spurious Emission Measurement


4.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

4.8.2 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The measurement distance is 3 meter.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement:
 VBW = 10 Hz, when duty cycle is no less than 98 percent.
 VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8.3 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

4.8.4 Test Result of Radiated Spurious at Band Edges



Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.41GHz	Polarization :	Horizontal


Data: 33



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.46	26.91	3.48	35.43	36.42	74.00	-37.58	Peak
2390.000	42.30	27.11	3.53	35.55	37.39	74.00	-36.61	Peak
2402.080	74.85	27.15	3.54	35.56	69.98	74.00	-4.02	Peak

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.41GHz	Polarization :	Vertical


Data: 37



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.49	26.91	3.48	35.43	23.45	54.00	-30.55	Average
2390.000	28.76	27.11	3.53	35.55	23.85	54.00	-30.15	Average
2402.080	66.11	27.15	3.54	35.56	61.24	54.00	7.24	Average

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.41GHz	Polarization :	Vertical


Data: 36



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.83	26.91	3.48	35.43	36.79	74.00	-37.21	Peak
2390.000	44.71	27.11	3.53	35.55	39.80	74.00	-34.20	Peak
2401.970	70.75	27.15	3.54	35.56	65.88	74.00	-8.12	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Horizontal


Data: 49



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2479.880	70.91	27.35	3.59	35.67	66.18	74.00	-7.82	Peak
2483.500	41.88	27.36	3.59	35.68	37.15	74.00	-36.85	Peak
2500.000	42.30	27.40	3.60	35.70	37.60	74.00	-36.40	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Horizontal


Data: 50



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.040	69.47	27.35	3.59	35.67	64.74	54.00	10.74	Peak
2483.500	28.74	27.36	3.59	35.68	24.01	54.00	-29.99	Peak
2500.000	28.86	27.40	3.60	35.70	24.16	54.00	-29.84	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Vertical


Data: 52



Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
2480.080	68.67	27.35	3.59	35.67	63.94	74.00	-10.06	Peak
2483.500	40.34	27.36	3.59	35.68	35.61	74.00	-38.39	Peak
2500.000	40.83	27.40	3.60	35.70	36.13	74.00	-37.87	Peak


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Vertical

Data: 53




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	68.44	27.35	3.59	35.67	63.71	54.00	9.71	Average
2483.500	28.81	27.36	3.59	35.68	24.08	54.00	-29.92	Average
2500.000	29.19	27.40	3.60	35.70	24.49	54.00	-29.51	Average

4.8.5 Test Result of Radiated Spurious Emission (1GHz ~ 10th Harmonic)




Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 31



Data: 32

Date: 2019-12-26




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	29.24	31.23	5.57	34.86	31.18	54.00	-22.82	Average
4804.000	41.55	31.23	5.57	34.86	43.49	74.00	-30.51	Peak
7206.000	26.61	35.87	7.63	36.40	33.71	54.00	-20.29	Average
7206.000	39.23	35.87	7.63	36.40	46.33	74.00	-27.67	Peak
9608.000	26.08	37.79	10.29	36.40	37.76	54.00	-16.24	Average
9608.000	41.43	37.79	10.29	36.40	53.11	74.00	-20.89	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 38



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2402.000	66.75	27.15	3.54	35.56	61.88	74.00	-12.12	Peak


Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 29



Data: 30

Date: 2019-12-26




Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
4804.000	29.13	31.23	5.57	34.86	31.07	54.00	-22.93	Average
4804.000	42.77	31.23	5.57	34.86	44.71	74.00	-29.29	Peak
7206.000	26.68	35.87	7.63	36.40	33.78	54.00	-20.22	Average
7206.000	38.86	35.87	7.63	36.40	45.96	74.00	-28.04	Peak
9608.000	28.23	37.79	10.29	36.40	39.91	54.00	-14.09	Average
9608.000	41.80	37.79	10.29	36.40	53.48	74.00	-20.52	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Data: 40




Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
2441.000	72.38	27.25	3.56	35.62	67.57	74.00	-6.43	Peak

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 41



Data: 42




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	29.26	31.42	5.55	34.79	31.44	54.00	-22.56	Average
4882.000	41.82	31.42	5.55	34.79	44.00	74.00	-30.00	Peak
7323.000	26.90	36.14	7.52	36.40	34.16	54.00	-19.84	Average
7323.000	39.41	36.14	7.52	36.40	46.67	74.00	-27.33	Peak
9764.000	27.77	38.08	10.75	36.40	40.20	54.00	-13.80	Average
9764.000	39.92	38.08	10.75	36.40	52.35	74.00	-21.65	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 39



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2441.000	67.92	27.25	3.56	35.62	63.11	74.00	-10.89	Peak


Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 43



Data: 44

Date: 2019-12-26




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	30.94	31.42	5.55	34.79	33.12	54.00	-20.88	Average
4882.000	42.17	31.42	5.55	34.79	44.35	74.00	-29.65	Peak
7323.000	26.93	36.14	7.52	36.40	34.19	54.00	-19.81	Average
7323.000	39.22	36.14	7.52	36.40	46.48	74.00	-27.52	Peak
9764.000	25.80	38.08	10.75	36.40	38.23	54.00	-15.77	Average
9764.000	39.49	38.08	10.75	36.40	51.92	74.00	-22.08	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Data: 51



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	69.87	27.35	3.59	35.67	65.14	74.00	-8.86	Peak


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 47



Data: 48

Date: 2019-12-26




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	28.84	31.60	5.52	34.73	31.23	54.00	-22.77	Average
4960.000	41.15	31.60	5.52	34.73	43.54	74.00	-30.46	Peak
7440.000	25.89	36.41	7.56	36.40	33.46	54.00	-20.54	Average
7440.000	38.41	36.41	7.56	36.40	45.98	74.00	-28.02	Peak
9920.000	27.13	38.36	11.17	36.40	40.26	54.00	-13.74	Average
9920.000	39.33	38.36	11.17	36.40	52.46	74.00	-21.54	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 54



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	68.97	27.35	3.59	35.67	64.24	74.00	-9.76	Peak


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 45



Data: 46


Date: 2019-12-26



Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
4960.000	31.39	31.60	5.52	34.73	33.78	54.00	-20.22	Average
4960.000	41.79	31.60	5.52	34.73	44.18	74.00	-29.82	Peak
7440.000	25.72	36.41	7.56	36.40	33.29	54.00	-20.71	Average
7440.000	37.76	36.41	7.56	36.40	45.33	74.00	-28.67	Peak
9920.000	27.15	38.36	11.17	36.40	40.28	54.00	-13.72	Average
9920.000	41.50	38.36	11.17	36.40	54.63	74.00	-19.37	Peak


Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

4.8.6 Test Result of Radiated Spurious Emission (30MHz ~ 1GHz)



Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Vertical

Data: 28



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
119.240	43.66	10.92	2.04	32.61	24.01	43.50	-19.49	Peak
167.740	45.56	13.41	2.23	32.63	28.57	43.50	-14.93	Peak
211.390	53.70	11.17	2.41	32.66	34.62	43.50	-8.88	Peak
359.800	44.75	15.00	3.09	32.76	30.08	46.00	-15.92	Peak
509.180	47.04	18.12	3.66	32.87	35.95	46.00	-10.05	Peak
696.390	38.49	21.16	4.25	32.31	31.59	46.00	-14.41	Peak

4.9 AC Conducted Emission Measurement

4.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


4.9.2 Test Procedures

7. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
8. Connect EUT to the power mains through a line impedance stabilization network (LISN).
9. All the support units are connecting to the other LISN.
10. The LISN provides 50 ohm coupling impedance for the measuring instrument.
11. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
12. Both sides of AC line were checked for maximum conducted interference.
13. The frequency range from 150 kHz to 30 MHz was searched.
14. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

4.9.3 Test Result of AC Conducted Emission



Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Jerry Wang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	BT Tethering+WLAN Link+NFC+RFID+Charging from Adapter		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.177	31.63	9.60	0.04	41.27	64.64	-23.37	QP
0.177	21.22	9.60	0.04	30.86	54.64	-23.78	Average
0.334	25.78	9.62	0.04	35.44	59.35	-23.91	QP
0.334	15.56	9.62	0.04	25.22	49.35	-24.13	Average
0.532	20.12	9.65	0.04	29.81	56.00	-26.19	QP
0.532	10.82	9.65	0.04	20.51	46.00	-25.49	Average
1.153	18.72	9.71	0.05	28.48	56.00	-27.52	QP
1.153	8.16	9.71	0.05	17.92	46.00	-28.08	Average
3.224	19.24	9.76	0.07	29.07	56.00	-26.93	QP
3.224	9.41	9.76	0.07	19.24	46.00	-26.76	Average
7.646	24.60	9.82	0.09	34.51	60.00	-25.49	QP
7.646	14.68	9.82	0.09	24.59	50.00	-25.41	Average

4.10 Antenna Requirements

4.10.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded..

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

4.10.2 Antenna Connected Construction

An embedded-in antenna design is used.

4.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY56070788	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56510025	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY57030005	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56510018	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56480002	2019-01-23	2020-01-22	Conducted
Thermal Chamber	Sanmtest	SMC-408-CD	2435	2019-05-09	2020-05-08	Conducted
Base Station	R&S	CMW 270	101231	2019-01-23	2020-01-22	Conducted
Signal Generator (Interferer)	Keysight	N5182B	MY56200384	2019-04-19	2020-04-18	Conducted
Signal Generator (Blocker)	Keysight	N5171B	MY56200661	2019-01-23	2020-01-22	Conducted

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV 40	101433	2019-02-18	2020-02-17	Radiation
Amplifier	Sonoma	310	363917	2019-01-22	2020-01-21	Radiation
Amplifier	Schwarzbeck	BBV 9718	327	2019-01-22	2020-01-21	Radiation
Amplifier	Narda	TTA1840-35-HG	2034380	2019-05-15	2020-05-14	Radiation
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	2017-03-03	2020-03-02	Radiation
Broadband Antenna	Schwarzbeck	VULB 9168	9168-757	2017-03-03	2020-03-02	Radiation
Horn Antenna	Schwarzbeck	BBHA 9120 D	1677	2017-03-03	2020-03-02	Radiation
Horn Antenna	COM-POWER	AH-1840	101117	2018-06-20	2021-06-19	Radiation
Test Software	Audix	E3	6.111221a	N/A	N/A	Radiation
Filter	Micro-Tronics	BRM 50702	G266	N/A	N/A	Radiation

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
LISN	R&S	ENV216	102125	2019-01-22	2020-01-21	Conducted
LISN	R&S	ENV432	101327	2019-01-22	2020-01-21	Conducted
EMI Test Receiver	R&S	ESR3	102143	2019-01-23	2020-01-22	Conducted
EMI Test Software	Audix	E3	N/A	N/A	N/A	Conducted

N/A: No Calibration Required

6 Uncertainty of Evaluation

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.64dB
Radiated emission	30MHz ~ 1GMHz	5.05dB
	1GHz ~ 18GHz	5.06 dB
	18GHz ~ 40GHz	3.65dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Appendix A: 20dB Emission Bandwidth

Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1		0.939	2401.541	2402.480	---	PASS
			0.963	2440.535	2441.498	---	PASS
			0.960	2479.538	2480.498	---	PASS
2DH5	Ant1		1.260	2401.379	2402.639	---	PASS
			1.269	2440.376	2441.645	---	PASS
			1.314	2479.346	2480.660	---	PASS
3DH5	Ant1		1.272	2401.361	2402.633	---	PASS
			1.296	2440.355	2441.651	---	PASS
			1.278	2479.361	2480.639	---	PASS

Test Graphs

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1		0.86666	2401.569	2402.436	---	PASS
			0.85627	2440.573	2441.430	---	PASS
			0.86017	2479.572	2480.432	---	PASS
2DH5	Ant1		1.1581	2401.423	2402.582	---	PASS
			1.1620	2440.423	2441.585	---	PASS
			1.1558	2479.424	2480.580	---	PASS
3DH5	Ant1		1.1513	2401.429	2402.581	---	PASS
			1.1762	2440.416	2441.592	---	PASS
			1.1783	2479.411	2480.589	---	PASS

Test Graphs


DH5_Ant1_2402




DH5_Ant1_2441



DH5_Ant1_2480




2DH5_Ant1_2402



2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441






Appendix C: Maximum conducted output power

Test Result


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1		1.25	<=20.97	PASS
			0.43	<=20.97	PASS
			0.46	<=20.97	PASS
2DH5	Ant1		1.21	<=20.97	PASS
			0.29	<=20.97	PASS
			0.35	<=20.97	PASS
3DH5	Ant1		1.57	<=20.97	PASS
			0.71	<=20.97	PASS
			0.7	<=20.97	PASS

Test Graphs


DH5_Ant1_2402




DH5_Ant1_2441



DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480




Appendix D: Carrier frequency separation

Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop_2441	1.008	≥ 0.642	PASS
2DH5	Ant1	Hop_2441	1.008	≥ 0.876	PASS
3DH5	Ant1	Hop_2441	1.004	≥ 0.864	PASS


Test Graphs

DH5_Ant1_Hop_2441



2DH5_Ant1_Hop_2441






Appendix E: Time of occupancy

Test Result



TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1		0.38	320	0.122	<=0.4	PASS
			0.38	320	0.122	<=0.4	PASS
			0.38	320	0.122	<=0.4	PASS
DH3	Ant1		1.64	170	0.278	<=0.4	PASS
			1.64	180	0.295	<=0.4	PASS
			1.64	190	0.311	<=0.4	PASS
DH5	Ant1		2.88	70	0.202	<=0.4	PASS
			2.89	100	0.289	<=0.4	PASS
			2.88	80	0.231	<=0.4	PASS
2DH1	Ant1		0.39	320	0.125	<=0.4	PASS
			0.39	320	0.125	<=0.4	PASS
			0.39	330	0.129	<=0.4	PASS
2DH3	Ant1		1.64	170	0.279	<=0.4	PASS
			1.64	180	0.296	<=0.4	PASS
			1.64	160	0.263	<=0.4	PASS
2DH5	Ant1		2.89	130	0.376	<=0.4	PASS
			2.89	110	0.318	<=0.4	PASS
			2.89	130	0.376	<=0.4	PASS
3DH1	Ant1		0.39	320	0.125	<=0.4	PASS
			0.39	330	0.129	<=0.4	PASS
			0.39	330	0.129	<=0.4	PASS
3DH3	Ant1		1.64	180	0.295	<=0.4	PASS
			1.64	180	0.295	<=0.4	PASS
			-1.85	170	-0.315	<=0.4	PASS
3DH5	Ant1		2.89	80	0.231	<=0.4	PASS
			2.89	110	0.318	<=0.4	PASS
			2.89	120	0.347	<=0.4	PASS

Test Graphs


DH1_Ant1_Hop_2402



DH1_Ant1_Hop_2441





DH1_Ant1_Hop_2480




DH3_Ant1_Hop_2402




DH3_Ant1_Hop_2441





DH3_Ant1_Hop_2480



DH5_Ant1_Hop_2402



DH5_Ant1_Hop_2441



DH5_Ant1_Hop_2480