#### FCC TEST REPORT

#### **FOR**

#### SISTEMAS APLICADOS USA, LLC

#### Tablet PC

Test Model: 707i

Additional Model No.: 708i, 709i, 711i, 712i, 713i, 807i, 808i, 809i, 811i, 812i, 813i, 907i, 908i, 909i, 911i, 912i, 913i, 1007i, 1008i, 1009i, 1010i, 1011i, 1012i

Prepared for : SISTEMAS APLICADOS USA, LLC

Address : 2005 E Griffin Pkwy Suite 150, Mission, Texas 78572, United States

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an

District, Shenzhen, Guangdong, China

Date of receipt of test sample : January 21, 2015

Number of tested samples : 1

Serial number : Prototype

Date of Test : January 21, 2015 - January 27, 2015

Date of Report January 27, 2015

#### FCC TEST REPORT

FCC CFR 47 PART 15 C(15.247): 2013

Report Reference No. .....: LCS1501271056E

Date of Issue .....: January 27, 2015

Testing Laboratory Name ......: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address .....: 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,

Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure ......: Full application of Harmonised standards

Partial application of Harmonised standards

Other standard testing method

Applicant's Name.....: SISTEMAS APLICADOS USA, LLC

Address ......: 2005 E Griffin Pkwy Suite 150, Mission, Texas 78572, United

States

**Test Specification** 

Standard ......: FCC CFR 47 PART 15 C(15.247): 2013

Test Report Form No. .....: LCSEMC-1.0

TRF Originator.....: Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF .....: Dated 2011-03

#### Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. ....: : Tablet PC

Trade Mark.....: Proteus

Model/ Type reference .....: 707i

Ratings .....: DC 3.7V by Lithium polymer battery (3000mAh)

Recharge Voltage: DC 5V/2000mA

Result .....: Positive

Compiled by:

**Supervised by:** 

Approved by:

Leo Lee/ File administrators

Danny Huang/ Technique principal

Gavin Liang/ Manager

# FCC -- TEST REPORT

**Test Report No.: LCS1501271056E** 

January 27, 2015 Date of issue

Type / Model..... : 707i EUT....:: Tablet PC Applicant.....:: SISTEMAS APLICADOS USA, LLC Address.....: 2005 E Griffin Pkwy Suite 150, Mission, Texas 78572, United States Telephone.....: : / Fax.....: : / Manufacturer.....: : Shenzhen StarWorth Manufacturing CO.,Ltd StarWorth(HongKong)Limited Address.....: 1-4Floor Building No.27 Chentian Industrial Estate, Xixiang Town, Baoan District, Shenzhen City, China Telephone....: : / Fax.....:: : / Factory.....: Shenzhen StarWorth Manufacturing CO.,Ltd StarWorth(HongKong)Limited Address.....: 1-4Floor Building No.27 Chentian Industrial Estate, Xixiang Town, Baoan District, Shenzhen City, China Telephone.....: : / Fax.....:: : /

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

# TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 Description of Device (EUT)	5
1.2 Support equipment List	6
1.3 External I/O	
1.4 Description of Test Facility	
1.5 Statement of The Measurement Uncertainty	
1.6 Measurement Uncertainty	
1.7 Description Of Test Modes	
2. TEST METHODOLOGY	9
2.1 EUT Configuration	9
2.2 EUT Exercise	9
2.3 General Test Procedures	9
3. SYSTEM TEST CONFIGURATION	10
3.1 Justification	10
3.2 EUT Exercise Software	
3.3 Special Accessories	
3.4 Block Diagram/Schematics	10
3.5 Equipment Modifications	10
3.6 Test Setup	10
4. ANTENNA PORT MEASUREMENT	11
4.1 Peak Power	11
4.2 Frequency Separation And 20 dB Bandwidth	12
4.3 Number Of Hopping Frequency	
4.4 Time Of Occupancy (Dwell Time)	23
4.5 Conducted Spurious Emissions and Band Edges Test	26
5. RADIATED MEASUREMENT	33
5.1 Test Equipment	33
5.2 Block Diagram of Test Setup	
5.3 Radiated Emission Limit	34
5.4 Instruments Setting	35
5.5 Test Procedures	
5.6 Results for Radiated Emissions	
5.5 Results for Band edge Testing (Radiated)	
6. LINE CONDUCTED EMISSIONS	40
6.1 Standard Applicable	40
6.2 Test Equipment	
6.3 Block Diagram of Test Setup	
6.4 Test Results	40
7. ANTENNA REQUIREMENT	42
7.1 Standard Applicable	
7.2 Antenna Connected Construction	
8 MANUEACTURER/APPROVAL HOLDER DECLARATION	13

## 1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : Tablet PC

Model Number : 707i

Power Supply : DC 3.7V by Lithium polymer battery (3000mAh)

Recharge Voltage: DC 5V/2000mA

EUT Support : WIFI/Bluetooth

**Radios Application** 

Bluetooth :

Frequency Range : 2402.00-2480.00MHz (Channel Frequency=2402+1(K-1), K=1,

2, 3 ......79)

Modulation Type : GFSK(1Mbps); π /4-DQPSK(2Mbps); 8-DPSK(3Mbps)

Channel Number : 79

Channel Spacing : 1MHz

Bluetooth Version : This report is only for Bluetooth V3.0 part only.

For Bluetooth V4.0 BLE part, please see another separate report.

Antenna Gain : FPC antenna, 2.0dBi(Max.)

# 1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN JIYIN SCIENCE				
& TECHNOLOGY	Adapter	JY-05200	/	VOC
DEVELOPMENT CO LTD				

## 1.3 External I/O

I/O Port Description	Quantity	Cable
Earphone Port	1	N/A
HDMI Port	1	N/A
USB Port	1	0.6m, unshielded
TF CARD Slot	1	N/A

# 1.4 Description of Test Facility

Site Description EMC Lab.

: Accredited by CNAS, June 04, 2010

The Certificate Registration Number. is L4595.

Shenzhen LCS Compliance Testing Laboratory Ltd.

The Certificate Registration Number. is 899208.

Shenzhen LCS Compliance Testing Laboratory Ltd.

The Certificate Registration Number. is 9642A-1

## 1.5 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6 Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
		9KHz~30MHz	±3.10dB	(1)
Radiation Uncertainty	:	30MHz~200MHz	±2.96dB	(1)
		200MHz~1000MHz	±3.10dB	(1)
		1GHz~26.5GHz	±3.80dB	(1)
		26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	±1.63dB	(1)
Power disturbance	:	30MHz~300MHz	±1.60dB	(1)

<sup>(1).</sup> This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7 Description Of Test Modes

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s. An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using GFSK techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a  $\pi$  /4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. All 3axis have been tested and the worse case was found when EUT in X position. The following operating modes were applied for the related test items. All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Operations	Frequency Range (MHz)	Data Rate (Mbps)			
CEGIZ	2402	1			
GFSK	2441	1			
	2480	1			
	2402	2			
π /4 DQPSK	2441	2			
	2480	2			
	2402	3			
8-DPSK	2441	3			
	2480	3			
F	For Conducted Emission				
Test Mode		ΓX Mode			
For Radiated Emission					
Test Mode		ΓX Mode			

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be TX(1Mbps-Hopping Mode).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX(1Mbps-High Channel).

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, RSS-210, FCC CFR PART 15C 15.207, 15.209, 15.247 and DA 00-705.

## 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C and RSS-210.

#### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009

# 3. SYSTEM TEST CONFIGURATION

## 3.1 Justification

The system was configured for testing in a continuous transmit condition.

## 3.2 EUT Exercise Software

N/A.

# 3.3 Special Accessories

N/A.

# 3.4 Block Diagram/Schematics

Please refer to the related document.

# 3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

# 3.6 Test Setup

Please refer to the test setup photo.


# 4. ANTENNA PORT MEASUREMENT

#### 4.1 Peak Power

## **4.1.1 Test Equipment**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Sensor	R&S	NRV-Z51	100458	2014-06-18	2015-06-17
2	Power Sensor	R&S	NRV-Z32	10057	2014-06-18	2015-06-17
3	Power Meter	R&S	NRVS	100444	2014-06-18	2015-06-17
4	DC Filter	MPE	23872C	N/A	2014-06-18	2015-06-17
5	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2014-06-18	2015-06-17

## 4.1.2 Block Diagram of Test Setup



#### 4.1.3 Limit

According to §15.247(a)(1) or A8.4 (2), For frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW..

#### **4.1.4 Test Procedure**

The transmitter output is connected to the Power Meter.

#### 4.1.5 Test Results

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (mW)	Result
	2402	3.21	2.09	125	Pass
GFSK	2441	3.44	2.21	125	Pass
	2480	3.53	2.25	125	Pass
/A	2402	2.07	1.61	125	Pass
π /4	2441	2.11	1.63	125	Pass
DQPSK	2480	2.17	1.65	125	Pass
	2402	2.09	1.62	125	Pass
8-DPSK	2441	2.14	1.64	125	Pass
	2480	2.20	1.66	125	Pass

## 4.2 Frequency Separation And 20 dB Bandwidth

#### 4.2.1 Limit


According to §15.247(c) or A8.1(a), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

### 4.2.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2014-06-16	2015-06-15
2	Signal analyzer	Agilent	E4448A(Ext ernal mixers to 40GHz)	US44300469	2014-06-16	2015-06-15
3	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2014-06-18	2015-06-17
4	DC Filter	MPE	23872C	N/A	2014-06-18	2015-06-17

#### 4.2.3 Block Diagram of Test Setup

Spectrum Analyzer



#### 4.2.4 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set to the maximum power setting and enable the EUT transmit continuously.
- D. For carrier frequency separation measurement, use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels;

RBW / RBW=100KHz / 300KHz; Sweep = auto; Detector function = peak;

Trace = max hold.

E. For 20dB bandwidth measurement, use the following spectrum analyzer settings: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW/VBW=30KHz / 100KHz; Sweep = auto; Detector function = peak; Trace = max hold.

## **4.2.5 Test Results**


The Measurement Result With 1Mbps For GFSK Modulation						
Channel	20dB Bandwidth (KHz)	Channel Separation (MHz)	Limit (MHz)	Result		
Low	738.045		>=25 KHz or 2/3 20 dB BW	Pass		
Middle	820.613	1.000	>=25 KHz or 2/3 20 dB BW	Pass		
High	817.353		>=25 KHz or 2/3 20 dB BW	Pass		

The Measurement Result With 2Mbps For π/4 DQPSK Modulation						
Channel	20dB Bandwidth (MHz)	Channel Separation (MHz)	Limit (MHz)	Result		
Low	1.117		>=25 KHz or 2/3 20 dB BW	Pass		
Middle	1.127	1.000	>=25 KHz or 2/3 20 dB BW	Pass		
High	1.113		>=25 KHz or 2/3 20 dB BW	Pass		


The Measurement Result With 3Mbps For 8-DPSK Modulation						
Channel	20dB Bandwidth (MHz)	Channel Separation (MHz)	Limit (MHz)	Result		
Low	1.170		>=25 KHz or 2/3 20 dB BW	Pass		
Middle	1.161	1.000	>=25 KHz or 2/3 20 dB BW	Pass		
High	1.166		>=25 KHz or 2/3 20 dB BW	Pass		

The test data refer to the following page.


## **Test Plot Of Frequency Separation (1Mbps)**



**Test Plot Of Frequency Separation (2Mbps)** 




**Test Plot Of Frequency Separation (3Mbps)** 




#### Measurement of 20dB Bandwidth

Test frequency: 2402MHz(1Mbps)



Test frequency: 2441MHz(1Mbps)




Test frequency: 2480MHz(1Mbps) 🕸 Agilent Trace/View Ch Freq 2.48 GHz Trig Free Trace Occupied Bandwidth Clear Write Ref 10 dBm Atten 20 dB #Peak Log Max Hold 10 dB/ Offst Min Hold 0.8 dΒ View Center 2.48 GHz Span 3 MHz Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) 99.00 % Occupied Bandwidth Blank Occ BW % Pwr x dB -20.00 dB 822.1412 kHz More Transmit Freq Error -7.046 kHz 1 of 2




817.353 kHz


x dB Bandwidth




Test frequency: 2441MHz(2Mbps)




Test frequency: 2480MHz(2Mbps)




Test frequency: 2402MHz(3Mbps)



Test frequency: 2441MHz(3Mbps)



Test frequency: 2480MHz(3Mbps)



## 4.3 Number Of Hopping Frequency

#### 4.3.1 Limit


According to §15.247(a)(1)(ii) or A8.1 (d), Frequency hopping systems operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels.

#### 4.3.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2014-06-16	2015-06-15
2	Signal analyzer	Agilent	E4448A(Ext ernal mixers to 40GHz)		2014-06-16	2015-06-15
3	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2014-06-18	2015-06-17
4	DC Filter	MPE	23872C	N/A	2014-06-18	2015-06-17

#### 4.3.3 Block Diagram of Test Setup

Spectrum Analyzer



#### **4.3.4 Test Procedure**


- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set Spectrum Analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz.
- E. Max hold, view and count how many channel in the band.

#### 4.3.5 Test Results


The Measurement Result With The Worst Case of 1Mbps For GFSK Modulation							
Total No. of	Measurement Result (No. of Ch)	Limit (MHz)	Result				
Hopping Channel	79	≥15	Pass				

The test data refer to the following page.

#### **Test Plot-1 For Number of Hopping Channel**



## **Test Plot-2 For Number of Hopping Channel**



## 4.4 Time Of Occupancy (Dwell Time)

#### 4.4.1 Limit


According to §15.247(a)(1)(iii) or A8.1 (d), Frequency hopping systems operating in the 2400MHz- 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

## 4.4.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2014-06-16	2015-06-15
2	Signal analyzer	Agilent	E4448A(Ext ernal mixers to 40GHz)		2014-06-16	2015-06-15
3	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2014-06-18	2015-06-17
4	DC Filter	MPE	23872C	N/A	2014-06-18	2015-06-17

#### 4.4.3 Block Diagram of Test Setup

Spectrum Analyzer



#### **4.4.4 Test Procedure**

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set center frequency of Spectrum Analyzer = operating frequency.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- E. Repeat above procedures until all frequency measured were complete.

#### 4.5.5 Test Results

The Measurement Result With The Worst Case of 3Mbps For 8-DPSK Modulation								
Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)				
Low	2.85	31.6	304.0	400				
Middle	2.85	31.6	304.0	400				
High	2.85	31.6	304.0	400				

## **Low Channel**

2.85\*(1600/6)/79\*31.6=304.0ms

#### **Middle Channel**


2.85\*(1600/6)/79\*31.6=304.0ms

## **High Channel**


2.85\*(1600/6)/79\*31.6=304.0ms

The test data refer to the following:


#### **Low Channel**



#### **Middle Channel**



## **High Channel**



## 4.5 Conducted Spurious Emissions and Band Edges Test

#### 4.5.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### 4.5.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2014-06-16	2015-06-15
2	Signal analyzer	Agilent	E4448A(Ext ernal mixers to 40GHz)		2014-06-16	2015-06-15
3	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2014-06-18	2015-06-17
4	DC Filter	MPE	23872C	N/A	2014-06-18	2015-06-17

## 4.5.3 Block Diagram of Test Setup

Spectrum Analyzer



#### 4.5.4 Test Proced DC Filter

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.


Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels

### 4.5.5 Test Results of Conducted Spurious Emissions


No non-compliance noted. Only record the worst test result (TX-GFSK) in this report. The test data refer to the following page.


#### **Test Plot**

#### 9KHz-26.5GHz Low Channel(GFSK)



## 9KHz-26.5GHz Middle Channel(GFSK)







## 4.5.5 Test Results of Band Edges Test

No non-compliance noted. Only record the worst test result in this report. The test data refer to the following page.


#### **Test Plot**


**Hopping On - (GFSK)** 







**Hopping Off - (GFSK)** 







## **Hopping On - (8-DPSK)**





## **Hopping Off - (8-DPSK)**






# 5. RADIATED MEASUREMENT


# 5.1 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2014-06-18	2015-06-17
2	Amplifier	SCHAFFNER	COA9231A	18667	2014-06-18	2015-06-17
3	Amplifier	Agilent	8449B	3008A02120	2014-06-16	2015-06-15
4	Amplifier	MITEQ	AMF-6F-260 400	9121372	2014-06-16	2015-06-15
5	Spectrum Analyzer	Agilent	E4407B	MY41440292	2014-06-16	2015-06-15
6	Signal analyzer	Agilent	E4448A(Exte rnal mixers to 40GHz)	US44300469	2014-06-16	2015-06-15
7	Loop Antenna	R&S	HFH2-Z2	860004/001	2014-06-18	2015-06-17
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2014-06-10	2015-06-09
9	Horn Antenna	EMCO	3115	6741	2014-06-10	2015-06-09
10	Horn Antenna	SCHWARZBECK	BBHA9170	BBHA91701 54	2014-06-10	2015-06-09
11	RF Cable-R03m	Jye Bao	RG142	CB021	2014-06-18	2015-06-17
12	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03СН03-НҮ	2014-06-18	2015-06-17


# 5.2 Block Diagram of Test Setup



Below 30MHz



Below 1 GHz



**Above 1 GHz** 

## 5.3 Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	$(\2\)$
13.36-13.41			

<sup>\1\</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

<sup>\2\</sup> Above 38.6

Part 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector.

Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Part 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30–88	100**	3
88–216	150**	3
216–960	200**	3
Above 960	500	3

## 5.4 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

The following the is the setting of spectrum unutject and recorded.					
Spectrum Parameter	Setting				
Attenuation	Auto				
Start Frequency	1000 MHz				
Stop Frequency	10th carrier harmonic				
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average				
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average				

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

#### 5.5 Test Procedures


- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

#### 5.6 Results for Radiated Emissions

#### PASS.

Only record the worst test result in this report. The test data please refer to following page:

## **Below 1GHz**



Env./Ins: EUT: M/N: Power Rati Test Mode: Rating: Operator: Memo:


pol:

24℃/56% Table PC AC 120V/60Hz TX-High Channel Leo

HORIZONTAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	55.22	9.73	0.46	13.01	23.20	40.00	-16.80	QP
2	97.90	16.17	0.61	13.03	29.81	43.50	-13.69	QP
3	110.51	16.10	0.61	12.16	28.87	43.50	-14.63	QP
4	124.09	12.33	0.71	9.85	22.89	43.50	-20.61	QP
5	233.70	14.50	0.87	11.81	27.18	46.00	-18.82	QP
6	296.75	8.64	1.12	13.00	22.76	46.00	-23.24	QP

Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that ate 20db blow the offficial limit are not reported



Env./Ins: EUT: M/N: Power Rating: Test Mode: Operator:

pol:

Table PC 707i AC 120V/60Hz TX-High Channel Leo

VERTICAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dВ	dB/m	dBuV/m	dBuV/m	dВ	
1	49.40	7.69	0.54	13.29	21.52	40.00	-18.48	QP
2	104.69	23.05	0.61	12.73	36.39	43.50	-7.11	QP
3	111.48	25.81	0.61	11.99	38.41	43.50	-5.09	QP
4	119.24	23.04	0.64	10.61	34.29	43.50	-9.21	QP
5	141.55	18.66	0.71	8.20	27.57	43.50	-15.93	QP
6	309.36	6.25	1.08	13.19	20.52	46.00	-25.48	QP

Note: 1. All readings are Quasi-peak values. 2. Measured= Reading + Antenna Factor + Cable Loss 3. The emission that ate 20db blow the offficial limit are not reported

\*\*\*Note:

Pre-scan all mode and recorded the worst case results in this report (TX(1Mbps-High Channel)). Emission level  $(dBuV/m) = 20 \log Emission level (uV/m)$ .

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

# **Above 1GHz**

The worst test result for GFSK, Tx-Low Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4804.11	54.01	33.06	35.04	3.94	55.97	74	-18.03	Peak	Horizontal
4804.13	43.98	33.06	35.04	3.94	45.94	54	-8.06	Average	Horizontal
4804.10	54.39	33.06	35.04	3.94	56.35	74	-17.65	Peak	Vertical
4804.13	44.08	33.06	35.04	3.94	46.04	54	-7.96	Average	Vertical

The worst test result for GFSK, Tx-Middle Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4882.24	54.45	33.16	35.15	3.96	56.42	74	-17.58	Peak	Horizontal
4882.26	44.14	33.16	35.15	3.96	46.11	54	-7.89	Average	Horizontal
4882.24	55.52	33.16	35.15	3.96	57.49	74	-16.51	Peak	Vertical
4882.26	45.19	33.16	35.15	3.96	47.16	54	-6.84	Average	Vertical

The worst test result for GFSK, Tx-High Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4960.36	54.79	33.26	35.14	3.98	56.89	74	-17.11	Peak	Horizontal
4960.39	45.12	33.26	35.14	3.98	47.22	54	-6.78	Average	Horizontal
4960.36	55.46	33.26	35.14	3.98	57.56	74	-16.44	Peak	Vertical
4960.39	45.89	33.26	35.14	3.98	47.99	54	-6.01	Average	Vertical

#### Notes:

- 1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
- 2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
- 3. 18~25GHz at least have 20dB margin. No recording in the test report.

# 5.5 Results for Band edge Testing (Radiated)

Only record the worst test case (Tx, GFSK, Non-hopping) as following:

Tx-2402, GFSK, Non-hopping

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2373.61	44.59	32.89	35.16	3.51	45.83	74	-28.17	Peak	Horizontal
2373.63	35.09	32.90	35.16	3.51	36.34	54	-17.66	Average	Horizontal
2400.00	48.53	32.92	35.16	3.54	49.83	74	-24.17	Peak	Horizontal
2399.99	38.35	32.92	35.16	3.54	39.65	54	-14.35	Average	Horizontal
2373.60	45.12	32.89	35.16	3.51	46.36	74	-27.64	Peak	Vertical
2373.63	35.49	32.90	35.16	3.51	36.74	54	-17.26	Average	Vertical
2400.00	49.34	32.92	35.16	3.54	50.64	74	-23.36	Peak	Vertical
2399.99	39.51	32.92	35.16	3.54	40.81	54	-13.19	Average	Vertical

Tx-2480, GFSK, Non-hopping

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2483.50	45.23	33.06	35.18	3.60	46.71	74	-27.29	Peak	Horizontal
2483.51	35.70	33.08	35.18	3.60	37.20	54	-16.80	Average	Horizontal
2488.54	44.60	33.08	35.18	3.62	46.12	74	-27.88	Peak	Horizontal
2488.56	34.99	33.08	35.18	3.62	36.51	54	-17.49	Average	Horizontal
2483.50	45.75	33.06	35.18	3.60	47.23	74	-26.77	Peak	Vertical
2483.51	35.96	33.08	35.18	3.60	37.46	54	-16.54	Average	Vertical
2488.54	44.82	33.08	35.18	3.62	46.34	74	-27.66	Peak	Vertical
2488.57	34.52	33.08	35.18	3.62	36.04	54	-17.96	Average	Vertical

## 6. LINE CONDUCTED EMISSIONS

# 6.1 Standard Applicable


According to §15.207 (a) or RSS-GEN: For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Eraguanay Danga(MHz)	Limits (dBμV)				
Frequency Range(MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56	56 to 46			
0.50 to 5	56	46			
5 to 30	60	50			

# 6.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	<b>EMC</b> Receiver	R&S	ESCS30	100174	2014-06-18	2015-06-17
3	50Ω Coaxial Switch	R&S	MP59B	M20531	2014-06-18	2015-06-17
4	Pulse Limiter	Anritsu	ESH3-Z2	100006	2014-06-18	2015-06-17
5	Voltage Probe	Rohde & Schwarz	TK9416	N/A	2014-06-18	2015-06-17
6	Coaxial Cable	LCS	2M_201401 01	N/A	2014-06-18	2015-06-17
1	<b>EMC</b> Receiver	R&S	ESCS30	100174	2014-06-18	2015-06-17


# 6.3 Block Diagram of Test Setup



#### 6.4 Test Results

PASS.

The test data please refer to following page.




Env. Ins: EUT: M/N: Power Rating: Test Mode: Operator:

24\*/56% Tablet PC 7071 AC 120V/60Hz TX Leo

Memo: Pol: LINE

	Freq	Reading	LisnFac	: CabLos	Atten_Fac	Measured	Limit	0ver	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBu∀	dB	
1	0.15403	32.11	9.58	0.02	10.00	51.71	65.78	-14.07	QP
2	0.15413	17.11	9.58	0.02	10.00	36.71	55.77	-19.06	Average
3	0.20181	26.23	9.63	0.02	10.00	45.88	63.54	-17.66	QP
4	0.20191	11.87	9.63	0.02	10.00	31.52	53.53	-22.01	Average
- 5	0.24945	23.59	9.63	0.03	10.00	43.25	61.78	-18.53	QP
6	0.24955	11.23	9.63	0.03	10.00	30.89	51.77	-20.88	Average
7	0.42149	22.52	9.62	0.04	10.00	42.18	57.42	-15.24	QP
8	0.42159	1.35	9.62	0.04	10.00	21.01	47.42	-26.41	Average
9	2.89979	23.64	9.64	0.06	10.00	43.34	56.00	-12.66	QP
10	2.90079	8.25	9.64	0.06	10.00	27.95	46.00	-18.05	Average
11	4.82243	22.22	9.65	0.06	10.00	41.93	56.00	-14.07	QP
12	4.82343	8.37	9.65	0.06	10.00	28.08	46.00	-17.92	Average

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten\_Fac. 2. The emission levels that are 20dB below the official limit are not reported.



Env. Ins: EUT: M/N:
Power Rating:
Test Mode:
Operator:
Memo:
Pol:

707i AC 120V/60Hz

NEUTRAL

	Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	0ver	Remark
	MHz	dBu∀	dB	dВ	dB	dBuV	dBuV	dB	
1	0.15403	31.22	9.69	0.02	10.00	50.93	65.78	-14.85	OP
2	0.15413	15.88	9.69	0.02	10.00	35.59	55.77	-20.18	Average
3	0.42149	27.79	9.61	0.04	10.00	47.44	57.42	-9.98	QP
4	0.42159	3.17	9.61	0.04	10.00	22.82	47.42	-24.60	Average
5	0.50469	24.26	9.62	0.04	10.00	43.92	56.00	-12.08	QP
6	0.50479	5.69	9.62	0.04	10.00	25.35	46.00	-20.65	Average
7	1.14733	24.72	9.63	0.05	10.00	44.40	56.00	-11.60	QP
8	1.14833	3.54	9.63	0.05	10.00	23.22	46.00	-22.78	Average
9	2.73562	25.48	9.64	0.05	10.00	45.17	56.00	-10.83	QP
10	2.73662	3.99	9.64	0.05	10.00	23.68	46.00	-22.32	Average
111	12.71611	26.11	9.73	0.09	10.00	45.93	60.00	-14.07	QP
121	12.71711	8.73	9.73	0.09	10.00	28.55	50.00	-21.45	Average

Measured = Reading + Lisn Factor +Cable Loss+Atten\_Fac.
 The emission levels that are 20dB below the official limit are not reported.

Note: Pre-scan all modes and recorded the worst case results in this report.

## 7. ANTENNA REQUIREMENT

## 7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 7.2 Antenna Connected Construction

#### 7.2.1. Standard Applicable

According to § 15.203 & RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 7.2.2. Antenna Connector Construction

The antenna used for transmitting is 2.0dBi(Max.), and the antenna is attached permanently and no consideration of replacement. Please see EUT photo for details.

7.2.3. Results: Compliance.

# 8. MANUFACTURER/ APPROVAL HOLDER DECLARATION

The following series model(s):

708i	709i	711i	712i
713i	807i	808i	809i
811i	812i	813i	907i
908i	909i	911i	912i
913i	1007i	1008i	1009i
1010i	1011i	1012i	

Belong to the tested device:

Product description : Tablet PC

Model name 707i

Remark: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.

-----THE END OF REPORT-----