

## RF Exposure

### Applicable Standard

According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline. This is a Portable device. The **Section 4.3.1 and Appendix A of KDB447498 D01 V05 was used as the guidance.**

### Calculation Result (Worse Case):

#### WIFI Mode (2.4G band) :

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 7.00/5 * 1.55 = 2.17$ , this value is less than 3.0 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

#### Bluetooth Mode

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 2.00/5 * 1.55 = 0.62$ , this value is less than 3.0 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

#### WIFI Mode (5.725-5.825G band) :

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 2.73/5 * 2.40 = 1.31$ , this value is less than 3.0 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Note: WIFI and Bluetooth can not transmit at the same time.

**The SAR measurement is not necessary.**